

SECTION 1: BUILDING DESCRIPTION

1.1 BUILDING NO. 01

1.1.1 BUILDING NO. 01

GROUND FLOOR

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s **“MEZZANINES”** brochure for more details of standard Mezzanine.

B. Mezzanine with Precast slab or hollow core slab supplied by Maimaar:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

• Exterior Mezzanine joists and beams in this area are designed to support Blockwall loads:

• Interior Mezzanine joists and beams in this area are designed to support Blockwall loads:

• 1.10 m high industrial handrail is provided at free ends of mezzanine:

No

No

No

Spacing of Mezzanine columns:

Sr. No.	Mezzanine Loads (KN/m²)				Area (m²)	Type of Floor &Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	**Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From of FFL to Top of RCC Slab	From FFL to Top of Concrete Slab
Ground Floor – (Refer Drawings for dimensions)									
1	As per Design	5.0	None	0.0	93.652	A	~5.337m	-	-

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)

***Note: The area under the mezzanine is covered by sheeting (by Maimaar Steel Pvt. Ltd) on three sides while the fourth side being the far side wall is covered by existing building.**