



## SECTION 1: BUILDING DESCRIPTION

### 1.1 BUILDING NO. 02

### MEZZ-02

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s “**MEZZANINES**” brochure for more details of standard Mezzanine.

B. Mezzanine with Precast slab or hollow core slab supplied by others:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

|                                                                                              |    |
|----------------------------------------------------------------------------------------------|----|
| • Exterior Mezzanine joists and beams in this area are designed to support block wall loads: | No |
| • Interior Mezzanine joists and beams in this area are designed to support block wall loads: | No |
| • 1.10 m high industrial handrail is provided at free ends of mezzanine:                     | No |

Spacing of Mezzanine columns:

| Sr. No. | Mezzanine Loads (kN/m²) |      |            |       | Area (m²) | Type of Floor & Thk. (mm) | Minimum Clear Heights (m)        |                                                      |                                  |
|---------|-------------------------|------|------------|-------|-----------|---------------------------|----------------------------------|------------------------------------------------------|----------------------------------|
|         | Dead*                   | Live | Collateral | Other |           |                           | From FFL to Bottom of Mezz. Beam | From Top of Concrete Slab to bottom of Rafter / Beam | From FFL to Top of Concrete Slab |
| 1       | As Per Design           | 5.0  | None       | None  | 118.12    | A(100)                    | 3.048                            | -                                                    | -                                |

\* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)

| STAIRS                                                                    |              |     |               |                                    |                              |                    |                    |                  |                         |
|---------------------------------------------------------------------------|--------------|-----|---------------|------------------------------------|------------------------------|--------------------|--------------------|------------------|-------------------------|
| Stair treads can be red oxide primed checkered plate.                     |              |     |               |                                    |                              |                    |                    |                  |                         |
| <b>Handrails are fabricated from pipe sections; these may be painted.</b> |              |     |               |                                    |                              |                    |                    |                  |                         |
| Sr.                                                                       | Located at   | Qty | Stair Type    | Out to Out width of staircase (mm) | 1.1m High Handrails Included | Qty of Top Landing | Qty of Mid Landing | Stair Height (m) | Type of Treads          |
| 1                                                                         | Mezzanine-02 | 01  | Single Flight | 1219                               | No                           | Yes (1)            | No                 | 3.298            | Checkered red Plate-5mm |