



SECTION 1: BUILDING DESCRIPTION

1.2 BUILDING NO. 01

MEZZANINES								
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7 mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's " MEZZANINES " brochure for more details of standard Mezzanine.								
B. Mezzanine with Precast slab or hollow core slab supplied by others:								
• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:							No	
• Interior Mezzanine joists and beams in this area are designed to support block wall loads:							No	
• 1.10 m high industrial handrail is provided at free ends of mezzanine:							Yes	
Spacing of Mezzanine columns:								
Sr. No.	Mezzanine Loads (kN/m ²)			Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Floor/ Slab
1	3.0 KN/Sq. m	3.0 KN/Sq .m	-	~614	Checkered Plate	3.962	-	-
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)								

Note: Above mentioned areas exclude openings. Final areas shall be decided as per approval drawings.