

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 01**

MEZZANINES									
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s “MEZZANINES” brochure for more details of standard Mezzanine.									
B. Mezzanine with Precast slab or hollow core slab supplied by others: No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.									
- Exterior Mezzanine joists and beams in this area are designed to support block wall loads: - Interior Mezzanine joists and beams in this area are designed to support block wall loads: 1.10 m high industrial handrail is provided at free ends of mezzanine:								No	
								No	
								No	
Spacing of Mezzanine columns:									
Sr. No.	Mezzanine Loads (kN/m ²)				Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per design	5.00	0.00	0.00	374.25	A (100mm)	3.500	-	-
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)									

ROOF ACCESSORIES		For Basic Price Only
		Quantity per Area
No.	Description	01
1	Roof Insulation. Type: Fiberglass Thick(mm):100 Density(Kg/m ³)=12 Facing: FRK (Silver) Coverage Area (m ²) = Full Roof Area	Not Applicable
2	Single Skin Clear (Translucent) Skylights Fiberglass Skylights Width: 1000mm , Length: 3000mm	Not Applicable

WALL ACCESSORIES		For Basic Price Only
		Quantity per Area
No.	Description	01
1	Wall Insulation. Type: Fiberglass Thick(mm):100 Density(Kg/m ³)=12 Facing: FRK (Silver) Coverage Area (m ²) = Full Wall Area	Not Applicable