

SECTION 1: BUILDING DESCRIPTION

1.1 BUILDING NO. 01 MEZZANINE FLOOR-FUTURE PROVISION

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s “**MEZZANINES**” brochure for more details of standard Mezzanine.

B. Mezzanine with Precast slab or hollow core slab supplied by others:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:

• Interior Mezzanine joists and beams in this area are designed to support block wall loads:

• 1.10 m high industrial handrail is provided at free ends of mezzanine:

NoNoNo

Spacing of Mezzanine columns:

Sr. No	Mezzanine Loads (kN/m²)				Area (m²)	Type of Floor &Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	3	N/A	N/A	510	A (100)	3.972	As Per Design	4.072

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)