



SECTION 1: BUILDING DESCRIPTION

1.1 Building No. 01

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's "**MEZZANINES**" brochure for more details of standard Mezzanine.

B. Mezzanine with Precast slab or hollow core slab supplied by others:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:	No
• Interior Mezzanine joists and beams in this area are designed to support block wall loads:	No
• 1.10 m high industrial handrail is provided at free ends of mezzanine:	No

Spacing of Mezzanine columns:

Sr. No	Mezzanine Loads (kN/m ²)				Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As Per Design	2.5	None	None	92.90	A (100)	7.620	-	-

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)

Notes:

1. Glass in Mezzanine is to be provided by others.
2. 100mm concrete is to be supplied by others.