

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 01**

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s **“MEZZANINES”** brochure for more details of standard Mezzanine.

• Exterior Mezzanine joists and beams in this area are designed to support blockwall loads: • Interior Mezzanine joists and beams in this area are designed to support blockwall loads: • 1.10 m high industrial handrail is provided at free ends of mezzanine:	No
	No
	No

Spacing of Mezzanine columns:

Sr. No.	Mezzanine Loads (KN/m²)				Area (m²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	3.00	0.00	0.00	33.84	A (100mm concrete)	As per site	-	

* - Dead Load includes the Self Weight of (Floor 3mm Chequered Plate)

Notes:

- Please note that all joists are chemically bolted to existing RCC Structure.
- The RCC Beam appears to be weak hence the holes will be drilled throughout the depth of beam and bolts will be installed through complete depth of the beam. (Refer drawings)