

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 01****MEZZANINES****A. Maimaar standard mezzanine:**

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's "MEZZANINES" brochure for more details of standard Mezzanine.

B. Mezzanine with Precast slab or hollow core slab supplied by others:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

- Exterior Mezzanine joists and beams in this area are designed to support blockwall loads:
- Interior Mezzanine joists and beams in this area are designed to support blockwall loads:
- 1.10 m high industrial handrail is provided at free ends of mezzanine:

No

No

Yes

Spacing of Mezzanine columns:

Sr. No.	Mezzanine Loads (kN/m ²)				Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	10.00	0.00	0.00	92	A	-	-	4.351
2	As per Design	10.00	0.00	0.00	15	A	-	-	4.351

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)

Please note that 2.0m width of mezzanine is resting between columns whereas the rest of 2.0m width is over hanging beyond the column.

PARTITIONS

ase refer to section "2" for partition panel description.

The supply of partitions includes all the necessary framing in addition to sheeting as described in the table below.

Insulation for partitions (if included) is holed in the accessories portion of this building.

#	Type	Qty	Length (m)	Height (m)	Open Wall Condition	Sheeting type
1	Longitudinal	2	14.000	Full Height	Fully Sheeted	75mm PU Sandwich Panels
2	Transverse	2	11.760	Full Height	Fully Sheeted	75mm PU Sandwich Panels

Please note that the partition walls are to be installed using U-Channels screwed to existing purlins.