

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 01****MEZZANINES****A. Maimaar standard mezzanine:**

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's "MEZZANINES" brochure for more details of standard Mezzanine.

B. Mezzanine Floor With 3mm Chequered Plate

- Exterior Mezzanine joists and beams in this area are designed to support blockwall loads:
- Interior Mezzanine joists and beams in this area are designed to support blockwall loads:
- 1.10 m high industrial handrail is provided at free ends of mezzanine:

No

No

No

Spacing of Mezzanine columns:

Sr. No.	Mezzanine Loads (KN/m ²)				Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
Admin Building (01)	As per Design	5	0.00	0.00	32.66	A (120mm)	4.42	-	-
Farmal Building (2)	As per Design	5	0.00	0.00	30	A (120mm)	3.048	-	-
Farmal Building (3)	As per Design	5	0.00	0.00	30	A (120mm)	3.048	-	-

*** - Dead Load includes the Self Weight of Concrete and Decking Panels**

Note: For admin building, additional tubes, purlins, trims and sandwich panels are supplied to cover the mezzanine floor and create a room as shown in 3D and drawings. The sandwich panels used are EPS Sandwich Panels (0.5mm PPGI Sheeting+ 50mm Polystyrene Insulation + 0.5mm PPGI Sheeting).