

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 01**

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s**“MEZZANINES”** brochure for more details of standard Mezzanine.

B. Mezzanine with Precast slab or hollow core slab supplied by Maimaar:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

- Exterior Mezzanine joists and beams in this area are designed to support blockwall loads: - Interior Mezzanine joists and beams in this area are designed to support blockwall loads: 1.10 m high industrial handrail is provided at free ends of mezzanine:	No
	No
	No

Spacing of Mezzanine columns:

Sr. No.	Mezzanine Loads (kN/m²)				Area (m²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per design	3.00	0.1	0.00	184	B (As per design)	2.740	-	-

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)

WALL ACCESSORIES		For Basic Price Only
		Quantity per Area
No.	Description	Bldg No. 01
1	Wall Insulation. Type: Fiberglass Thick(mm):100 Density(Kg/m ³)=12 Facing: FRK (Silver) Coverage Area (m ²) = Full Sheeted Area	Full Sheeted Area

ROOF ACCESSORIES		For Basic Price Only
		Quantity per Area
No.	Description	Bldg No. 01
1	Roof Insulation. Type: Fiberglass Thick(mm):100 Density(Kg/m ³)=12 Facing: FRK (Silver) Coverage Area (m ²) = Full Roof Area	Full Sheeted Area