



SECTION 1: BUILDING DESCRIPTION

1.1 BUILDING NO. 01

AREA NO. 01

MEZZANINES									
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.914mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's "MEZZANINES" brochure for more details of standard Mezzanine.									
• Exterior Mezzanine joists and beams in this area are designed to support block wall loads: • Interior Mezzanine joists and beams in this area are designed to support block wall loads: • 1.10 m high industrial handrail is provided at free ends of mezzanine:								No	
								No	
								No	
Spacing of Mezzanine columns:									
Sr. No	Mezzanine Loads (kN/m ²)				Area (m ²)	Type of Floor &Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As Per Design	5	0.00	0.00	12.23	A (100mm Concrete by Others)	3.37	-	-
2	As Per Design	5	0.00	0.00	12.23	A (100mm Concrete by Others)	3.37	-	-
3	As Per Design	5	0.00	0.00	12.23	A (100mm Concrete by Others)	3.37	-	-
4	As Per Design	5	0.00	0.00	12.23	A (100mm Concrete by Others)	3.37	-	-
5	As Per Design	5	0.00	0.00	12.23	A (100mm Concrete by Others)	3.37	-	-
6	As Per Design	5	0.00	0.00	12.23	A (100mm Concrete by Others)	3.37	-	-
7	As Per Design	5	0.00	0.00	12.23	A (100mm Concrete by Others)	3.37	-	-
8	As Per Design	5	0.00	0.00	12.23	A (100mm Concrete by Others)	3.37	-	-
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)									