



SECTION 1: BUILDING DESCRIPTION

1.2 BUILDING NO. 01

MEZZANINES								
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s “MEZZANINES” brochure for more details of standard Mezzanine.								
• Exterior Mezzanine joists and beams in this area are designed to support block wall loads: • Interior Mezzanine joists and beams in this area are designed to support block wall loads: • 1.10 m high industrial handrail is provided at free ends of mezzanine:							No	
							No	
							No	
Spacing of Mezzanine columns:								
Sr. No.	Mezzanine Loads (kN/m²)			Area (m²)	Type of Floor &Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As Per Design	4.0	0.15	88	A (100)	2.830	None	3.500
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)								
STAIRS								
Handrails are fabricated from pipe sections; painted.								
Sr. No.	Located in Mezz. No.	Qty	Stair Type	Out to Out width of staircase (mm)	1.1m High Handrails Included	Qty of Top Landing	Qty of Mid Landing	Stair Height (m)
1	External Staircase	01	Double	1200 65,284	Yes	Yes	Yes	3.458

SECTION 2: PANEL DESCRIPTION

2.1 BUILDING NO. 01

DECKING PANELS		
Single Skin	Profile	Standard Profile
	Material	0.7 mm Galvanized Iron Decking Panels
	Finish	Galvanized Iron
	Color	Maimaar Standard
Note: Special Colors will be charged extra according to quantity and will have longer delivery period.		