



SECTION 1: BUILDING DESCRIPTION

1.1 BUILDING NO. 01

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s **“MEZZANINES”** brochure for more details of standard Mezzanine.

• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:	No
• Interior Mezzanine joists and beams in this area are designed to support block wall loads:	No
• 1.10 m high industrial handrail is provided at free ends of mezzanine:	No

Spacing of Mezzanine columns:

Sr. No.	Mezzanine Loads (kN/m²)			Area (m²)	Type of Floor &Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As Per Design	5.0	None	287.53	A (100)	5.596	None	None.

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)

FASCIA							
The height of the fascia, the fascia projection and optional fascia features greatly affect the fascia price. Optional fascia features include soffit panels, back up panels and valley gutters. Cap flashing is always a standard supply item.							
Type of Fascia: Parapet							
Sr.	Location	Height (m)	Length (m)	Projection FASCIAS (m)	Optional Fascia Features		Gutter Type
					Soffit Panel included	Backup Panel included	
1	Near Sidewall	2.349	14.021	As Per Design	No	No	Eave Gutter