

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1ST AND 2ND FLOOR MEZZANINE****1.1.1 BUILDING NO. 01****AREA NO. 01****MEZZANINES****A. Maimaar standard mezzanine:**

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's **"MEZZANINES"** brochure for more details of standard Mezzanine.

B. Mezzanine with Precast slab or hollow core slab supplied by others:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

- Exterior Mezzanine joists and beams in this area are designed to support block wall loads:

No

- Interior Mezzanine joists and beams in this area are designed to support block wall loads:

No

- 1.10 m high industrial handrail is provided at free ends of mezzanine:

Yes**Spacing of Mezzanine columns:**

Sr. No.	Mezzanine Loads (KN/m ²)				Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Beam	From FFL to Top of Concrete Slab
1	As per design	3.00	0.00	0.00	660	A	4.267 (14')	As per design	As per design
2	As per design	3.00	0.00	0.00	660	A	3.048 (10') from FFL of Mezzanine No. 01	As per design	As per design

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)