

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 01****MEZZANINES****A. Maimaar standard mezzanine:**

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's **"MEZZANINES"** brochure for more details of standard Mezzanine.

B. Mezzanine Floor With 3mm Chequered Plates**C. Mezzanine Floor With Pre-Cast or Hollow Core Concrete Slabs**

- Exterior Mezzanine joists and beams in this area are designed to support block wall loads:
- Interior Mezzanine joists and beams in this area are designed to support block wall loads:
- 1.10 m high industrial handrail is provided at free ends of mezzanine:

No

No

No

Spacing of Mezzanine columns:

Sr. No.	Mezzanine Loads (KN/m ²)				Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	5.00	0.00	0.00	1,659	B (As per design)	4.267	-	-

* - Dead Load includes the Self Weight of Hollow Core Slabs

STAIRS (Maimaar Standard Stair is 1.2m wide and 3.6m high with one intermediate landing).

Stair treads can be red oxide primed checkered plate, painted "U" shaped pans or galvanized Grating.

Handrails are fabricated from pipe sections; these may be primed or painted.

Sr. No.	Located in Mezz. No.	Qty	Stair Type	Out to Out width of staircase (mm)	1.1m High Handrails Included	Qty of Top Landing	Qty of Mid Landing	Stair Height (m)	Type of Treads
1	01	01	Single Flight	1200	Yes	01	01	~4.500	Checkered