

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 01****MEZZANINES****A. Maimaar standard mezzanine:**

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's **"MEZZANINES"** brochure for more details of standard Mezzanine.

B. Mezzanine Floor With 3mm Chequered Plate

- Exterior Mezzanine joists and beams in this area are designed to support blockwall loads:
- Interior Mezzanine joists and beams in this area are designed to support blockwall loads:
- 1.10 m high industrial handrail is provided at free ends of mezzanine:

No**No****No****Spacing of Mezzanine columns:**

Sr. No.	Mezzanine Loads (KN/m ²)				Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
GF Mezzanine Room-1	As per Design	5	0.10	0.00	62.27	120mm (By Others)	-	-	-
GF Mezzanine Room-2	As per Design	5	0.10	0.00	60.50	120mm (By Others)	-	-	-
GF Mezzanine	As per Design	5	0.10	0.00	178.62	120mm (By Others)	-	-	-
FF Mezzanine	As per Design	5	0.10	0.00	159.32	120mm (By Others)	-	-	-
7 th Floor Mezzanine	As per Design	5	0.10	0.00	319.50	120mm (By Others)	2.134	-	-
Opening Mezzanines QTY: 08	As per Design	5	0.10	0.00	14.70	120mm (By Others)	-	-	-

* - Dead Load includes the Self Weight of Concrete and Decking Panels