



SECTION 1: BUILDING DESCRIPTION

1.2 BUILDING NO. 01

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s **“MEZZANINES”** brochure for more details of standard Mezzanine.

Exterior Mezzanine joists and beams in this area are designed to support block wall loads:

No

Interior Mezzanine joists and beams in this area are designed to support block wall loads:

No

1.10 m high industrial handrail is provided at free ends of mezzanine:

No

Spacing of Mezzanine columns:

Sr. No.	Mezzanine Loads (kN/m²)			Area (m²)	Type of Floor &Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	5.0	None	383.46	A (100)	2.234	None	None

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)

STAIRS

Stair treads can be red oxide primed checkered plate.

Handrails are fabricated from pipe sections; painted.

Sr. No.	Located in Mezz. No.	Qty	Stair Type	Out to Out width of staircase (mm)	1.1m High Handrails Included	Qty of Top Landing	Qty of Mid Landing	Stair Height (m)	Type of Treads
1	02	02	Single Flight	1219	None.	Yes	None.	2.234	Pan type