



SECTION 1: BUILDING DESCRIPTION

1.2 BUILDING NO. 01

MEZZANINES								
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s “MEZZANINES” brochure for more details of standard Mezzanine.								
• Exterior Mezzanine joists and beams in this area are designed to support block wall loads: • Interior Mezzanine joists and beams in this area are designed to support block wall loads: • 1.10 m high industrial handrail is provided at free ends of mezzanine:							No	
							No	
							No	
Spacing of Mezzanine columns:								
Sr. No.	Mezzanine Loads (kN/m²)			Area (m²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	5.0	None	42.71	A (100)	3.658	None	None
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)								

***Note: MS-Hand Rail is not considered at Mezzanine.**

SECTION 2: PANEL DESCRIPTION

2.1 BUILDING NO. 01

DECKING PANELS		
Single Skin	Profile	Standard Profile
	Material	0.7 mm Galvanized Iron Decking Panels
	Finish	Galvanized Iron
	Color	Maimaar Standard
Note: Special Colors will be charged extra according to quantity and will have longer delivery period.		