



SECTION 1: BUILDING DESCRIPTION

1.1 BUILDING NO. 01

MEZZANINES								(Option-01)
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's " MEZZANINES " brochure for more details of standard Mezzanine.								
• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:								No
• Interior Mezzanine joists and beams in this area are designed to support block wall loads:								No
• 1.10 m high industrial handrail is provided at free ends of mezzanine:								No
Spacing of Mezzanine columns:								
Sr. No.	Mezzanine Loads (kN/m ²)			Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	5.0	None	141.21	A (120)	4.572	None	None
2	As per Design	5.0	None	141.21	A (120)	3.048	None	None
3	As per Design	5.0	None	141.21	A (120)	3.048	None	None
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)								

MEZZANINES								(Option-02)	
B. Mezzanine with Checkered Plate on Floor:									
No deck is supplied in this option. Checkered Plates, Steel columns, primary beams and connecting joists are supplied.									
- Exterior Mezzanine joists and beams in this area are designed to support block wall loads: - Interior Mezzanine joists and beams in this area are designed to support block wall loads: 1.10 m high industrial handrail is provided at free ends of mezzanine:								No	
								No	
								No	
Spacing of Mezzanine columns:									
Sr. No.	Mezzanine Loads (kN/m ²)			Area (m ²)	Checkered Pl.		Minimum Clear Heights (m)		
	Dead*	Live	Other		Type of Floor	Thick (mm)	From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	5.0	None	141.21	Check.	3	4.572	None	None
2	As per Design	5.0	None	141.21	Check.	3	3.048	None	None
3	As per Design	5.0	None	141.21	Check.	3	3.048	None	None
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)									