



SECTION 1: BUILDING DESCRIPTION

1.1 BUILDING NO. 01

(AREA-01 MEZZANINE EXTENSION)

MEZZANINES								
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s “MEZZANINES” brochure for more details of standard Mezzanine.								
- Exterior Mezzanine joists and beams in this area are designed to support block wall loads: - Interior Mezzanine joists and beams in this area are designed to support block wall loads: 1.10 m high industrial handrail is provided at free ends of mezzanine:							No	
							No	
							Yes	
Spacing of Mezzanine columns:								
Sr. No.	Mezzanine Loads (kN/m ²)			Area (m ²)	Type of Floor &Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	5.0	None	22	A (120) (By others)	4.572	None.	None
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)								