



SECTION 1: BUILDING DESCRIPTION

1.2 BUILDING NO. 01

MEZZANINES								
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7 mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s “MEZZANINES” brochure for more details of standard Mezzanine.								
B. Mezzanine with Precast slab or hollow core slab supplied by others:								
• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:							No	
• Interior Mezzanine joists and beams in this area are designed to support block wall loads:							No	
• 1.10 m high industrial handrail is provided at free ends of mezzanine:							No	
Spacing of Mezzanine columns:								
Sr. No.	Mezzanine Loads (kN/m²)			Area (m²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Floor/ Slab
1	As per design	2.5 KN/Sq .m	-	186	A (100mm Concrete by others)	4.266	-	-
2	As per design	2.5 KN/Sq .m	-	49	A (100mm Concrete by others)	4.266	-	-
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)								

Note: Above mentioned areas exclude openings. Final areas shall be decided as per approval drawings.