



SECTION 1: BUILDING DESCRIPTION

MEZZANINES								
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's "MEZZANINES" brochure for more details of standard Mezzanine.								
• Exterior Mezzanine joists and beams in this area are designed to support block wall loads: • Interior Mezzanine joists and beams in this area are designed to support block wall loads: • 1.10 m high industrial handrail is provided at free ends of mezzanine:							No	
							No	
							No	
Spacing of Mezzanine columns:								
Sr. No.	Mezzanine Loads (kN/m ²)			Area (m ²)	Type of Floor &Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As Per Design	4.0	None	635	A (100)	2.430	None	None.
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)								

SECTION 2: PANEL DESCRIPTION

2.1 BUILDING NO. 01

ROOF PANEL			Mumty's and Dome Area
Single Skin	Profile	Standard Profile	
	Material	0.5 mm PPGI in Roof	
	Finish	Polyester Painted	
	Color	Maimaar Standard	
Note: Special Colors will be charged extra according to quantity and will have longer delivery period.			

Note: -

It is important to select the color of panel required at the time of signing /confirming the order. If a special color is selected after signing the contract which was based on a standard color, additional charge and extended delivery period will be applied.