

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 02**

MEZZANINES									
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s “ MEZZANINES ” brochure for more details of standard Mezzanine.									
B. Mezzanine with Precast slab or hollow core slab supplied by Maimaar: No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.									
- Exterior Mezzanine joists and beams in this area are designed to support Block wall loads: - Interior Mezzanine joists and beams in this area are designed to support Block wall loads: 1.10 m high industrial handrail is provided at free ends of mezzanine:								No	
								No	
								No	
Spacing of Mezzanine columns:									
Sr. No.	Mezzanine Loads (KN/m²)				Area (m²)	Type of Floor &Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	**Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From of FFL to Top of RCC Slab	From FFL to Top of Concrete Slab
Ground Floor – (Refer Drawings for dimensions)									
1	As per Design	4.0 (4.78 at lobbies & 2.0 in class rooms)	0.10	0.0	2547.6	A	3.657	As per Design	As per design
First Floor – (Refer Drawings for dimensions)									
2	As per design	3.0	0.10	0.0	1883.6	A	3.657	As per Design	As per design
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)									