

Functions

Mairead Meagher

Waterford Institute of Technology,

2017



Waterford Institute of Technology
INSTITIÚID TEICNEOLAÍOCHTA PHORT LÁIRGE

Functions

- A function is a relation with extra constraints.
- For each element x in the domain of a function f , there must be only one mapping containing the element x .
- Thus all we have seen about relations can be used with functions.
- Functions and relations are both represented in Z as sets of ordered pairs.
- A function from set X to a set Y and a relation between X and Y are both of type

$$\mathbb{P}(X \times Y)$$

or $X \leftrightarrow Y$

- There must be only one occurrence of each X element in the domain, i.e. members of the domain map

What is a Function




Figure 1: This is not a function




Figure 2: This is a function

Declaring a Function

Formally, we can describe the functionality requirement by the following property for relation R

$$x \mapsto y \in R \wedge (x \mapsto z) \in R \Rightarrow y = z$$

Example

Given:

$[PERSON, MODULE]$

$studies : PERSON \leftrightarrow MODULE$

maps a student to the modules they are currently studying

e.g.

$studies = \{nathan \mapsto prog, nathan \mapsto database, \\ viola \mapsto maths, viola \mapsto prog\}$

is a relation (many-to-many)

$inSemester : PERSON \leftrightarrow \mathbb{N}$

maps a student to their semester number

$inSemester = \{oliver \mapsto 6, nathan \mapsto 6, gabriel \mapsto 8\}$

is a function (many-to-one)

More on Functions

- Two distinct values in the domain to be mapped onto the same element in the range of the function (many-to-one).
- this means that the inverse of a function is not always itself a function

- We have the capability to apply a function to a value.
- The value of **f applied to x** is the value in the range of the function f corresponding to the value x in its domain.
- The application is meaningless if the value of x is not in the domain of f - thus not defined.
- The application of the function f to the value x (called its argument) is written:

$$f\ x$$
$$f(x)$$

or
(i.e. brackets not necessary)

Function Application




Figure 3: Function Application

For example, application of **inSemester** to oliver yields a unique semester number.

$$\text{inSemester}(\text{oliver}) = 6$$

No Such Application with Relations

studies, on the other hand, maps nathan to prog and database, so application is undefined. To follow the relation from nathan, we use the **relational image** of the set containing nathan. This yields a set containing MODULEs.

$$\text{studies}(\{ \text{nathan} \}) = \{ \text{prog}, \text{database} \}$$

The following are all different kinds of functions:

- partial and total
- injective, surjective, bijective
- finite and infinite

The particular properties to be associated with a function for a given type are indicated in Z by the kind of arrow used in the function declaration. For example,

$$f : X \rightarrow Y$$

Partial Functions




Figure 4: Partial Function

- Most general kind of a function.
- All functions are partial
- Partial functions from some set X map some or all of the elements of X .

- A partial function fp from X to Y is declared in Z as :

$$fp : X \rightarrowtail Y$$

- $X \rightarrowtail Y$ denotes the set of all possible partial functions from X to Y .
- For example, if we look at an identity number scheme where not necessarily every person has an identity number. This is declared as

$$identityNo : PERSON \rightarrowtail \mathbb{N}$$

- Formally, we can generically define the partial function arrow.

$$\begin{aligned} X \rightharpoonup Y \equiv & \\ & \{R : X \leftrightarrow Y \mid \\ & (\forall x : X; y, z : Y \bullet x \mapsto y \in R \wedge x \mapsto z \in R \Rightarrow y = z) \\ & \bullet R\} \end{aligned}$$

- Note that this is the set of all functions from X to Y .

- Most functions in Z-specifications are partial.
- This means that function application wont always be defined.
- We need to preclude the application of a partial function to elements outside its domain.
- A useful phrase in specifications is :

$\forall x : \text{dom } f \dots$

- This ensures that youre not applying a function to an element outside its domain. Use this whenever possible!

(Note that there is probably a need for constraining the function so that no two people have the same identity number. That is not implied in the above declaration.)

Total Functions




Figure 5: Total Function

- A total function is one where there is a mapping for every possible value of x , so $f(x)$ is always defined.

- Formally, total functions are functions whose domain is the whole of their source.

$$X \rightarrow Y == \{f : X \rightarrow Y \mid \text{dom } f = X \bullet f\}$$



$$ft : X \rightarrow Y$$

is an example of the declaration of a total function in Z.

Examples of Total Function

- An age function (from PERSON to \mathbb{N}) would be total (every one has an age), so:

$$\text{age} : \text{PERSON} \rightarrow \mathbb{N}$$

- A function to map a number to its double (we call these constant or mathematical functions):

$$\text{double} : \mathbb{Z} \rightarrow \mathbb{Z}$$

Total Functions - Use with care

- Use partial functions when we need to treat mappings as dynamic entities.
- For example, if we have the owner function to model ownership of objects in a database:

owner : OBJECT \rightarrow PERSON

- Because of the totality of the function, objects cannot be deleted from the mapping. Better to use a partial function in this case:

owner : OBJECT \rightarrow PERSON

- Unless the function is obviously total, use partial functions.
- We will see that constant functions (e.g. mathematical functions) are the examples of total functions that we will use.

Injective functions(One-to-one)




Figure 6: Injective Function

- An injection, an injective function, or a one-to-one function is one which maps different values of the source onto different values of the target.

Injective functions(One-to-one)

- Note that the inverse of an injective is itself a function and indeed an injective function.
- In fact, if a function is not an injective function then the inverse is in general a relation.
- For instance, the function *identityNo* is injective if we propose that each identity number is unique.
- We write it as follows:

$$\textit{identityNo} : \textit{PERSON} \mapsto \mathbb{N}$$

Injective functions(One-to-one)

- This is a partial injective function (not everyone has an identity number).
- If we added the constraint that every Person must have an associated identity number, then it becomes a total injective function.

$$\textit{identityNo} : \textit{PERSON} \mapsto \mathbb{N}$$

Injective functions(One-to-one)

- Formally, we can define the meaning of the injective arrows, partial first.
- Partial injective functionc

$$X \multimap Y == \{f : X \multimap Y \mid (\forall x_1, x_2 : \text{dom } f \bullet f(x_1) = f(x_2) \Rightarrow x_1 = x_2) \bullet f\}$$

- Total injective function

$$X \rightarrow Y == \{f : X \rightarrow Y \mid (\forall x_1, x_2 : \text{dom } f \bullet f(x_1) = f(x_2) \Rightarrow x_1 = x_2) \bullet f\}$$

Examples of partial, total injective functions

partial decrement is a function which subtracts one from the positive natural numbers.

$$\text{decrement} : \mathbb{N} \rightarrow \mathbb{N}$$

- Note this is not total because there the function cannot be applied to 0.

total decremementot is a function which subtracts one from all the positive natural numbers to all the natural numbers.

$$\text{decremementot} : \mathbb{N}_1 \rightarrow \mathbb{N}$$

- This is a function from positive natural numbers to the natural numbers, so it is total ($1 - 1 = 0$, and $0 \in \mathbb{N}_1$).

Surjective functions




Figure 7: Surjective Function

- A surjection or a surjective function is a function for which there is a value in the range for every value in the target.

Surjective functions

- Given a function f from X to Y , surjective functions have the property that

$$\text{ran } f = Y$$

- Surjective functions can be partial or total.
- They are written

→ partial surjective function

→ total surjective function

Surjective functions - An Example

- There are 100 student lockers in the college, and 200 students.
- Students are assigned the use of a particular locker, depending on needs.
- All lockers are used. Students may share lockers.
- Not all students are assigned a locker.

[STUDENT, LOCKER]

hasUseOf : STUDENT \rightarrow LOCKER

Surjective functions - An Example

- This is a partial surjective function because all lockers are assigned to (possibly more than one) student.
- If all students were assigned a locker and still all lockers were used, then this would yield

everyoneHasUseOf : STUDENT \rightarrow LOCKER

- However, this means that
'Every STUDENT who ever lived, lives or ever will live'
is assigned a locker.
- This is not usually what we want.

Surjective functions - Formally

Formally,

$$X \twoheadrightarrow Y == \{f : X \twoheadrightarrow Y \mid \text{ran}f = Y \bullet f\}$$

$$X \twoheadrightarrow Y == \{f : X \rightarrow Y \mid \text{ran}f = Y \bullet f\}$$

Note: There should be a vertical line through the arrow for the partial surjection.

Bijjective functions

- A bijection or a bijective function is one which maps every element of the source on to every element of the target in a one-to-one relationship.
- It is
 - injective
 - total, and
 - surjective.
- For example a function that maps uppercase letters to their lowercase equivalents:

lowercase : UPPERCASE \rightarrow LOWERCASE

- This function is bijective because
 - for each uppercase letter there is exactly one corresponding lowercase letter;
 - each lowercase letter has exactly one corresponding uppercase letter.

- A bijection between two sets is a very strong condition and is sometimes called an **isomorphism**; the sets UPPERCASE and LOWERCASE are said to be isomorphic and are essentially the same.
- The only difference between them is the names of their elements.

- It is useful to be able to ignore the issue of whether the sets being used to model the system are finite or infinite.
- The use of infinite sets avoids the need to address implementation issues at this stage. However, sometimes, it may be useful to stress that a function from an infinite set may have a finite domain.
- The set of finite partial functions from X to Y is denoted

$$X \multimap Y$$

- The set of finite partial injections from X to Y is denoted

$$X \multimap_{\text{inj}} Y$$

Summary of notation

- the long arrow indicates a function
- the double arrowhead indicates surjection
- the arrow-shaped tail indicates injection
- a central bar indicates that the function is partial
- a double central bar indicates that a partial function is finite

Constant Functions - Axiomatic Definitions

- Some functions are used as a means of providing a value, given a parameter or parameters.
- These are usually functions which maintain a constant mapping from their input parameters to their output values.
- If the value of the mapping is known, a value can be given to the function by an axiomatic definition
- e.g. to define the function **square**:

$$\begin{array}{|l} \text{square} : \mathbb{N} \rightarrow \mathbb{N} \\ \hline \forall n : \mathbb{N} \bullet \text{square } n = n^2 \end{array}$$

- Several functions may be combined into one axiomatic definition

square : $\mathbb{N} \rightarrow \mathbb{N}$

cube : $\mathbb{N} \rightarrow \mathbb{N}$

$\forall n : \mathbb{N} \bullet \text{square } n = n^2$

$\forall n : \mathbb{N} \bullet \text{cube } n = n^3$

Constant Functions - Set Comprehension

- Constant functions can also be written/specified using set comprehension
- Looking at the square function as seen in the previous slide,

$$\text{square} == \{n : \mathbb{N} \bullet (n, n^2)\}$$

- **Note** that the totality of the function or otherwise can be implied from the need or otherwise of any constraint.
- Both these specifications specify the same function.

- A function can be modified by adding mapping pairs to it or by removing pairs.
- It can also be changed so that for a particular set of values in the domain, the function maps to different values in the range.
- This is done by using the relational override operator.
- It is denoted by :

$$f1 \oplus f2$$

Functional Overriding - \oplus - Example

- Functional Overriding is used for modelling a small change to an existing function.

Example Given the following and using the before \rightarrow after state notation :

bankBalance, bankBalance' : PERSON \rightarrow \mathbb{Z}

...and...

bankBalance = $\{\dots, markus \mapsto 1000, mairead \mapsto 100, \dots\}$

Then the following two statements specify the effect of functional overriding

bankBalance' = bankBalance \oplus $\{markus \mapsto 500\}$

bankBalance' = $\{\dots, markus \mapsto 500, mairead \mapsto 100, \dots\}$

Functional Overriding - \oplus - Class Exercise

- Given

$$f, g : X \rightarrow Y$$

- Write down the specification of

$$f \oplus g$$

Given

$$f, g : X \rightarrow Y$$

$$f \oplus g = g \cup (\text{dom } g \triangleleft f)$$

Note that the function overriding

- updates (changes) the mapping if it exists;
- adds the mapping if it's not already there

Another example - Barack's birthday

Given

$$age : PERSON \rightarrow \mathbb{N}$$

$$age = \{\dots, barack \mapsto 55, \dots\}$$

$$age' = age \oplus \{barack \mapsto 56\}$$

then

$$age' = \{\dots, barack \mapsto 56, \dots\}$$

But: Is there anyway of 'formulating'

It's Barack's birthday - increase his age by one.

?

Try this as an exercise. (Hint : use function application.)

Another example - Barack's birthday - Solution

Solution:

$$age' = age \oplus \{barack \mapsto age(barack) + 1\}$$

More generally: The recorded age of a person **p?** is to be increased by one. (Note we would need to be sure that $p \in \text{dom } age$)

$$age' = age \oplus \{p? \mapsto age(p?) + 1\}$$

The function **age** is overridden by the function with only **p?** in its domain which maps to the former value plus one (using function application).

Functions of Several arguments

A function is just a set of pairs. So a function can only have one argument - the first member of the pair. If the function really has several arguments, these are combined into a single element.

wedding : (*PERSON* \times *PERSON*) $\rightarrow \mathbb{N}$

then

wedding = $\{(brad, angelina) \mapsto 2014, (angela, joachim) \mapsto 1968, (homer, marge) \mapsto 1985)\}$

- Note that were mixing the (x, y) and $x \mapsto y$ notation for clarity.
- Note that this model does not allow the same couple to marry twice!

Curried Functions

Sometimes there is a more useful way of expressing functions of more than one argument. For instance if a person can have a bank account at several different banks, we might model the information as follows:

$$\textit{balance} : (\textit{PERSON} \times \textit{BANK}) \rightarrow \mathbb{Z}$$

For example:

$$\begin{aligned} \textit{balance} = \{ & (\textit{georgShaeffler}, \textit{NRW}) \mapsto 100000, \\ & (\textit{suzanneKlatten}, \textit{Commerzbank}) \mapsto 500000, \\ & (\textit{suzanneKlatten}, \textit{DeutscheBank}) \mapsto 1000000, \\ & (\textit{LarryLecturer}, \textit{Volksbank}) \mapsto 50 \} \end{aligned}$$

This doesn't naturally answer the question for *suzanneKlatten*
'how much money do I have in all my accounts?'

Another way of modelling the above information :

$balance_2 : PERSON \rightarrow (BANK \rightarrow \mathbb{Z})$

$balance_2 = \{ \dots$

$georgShaeffler \mapsto \{(NRW, 100000)\},$

$suzanneKlatten \mapsto \{(Commerzbank, 500000),$
 $(DeutscheBank, 1000000)\},$

$LarryLecturer \mapsto \{(Volksbank, 50), \dots\}$
 $\dots\}$

- This function is a function from a person to a function mapping all the accounts that person has to the amount in that account.
- This use of a function on the left hand side is called “Currying”.

Which data model to use?

- There will usually be many ways to model the data we are analysing.
- We choose the option that best helps to simplify the operations that need to be specified.
- This is not an exact Science.
- We look for elegance and clarity of specification.

Any questions?

