

# PROGRAMMING IN HASKELL



## Chapter 8.2 Function Application

# \$ as function application

\$ is the function application operator

```
($) :: (a -> b) -> a -> b
```

$$f \$ x = f x$$

# \$ as function application

It's function application but:

- normal function application has high precedence,
- \$ has low precedence
- normal function application is left associate, e.g.,  
 $f\ a\ b\ c === ((f\ a)\ b)\ c$
- \$ is right associative

# \$ as function application

```
*Main> (^2) 4 + 3  
19
```

```
*Main> (^2) $ 4 + 3  
49
```

# Improved syntax with \$

Most often it's a convenience that lets us write fewer parentheses.

Example:

```
sum (map sqrt [1..130])
```

Is better written as:

```
sum $ map sqrt [1..130]
```

when \$ is encountered, expression on right is used as parameter to function on left

## More examples

`sqrt (3+4+9)`



`sqrt $ 3+4+9`

```
*Main> sum (filter (> 10) (map (*2) [2..10]))
```

80

```
*Main> sum $ filter (> 10) (map (*2) [2..10])
```

80

```
*Main> sum $ filter (> 10) $ map (*2) [2..10]
```

80

## Another example

```
*Main> (10*) $ 3
```

```
30
```

```
*Main> ($ 3) (10*)
```

```
30
```

```
map ($ 3) [(4+), (10*), (^2), sqrt]  
[7.0,30.0,9.0,1.7320508075688772]
```

How does this work?

expression on right is used as parameter to  
function on left

