

Foody External API Integration Document

V 0.0.7
12, July, 2021

1 / 50

Change History

No	Version	Content of Change	Who	Date
----	---------	-------------------	-----	------

1	0.0.1	Created	Ho Xuan Hien	26 Feb
2	0.0.2	Add dish API, topping API and restaurant API	Cao Cong Danh	12 March
3	0.0.3	Add Driver callback API	Cao Cong Danh	04 Nov
4	0.0.4	Add api restaurant_api: get_restaurant_info, get_operation_time_ranges, set_operation_time_ranges	Doan Minh Hieu	21 May
5	0.0.5	Allow cascade restaurants in brand, api: dish.create, dish.update, topping.create, topping.update, topping.update_prices	Doan Minh Hieu	9 July
6	0.0.6	Remove unsupported APIs: dish.bulk_create_group, dish.bulk_update_group	Doan Minh Hieu	24 June, 2021
7	0.0.7	Update signature example	Doan Minh Hieu	12 July, 2021

8	0.0.8	Update /s2s/order/update : add reason_id 79 and 81	Nhung Nguyen	18 Sept 2023

2 / 50

Table of Contents

1. Access and signature

Access

Signature

2. Data Definition

2.1 Restaurant

2.2 Dish

2.3 Dish Group

2.4 Topping

ExternalAppType

ClientType

OrderMerchantStatus

OrderUpdateStatus RejectOrderReason

DishStatus

ToppingStatus

MenuObjectType

MenuObjectUpdateType

ShippingMethod OrderUpdateType

PartnerErrorType

ToggleType

ConfirmMethod

Weekday

PaymentMethod

MerchantPaidStatus

BuyerPaymentMethod

3. FoodyAPI Definition

General

3.1 OrderApi

[3.2DishApi dish.create](#)

[dish.bulk_create](#) [dish.update](#)
[dish.bulk_update](#)
[dish.update_partner_id_mappings](#)
[dish.delete](#) [dish.set_statuses](#)
[dish.get_out_of_service](#)
[dish.create_topping_mapping](#)
[dish.delete_topping_mapping](#)
[dish.create_group](#)
[dish.bulk_create_group](#)
[dish.update_group](#)
[dish.bulk_update_group](#)
[dish.delete_group](#)
[dish.update_partner_group_id_mappings](#) [dish.get_groups](#)
[dish.get_partner_group_id_mappings](#) [dish.get](#)
[dish.get_partner_id_mappings](#)
[dish.get_topping_mapping](#)
[dish.get_group_detail](#)
[dish.get_detail](#)
[dish.upload_picture](#)
[dish.delete_picture](#)
[dish.get_approval_status](#)

[3.3ToppingApi topping.create_group](#)

[topping.bulk_create_group](#)
[topping.update_group](#)
[topping.bulk_update_group](#)
[topping.delete_group](#)
[topping.update_partner_group_id_mappings](#)
[topping.create_topping.bulk_create](#)

4/5

0 [topping.update](#) [topping.bulk_update](#) [topping.delete](#)
[topping.update_partner_id_mappings](#) [topping.get_groups](#)
[topping.get_partner_group_id_mappings](#) [topping.get](#) [topping.get_partner_id_mappings](#)
[topping.get_group_detail](#) [topping.get_detail](#) [topping.set_group_quantity](#)
[topping.update_prices](#) [topping.set_statuses](#) [topping.get_out_of_service](#)

[3.4 Restaurant Api restaurant.get_restaurant_info](#)

[restaurant.get_operation_time_ranges](#)
[restaurant.set_operation_time_ranges](#)

[3.5 Internal Api driver.update_arriving_times](#)

[3.5 Menu Api menu.sync](#)

[4. Webhooks](#)

[4.1 Order Api](#)

[partner api url callback/update order](#)

[4.2 Menu Api](#) [partner api url callback](#)

[export error menu](#)

[4.3 Driver Api](#)

[partner api url callback/update drivers status](#)

5 / 50

1. Access and signature

• Access

To access Foody External API, you need to

- Apply to whitelist your ip addresses.
- Get signature key to sign your request data

• Signature

HTTP requests must be signed by the requester. The key used to sign requests could be app_key or post_key.

For example, if the request is

```
POST /s2s/order/update HTTP/1.1
Content-Type: application/json
Host: testexternalapi.deliverynow.vn
Content-Length: 63

{
  "now_order_id": 11378,
  "order_id": 119,
  "status": 3,
}
```

Here are the steps to generate the signature.

1. Generate Signature Base String

The Signature Base String is a consistent reproducible concatenation of the request elements into a single string. It includes 3 parts.

- The HTTP request method used to send the request. Value MUST be uppercase, for example: HEAD, GET , POST, etc.

Here it is **POST**

b. The full request URL includes GET parameters. Here it is
<http://testexternalapi.deliverynow.vn/s2s/order/update> c. The HTTP request
body Here it is
{ "now_order_id":11378,"order_id":119,"status":3}
Then join these 3 parts with "|" to get the Signature Base String.
Here it is

6 / 50

POST|<http://testexternalapi.deliverynow.vn/s2s/order/update>|{"now_order_id":11378,"order_id":119,"status":3}

Example with GET request:
if full request URL is like
this:

http://testexternalapi.deliverynow.vn/s2s/order/get_list?from_item_id=0&request_count=30&sort=1&status=1&from_date=2018-08-17&last_request=2017-08-22+11%3A00%3A33 then

Signature Base String will be:

GET|http://testexternalapi.deliverynow.vn/s2s/order/get_list?from_item_id=0&request_count=30&sort=1&status=1&from_date=2018-08-17&last_request=2017-08-22+11%3A00%3A33| Please
notice that HTTP request body is empty in this case

2. Calculate the signature

base_string must be encoded with UTF-8 encoding before calculating signature
Signature = HEX(HMAC-SHA256(Key=key.decode('hex'), Data=base_string)) If
the key is [5feceb66ffc86f38d952786c6d696c79](#) and the base string is:

GET|http://testexternalapi.deliverynow.vn/s2s/order/get_list?from_item_id=0&request_count=30&sort=1&status=1&from_date=2018-08-17&last_request=2017-08-22+11%3A00%3A33| Then
the signature is [c514bd078e8ff4f1c9e2c0c296f99f98ce20aaa1e1dc37e2f82415758fe0affb](#)
(Notice that the key need to be decoded from hexadecimal in advance, otherwise the incorrect
signature will be [4e1b0e4fcf9a1d3fee599204595423089d7adc94789faaf2f120e9af5ab49e8a](#))

3. Add signature in HTTP header

Append "Authorization" Header in HTTP request. The format is as follows.

Authorization: Signature e4874f45173996c8e3e35a6f513c28a8fa022e1e04f4b5d570468fe12eb4386f

So the final HTTP request is as follows.

POST /s2s/order/update HTTP/1.1 Content-Type: application/json Host: testexternalapi.deliverynow.vn Content-Length: 65 Authorization: Signature e4874f45173996c8e3e35a6f513c28a8fa022e1e04f4b5d570468fe12eb4386f X-FoodyApp-Id:

```
10001
X-Foody-API-Version: 1
X-Foody-Request-Id: 1
X-Foody-Language: vi
{
  "now_order_id": 11378,
```

7 / 50

```
"order_id": 119,
"status": 3
}
```

2. Data Definition

2.1 Restaurant

Restaurants are entities to sell their products to customers. And brand name can be to have restaurants.

2.2 Dish

Dish is items that are sold for customer from Merchant, for dishes example: Chicken Cordon Bleu, Spaghetti with Sausage and Tomato Sauce

2.3 Dish Group

Dishes that are the same functions will be grouped together that is called dish group

2.4 Topping

A layer of food poured or spread over a base of a different type of food to add flavor. For topping example for Pizza: Black olives, Green peppers,...

- **ExternalAppType**

EXTERNAL_CLIENT_APP = 10004 (request foody to get your app id)

- **ClientType**

CLIENT_WEB = 1

- **OrderListStatus**

PROCESSING = 1

COMPLETED = 2

CANCELLED = 3

CONFIRMED = 4

8 / 50

- **OrderMerchantStatus**

PICKED = 1 (Driver picks order at the store)

DELIVERED = 2 (Order is delivered)

CONFIRMED = 3 (Order is confirmed)

M_CHANGED = 4 (Not in use)

M_ASSIGNED = 5 (Order is assigned/sent to merchant)

M_RECEIVED = 6 (After merchants responses 200, order is marked as received by merchant) M_OUT_OF_SERVICE = 7 (Order cannot be fulfilled by merchant and awaiting to be canceled) CANCELLED = 8 (Order is canceled)

M_TIMEOUT = 9 (Not in use)

VERIFIED = 10 (Not in use)

- **Order Status Machine**

Happy flow: M_ASSIGNED >> M_RECEIVED >> CONFIRMED >> PICKED >> DELIVERED

Canceled order: M_ASSIGNED >> M_RECEIVED >> M_OUT_OF_SERVICE >> CANCELED

- **OrderUpdateStatus**

CONFIRM = 0 (Merchant can update this status to confirm orders)

RECEIVED = 1 (not in use)

OUT_OF_SERVICE = 2 (Merchant can update this status to send request to cancel orders to SPF)

DONE = 4 (not in use)

CANCEL = 6

RejectOrderReason

WRONG_MENU = 1

RESTAURANT_BUSY = 2

RESTAURANT_CLOSING = 3

WRONG_COMMISSION = 4 CUSTOM

= 5

9 / 50

- **DishStatus**

AVAILABLE = 1

OUT_OF_STOCK = 2

INACTIVE = 3

- **ToppingStatus**

AVAILABLE = 1

OUT_OF_STOCK = 2

INACTIVE = 3

- **MenuObjectType**

DISH_TYPE = 1

DISH = 2

DISH_ATTRIBUTE = 3 (Topping Group)

DISH_ATTRIBUTE_VALUE = 4 (Topping)

- **MenuObjectUpdateType**

ADD = 1

CHANGE_STATUS = 2

UPDATE = 3

DELETE = 4

REJECT_REQUEST = 5

- **ShippingMethod**

FOODY_DELIVERY = 1

MERCHANT_DELIVERY = 2

CUSTOMER_PICKUP = 3

- **OrderUpdateType**

UPDATE_ORDER = 1

UPDATE_ORDER_STATUS = 2

- **PartnerErrorType**

EXPORT_FAIL = 1

PARTNER_ITEM_ID_NONE = 2

- **ToggleType**

OFF = 0

10 / 50

1

ON =

- **ConfirmMethod**

MANUAL = 1

AUTO = 2

- **Weekday**

MONDAY = 1

TUESDAY = 2

WEDNESDAY = 3 THURSDAY

= 4

FRIDAY = 5

SATURDAY = 6

SUNDAY = 7

- **PaymentMethod**

COD = 1

MERCHANT_WALLET = 6

- **MerchantPaidStatus**

UN_PAID = 1

PAID = 2

FAIL = 3

REFUNDED = 4

- **BuyerPaymentMethod(Not online)**

COD = 1

CYBER_SOURCE = 4

TOPPAY = 6

VNPAY = 8

3. Foody API Definition

General

HTTP Request Domain:

Live: <https://gexternalapi.deliverynow.vn>

Staging: <https://gstageexternalapi.deliverynow.vn> Test:

<https://gexternalapi.test.now.vn>

QA: <https://gqaexternalapi.test.now.vn> Request:

11 / 50 GET / POST

Content-Type: application/json Header:

required ExternalAppType X-Foody-App-Id required uint32 XFoody-API-Version: current version is 1 required uint32 XFoody-Request-Id: random integer in range (0,

10^10) required string X-Foody-Country: VN, TH optional string

X-Foody-Language: vi, en, th ...(default: en) Reply:

Http status = 200 (other error codes need to be retry)

Json data in body

{“result”: result_code, “reply”: //json_format_define_in_s2s//} Common

Result Code:

success error_params

error_header

error_server

error_forbidden

error_access_token

error_version_too_low

w

3.1 Order Api

List api support management order flow

- **order.get_list**

Description: Get list order by status and date time

Method: POST

URI: /s2s/order/get_list Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required
OrderListStatus status required string
from_date: in format yyyy-mm-dd
optional string to_date: in format yyyy-mm-dd (default: end of current day)
required uint32 limit (max 100) required
uint32 offset

Reply:

required array orders required
OrderMerchantStatus status required
string code

12 / 50

required object restaurant:
 required uint32 id required
 string name
optional object assignee:
 required uint32 id
 required string name
 required string phone
 required string
 order_time (format like
 2017-07-15 14:30:00) optional string pick_time
(format like 2017-07-15 14:30:00)
optional string delivery_time (format like 2017-07-15 14:30:00)
required string distance required
object order_value required
uint32 value required string unit
required string text required
object total_value required
uint32 value required string unit
required string text
optional object pay_to_merchant:
 required PaymentMethod type
optional MerchantPaidStatus status Error: error_params Sample:

Request:

```
POST /s2s/order/get_list
restaurant_id=148
from_date="2018-03-14"
status=1 limit=100 offset=0
```

Reply:

```
{"reply":{"orders":[{"status":9,"distance":"2.4 km","code":"14039-421176156","order_value":{"text":"291,000đ","value":291000.0,"unit":"đ"},"order_time": "2019-03-14 11:41:57","restaurant":{"id":148,"name":"Quán demo"},"total_value":{"text":"145,500đ","value":145500.0,"unit":"đ"},"delivery_time":"2019-03-14 12:55:00","pick_time":"2019-03-14 12:40:00","pay_to_merchant":{"status":1,"type":1}}],"result":"success"}}
```

• order.get_details

Description: Get order details

13 / 50

Method: POST

URI: /s2s/order/get_details Request:

required string order_code

optional ToggleType mark_as_received // default = ToggleType.ON Reply:

required string code required

string serial

optional object customer_pay: required

BuyerPaymentMethod type optional

object pay_to_merchant:

required PaymentMethod type

optional MerchantPaidStatus status

required object restaurant: required uint32

id required string name required

string partner_restaurant_id

required OrderMerchantStatus status required string order_time
(format like 2017-07-15 14:30:00)

optional string pick_time (format like 2017-07-15 14:30:00) optional

string delivery_time (format like 2017-07-15 14:30:00) optional

object assignee required uint32 id required string name required

string phone optional object deliver_address required uint32 id

required string name required string phone required string address

optional DeliveryOption delivery_option optional

string gate

optional object customer required

string name required

string phone

required object shipping: required
ShippingMethod type required
string name
required object extra_fee required
uint32 value required string unit
required string text required object
total_merchant_discount

14 / 50

requireduint32value requiredstringunit
Requiredstringtext
requiredobjectorder_value
requireduint32value requiredstringunit
requiredstringtext
requiredobjectcommission_amount
requireduint32value requiredstringunit
requiredstringtext
requiredobjecttotal_value
requireduint32value
requiredstringunit requiredstringtext
requiredobjectcustomer_bill required
double total_amount
requireduint32value
requiredstringunit requiredstringtext
requireddoublesurcharge_fee
requireduint32value
requiredstringunit requiredstringtext
requireddoubleservice_fee
requireduint32value
requiredstringunit requiredstringtext
requireddoubleshipping_fee
requireduint32value
requiredstringunit requiredstringtext
requireddoublepacking_fee
requireduint32value
requiredstringunit requiredstringtext
requireddoublehand_deliver_fee
requireduint32value
requiredstringunit requiredstringtext
requireddoublevat_deliver_fee
requireduint32value
requiredstringunit

15/50

required string text

required double confirm_fee
 required uint32 value
 required string unit required
 string text
 required double merchant_discount
 required uint32 value
 required string unit required
 string text
 required double foody_discount
 required uint32 value
 required string unit required
 string text
 required double total_discount
 required uint32 value
 required string unit required
 string text
 required array object merchant_discounts required
 string name
 optional string code
 required object merchant_discount
 required uint32 value
 required string unit
 required string text
 optional string note optional
 string merchant_note optional
 string note_for_shipper
 optional string cs_note optional
 object vat_info:
 required uint32 id required string
 tax_number required string address
 required string company_name
 required OrderMerchantStatus
 status
 required bool allow_cancel
 optional bool allow_confirm // if current status is M_TIMEOUT optional
 string confirm_expired_time (format like 2017-07-15 14:30:00)
 optional int confirm_remaining_time (in seconds) required array object
 dish_groups required uint32 dish_group_id optional string
 partner_dish_group_id
 required string group_name required
 array object dishes

required uint32 dish_id
 optional string partner_dish_id

required string dish_name
required uint32 quantity
required bool out_of_stock
required object price:
required uint32 value
required string unit required
string text
optional object original_price:
 required uint32 value
 required string unit
 required string text
 required object total:
 required uint32 value
 required string unit
 required string text
optional string note optional
string cs_note
required array object topping_groups:
 required uint32 topping_group_id optional
 string partner_topping_group_id
 required string group_name required
 array object toppings:
 required uint32 topping_id optional
 string partner_topping_id required
 string topping_name required
 uint32 quantity required object
 price required uint32 value
 required string unit required string
 text
 required object original_price
 required uint32 value required
 string unit

required string text Error: error_params

Sample:

Request: POST /s2s/order/get_details
--

order_code=14039-421176156

Reply:

```
{
  "reply": {
    "status": 9,
    "delivery_time": "2019-03-14 12:55:00",
    "code": "14039-421176156",
    "order_value": {
      "text": "291,000đ",
      "value": 291000.0,
      "unit": "đ"
    },
    "order_time": "2019-03-14 11:41:57",
    "restaurant": {
      "id": 148,
      "name": "Quán demo"
    },
    "confirm_remaining_time": 0,
    "extra_fee": {
      "text": "0đ",
      "value": 0.0,
      "unit": "đ"
    },
    "total_value": {
      "text": "145,500đ",
      "value": 145500.0,
      "unit": "đ"
    },
    "allow_cancel": false,
    "dish_groups": [
      {
        "dish_group_id": 580,
        "dishes": [
          {
            "dish_id": 142191,
            "quantity": 1,
            "price": {
              "text": "88,000đ",
              "value": 88000.0,
              "unit": "đ"
            },
            "topping_groups": [
              {
                "topping_group_id": 3604,
                "toppings": [
                  {
                    "topping_name": "Thạch Topping",
                    "price": {
                      "text": "3,000đ",
                      "value": 3000.0,
                      "unit": "đ"
                    },
                    "topping_id": 48562,
                    "quantity": 1
                  },
                  {
                    "topping_name": "Thạch",
                    "order_dish_id": 246799,
                    "dish_name": "CHOCOLATE",
                    "total": {
                      "text": "88,000đ",
                      "value": 88000.0,
                      "unit": "đ"
                    },
                    "out_of_stock": 0
                  },
                  {
                    "dish_id": 142190,
                    "quantity": 1,
                    "price": {
                      "text": "113,000đ",
                      "value": 113000.0,
                      "unit": "đ"
                    },
                    "topping_groups": [
                      {
                        "topping_group_id": 3602,
                        "toppings": [
                          {
                            "topping_name": "100",
                            "price": {
                              "text": "10,000đ",
                              "value": 10000.0,
                              "unit": "đ"
                            },
                            "topping_id": 48563,
                            "quantity": 1
                          },
                          {
                            "topping_name": "Đá Topping",
                            "price": {
                              "text": "0đ",
                              "value": 0.0,
                              "unit": "đ"
                            },
                            "topping_id": 48560,
                            "quantity": 1
                          }
                        ],
                        "group_name": "Đá"
                      }
                    ],
                    "order_dish_id": 246800,
                    "dish_name": "ICE BLENDED COFFEE",
                    "total": {
                      "text": "113,000đ",
                      "value": 113000.0,
                      "unit": "đ"
                    },
                    "out_of_stock": 0
                  },
                  {
                    "group_name": "Coffee"
                  }
                ],
                "dish_group_id": 35863,
                "dishes": [
                  {
                    "dish_id": 142193,
                    "quantity": 1,
                    "price": {
                      "text": "90,000đ",
                      "value": 90000.0,
                      "unit": "đ"
                    },
                    "topping_groups": [],
                    "order_dish_id": 246801,
                    "dish_name": "SMOOTHIES",
                    "total": {
                      "text": "90,000đ",
                      "value": 90000.0,
                      "unit": "đ"
                    },
                    "out_of_stock": 0
                  },
                  {
                    "group_name": "Tea"
                  }
                ],
                "total_merchant_discount": {
                  "text": "0đ",
                  "value": 0.0,
                  "unit": "đ"
                },
                "allow_confirm": true,
                "pick_time": "2019-03-14 12:40:00",
                "serial": "0x0000000000C9C25F",
                "pay_to_merchant": {
                  "status": 1,
                  "type": 1,
                  "customer_pay": {
                    "type": 1
                  },
                  "merchant_discounts": [],
                  "result": "success"
                }
              }
            ]
          }
        ]
      }
    ]
  }
}
```

● **order.update**

Description: update merchant order

Method: POST URI:

/s2s/order/update

Request:

required string order_code required string serial

required OrderUpdateStatus status optional

ConfirmMethod confirm_method // default =

ConfirmMethod.MANUAL optional string pick_time (format like 2017-07-15

14:30:00) optional string merchant_note optional string note_for_shipper optional

object cancel_reasons:

optional array uint32 reason_ids (get from meta)

-reason_id 79 : [VI] Quán hết món [EN] Out of Stock

-reason_id 81 : [VI] Quán đóng cửa [EN] Shop was closed

optional string other_reason

optional uint32 restaurant_id optional string partner_restaurant_id

(required this or restaurant_id) optional ConfirmType confirm_type

optional object reject_reasons optional RejectOrderReason type
optional object price_updates

optional array dishes
required uint32 order_dish_id
required uint32 dish_id required
double price
optional array toppings required
uint32 order_dish_id required
uint32 dish_id required
uint32 topping_id required
double price
optional object out_of_stock optional array dishes required uint32
order_dish_id required uint32 dish_id required string from
(format like 2017-07-15 14:30:00) required string to
(format like 2017-07-15 14:30:00)
optional array toppings required uint32
order_dish_id
required uint32 topping_id required string from
(format like 2017-07-15 14:30:00) required string to
(format like 2017-07-15 14:30:00)
optional object busy_info optional uint32
total_minute
optional string from (format like 2017-07-15 14:30:00)
optional string to (format like 2017-07-15 14:30:00)
optional string custom_note Reply:

Empty

Error:

error_out_of_update_order
error_require_assignee_or_res_id
error_order_total_amount_invalid
error_restaurant_invalid
error_order_sub_total_value
error_order_pick_time_invalid
error_order_cannot_pay Sample:

Request:

POST /s2s/order/update status=1 order_code= "ABDE124" merchant_note='note...'

Reply:

19 / 50

{"reply": {"pay_to_merchant" : {"type": 6, state": 2}}, "result": "success"}

Sample(cancel):

Request:

POST /s2s/order/update

```
{
  "order_code": "05093-476149827",
  "serial": "6f0171ab2c2e9b56ec3dec211a95e926",
  "status": 6,
  "restaurant_id": 774647,
  "cancel_reasons": {
    "reason_ids": [79, 81]
  }
}
```

Reply:

```
{"reply": null, "result": "success"}
```

3.2 Dish Api

- **dish.create**

Description: create dish

Method: POST URI:

/s2s/dish/create

Request:

optional uint32 restaurant_id optional string partner_restaurant_id
 (required this or restaurant_id)
 required string partner_dish_id
 required string name required string
 partner_dish_group_id required double
 price
 optional string name_en
 optional int32 display_order
 optional string description
 optional uint32 picture_id
 optional bool is_apply_all
 optional array uint32
 branch_ids Reply:
 required bool is_pending optional
 uint32 dish_id Sample:

Request:

POST /s2s/dish/create

Reply:

```
{"reply": {"dish_id": 10, "is_pending": False}, "result": "success"}
```

- **dish.bulk_create**

Description: bulk create dish

Method: POST

URI: /s2s/dish/bulk_create Request:

optional uint32 restaurant_id optional string partner_restaurant_id

(required this or restaurant_id)
required array object dishes required
string partner_dish_id

20 /

50 required string name required string partner_dish_group_id required
double price
optional string name_en
optional int32 display_order optional string description
optional uint32 picture_id Reply:

Sample:

Request: POST /s2s/dish/bulk_create Reply: { "result": "success", "reply": [] }

● dish.update

Method: POST URI:

/s2s/dish/update

Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required
string partner_dish_id optional string
name optional string
name_en optional string
partner_dish_group_id optional
double price optional uint32
display_order optional string
description optional uint32 picture_id
optional bool is_apply_all optional
array uint32 branch_ids

Reply: required bool is_pending Error:

error_object_invalid_to_update Sample:

Request:

POST /s2s/dish/update

Reply:

```
{"reply":{"is_pending": False}, "result":"success"}
```

- **dish.bulk_update**

Method: POST

URI: /s2s/dish/bulk_update Request:

optional uint32 restaurant_id optional string partner_restaurant_id

(required this or restaurant_id)

required array object dishes required

string partner_dish_id

optional string name optional string

name_en optional string

partner_dish_group_id optional

double price

optional uint32 display_order

optional string description optional uint32 picture_id

Sample:

Request:

POST /s2s/dish/bulk_update

Reply:

```
{  
  "result":"success",  
  "reply": []  
}
```

- **dish.update_partner_id_mappings**

Method: POST

URI: /s2s/dish/update_partner_id_mappings Request:

required uint32 restaurant_id required

array object dishes required uint32 dish_id required

string partner_dish_id Reply:

Error:

22 / 50

Sample:

Request:

POST /s2s/dish/update_partner_id_mappings **Reply:**

```
{"reply":null, "result":"success"}
```

- **dish.delete**

Method: POST URI:

/s2s/dish/delete

Request:

optional uint32 restaurant_id optional string partner_restaurant_id (required this or restaurant_id) required string partner_dish_id Reply:

required bool is_pending Sample:

Request: POST /s2s/dish/update Reply: { "reply": { "is_pending": False }, "result": "success" }
--

- **dish.set_statuses**

Method: POST

URI: /s2s/dish/set_statuses Request:

optional uint32 restaurant_id optional string partner_restaurant_id (required this or restaurant_id) optional bool is_apply_all optional array uint32 branch_ids

required array object dishes required string partner_dish_id required DishStatus status optional string from_time // format: YYYY-MM-DD hh:mm:ss, required if

set OUT_OF_STOCK optional string to_time // required if set OUT_OF_STOCK

Sample:

Request:

23 / 50

POST /s2s/dish/set_statuses Reply: { "reply": null, "result": "success" }
--

- **dish.get_out_of_service**

Method: POST

URI: /s2s/dish/get_out_of_service Request:

optional uint32 restaurant_id optional string partner_restaurant_id (required this or restaurant_id) required array string partner_dish_ids Reply:

required array object dishes:

required uint32 dish_id required string partner_dish_id required

string from_time required string
to_time

Sample:

Request: POST /s2s/dish/get_out_of_service Reply: { "reply": { "dishes": [] }, "result": "success" }

- **dish.create_topping_mapping**

Method: POST

URI: /s2s/dish/create_topping_mapping Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required
string partner_dish_id
optional bool is_apply_all optional
array uint32 branch_ids
required array toppings required string
partner_topping_id required double
price
optional boolean is_required Error:
error_object_invalid_to_update

24 / 50

Sample:

Request: POST /s2s/dish/create_topping_mapping Reply: { "reply": None, "result": "success" }
--

- **dish.delete_topping_mapping**

Method: POST

URI: /s2s/dish/delete_topping_mapping Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required
string partner_dish_id required array
string

partner_topping_ids Error: error_object_invalid_to_update

Sample:

Request: POST /s2s/dish/delete_topping_mapping Reply:
--

```
["reply": None, "result": "success"]
```

- **dish.create_group**

Description: create dish group

Method: POST

URI: /s2s/dish/create_group Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required
string partner_dish_group_id required
string name
optional string name_en
optional int32 display_order
optional string description
optional bool is_apply_all
optional array uint32
branch_ids

Reply:

required uint32 dish_group_id

25 / 50

Error: error_object_invalid_to_update Sample:

Request:

POST /s2s/dish/create_group

Reply:

```
["reply": {"dish_group_id": 1}, "result": "success"]
```

- **dish.update_group**

Description: update dish group

Method: POST

URI: /s2s/dish/update_group Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required
string partner_dish_group_id
optional string name optional string
name_en optional int32
display_order optional string
description optional bool
is_apply_all optional array uint32
branch_ids

Reply:

Error: error_object_invalid_to_update Sample:

Request:

POST /s2s/dish/update_group

Reply:

{"reply": null, "result": "success"}

- **dish.delete_group**

Method: POST

URI: /s2s/dish/delete_group Request:

optional uint32 restaurant_id

optional string partner_restaurant_id (required this or restaurant_id)

26 / 50 required string partner_dish_group_id Reply:

Sample:

Request:

POST /s2s/dish/delete_group

Reply:

{"reply": null, "result": "success"}

- **dish.update_partner_group_id_mappings**

Method: POST

URI: /s2s/dish/update_partner_group_id_mappings Request:

required uint32 restaurant_id required array

object dish_groups required uint32 dish_group_id required

string partner_dish_group_id Reply:

Sample:

Request:

POST /s2s/dish/update_partner_group_id_mappings

Reply:

{"reply": null, "result": "success"}

- **dish.get_groups**

Description: get dish groups

Method: GET

URI: /s2s/dish/get_groups Request:

optional uint32 restaurant_id
optional string partner_restaurant_id (required this or restaurant_id) Reply:
required array dish_groups:
 required uint32 dish_group_id
 required string
 partner_dish_group_id required
 string name required string name_en

27 / 50 optional string description

required uint32 display_order Sample:

Request: GET /s2s/dish/get_groups Reply: {"reply":{"dish_groups":[]},"result":"success"}
--

- **dish.get_partner_group_id_mappings**

Description: get dish group mapping

Method: GET

URI: /s2s/dish/get_partner_group_id_mappings Request:

required uint32 restaurant_id Reply:

 required array dish_groups:

 required uint32 dish_group_id

required uint32 pos_id required string

partner_dish_group_id required string name Sample:

Request: GET /s2s/dish/get_partner_group_id_mappings Reply: {"reply":{"dish_groups":[]},"result":"success"}

- **dish.get**

Description: get list of dishes by restaurant

Method: GET URI:

/s2s/dish/get

Request:

 optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) optional string partner_dish_group_id Reply:

 required array dishes:

required uint32 dish_id required
uint32 dish_group_id required
string partner_dish_id

28 / 50

required string name required string name_en required
uint32 display_order required double price required
string description required bool is_active required string
partner_dish_group_id required string created_time
#YYYY-mm-dd HH:MM:SS required string
updated_time #YYYY-mm-dd HH:MM:SS
optional object picture required
uint32 id required
string url Sample:

Request: GET

/s2s/dish/get

Reply:

```
{"reply":{"dishes":[]},"result":"success"}
```

• dish.get_partner_id_mappings

Method: GET

URI: /s2s/dish/get_partner_id_mappings

Request: required uint32 restaurant_id Reply:

required array dishes:

required uint32 dish_id

required uint32 pos_id required uint32 restaurant_id

required string partner_dish_id required string

name Sample:

Request:

GET /s2s/dish/get_partner_id_mappings

Reply:

```
{"reply":{"dishes":[]},"result":"success"}
```

• dish.get_topping_mapping

Method: GET

29 / 50

URI: /s2s/dish/get_topping_mapping Request:

optional uint32 restaurant_id optional string partner_restaurant_id (required
this or restaurant_id) required string partner_dish_id Reply:

required string partner_dish_id required array toppings required uint32
topping_id required uint32 topping_group_id required string
partner_topping_id required double price // price when mapped with
current dish_id required string

partner_topping_group_id required boolean is_required
required uint32 min_quantity required uint32 max_quantity

Sample:

Request:

GET /s2s/dish/get_topping_mapping

Reply:

```
{"reply":{"dish_id":65918,"toppings":[]}, "result":"success"}
```

- **dish.get_group_detail**

Description: get dish group detail

Method: GET

URI: /s2s/dish/get_group_detail Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) optional uint32 dish_group_id optional string
partner_dish_group_id (required this or dish_group_id) Reply:

required uint32 dish_group_id

required string

partner_dish_group_id required

uint32 restaurant_id required string

name required string name_en

required int32 display_order required

string description required bool

is_active

30 / 50

Sample:

Request:

GET /s2s/dish/get_group_detail **Reply:**

```
{"reply":{},"result":"success"}
```

- **dish.get_detail**

Description: get dish

Method: GET

URI: /s2s/dish/get_detail Request:

optional uint32 restaurant_id optional string partner_restaurant_id

(required this or restaurant_id) optional uint32 dish_id optional

string partner_dish_id (required this or dish_id) Reply:

required uint32 dish_id required uint32
dish_group_id required string
partner_dish_id required string name
required string name_en required
int32 display_order required string
description required uint32
restaurant_id required string
partner_dish_group_id required bool
is_active required bool is_deleted
required double price required string
created_time required string
updated_time
optional object picture

required uint32 id required string url Sample:

Request:

GET /s2s/dish/get_detail **Reply:**

```
{"reply": {}, "result": "success"}
```

31 / 50

- **dish.upload_picture**

Method: POST

URI: /s2s/dish/upload_picture Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required
string image_base_64
optional bool is_apply_all

optional array uint32 branch_ids Reply:

required uint32 picture_id required
string url Sample:

Request:

POST /s2s/dish/upload_picture

Reply:

```
{"reply": null, "result": "success"}
```

- **dish.delete_picture**

Method: POST

URI: /s2s/dish/delete_picture Request:

optional uint32 restaurant_id optional string partner_restaurant_id

(required this or restaurant_id) required

string

partner_dish_id required uint32 picture_id

Reply: required bool is_pending Sample:

```
Request:
POST /s2s/dish/delete_picture

Reply:
{"reply":{"is_pending": False}, "result": "success"}
```

32 / 50

• dish.get_approval_status

Description: get list approval status by restaurant

Method: POST

URI: /s2s/dish/get_approval_status Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) optional uint32 dish_id optional
string partner_dish_id (required this or dish_id)

Reply:

required uint32 status required
uint32 dish_id

Sample:

```
Request:
POST /s2s/dish/get_approval_status

Reply:
{"reply":{"status": 3, 'dish_id': 16625}, "result": "success"}
```

3.3 Topping Api

• topping.create_group

Description: create topping group

Method: POST

URI: /s2s/topping/create_group Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required
string partner_topping_group_id required
string name
optional string name_en

optional uint32 display_order optional string

description optional bool is_apply_all

optional array uint32 branch_ids Reply:

required uint32 topping_group_id

Request:
 POST /s2s/topping/create_group

Reply:
 {"reply": {"topping_group_id": 1}, "result": "success"}

• topping.bulk_create_group

Description: bulk create topping group

Method: POST

URI: /s2s/topping/bulk_create_group Request:

optional uint32 restaurant_id optional string partner_restaurant_id
 (required this or restaurant_id) required array
 object topping_groups required string
 partner_topping_group_id required string
 name

optional string name_en

optional uint32 display_order optional string description

Reply:

Sample:

Request:
 POST /s2s/topping/bulk_create_group

Reply:
 {
 "result": "success",
 "reply": []
 }

• topping.update_group

Description: update topping group

Method: POST

URI: /s2s/topping/update_group Request:

optional uint32 restaurant_id optional string partner_restaurant_id
 (required this or restaurant_id) required
 string partner_topping_group_id optional
 string name

34 / 50 optional string name_en

optional uint32 display_order optional
 string description optional bool is_apply_all
 optional array uint32 branch_ids Reply:

Sample:

Request: POST /s2s/topping/update_group Reply: { "reply": null , "result": "success" }

- **topping.bulk_update_group**

Description: bulk update topping group

Method: POST

URI: /s2s/topping/bulk_update_group Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required array
object topping_groups required string
partner_topping_group_id
optional string name optional
string name_en optional
uint32 display_order
optional string description

Reply:

Sample:

Request: POST /s2s/topping/bulk_update_group Reply: { "result": "success", "reply": [] }
--

- **topping.delete_group**

Description: delete

Method: POST

URI: /s2s/topping/delete_group Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required string partner_topping_group_id Reply:

Error:

Sample:

Request: POST /s2s/topping/delete_group Reply: { "result": "success" }

- **topping.update_partner_group_id_mappings** Method:

POST

URI: /s2s/topping/update_partner_group_id_mappings Request:

required uint32 restaurant_id required array

object topping_groups required string

partner_topping_group_id required uint32 topping_group_id

Reply:

Sample:

Request: POST /s2s/topping/update_partner_group_id_mappings Reply: { "reply": null, "result": "success" }
--

- **topping.create**

Method: POST URI:

/s2s/topping/create

Request:

optional uint32 restaurant_id optional string partner_restaurant_id

(required this or restaurant_id) required

string partner_topping_id

36 / 50 required string partner_topping_group_id required string name

required double price

optional string name_en

optional uint32 display_order optional bool

is_apply_all optional array uint32

branch_ids Reply:

optional uint32 topping_id required

bool is_pending Sample:

Request: POST /s2s/topping/create Reply: { "reply": { "topping_id": 1, "is_pending": False }, "result": "success" }
--

- **topping.bulk_create**

Method: POST

URI: /s2s/topping/bulk_create Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) require
array object toppings required string
partner_topping_id required string
partner_topping_group_id required string
name required double price
optional string name_en
optional uint32 display_order Sample:

Request:

POST /s2s/topping/bulk_create

Reply:

```
{
  "result": "success",
  "reply": [
    {"result": "success", "reply": {"topping_id": 1, "partner_topping_id": "1"}} {"result":
    "pending", "reply": {"partner_topping_id": "2"}}
  ]
}
```

37 / 50

• **topping.update**

Method: POST URI:

/s2s/topping/update

Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required
string partner_topping_id
optional string
partner_topping_group_id optional
string name optional string name_en
optional uint32 display_order

optional double price optional bool

is_apply_all optional array uint32

branch_ids Reply: required bool is_pending

Error:

error_object_invalid_to_update Sample:

Request:

POST /s2s/topping/update

Reply:

```
{"reply": {"is_pending": False}, "result": "success"}
```

• **topping.bulk_update**

Method: POST

URI: /s2s/topping/bulk_update Request:

optional uint32 restaurant_id optional string partner_restaurant_id (required this or restaurant_id)
required array object toppings required
string partner_topping_id
optional string
partner_topping_group_id optional
string name optional string name_en
optional uint32 display_order optional
double price

- **topping.delete**

Description: delete

Method: POST

38 / 50

URI: /s2s/topping/delete Request:

optional uint32 restaurant_id optional string partner_restaurant_id
(required this or restaurant_id) required string partner_topping_id Reply: required
bool is_pending Error:

Sample:

Request: POST /s2s/topping/delete Reply: {"reply": {"is_pending": False}, "result": "success"}

- **topping.update_partner_id_mappings**

Method: POST

URI: /s2s/topping/update_partner_id_mappings Request:

required uint32 restaurant_id required
array object toppings required uint32 topping_id required
string partner_topping_id Reply:

Sample:

Request: POST /s2s/topping/update_partner_id_mappings Reply: {"reply": null, "result": "success"}
--

- **topping.get_groups**

Method: GET

URI: /s2s/topping/get_groups Request:

optional uint32 restaurant_id
optional string partner_restaurant_id (required this or restaurant_id) Reply:
required array topping_groups:

39 / 50 required uint32 topping_group_id

required string partner_topping_group_id required string
name required string name_en required uint32
display_order required bool is_active required string
description Error:

error_object_not_approved Sample:

Request:

GET /s2s/topping/get_groups

Reply:

```
{"reply":{"topping_groups":[]},"result":"success"}
```

● **topping.get_partner_group_id_mappings** Description:

get topping group mapping ocha

Method: GET

URI: /s2s/topping/get_partner_group_id_mappings Request:

required uint32 restaurant_id Reply:

required array topping_groups:

required uint32 topping_group_id

required uint32 pos_id required string

partner_topping_group_id required string name Sample:

Request:

GET /s2s/topping/get_partner_group_id_mappings

Reply:

```
{"reply":{"topping_groups":[]},"result":"success"}
```

● **topping.get**

Method: GET URI:

/s2s/topping/get

Request:

optional uint32 restaurant_id

optional string partner_restaurant_id (required this or restaurant_id)

40 / 50 optional string partner_topping_group_id Reply:

required array toppings:

required uint32 topping_id required

uint32 topping_group_id

required string

partner_topping_id required

string name required string

name_en

required uint32 display_order

required double price

required bool is_active

required string partner_topping_group_id Sample:

Request:

GET /s2s/topping/get

Reply:

```
{"reply":{"toppings":[]},"result":"success"}
```

• **topping.get_partner_id_mappings** Method:

GET

URI: /s2s/topping/get_partner_id_mappings

Request: required uint32 restaurant_id Reply:

required array toppings:

required uint32 topping_id

required uint32 pos_id required string

partner_topping_id required string name Sample:

Request:

GET /s2s/topping/get_partner_id_mappings

Reply:

```
{"reply":{"toppings":[]},"result":"success"}
```

• **topping.get_group_detail**

Method: GET

URI: /s2s/topping/get_group_detail

41 / 50 Request:

optional uint32 restaurant_id optional string partner_restaurant_id (required this or restaurant_id) optional uint32 topping_group_id optional string partner_topping_group_id (required this or topping_group_id) Reply:

required uint32 topping_group_id required string partner_topping_group_id required uint32 restaurant_id required string name required string name_en required int32 display_order required string description required bool is_active required bool is_deleted Sample:

Request:

GET /s2s/topping/get_group_detail **Reply:**

```
{"reply":{},"result":"success"}
```

• **topping.get_detail**

Method: GET

URI: /s2s/topping/get_detail Request:

optional uint32 restaurant_id optional string partner_restaurant_id

(required this or restaurant_id) required

uint32 topping_id

required string partner_topping_id (required this or topping_id) Reply:

required uint32 topping_id required

uint32 topping_group_id required string

partner_topping_id required string

partner_topping_group_id required

string name required string name_en

required double price required int32

display_order required bool is_active

required bool is_deleted

42 / 50 optional uint32 max_quantity

required uint32 restaurant_id Sample:

Request:

GET /s2s/topping/get_detail

Reply:

{"reply": {}, "result": "success"}

• **topping.set_group_quantity**

Method: POST

URI: /s2s/topping/set_group_quantity Request:

optional uint32 restaurant_id optional string partner_restaurant_id

(required this or restaurant_id) required

string

partner_topping_group_id required array

object dishes required string partner_dish_id

required uint32 min_quantity required uint32

max_quantity

optional bool is_apply_all

options array uint32 branch_ids Reply:

None Sample:

Request:

POST /s2s/topping/set_group_quantity **Reply:**

{"reply": null, "result": "success"}

• **topping.update_prices**

Method: POST

URI: /s2s/topping/update_prices Request:

optional uint32 restaurant_id

optional string partner_restaurant_id (required this or restaurant_id)

required array object toppings required

string partner_topping_id

required string partner_dish_id

43 / 50 required double price

optional bool is_apply_all

optional array uint32 branch_ids Reply:

Sample:

Request:

POST /s2s/topping/update_prices **Reply:**

{"reply":null,"result":"success"}

- **topping.set_statuses**

Method: POST

URI: /s2s/topping/set_statuses Request:

optional uint32 restaurant_id optional string partner_restaurant_id

(required this or restaurant_id) required array object toppings required

string partner_topping_id required

ToppingStatus status optional string from_time // format: YYYY-MMDD
hh:mm:ss, required if

set OUT_OF_STOCK optional string to_time // required if set

OUT_OF_STOCK

optional bool is_apply_all

optional array uint32 branch_ids Reply:

Sample:

Request:

POST /s2s/topping/set_statuses

Reply:

{"reply":null,"result":"success"}

- **topping.get_out_of_service**

Method: POST

URI: /s2s/topping/get_out_of_service Request:

optional uint32 restaurant_id

44 / 50 optional string partner_restaurant_id (required this or restaurant_id)
required array string partner_topping_ids Reply:

required array object toppings:
required string partner_topping_id
required string from_time
required string to_time

Sample:

Request: POST /s2s/topping/get_out_of_service Reply: { "reply": {}, "result": "success" }
--

3.4 Restaurant Api

- **restaurant.get_restaurant_info**

Description: get restaurant info by partner id and/or restaurant_id

Method: POST

URI: /s2s/restaurant/get_restaurant_info Request:

optional string partner_restaurant_id (required if not restaurant_id)

optional uint32 restaurant_id (required if not partner_restaurant_id) Reply:

required array object restaurants required
string partner_restaurant_id required uint32
restaurant_id required string name required string
address required string city optional string
foody_service Sample:

Request: POST /restaurant/get_restaurant_info { "restaurant_id": 29187 } Reply: { "result": "success", "reply": {} }
--

- **restaurant.get_operation_time_ranges**

Description: get restaurant 's opening hours

45 / 50

Method: GET

URI: /s2s/restaurant/get_operation_time_ranges Request:

optional uint32 restaurant_id (required if not partner_restaurant_id)

optional string partner_restaurant_id (required if not restaurant_id) Reply:

required array object days optional Weekday day_of_week (required if not custom_date)
 optional string custom_date (yyyy-mm-dd) (required if not day_of_week)
 required bool is_closed
 optional array object time_ranges optional
 uint32 id
 required string open_time (format: hh:mm) required
 string close_time

Error:

success

error_restaurant_invalid Sample:

Request:
 GET /s2s/restaurant/get_operation_time_ranges
 {"restaurant_id": 29214}

Reply:
 {"result": "success", "reply": {}}

● restaurant.set_operation_time_ranges

Description: set restaurant 's opening hours

Method: POST

URI: /s2s/restaurant/set_operation_time_ranges Request:

optional uint32 restaurant_id (required if not partner_restaurant_id) optional
 string partner_restaurant_id (required if not restaurant_id)
 required array object days optional Weekday day_of_week (required if not custom_date)
 optional string custom_date (yyyy-mm-dd) (required if not day_of_week)
 required bool is_closed
 optional array object time_ranges optional
 uint32 id
 required string open_time (format: hh:mm) required
 string close_time

46 / 50 Reply:

Error:

success error_params
 error_restaurant_invalid
 error_invalid_start_time_end_time
 error_overlap_time_range
 error_invalid_time_range_id
 error_duplicate_setting_time_range_da
 y

Sample:

Request: POST /s2s/restaurant/set_operation_time_ranges Reply: { "result": "success", "reply": {} }
--

3.5 Internal Api

- **driver.update_arriving_times**

Description: request mapping partner restaurant id with Now Restaurant

Method: POST

URI: /s2s-internal/driver/update_arriving_times Request:

required array object arriving_times

required string order_code required uint32

restaurant_id required uint32 driver_uid required

uint32 arriving_time Reply: None Sample:

Request: POST /s2s/restaurant/request_mapping Reply: { "reply": null, "result": "success" }
--

47 / 50

3.5 Menu Api

- **menu.sync**

Description: sync menu from partner restaurant

Method: POST

URI: /s2s/menu/sync Request:

required string

partner_restaurant_id Reply:

Error: success

Sample:

Request: POST /s2s/menu/sync { "partner_restaurant_id": "test_29214" } Reply: { "reply": null, "result": "success" }
--

4. Webhooks

Webhooks allows you to receive real-time HTTP notifications of changes to specific objects in the Foody system. For example, we could send you a notification when a new order or order had been changed status. This prevents you from having to query the Foody external api for changes to objects that may or may not have happened, and helps you avoid reaching your rate limit.

You need to give us your url callback link and implement the following api to handle our requests.

4.1 Order Api

- **partner_api_url_callback/update_order**

Description: Foody will call this API when order is updated

Method: POST URI:

/update_order

Request:

required string order_code required OrderUpdateType
update_type required uint32 restaurant_id optional string
pick_time (format like 2017-07-15 14:30:00)

48 / 50

optional OrderMerchantStatus status optional string merchant_note optional string
note_for_shipper optional string partner_restaurant_id optional string serial (deprecated)

Reply: empty

4.2 Menu Api

- **partner_api_url_callback**

Description: Foody will call this API when menu is updated

Method: POST URI:

Request:

required array object object_changes required uint64
event_id required [MenuObjectType](#)
object_type required uint32 object_id required
[MenuObjectUpdateType](#) update_type
required uint32 restaurant_id optional string
partner_restaurant_id

optional string partner_object_id Reply: Empty

- **export_error_menu** required

[MenuObjectType](#) object_type
required uint32 object_id required
uint32 restaurant_id

optional string partner_restaurant_id optional
string partner_object_id optional uint64
event_id optional [MenuObjectUpdateType](#)
update_type optional [PartnerErrorType](#)
error_type optional string error_time

4.3 Driver Api

- **partner_api_url_callback/update_drivers_status**

Description: Foody will call this API when Driver status is updated

49 / 50

Method: POST

URI: /update_drivers_status Request:

required array object driver_arriving_times
required string order_code
required uint32 restaurant_id
optional string partner_restaurant_id

required uint32 driver_uid required uint32

arriving_time (minutes) Reply: Empty

