

# This document serves as supplementary to the paper titled 'Decoupled and Closed-loop Control of Position and Stiffness for Articulated Soft Robots driven by a Class of Electromechanical Variable Stiffness Actuators'.

Maja Trumić, *Member, IEEE*, Franco Angelini, *Member, IEEE*,  
Kosta Jovanović, *Member, IEEE*, and Adriano Fagiolini, *Senior Member, IEEE*

This document serves as supplementary for the paper titled 'Decoupled and Closed-loop Control of Position and Stiffness for Articulated Soft Robots driven by a Class of Electromechanical Variable Stiffness Actuators'.

## I. EXPERIMENTAL RESULTS FOR A THREE-DEGREE-OF-FREEDOM ARTICULATED SOFT ROBOT

To validate the control approach on a multi-DoF setup, we mounted an additional link to the robotic setup, thus adding a degree of freedom to the previous robot such that the total number of degrees of freedom is equal to three, as shown in Fig. 1.

Again, the position and stiffness were commanded to follow the sinusoidal references. The trajectories are described as  $q_{i,d} = \epsilon_{q_i} + A_{q_i} \sin \omega_{q_i} t$  and  $\sigma_{i,d} = \epsilon_{\sigma_i} + A_{\sigma_i} \sin \omega_{\sigma_i} t$ , for  $i \in \{1, 2, 3\}$ , where  $\epsilon_{q_1} = 0.15$ ,  $\epsilon_{q_2} = -0.3$ ,  $\epsilon_{q_3} = 0.6$ ,  $A_{q_1} = 0.1$ ,  $A_{q_2} = 0.15$ ,  $A_{q_3} = 0.15$ ,  $\omega_{q_1} = \pi/15$ ,  $\omega_{q_2} =$

$\pi/7$ ,  $\omega_{q_3} = \pi/7$ ,  $\epsilon_{\sigma_1} = 11$ ,  $\epsilon_{\sigma_2} = 10$ ,  $\epsilon_{\sigma_3} = 7$ ,  $A_{\sigma_1} = 1$ ,  $A_{\sigma_2} = 1$ ,  $A_{\sigma_3} = 2$ ,  $\omega_{\sigma_1} = \pi/10$ ,  $\omega_{\sigma_2} = \pi/8$ , and  $\omega_{\sigma_3} = \pi/8$ . Intentionally, stiffness of the first two joints is set to a higher value such that these actuator are capable of supporting the robot structure.

Figure 2 reports that the resulting positions and stiffness of all three joints converge to the desired trajectories, while the estimated parameters converge to the constant values. The figure also shows the commanded and achieved motor positions, as well as the corresponding tracking errors. One can additionally observe that the commanded values are smooth.




Fig. 1. A three degrees-of-freedom hardware setup used for the validation.

This work was partially supported by the European Union under the Italian National Recovery and Resilience Plan (NRRP) of NextGenerationEU, partnership on "Telecommunications of the Future" (PE00000001 - program "RESTART"), by the Science Fund of the Republic of Serbia, Green Program of Cooperation between Science and Industry, under Grant 6784, and by the Serbian Ministry of Science, Technological Development and Innovation (451-03-65/2024-03/200103 and 451-03-66/2024-03/200103).

Maja Trumić is with the School of Electrical Engineering, University of Belgrade, Serbia (e-mail: maja.trumic@etf.rs).

Franco Angelini is with Centro di Ricerca "Enrico Piaggio", and Dipartimento di Ingegneria dell'Informazione, Università di Pisa, Largo Lucio Lazzarino 1, 56122 Pisa, Italy (e-mail: franco.angelini@unipi.it).

Kosta Jovanović is with the School of Electrical Engineering, University of Belgrade, Serbia (e-mail: kostaj@etf.rs).

Adriano Fagiolini, the corresponding author, is with the Mobile and Intelligent Robots @ Panormus Laboratory (MIRPALab), Department of Engineering, University of Palermo, Italy (e-mail: adriano.fagiolini@unipa.it).




Fig. 2. The experiment on a three-DOF electromechanical articulated soft robot by using nonlinear adaptive control. All joint positions and joint stiffnesses are tracked accurately, while the parameters converge to constant values and the commanded motor positions have smooth behavior. The decoupling effect can again be observed in the leftmost figure, since the link positions remain constant despite the change of joint stiffness and other links position.