Experiment No: 10 Write a program to perform different operation using Pandas Module.

In [1]:
```
import pandas
```

In [2]:
```
import pandas as pd

mydataset = {
  'cars': ["BMW", "Volvo", "Ford"],
  'passings': [3, 7, 2]
}

myvar = pd.DataFrame(mydataset)

print(myvar)
```

```
    cars  passings
0    BMW         3
1  Volvo         7
2   Ford         2
```

In [3]:
```
import pandas as pd
```

In [4]:
```
import pandas as pd

mydataset = {
  'cars': ["BMW", "Volvo", "Ford"],
  'passings': [3, 7, 2]
}

myvar = pd.DataFrame(mydataset)

print(myvar)
```

```
    cars  passings
0    BMW         3
1  Volvo         7
2   Ford         2
```

In [5]:
```
import pandas as pd

print(pd.__version__)
```

```
1.1.3
```

In [6]:
```
import pandas as pd

a = [1, 7, 2]

myvar = pd.Series(a)

print(myvar)
```

```
0    1
1    7
2    2
dtype: int64
```

In [7]:
```
import pandas as pd

a = [1, 7, 2]

myvar = pd.Series(a)

print(myvar[0])
```

```
1
```

In [8]:
```
import pandas as pd

a = [1, 7, 2]

myvar = pd.Series(a, index = ["x", "y", "z"])

print(myvar)
```

```
x    1
y    7
z    2
dtype: int64
```

In [9]:
```
import pandas as pd

a = [1, 7, 2]

myvar = pd.Series(a, index = ["x", "y", "z"])

print(myvar["y"])
```

```
7
```

In [10]:
```
import pandas as pd

calories = {"day1": 420, "day2": 380, "day3": 390}

myvar = pd.Series(calories)

print(myvar)
```

```
day1    420
day2    380
day3    390
dtype: int64
```

In [11]:
```
import pandas as pd

calories = {"day1": 420, "day2": 380, "day3": 390}

myvar = pd.Series(calories, index = ["day1", "day2"])

print(myvar)
```

```
day1    420
day2    380
dtype: int64
```

In [12]:
```
import pandas as pd

data = {
  "calories": [420, 380, 390],
  "duration": [50, 40, 45]
}

myvar = pd.DataFrame(data)

print(myvar)
```

```
   calories  duration
0       420        50
1       380        40
2       390        45
```

In [13]:
```
import pandas as pd

data = {
  "calories": [420, 380, 390],
  "duration": [50, 40, 45]
}

#load data into a DataFrame object:
df = pd.DataFrame(data)

print(df)
```

```
   calories  duration
0       420        50
1       380        40
2       390        45
```

In [14]:
```
#refer to the row index:
print(df.loc[0])
```

```
calories    420
duration     50
Name: 0, dtype: int64
```

In [15]:
```
#use a list of indexes:
print(df.loc[[0, 1]])
```

```
   calories  duration
0       420        50
1       380        40
```

In [16]:
```
import pandas as pd

data = {
  "calories": [420, 380, 390],
  "duration": [50, 40, 45]
}

df = pd.DataFrame(data, index = ["day1", "day2", "day3"])

print(df)
```

```
      calories  duration
day1       420        50
day2       380        40
day3       390        45
```

In [17]:
```
#refer to the named index:
print(df.loc["day2"])
```

```
calories    380
duration     40
Name: day2, dtype: int64
```

In [21]:
```
import pandas as pd

print(pd.options.display.max_rows)
```

```
60
```

In [23]:
```
import pandas as pd

data = {
  "Duration":{
    "0":60,
    "1":60,
    "2":60,
    "3":45,
    "4":45,
    "5":60
  },
  "Pulse":{
    "0":110,
    "1":117,
    "2":103,
    "3":109,
    "4":117,
    "5":102
  },
  "Maxpulse":{
    "0":130,
    "1":145,
    "2":135,
    "3":175,
    "4":148,
    "5":127
  },
  "Calories":{
    "0":409.1,
    "1":479.0,
    "2":340.0,
    "3":282.4,
    "4":406.0,
    "5":300.5
  }
}

df = pd.DataFrame(data)

print(df)
```

```
   Duration  Pulse  Maxpulse  Calories
0        60    110       130     409.1
1        60    117       145     479.0
2        60    103       135     340.0
3        45    109       175     282.4
4        45    117       148     406.0
5        60    102       127     300.5
```

In [1]:
```
import pandas as pd

df = pd.read_csv(r"C:\Users\Admin\Documents\student.csv")
print(df)
```

```
     Name  Age  Marks
0  Prachi   19     85
1    Riya   20     90
2   Priya   19     88
```

In [2]:
```
import pandas as pd

df = pd.read_csv(r"C:\Users\Admin\Documents\student.csv")
print(df.head(2))
```

```
     Name  Age  Marks
0  Prachi   19     85
1    Riya   20     90
```

In [ ]:
```

```