

Report Laboratories 4

Maciej Janicki 156073 Jakub Kubiak 156049

Source code

Problem Description

Given a set of nodes, each having a set of coordinates (x, y) and inherent cost, pick exactly half of the nodes to form a Hamiltonian cycle.

The goal is to minimize the sum of total path length plus the total cost of the selected nodes.

Current implementation is about improving the efficiency of the steepest local search with the use of candidate moves.

Pseudocode

Common Functionality

```
FUNCTION get_move_delta(move, solution, dataset, dist):
    SWITCH move.kind:
        CASE INTER_ROUTE:
            candidate := dataset[move.dataset_index]
            prev_node := solution[move.solution_index - 1]
                        if move.solution_index > 0 else solution.size - 1]
            swap_out_node := solution[move.solution_index]
            next_node := solution[(move.solution_index + 1) % solution.size]
            old_cost := dist(prev_node, swap_out_node) +
                        dist(swap_out_node, next_node) + swap_out_node.cost
            new_cost := dist(prev_node, candidate) +
                        dist(candidate, next_node) + candidate.cost
            RETURN new_cost - old_cost

        CASE INTRA_ROUTE_NODE_EXCHANGE:
            node_a := solution[move.swap_index_a]
            node_b := solution[move.swap_index_b]
            prev_a := solution[move.swap_index_a - 1]
                        if move.swap_index_a > 0 else solution.size - 1]
            next_a := solution[(move.swap_index_a + 1) % solution.size]
            prev_b := solution[move.swap_index_b - 1]
                        if move.swap_index_b > 0 else solution.size - 1]
            next_b := solution[(move.swap_index_b + 1) % solution.size]
            IF next_a.id == node_b.id OR next_b.id == node_a.id:
                old_cost := dist(prev_a, node_a) +
                            dist(node_a, node_b) + dist(node_b, next_b)
                new_cost := dist(prev_a, node_b)
                            + dist(node_b, node_a) + dist(node_a, next_b)
            ELSE:
                old_cost := dist(prev_a, node_a) + dist(node_a, next_a)
                            + dist(prev_b, node_b) + dist(node_b, next_b)
                new_cost := dist(prev_a, node_b) + dist(node_b, next_a)
                            + dist(prev_b, node_a) + dist(node_a, next_b)
            RETURN new_cost - old_cost

        CASE INTRA_ROUTE_EDGE_EXCHANGE:
            a := move.swap_index_a
            b := move.swap_index_b
            c := (a + 1) % solution.size
            d := (b + 1) % solution.size
            node_a := solution[a]
            node_b := solution[b]
            node_c := solution[c]
```

```

        node_d := solution[d]
        old_cost := dist(node_a, node_c) + dist(node_b, node_d)
        new_cost := dist(node_a, node_b) + dist(node_c, node_d)
        RETURN new_cost - old_cost

FUNCTION act_on_move(move, solution, dataset, used):
    IF NOT move.valid: RETURN false
    SWITCH move.kind:
        CASE INTER_ROUTE:
            used[solution[move.solution_index].id] := false
            used[move.dataset_index] := true
            solution[move.solution_index] := dataset[move.dataset_index]
        CASE INTRA_ROUTE_NODE_EXCHANGE:
            SWAP(solution[move.swap_index_a], solution[move.swap_index_b])
        CASE INTRA_ROUTE_EDGE_EXCHANGE:
            a := move.swap_index_a
            b := move.swap_index_b
            IF a < b:
                REVERSE(solution[a+1 to b])
            ELSE:
                segment := solution[a+1 to end] + solution[0 to b]
                REVERSE(segment)
                FOR i IN 0 to segment.size - 1:
                    solution[(a+1+i) % solution.size] := segment[i]
    RETURN true

```

Candidate moves

```

FUNCTION precompute_nearest_neighbors_inter(dataset, dist, n_candidates):
    n := dataset.size
    neighbors := vector of n empty vectors

    FOR i IN 0 to n-1:
        queue := empty list
        FOR j IN 0 to n-1:
            IF i == j: CONTINUE
            cost := dist(dataset[i], dataset[j]) + dataset[j].cost
            ADD (cost, j) TO queue

        KEEP n_candidates smallest elements in queue by cost

        FOR each (cost, idx) IN first n_candidates of queue:
            ADD idx TO neighbors[i]

    RETURN neighbors

FUNCTION get_best_move_candidate(solution, dataset, dist, used,
                                inter_neighbors, n_candidates):
    best_move.valid := false
    best_delta := 0

    FOR i IN 0 to solution.size - 1:
        candidate_node := solution[i]

        FOR j IN inter_neighbors[candidate_node.id]:
            IF used[j]:
                move := INTRA_EDGE_EXCHANGE_MOVE(i, j)
            ELSE:
                move := INTER_ROUTE_MOVE(i, j)
            delta := get_move_delta(move, solution, dataset, dist)

```

```

        IF delta < best_delta:
            best_move := move
            best_delta := delta
RETURN best_move

FUNCTION get_local_search_candidate(solution, dataset, dist, n_candidates):
    used := array(dataset.size) initialized false
    FOR node IN solution:
        used[node.id] := true

    WHILE true:
        move := get_best_move_candidate(solution, dataset, dist, used, n_candidates)
        IF NOT act_on_move(move, solution, dataset, used):
            BREAK

    RETURN solution

```

Result Comparison

Algorithm	TSPA Cost (Mean (Min, Max))	TSPB Cost (Mean (Min, Max))
Random	265,135 (241,347, 291,966)	213,771 (190,834, 241,363)
Nearest Neighbor #1	85,108.5 (83,182, 89,433)	54,390.4 (52,319, 59,030)
Nearest Neighbor #2	73,601.7 (71,868, 75,953)	48,723.2 (44,609, 57,315)
Greedy Cycle	72,646.4 (71,488, 74,410)	51,400.6 (49,001, 57,324)
Nearest Neighbor Regret	117,516 (107,945, 128,071)	73,512.7 (67,345, 78,889)
Greedy Cycle Regret	115,137 (106,052, 123,750)	73,316.1 (67,729, 77,498)
Nearest Neighbor Regret Weighted (0.5, 0.5)	73,566.7 (70,894, 75,929)	49,847 (44,901, 57,036)
Greedy Cycle Regret Weighted (0.5, 0.5)	72,137.6 (71,108, 73,395)	50,827.2 (47,144, 55,700)
Nearest Neighbor Regret Weighted (0.3, 0.7)	75,562.1 (72,155, 78,661)	51,784.2 (47,543, 59,409)
Greedy Cycle Regret Weighted (0.3, 0.7)	73,010.6 (70,475, 75,365)	52,420.1 (49,944, 56,179)
Nearest Neighbor Regret Weighted (0.7, 0.3)	73,412.8 (71,519, 75,234)	48,816.6 (45,153, 53,425)
Greedy Cycle Regret Weighted (0.7, 0.3)	72,437.2 (71,163, 73,759)	51,173.3 (49,326, 53,437)
Local Search Greedy + Intra Nodes + Random Start	83,804.35 (77,418, 90,972)	59,076.75 (52,869, 67,067)
Local Search Greedy + Intra Nodes + Greedy Start	72,806.49 (71,034, 74,987)	45,468.38 (43,989, 51,040)
Local Search Greedy + Intra Edges + Random Start	73,387.63 (71,248, 78,480)	48,161.21 (45,907, 51,461)
Local Search Greedy + Intra Edges + Greedy Start	71,067.07 (70,046, 73,486)	45,053.77 (43,947, 50,319)
Local Search Steepest + Intra Nodes + Random Start	87,883.71 (79,593, 98,325)	62,947.23 (54,122, 71,598)
Local Search Steepest + Intra Nodes + Greedy Start	72,807.32 (71,034, 74,904)	45,414.50 (43,826, 50,876)
Local Search Steepest + Intra Edges + Random Start	73,938.93 (71,428, 77,903)	48,323.99 (45,670, 51,667)
Local Search Steepest + Intra Edges + Greedy Start	70,975.96 (69,864, 73,068)	44,974.89 (43,921, 50,319)
Candidate Local Search Steepest (k=10)	80,070.30 (75,097, 85,343)	49,548.59 (46,836, 51,921)
Candidate Local Search Steepest (k=15)	76,673.52 (72,509, 80,911)	48,723.89 (45,961, 51,644)
Candidate Local Search Steepest (k=20)	75,295.08 (72,316, 79,297)	48,457.54 (45,886, 51,560)

Execution Time Comparison

Algorithm	TSPA Time (Mean (Min, Max)) [ms]	TSPB Time (Mean (Min, Max)) [ms]
Local Search Greedy + Intra Nodes + Random Start	36.36 (16.00, 69.92)	35.84 (19.78, 59.54)
Local Search Greedy + Intra Nodes + Greedy Start	2.49 (1.80, 5.13)	2.67 (1.85, 7.62)
Local Search Greedy + Intra Edges + Random Start	48.81 (23.56, 70.97)	42.71 (22.79, 62.96)
Local Search Greedy + Intra Edges + Greedy Start	3.28 (1.95, 5.24)	2.92 (1.77, 7.81)
Local Search Steepest + Intra Nodes + Random Start	21.89 (16.96, 31.65)	22.20 (17.60, 29.57)
Local Search Steepest + Intra Nodes + Greedy Start	2.10 (1.55, 3.00)	2.31 (1.81, 4.95)
Local Search Steepest + Intra Edges + Random Start	15.45 (13.59, 19.09)	**15.45 (13.17, 17.90)
Local Search Steepest + Intra Edges + Greedy Start	2.78 (1.83, 3.85)	2.36 (1.86, 4.88)
Candidate Local Search Steepest (k=10)	4.31 (3.09, 7.61)	3.97 (3.26, 9.21)
Candidate Local Search Steepest (k=15)	4.21 (3.74, 4.73)	4.17 (3.68, 4.62)
Candidate Local Search Steepest (k=20)	4.92 (4.20, 8.74)	4.47 (3.86, 5.23)


Visualizations

TSPA

Steepest Local Search + Intra Edges + Random Start

89, 183, 23, 137, 176, 51, 118, 59, 65, 116, 43, 42, 181, 159, 193, 41, 139, 115, 198, 46, 68, 0, 143, 117, 93, 140, 108, 69, 18, 22, 146, 34, 160, 54, 177, 10, 4, 112, 84, 184, 149, 123, 127, 70, 135, 154, 180, 162, 151, 133, 79, 80, 94, 63, 158, 53, 121, 100, 26, 97, 152, 1, 101, 86, 75, 2, 129, 92, 57, 179, 145, 78, 120, 44, 16, 171, 175, 113, 31, 196, 81, 90, 27, 165, 40, 185, 55, 52, 106, 178, 14, 49, 102, 144, 62, 9, 37, 148, 15, 186, 89


Baseline Steepest Local Search | Avg time: 8.53 ms | Score: 73780 (71726, 78885)



Candidate Moves approach (k=10)

4, 84, 190, 10, 177, 184, 35, 65, 116, 43, 42, 160, 34, 181, 146, 22, 159, 96, 41, 193, 18, 69, 108, 140, 93, 46, 139, 115, 59, 118, 51, 0, 117, 143, 183, 89, 23, 137, 176, 80, 79, 122, 63, 94, 124, 167, 148, 15, 9, 62, 144, 14, 102, 49, 32, 138, 165, 39, 7, 164, 27, 107, 90, 81, 196, 40, 185, 106, 3, 178, 52, 55, 57, 92, 145, 78, 31, 113, 175, 171, 16, 25, 44, 120, 2, 152, 97, 1, 101, 75, 86, 53, 180, 154, 135, 133, 151, 162, 123, 112, 4


Candidate Steepest Local Search | Avg time: 6.17 ms | Score: 80070 (75097, 85343)



Candidate Moves approach (k=15)

146, 22, 18, 69, 108, 93, 117, 0, 143, 183, 89, 23, 137, 176, 80, 79, 63, 94, 148, 37, 15, 9, 62, 144, 102, 49, 14, 138, 164, 27, 90, 81, 40, 119, 165, 185, 106, 178, 52, 55, 57, 129, 92, 78, 145, 196, 31, 56, 113, 175, 171, 16, 44, 120, 2, 152, 97, 1, 101, 75, 86, 26, 53, 180, 154, 70, 135, 162, 133, 151, 51, 59, 65, 116, 105, 43, 77, 149, 123, 127, 112, 4, 84, 35, 184, 190, 10, 177, 54, 48, 160, 34, 181, 42, 115, 46, 139, 41, 193, 159, 146


Candidate Steepest Local Search | Avg time: 6.41 ms | Score: 76673 (72509, 80911)



Candidate Moves approach (k=20)

180, 154, 135, 70, 127, 123, 162, 151, 133, 79, 63, 94, 80, 176, 51, 118, 59, 115, 46, 68, 110, 139, 41, 193, 159, 181, 42, 5, 43, 105, 116, 65, 149, 131, 35, 184, 10, 177, 54, 160, 34, 103, 146, 22, 18, 108, 140, 93, 117, 0, 143, 183, 89, 186, 23, 137, 148, 9, 62, 102, 49, 144, 14, 138, 21, 7, 164, 27, 90, 165, 185, 40, 81, 196, 31, 113, 175, 171, 16, 44, 78, 145, 106, 178, 52, 55, 57, 92, 129, 120, 2, 152, 97, 1, 101, 75, 86, 26, 53, 158, 180

Candidate Steepest Local Search | Avg time: 6.86 ms | Score: 75295 (72316, 79297)




TSPB

Steepest Local Search + Intra Edges + Random Start

139, 11, 182, 138, 33, 160, 144, 111, 29, 0, 109, 35, 106, 124, 62, 18, 55, 34, 152, 183, 140, 149, 28, 20, 148, 47, 94, 66, 179, 185, 99, 130, 95, 86, 166, 194, 88, 176, 180, 113, 103, 114, 137, 127, 165, 89, 163, 187, 146, 153, 81, 77, 82, 8, 21, 141, 91, 61, 36, 177, 5, 78, 175, 45, 80, 190, 136, 73, 54, 31, 193, 117, 198, 1, 131, 121, 51, 125, 191, 90, 122, 135, 63, 100, 40, 107, 133, 147, 134, 6, 188, 169, 132, 70, 3, 15, 145, 13, 195, 168, 139

Baseline Steepest Local Search | Avg time: 10.03 ms | Score: 48367 (45603, 51479)




Candidate Moves approach (k=10)

148, 47, 94, 66, 179, 172, 52, 166, 194, 88, 176, 180, 113, 103, 114, 127, 89, 163, 153, 81, 77, 82, 21, 141, 91, 61, 36, 177, 5, 175, 80, 190, 73, 164, 31, 54, 193, 117, 198, 156, 1, 27, 38, 135, 63, 40, 107, 122, 133, 10, 147, 71, 51, 191, 90, 131, 121, 25, 138, 104, 8, 111,

35, 109, 0, 29, 160, 33, 11, 139, 43, 168, 195, 188, 169, 132, 13, 145, 15, 70, 3, 155, 152, 55, 18, 62, 124, 106, 86, 95, 185, 22, 99, 130, 183, 140, 149, 28, 20, 60, 148


Candidate Steepest Local Search | Avg time: 6.62 ms | Score: 49548 (46836, 51921)



Candidate Moves approach (k=15)

11, 138, 33, 160, 104, 8, 111, 144, 29, 0, 35, 109, 189, 155, 184, 152, 170, 34, 55, 18, 62, 124, 106, 128, 86, 95, 183, 140, 149, 28, 20, 60, 148, 47, 94, 179, 99, 185, 166, 194, 176, 113, 103, 127, 89, 163, 187, 153, 81, 77, 97, 141, 91, 36, 61, 82, 87, 21, 177, 5, 78, 175, 80, 190, 193, 31, 164, 73, 54, 117, 198, 1, 38, 135, 102, 63, 40, 107, 10, 133, 122, 90, 131, 121, 51, 71, 147, 134, 6, 188, 169, 132, 70, 3, 15, 145, 13, 195, 168, 139, 11

Candidate Steepest Local Search | Avg time: 8.54 ms | Score: 48723 (45961, 51644)




Candidate Moves approach (k=20)

177, 5, 45, 142, 78, 175, 162, 80, 190, 136, 73, 54, 31, 193, 117, 198, 156, 1, 16, 27, 38, 63, 40, 107, 100, 135, 131, 121, 51, 191, 90, 122, 133, 147, 134, 139, 11, 168, 195, 132, 169, 188, 70, 3, 15, 145, 155, 29, 0, 109, 35, 106, 124, 62, 18, 55, 34, 152, 183, 140, 149,

28, 20, 60, 148, 47, 94, 179, 185, 99, 130, 95, 86, 166, 194, 176, 180, 113, 103, 114, 137, 127, 165, 89, 163, 153, 81, 77, 141, 36, 61, 21, 82, 8, 104, 160, 33, 138, 182, 25, 177

Candidate Steepest Local Search | Avg time: 7.91 ms | Score: 48457 (45886, 51560)



All solutions were checked with solution checker.

Conclusions

- Evaluating only a subset of ‘nearest’ neighbors is enough to capture the good moves
- Candidate approach might be a good alternative for the greedy approaches, especially for larger instances, where the number of neighbors to evaluate is too large to be feasible.