

MURA115T3, MURA120T3

Preferred Devices

Surface Mount Ultrafast Power Rectifiers

Ideally suited for high voltage, high frequency rectification, or as free wheeling and protection diodes in surface mount applications where compact size and weight are critical to the system.

- ? Small Compact Surface Mountable Package with J-Bend Leads
- ? Rectangular Package for Automated Handling
- ? High Temperature Glass Passivated Junction
- ? Low Forward Voltage Drop (0.71 Volts Max @ 1.0 A, T_J= 150 °C)

Mechanical Characteristics:

- ? Case: Epoxy, Molded
- ? Weight: 70 mg (approximately)
- ? Finish: All External Surfaces Corrosion Resistant and Terminal Leads are Readily Solderable
- ? Lead and Mounting Surface Temperature for Soldering Purposes: 260 °C Max. for 10 Seconds
- ? Shipped in 12 mm Tape and Reel, 5000 units per reel
- ? Polarity: Polarity Band Indicates Cathode Lead
- ? ESD Protection: Human Body Model > 4000 V (Class 3)
ESD Protection: Machine Model > 400 V (Class C)
- ? Marking: U4C, U4D

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	150 200	V
Average Rectified Forward Current @ T _L = 155 °C @ T _L = 135 °C	$I_{F(AV)}$	1.0 2.0	A
Non-Repetitive Peak Surge Current (Surge Applied at Rated Load Conditions Halfwave, Single Phase, 60 Hz)	I_{FSM}	40	A
Operating Junction Temperature Range	T _J	- 65 to +175	°C



ON Semiconductor®


<http://onsemi.com>

ULTRAFAST RECTIFIERS 1 AMPERE 100-200 VOLTS



SMA
CASE 403D
PLASTIC

MARKING
DIAGRAM



x = C (115T3)
D (120T3)

ORDERING INFORMATION

Device	Package	Shipping
MURA115T3	SMA	5000/Tape & Reel
MURA120T3	SMA	5000/Tape & Reel

Preferred devices are recommended choices for future use and best overall value.

MURA115T3, MURA120T3

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Lead ($T_L = 25\text{ }^{\circ}\text{C}$) (Note 1)	Ψ_{JL} (Note 2)	24	$^{\circ}\text{C/W}$
Thermal Resistance, Junction to Ambient (Note 1)	R_{JA}	216	

ELECTRICAL CHARACTERISTICS

Maximum Instantaneous Forward Voltage (Note 3) ($i_F = 1.0\text{ A}$, $T_J = 25\text{ }^{\circ}\text{C}$) ($i_F = 1.0\text{ A}$, $T_J = 150\text{ }^{\circ}\text{C}$)	V_F	0.875 0.71	Volts
Maximum Instantaneous Reverse Current (Note 3) (Rated dc Voltage, $T_J = 25\text{ }^{\circ}\text{C}$) (Rated dc Voltage, $T_J = 150\text{ }^{\circ}\text{C}$)	i_R	2.0 50	μA
Maximum Reverse Recovery Time ($i_F = 1.0\text{ A}$, $di/dt = 50\text{ A}/\mu\text{s}$)	t_{rr}	35	ns

1. Rating applies when surface mounted on the minimum pad size recommended, PC Board FR-4.
2. In compliance with JEDEC 51, these values (historically represented by R_{JL}) are now referenced as Ψ_{JL} .
3. Pulse Test: Pulse Width = 300 μs , Duty Cycle $\leq 2.0\%$.




Figure 1. Typical Reverse Current




Figure 2. Maximum Reverse Current




Figure 3. Typical Forward Voltage




Figure 4. Maximum Forward Voltage

MURA115T3, MURA120T3




Figure 5. Typical Capacitance




Figure 6. Maximum Capacitance




Figure 7. Current Derating, Lead




Figure 8. Current Derating, Ambient
(FR-4 Board with Minimum Pad)





Figure 9. Power Dissipation

MURA115T3, MURA120T3



PACKAGE DIMENSIONS

SMA
CASE 403D-02
ISSUE A




- NOTES:
- 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 - 2. CONTROLLING DIMENSION: INCH.
 - 3. 403D-01 OBSOLETE, NEW STANDARD IS 403D-02.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.160	0.180	4.06	4.57
B	0.090	0.115	2.29	2.92
C	0.075	0.095	1.91	2.41
D	0.050	0.064	1.27	1.63
H	0.002	0.006	0.05	0.15
J	0.006	0.016	0.15	0.41
K	0.030	0.060	0.76	1.52
S	0.190	0.220	4.83	5.59



SMA FOOTPRINT

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in SCILLC data sheets and/or “Typicals” specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including validated for each customer application by customer’s technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

JAPAN : ON Semiconductor, Japan Customer Focus Center
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051
Phone : 81-3-5773-3850
Email : r14525@onsemi.com

ON Semiconductor Website : <http://onsemi.com>

For additional information, please contact your local
Sales Representative.