

Technical drawing of a Three Phase Explosion-Proof NEMA Premium motor nameplate. The drawing includes dimensions and specifications for the motor.

Dimensions:

- Overall width: 100
- Overall height: 70
- Top flange width: 6.5
- Top flange thickness: 2
- Mounting hole diameter: $4 \times \varnothing 2.6^{+0.18}_0$
- Mounting hole spacing: 14
- Bottom flange thickness: 3.5
- Bottom flange width: 6.5

Specifications:

- WorldWide** logo
- THREE PHASE EXPLOSION-PROOF**
- NEMA PREMIUM**
- TYPE**: SER. NO. IP
- FR.**: ENCL. INS. CLASS. DESIGN B
- HZ**: VOLTS. CONN. MAX. AMB. °C
- HP**: AMPS
- RPM**: S.F.
- NOM. EFF.**: MIN. EFF.
- P.F.**: CODE
- BRG. DE.**: BRG. NO. WEIGHT DATE
- USABLE AT 50Hz 380V HP A RPM S.F. 1.0 EFF. CODE**

CONNECTION

1 2 3
L1 L2 L3

MADE IN VIETNAM

WorldWide Electric Corporation CC039B

92±0.2

100

Technical drawing of a NEMA Premium motor nameplate with dimensions and specifications.

Dimensions:

- Overall width: 92 ± 0.2
- Overall height: 70
- Top mounting hole spacing: 6.5
- Top mounting hole diameter: 2
- Right side mounting hole spacing: 14
- Right side mounting hole diameter: $R5$
- Right side mounting hole offset: $4 \times \phi 2.6^{+0.18}_0$
- Bottom mounting hole spacing: 6.5
- Bottom mounting hole diameter: 3.5
- Bottom mounting hole offset: 42 ± 0.2

Nameplate Content:

WORLDWIDE **THREE PHASE EXPLOSION-PROOF** **NEMA PREMIUM**

TYPE		SER. NO.		IP	
FR.	ENCL.	INS. CLASS.		DESIGN B	
HZ.	VOLTS	CONNL.		MAX. AMB. °C	
HP.	AMPS	Low Voltage		High Voltage	
RPM	S.F.	70 80 90		70 80 90	
NOM. EFF.	MIN. EFF.	60 40 50		40 50 60	
P.F.	CODE	10 L1 20 L2 30 L3		10 L1 20 L2 30 L3	
BRG. DE.	BRG. NDE.	WEIGHT		DATE	
USABLE AT 50Hz 380V HP A RPM S.F. 1.0 EFF. CODE					

MADE IN VIETNAM

WorldWide Electric Corporation **CC039B**

表1

注：

Technical drawing of a three-phase explosion-proof terminal box. The drawing includes dimensions and labels for the box and its components.

Dimensions:

- Overall width: 92 ± 0.2
- Overall height: 70
- Top flange thickness: 2
- Top flange width: 6.5
- Bottom flange thickness: 6.5
- Bottom flange width: 6.5
- Terminal box height: 14
- Terminal box width: $4 \times \phi 2.6^{+0.18}_0$
- Terminal box depth: 3.5

Labels and Markings:

- WorldWide** (Logo)
- THREE PHASE EXPLOSION-PROOF**
- NEMA PREMIUM** (Logo)
- TYPE**
- SER. NO.**
- IP**
- FR.**
- ENCL.**
- INS. CLASS**
- DESIGN B**
- HZ.**
- VOLTS**
- CONN.**
- MAX. AMB.**
- °C**
- HP.**
- AMPS**
- RPM**
- S.F.**
- NOM. EFF.**
- MIN. EFF.**
- P.F.**
- CODE**
- BRG. DE.**
- BRG. NDE.**
- WEIGHT**
- DATE**
- USABLE AT 50Hz 380V HP A RPM S.F. 1.0 EFF. CODE**
- MADE IN VIETNAM**
- WorldWide Electric Corporation**
- CC039B**

Technical drawing of a NEMA Premium Three Phase Explosion-Proof motor nameplate. The drawing shows a rectangular plate with various fields for technical specifications. Dimensions are given in inches: overall width 14, overall height 7.0, mounting hole spacing 4.2 ± 0.2, and mounting hole diameter 0.375. The nameplate includes fields for TYPE, SER. NO., IP, FR., ENCL., INS. CLASS, DESIGN B, HZ., VOLTS, CONN., MAX. AMB., °C, HP., AMPS, Low Voltage and High Voltage terminal diagrams, RPM, S.F., MIN. EFF., P.F., CODE, BRG. DE., BRG. INDE., WEIGHT, DATE, and USABLE AT 50Hz 380V HP A RPM S.F. 1.0 EFF. CODE. The bottom of the plate features the WorldWide Electric Corporation logo and name, and the code CC039B. A note indicates the plate is made in Vietnam.

Dimensions (inches):

- Overall Width: 14
- Overall Height: 7.0
- Mounting Hole Spacing: 4.2 ± 0.2
- Mounting Hole Diameter: 0.375

Nameplate Fields:

TYPE		SER. NO.		IP	
FR.	ENCL.	INS. CLASS		DESIGN B	
HZ.	VOLTS	CONN.		MAX. AMB. °C	
HP.	AMPS	Low Voltage 		High Voltage 	
RPM	S.F.				
MIN. EFF.					
P.F.	CODE				
BRG. DE.		BRG. INDE.		WEIGHT	
DATE					
USABLE AT 50Hz 380V HP A RPM S.F. 1.0 EFF. CODE					
WorldWide Electric Corporation					
CC039B					

Additional Information:

- MADE IN VIETNAM
- 4xØ2.6 ± 0.015

技术要求

[illegible]