

# COMP 472 Artificial Intelligence

## State Space Search *part #3*

### Uninformed Search *video #2*

- Russell & Norvig - Section 3.4

- see also: <https://www.javatpoint.com/ai-uninformed-search-algorithms>

# Today

1. State Space Representation

2. State Space Search

a) Overview

YOU ARE HERE!

b) Uninformed search

1. Breadth-first and Depth-first

2. Depth-limited Search

3. Iterative Deepening

4. Uniform Cost

c) Informed search

1. Intro to Heuristics

2. Hill climbing

3. Best-First

4. Algorithms A & A\*

5. More on Heuristics


d) Summary

# Uninformed VS Informed Search

## ■ Uninformed search


- all nodes are equally promising, so we explore them systematically
- aka: systematic/blind/brute force search
- many algorithms:
  1. Breadth-first search
  2. Depth-first search
  3. Uniform-cost search
  4. Depth-limited search
  5. Iterative deepening search
  6. ...

352  
video today



## ■ Informed search (heuristic search)

- we try to identify which nodes seem more promising, and explore these first
- many algorithms:
  1. Hill climbing
  2. Greedy Best-First search
  3. algorithms A and A\*
  4. ...




# Data Structures

- Most search strategies require:
  - open list (aka the frontier) *To-DO*
    - lists generated nodes not yet expanded
    - order of nodes controls order of search
  - closed list (aka the explored set)
    - stores all the nodes that have already been visited (to avoid cycles).
- ex:


Closed = [A, B, C, D, E]

Open = [F, G, H, I, J, K, L]



# Data Structures

- state space representation: To trace back the solution path after the search, each node in the lists contain:



# Generic Search Algorithm

1. Initialize the <sup>{ TO-DO</sup>open list with the initial node  $s_0$  (top node)
2. Initialize the <sup>{ done / visited</sup>closed list to empty
3. Repeat
  - a) If the open list is empty, then exit with failure.
  - b) Else, take the first node  $s$  from the open list.
  - c) If  $s$  is a goal state, exit with success. Extract the solution path from  $s$  to  $s_0$
  - d) Else, insert  $s$  in the closed list ( $s$  has been visited /expanded)
  - e) Insert the successors of  $s$  in the open list in a certain order if they are not already in the closed and/or open lists (to avoid cycles)

Notes:

- The order of the nodes in the open list depends on the search strategy

# Today


1. State Space Representation
2. State Space Search
  - a) Overview
  - b) Uninformed search
    1. Breadth-first Search and Depth-first Search
    2. Depth-limited Search
    3. Iterative Deepening
    4. Uniform Cost
  - c) Informed search
    1. Intro to Heuristics
    2. Hill climbing
    3. Best-First
    4. Algorithms A & A\*
    5. More on Heuristics
  - d) Summary



# Depth-first vs Breadth-first Search


## ■ Depth-first (DFS):

- visit successors before siblings
- Open list is a stack



## ■ Breadth-first (BFS):

- visit siblings before successors
- ie. visit level-by-level
- open list is a queue






# DFS and BFS

- DFS and BFS differ only in the way they order nodes in the open list:


- DFS uses a stack:

- nodes are added on the top of the <sup>open</sup> list.



- BFS uses a queue:

- nodes are added at the end of the list.



# Breadth-First Search

```
begin
  open := [Start];
  closed := [ ];
  while open ≠ [ ] do
    begin
      remove leftmost state from open, call it X;
      if X is a goal then return SUCCESS
      else begin
        generate children of X;
        put X on closed;
        discard children of X if already on open or closed;
        put remaining children on right end of open
      end
    end
  end
  return FAIL
end.
```

% initialize

% states remain

% goal found

% loop check

% queue


% no states left

# Breadth-First Search Example

## ■ BFS: (open is a queue)

Assume U is goal state

*name of node*  
*name of parent node*



1. open = [A-null] closed = []
2. open = [B-A, C-A, D-A] closed = [A]
3. open = [C-A, D-A, E-B, F-B] closed = [B, A]
4. open = [D-A, E-B, F-B, G-C, H-C] closed = [C, B, A]
5. open = [E-B, F-B, G-C, H-C, I-D, J-D] closed = [D, C, B, A]
6. open = [F-B, G-C, H-C, I-D, J-D, K-E, L-E] closed = [E, D, C, B, A]
7. open = [G-C, H-C, I-D, J-D, K-E, L-E, M-F] as L is already in open closed = [F, E, D, C, B, A]
8. and so on until either U is found or open = []

*visit*  $\Rightarrow$  run goal function

$\rightarrow$  { search path = A B C D E F G H I J K L M N ... U // closed list  
 solution path = A C H P U with a cost of 4 // extract by following the parent pointer

# Depth-First Search

```
begin
  open := [Start];                                % initialize
  closed := [ ];
  while open ≠ [ ] do                             % states remain
    begin
      remove leftmost state from open, call it X;
      if X is a goal then return SUCCESS           % goal found
      else begin
        generate children of X;
        put X on closed;
        discard children of X if already on open or closed;
        put remaining children on left end of open
      end
    end
  end;
  return FAIL
end.
```


% loop check  
% stack  
% no states left

# Depth-First Search Example

## ■ DFS: (open is a stack)

Assume U is goal state

1. open = [A-null] closed = []
2. open = [B-A C-A D-A] closed [A]
3. open = [E-B F-B C-A D-A] closed = [B A]
4. open = [K-E L-E F-B C-A D-A] closed = [E B A]
5. open = [S-K L-E F-B C-A D-A] closed = [K E B A]
6. open = [L-E F-B C-A D-A] closed = [S K E B A]
7. open = [T-L F-B C-A D-A] closed = [L S K E B A]
8. open = [F-B C-A D-A] closed = [T L S K E B A]
9. open = [M-F C-A D-A] as L is already on closed closed = [F T L S K E B A]
10. open = [C-A D-A] closed = [M F T L S K E B A]
11. open = [G-C H-C D-A] closed = [C M F T L S K E B A]



search path = A B E K S L ... U // closed list  
 solution path = A C H P U with a cost of 4

# Depth-first vs. Breadth-first

## ■ Breadth-first:

- advantage: optimal, i.e. will always find shortest path
- disadvantage:
  - high memory requirement as we need to keep all states of a level before expanding to the next level
  - exponential space for states required  $B^n$  // B=branching factor, n=level


*solution*

*average # of successors*

## ■ Depth-first:

- advantage: Requires less memory
- disadvantage: Not optimal (no guarantee to find the shortest path)

*300 steps*



# Today

1. State Space Representation
2. State Space Search
  - a) Overview
  - b) Uninformed search
    1. Breadth-first Search and Depth-first Search ✓
    2. Depth-limited Search
    3. Iterative Deepening
    4. Uniform Cost
  - c) Informed search
    1. Intro to Heuristics
    2. Hill climbing
    3. Best-First
    4. Algorithms A & A\*
    5. More on Heuristics
  - d) Summary



YOU ARE HERE!

# Depth-Limited Search

- Compromise for DFS :
  - Do depth-first but
  - with depth cutoff  $k$  (depth at which nodes are not expanded)
- Three possible outcomes:
  - Solution *within your  $k$  limit :)*
  - Failure (no solution)
  - Cutoff (no solution found within cutoff) ✗
- advantage: memory efficient - it's a DFS
- disadvantage: may not find a solution if it is below the cutoff



# Today

1. State Space Representation
2. State Space Search
  - a) Overview
  - b) Uninformed search
    1. Breadth-first search and Depth-first search
    2. Depth-limited Search
    3. Iterative Deepening
    4. Uniform Cost
  - c) Informed search
    1. Intro to Heuristics
    2. Hill climbing
    3. Best-First
    4. Algorithms A & A\*
    5. More on Heuristics
  - d) Summary




# Iterative Deepening

- Combination of BFS and DFS:
  - do depth-first search, but
  - with a maximum depth before going to next level
  - i.e. Repeats depth first search with gradually increasing depth limits
- advantage:
  - Requires little memory (fundamentally, it's a depth first) —
  - optimal: will find the shortest path (limited depth) —
- disadvantage:
  - repeated traversal of the tree top

# Iterative Deepening: Example

Limit = 0




black node  
 $\Rightarrow$  node has been  
visited


# Iterative Deepening: Example




# Iterative Deepening: Example



# Iterative Deepening: Example



# Today

1. State Space Representation
2. State Space Search
  - a) Overview
  - b) Uninformed search
    1. Breadth-first and Depth-first
    2. Depth-limited Search
    3. Iterative Deepening
    4. Uniform Cost 
  - c) Informed search
    1. Intro to Heuristics
    2. Hill climbing
    3. Best-First
    4. Algorithms A & A\*
    5. More on Heuristics
  - d) Summary

# Uniform Cost Search


- all algorithms so far assume that all edges have the same cost
- but what if they have different costs?
  - eg: move UP  $\rightarrow$  2pts but move DOWN  $\rightarrow$  1 pt
  - eg: cost(residential road) > cost(commercial road)

## Breadth First Search

- uses OPEN as a priority queue sorted by the depth of nodes
- guarantees to find the shortest solution path

## Uniform Cost Search

- takes the cost of the edge into account
- uses OPEN as a priority queue sorted by the total cost from the root to node n - later we will call this  $g(n)$
- guarantees to find the lowest cost solution path





# Example

node  
parent node  
total cost from root to n

open

closed

$\{P_{s1} E_{s9} D_{s3}\}$   
 $\{P_{s1} D_{s3} E_{s9}\}$

$\Delta$   $S_{null} \emptyset$   
#1 replace old  $E$  with new shorter path to  $E$

$\{Q_{p16} D_{s3} E_{s9}\}$   
 $\{D_{s3} E_{s9} Q_{p16}\}$

$S_{null} \emptyset P_{s1}$

$\{B_{d4} C_{d11} E_{d5} Q_{p16}\}$   
 $\{B_{d4} E_{d5} C_{d11} Q_{p16}\}$

$S_{null} \emptyset P_{s1} D_{s3}$

$\Delta$  #2 if 2 nodes have the same cost in the open list  $\Rightarrow$  arbitrary choice

$\{A_{b6} E_{d5} C_{d11} Q_{p16}\}$   
 $\{E_{d5} A_{b6} C_{d11} Q_{p16}\}$


$S_{null} \emptyset P_{s1} D_{s3} B_{d4}$

$\{H_{e6} R_{e14} A_{b6} C_{d11} Q_{p16}\}$   
 $\{H_{e6} A_{b6} C_{d11} R_{e14} Q_{p16}\}$

$E_{d5}$

Is skipped the last steps

solution path : Goal F R E D S cost of 24




# Today

1. State Space Representation ✓
  2. State Space Search ✓
    - a) Overview ✓
    - b) Uninformed search ✓
      1. Breadth-first and Depth-first ✓
      2. Depth-limited Search ✓
      3. Iterative Deepening ✓
      4. Uniform Cost ✓
    - c) Informed search
      1. Intro to Heuristics
      2. Hill climbing
      3. Best-First
      4. Algorithms A & A\*
      5. More on Heuristics
    - d) Summary
- 352

# Problem with Uninformed Search

- inefficient for most AI problems, the state space is too large!
  - e.g. state space of all possible moves in chess =  $10^{120}$
  - $10^{75}$  = nb of molecules in the universe
  - $10^{26}$  = nb of nanoseconds since the "big bang"



- we need a way to try the most promising nodes first

# Up Next

1. State Space Representation
2. State Space Search
  - a) Overview
  - b) Uninformed search
    1. Breadth-first and Depth-first
    2. Depth-limited Search
    3. Iterative Deepening
    4. Uniform Cost
  - c) **Informed search**
    1. Intro to Heuristics  $h(n)$
    2. Hill climbing
    3. Best-First
    4. Algorithms A & A\*
    5. More on Heuristics
  - d) Summary

