

```
import math
def majo_al_cuadrado(x):
    y=x**2
    return y
```

```
majo_al_cuadrado(1)
```

```
1
```

```
def majo2(x):
    y=math.pi*x+1
    return y
majo2(2)
```

```
7.283185307179586
```

```
def majo3(x):
    y=(x+3)/(x**2+1)
    return y
majo3(5)
```

```
0.3076923076923077
```

```
math.log10(1)
```

```
0.0
```

```
def majo4(x):
    y=math.log10((x+3*x**2)/(2+5*math.pi))
    return y
majo4(2)
# tambien se puede determinar cual seria el numerador y el denominador
```

```
-0.10204057676209283
```

```
math.exp(1)
```

```
2.718281828459045
```

```
def majo5(x):
    y=math.exp((5*x+4)/(math.pi+7*x))
    return y
majo5(2)
```

```
2.263080435968593
```

```
x1=[10,2,3,40,5,-30]
print(x1)
print(x1[0])
print(x1[1])
```

```
[10, 2, 3, 40, 5, -30]
10
2
```

```
for x in x1:
    # Bloque de código a ejecutar
    print(x)
```

```
10
2
3
40
5
-30
```

```
for x in x1:
    print(majo4(x))
```

```
1.2431930813939418
-0.10204057676209283
0.2289526422793316
2.4366767492040817
0.6549213745516128
2.1783426489242443
```

```
for x in range(5):
    print(x)
```

```
0
1
2
3
4
```

```
for x in range(5):
    print(majo3(x))
```

```
3.0
2.0
1.0
0.6
0.4117647058823529
```

```
abs(-1)
```

```
1
```

```
for x in range(-5,5):
    print(majo2(x))
```

```
-14.707963267948966
-11.566370614359172
-8.42477796076938
-5.283185307179586
-2.141592653589793
1.0
4.141592653589793
7.283185307179586
10.42477796076938
13.566370614359172
```

```
def majo_valor_absoluto(x):
    if x>0:
        y=x
    elif x<0:
        y=-x
    else
        y=0
    return y
majo_valor_absoluto(-1)
```

1

```
#el mayor numero entre 3
def numero_mayor(a,b,c):
    if a>b and a>c:
        y=a
    elif b>c and b>a:
        y=b
    else:
        y=c
    return y

numero_mayor( -1,0,5)
```

5