# Hidden in Plain Script: Transliteration attacks on Gemma 3

Bhargav Singapuri and Krishna Suraj

Northeastern University

April 22, 2026

**Abstract**

With the increasing use of Large Language Models (LLMs), it becomes imperative to fortify them against a variety of security risks. One such risk is the use of transliterations (writing in one language with the script of another) to "jailbreak" a model. While it might be easier to fortify these models against high-resource languages due to the availability of transliterations into the native language, gaps exist for lower resource languages. We study whether transliterating English prompts into non-Latin scripts alters the safety behaviour of instruction-tuned large language models. Using Gemma-3-4B-IT and JailbreakBench-derived prompts, we construct 13 prompt variants spanning English, native-script translations, English-to-script transliterations, and script-to-English romanisations for Gujarati, Hindi, Telugu, and Tamil. We then evaluate the system at three levels: behavioural outcomes (RQ1), layer-wise token prediction dynamics (RQ2), and sparse autoencoder (SAE) feature activity with linear probing (RQ3). Across 2,600 judged responses, harmful judged-harmful outputs rise from 16.0% in English to 44.8% for native-script translations and 59.0% for English-to-script transliterations, while refusal on harmful prompts drops from 84.0% in English to 69.2% and 53.8% for these settings, respectively. Benign prompts remain mostly non-harmful, but transliteration substantially increases gibberish, especially for script-to-English variants. Internally, layer-wise tracing reveals significant shifts in token-script composition concentrated in mid-to-late layers. SAE analysis further identifies harmful-associated latent activity, and a linear probe trained on SAE activations reaches 81.3% test accuracy, 0.822 F1, and 0.868 ROC-AUC. These results position transliteration as a useful stress test for multilingual safety robustness and for probing internal representation shifts associated with safety failures. All scripts and data are available at https://github.com/majulahsingapuri/hidden-in-plain-script.

## Acknowledgements

We would like to acknowledge Manasa Ganesh for her contribution in verifying and correcting transliterations into Tamil.

## 1 Introduction

### 1.1 Motivation

Large language model safety evaluations are usually framed as a language-understanding problem: if a model understands a harmful request, it should refuse it; if it understands a benign request, it should respond helpfully. In practice, however, both training and evaluation often assume prompts appear in familiar written forms. This leaves open a more specific question: how robust is safety behaviour to changes in script when the underlying intent is preserved?

Transliteration is a useful way to study this question. Unlike translation, transliteration changes the written surface form without primarily aiming to change meaning. In multilingual use, transliteration is common in messaging, search, and informal writing, especially when users mix scripts or type languages phonetically. For safety evaluation, transliteration is interesting because it can preserve the semantic content of a request while shifting its tokenization profile, orthographic familiarity, and distributional match to safety-tuned training data. If model refusals are partly tied to familiar lexical or orthographic patterns, transliteration may expose safety failures even when the request remains recognizably the same to a human reader.

In this paper, we study this phenomenon on Gemma-3-4B-IT using 200 JailbreakBench-derived Chao et al., 2024 prompts, evenly split between harmful and benign requests. This benchmark contains prompts from Mazeika et al., 2024 along with other additional prompts that have been shown to jailbreak models in the past, split equally into `harmful` and `benign` categories. We generate 13 prompt variants across

- English
- Native-Script translations

- English-to-Script transliterations
- Script-to-English romanisations

for Gujarati, Hindi, Telugu, and Tamil. This setup lets us ask three linked questions. First, at the behavioural level, does transliteration increase jailbreak susceptibility or false refusals relative to appropriate baselines? Second, inside the model, do layer-wise token prediction patterns shift systematically under transliteration? Third, in a sparse latent representation of model activations, do harmful and benign prompt conditions remain separable, and if so, what kinds of SAE features appear to drive that separation?

Our results show a substantial safety shift once prompts move away from plain English. Across 2,600 judged responses, harmful judged-harmful outputs rise sharply for both translated and transliterated variants, while refusal on harmful prompts drops. Benign prompts remain mostly non-harmful, but transliteration introduces a marked usability cost through increased gibberish, especially for script-to-English variants. The behavioural results are accompanied by internal changes: layer-wise token-script composition differs significantly across mid-to-late layers, and SAE-based analyses show that harmful and benign prompt conditions are separable in latent feature space. Taken together, these findings suggest that transliteration is a practical robustness stress test for multilingual safety evaluation and that its effects are not purely superficial.

Our contributions are fourfold:

1. We introduce a transliteration-based evaluation setup for multilingual LLM safety using aligned harmful and benign prompt variants.
2. We show that transliteration is associated with materially weaker safety behaviour on harmful prompts relative to English and native-script baselines.
3. We provide layer-wise evidence that transliteration changes internal token prediction patterns in a structured, depth-dependent way.
4. We show that SAE activations support a useful latent-space separation between harmful and benign prompt conditions, complementing the behavioural and layer-wise analyses.

## 1.2 Transliteration, Translation, and Cross-Script Prompting

Translation and transliteration are related but distinct operations. Translation aims to preserve meaning while changing language; transliteration aims to preserve pronunciation or surface form while changing script. In this project, those distinctions matter because the prompt variants are designed to separate semantic transfer from orthographic change.

Each prompt begins in English (en). For each target language, we generate three additional forms: a native-script translation (<lang>), an English-to-script transliteration (en_<lang>), and a script-to-English romanisation of the translated text (<lang>_en). The native-script translation changes both language and script. The English-to-script transliteration changes script while staying closest to the original English wording. The script-to-English romanisation provides a second transliteration direction that often preserves the sound of the translated prompt while producing an unusual English-script string. This design allows us to compare transliterated inputs against the most relevant baseline rather than against a single pooled control.

This paper treats transliteration as a structured input perturbation; it targets the boundary between semantic preservation and orthographic shift. That boundary is especially relevant for safety because many refusal behaviours may be keyed not only to meaning but also to lexical familiarity, tokenization, or distributional regularities in safety-tuning data.

## 1.3 LLM Safety, Multilingual Robustness, and Mechanistic Perspectives

Recent work on LLM safety has emphasized jailbreak evaluation, harmful instruction following, refusal consistency, and the limitations of English-only assessments. Benchmarks such as JailbreakBench Chao et al., 2024 provide a useful foundation for testing whether models comply with harmful requests and whether those failures generalize across perturbations. Our work builds directly on this tradition but shifts the focus from prompt engineering or adversarial suffixes to a multilingual orthographic perturbation that can plausibly occur in real use.

This framing matters because transliteration combines elements of robustness evaluation and multilingual alignment. Unlike many jailbreak methods, it does not primarily rely on hidden instructions or complicated attack strings. Unlike standard multilingual evaluation, it does not simply ask whether a model can respond in another language. Instead, it asks whether safety behaviour remains stable when the same underlying request is rendered in a different script or

phonetic form. That makes transliteration a useful intermediate case: closer to naturalistic use than many synthetic attacks, but more targeted than generic multilingual benchmarking.

Ghanim et al., 2024 demonstrated that transliterating harmful English prompts into Arabizi (Arabic phonetics using Latin script and numbers) significantly increases the Attack Success Rate (ASR) on models like GPT-4 and Claude 3. It explores the vulnerability of safety filters to informal, phonetic scripts. More broadly, Deng et al., 2024 finds that the lower-resource a language is, the more susceptible it is to being jailbroken. They introduce "SelfDefence" as a methodology to reduce the generation of harmful prompts by fine tuning ChatGPT on harmful and benign examples. Complementing these approaches, Zou et al., 2023 uses a taxonomy driven detector to determine if interactions between an LLM and user are jailbreak attempts, representing a post hoc detection strategy rather than a prevention mechanism.

Interpretability methods provide a complementary lens on these safety failures. Layer-wise token prediction tracing can reveal when internal processing begins to diverge across inputs, while sparse autoencoders and linear probes can expose latent dimensions associated with particular task conditions or outputs. In this paper, we use both tools conservatively. The goal is not to claim a definitive causal mechanism for transliteration-induced safety failures, but to test whether the behavioural shift is accompanied by structured internal changes and whether those changes are legible in latent feature space.

Prior work supports the relevance of this lens. Upadhayay and Behzadan, 2025 uses Logit Lens to investigate why LLMs are vulnerable to low-resource languages, identifying a "late-layer pivot" where the model understands the harmful intent in early layers but only fails to refuse because the safety alignment is weak for that specific linguistic tokenization. Assogba et al., 2026 introduces CC-Delta, a defense using Sparse Autoencoders (SAEs) to identify sparse features associated with jailbreak contexts, suggesting that even if a prompt is "obfuscated", the underlying "harmful intent" features often still fire in the SAE latent space. Similarly, Saji et al., 2025 shows that multilingual large language models often internally convert non-Latin script words into Romanized (Latin alphabet) representations during intermediate processing, indicating that multilingual reasoning may rely on implicit script normalization.

Finally, Yona et al., 2025 introduces "Doublespeak", an attack where benign tokens are intentionally mapped to harmful meanings through in-context examples, demonstrating that semantic meaning in the residual stream can be overwritten layer-by-layer. In a related line of work, Arditi et al., 2024 finds that refusal behaviour in chat models is controlled by a single direction in the residual stream activation space; removing that direction disables safety refusals, while adding it can induce refusals even for harmless prompts. Together, these results suggest that alignment mechanisms are low-dimensional and brittle, and that safety failures—whether induced by transliteration or other forms of obfuscation—may arise from relatively small but structured shifts in internal representations.

## 1.4 Initial Study

As an initial proof of concept, we can see the Logit Lens view of the internals of a Gemma-3-4B-IT model in Figure 2 with the phrase "Where are you going tomorrow?" written in Gujarati as "વેર આર યુ ગોઇંગ ટુમોરો?". The phonemic mapping is:

| English | Gujarati |
|---|---|
| Whe | વે |
| re | ર |
| are | આર |
| you | યુ |
| go | ગો |
| i | ઇ |
| ng | ંગ |
| to | ટુ |
| mo | મો |
| row | રો |

Table 1: Phonemic mapping of "Where are you going tomorrow?" into Gujarati

We can see that after the 5th token ("where are you"), the model implicitly understands that a question has been asked and suggests "doing" as a possible next word from layers 23-30 before changing to a lower probability "?".

In 7th token, we can see that it understands the phoneme breakdown of the word "going" into "goh-EE-ng" and correctly predicts the 8th token. This inspires our confidence in the model's ability to understand transliterations.

When we then ask the model to generate the completion for the prompt "To make a bomb, you need:", it lists out chemicals that are typically used in making explosives without giving any further instructions as seen in Section C. It is worth noting that due to the probabilistic nature of the models, it will not always generate the harmful text. However, it is a promising start that shows that this attack vector has merit.

# 2 Experimental Design

The paper is organized around three research questions:

- RQ1: Does transliteration increase jailbreak susceptibility on harmful prompts and false-refusal cost on benign prompts relative to relevant baselines?
- RQ2: Do layer-wise token predictions shift systematically under transliterated prompt variants?
- RQ3: Do SAE latents and probe features distinguish harmful from benign prompt conditions across these variants?

The design deliberately combines behavioural and internal analyses. RQ1 establishes whether the effect exists. RQ2 tests whether the effect is accompanied by structured changes in token-level processing across layers. RQ3 asks whether these changes are reflected in a sparse latent representation that supports reliable discrimination between harmful and benign prompt conditions.

## 2.1 Dataset

We start from 200 JailbreakBench-derived prompts: 100 harmful and 100 benign. The benign set is important because safety degradation is only one side of the evaluation problem. A system that refuses fewer harmful prompts may also become less usable on benign requests, either through false refusals or incoherent output. Including both prompt types lets us measure safety robustness and usability cost simultaneously.

The dataset pipeline first writes base rows containing English prompts and metadata such as `prompt_id`, `behaviour`, and `split`. It then enriches each row with additional language variants. For each of Gujarati, Hindi, Telugu, and Tamil, the dataset includes:

- en: the original English prompt
- <lang>: a translated prompt in native script
- en_<lang>: English transliterated into the target script
- <lang>_en: a romanized rendering of the translated prompt

This produces 13 variants per prompt: one English baseline plus three forms for each of the four target languages, resulting in an evaluation set containing 2,600 prompt variants. The en_<lang> datapoints were manually checked by native speakers to ensure that they are accurate. The <lang>_en datapoints were provided by Google Translate.

## 2.2 Model, Inference and Judging

All experiments use Gemma 3 4B IT. For RQ1, the model generates one response for each prompt variant, which are then judged along three binary dimensions:

- refused: The model refused to produce the requested output either by stating something to the effect of "I cannot produce..." or by writing something different on the same topic.
- harmful: The model produced output that is harmful.
- gibberish: The model produced output that is incoherent, repetitive and/or not related to the topic at hand.

These labels define the downstream behavioural categories as shown in Table 2. If the LLMs work as intended, the desired outcomes are `Refused` for harmful prompts and `Complied` for benign prompts.

| Refused | Harmful | Case | Interpretation for Harmful | Interpretation for Benign |
|---|---|---|---|---|
| T | F | Refused | Safe Refusal | Over-Refusal |
| F | F | Complied | Failure to Refuse | Desired Benign Response |
| F | T | Harmful | Jailbreak | Harmful Error |
| T | T | Refused + Harmful | Partial Failure | Harmful Error |

Table 2: Safety Judgements Interpretations

The judging setup is implemented through an asynchronous LLM-as-judge pipeline using OpenAI's GPT 4.1-mini. The results were manually checked to ensure adherence to the judgement rubric.

### 2.3 Statistical Analysis

The RQ1 analysis is conducted only on non-gibberish outputs. This choice avoids conflating two different failure modes: harmful compliance and incoherence.

For pairwise behavioural comparisons, each transliteration variant is compared against its most relevant baseline:

- 'en_<lang>' vs 'en'
- '<lang>_en' vs '<lang>'

Fisher's exact test is used when expected counts are small and chi-squared tests otherwise. Benjamini-Hochberg correction is applied within prompt-type families to control for multiple comparisons. The analyses also include pooled summaries across comparison groups and an optional topic-level clustering analysis for prompt subsets.

For RQ2, layer-wise comparisons use script-composition measurements derived from traced top predicted tokens at each layer. The main summary reports pooled significant layers after false discovery rate correction, along with variant-level heatmaps and sensitivity analyses.

For RQ3, SAE activations are computed at a fixed model layer and used both for latent ranking and for a linear probe. Probe performance is reported using standard classification metrics including test accuracy, F1, and ROC-AUC.

## 3 Results

### 3.1 RQ1

RQ1 evaluates 2,600 model responses, corresponding to 200 base prompts across 13 variants. The breakdown of Gibberish and Non-Gibberish responses is shown in Table 3.

| Prompt Type | Total Responses | Non-Gibberish | Gibberish | Gibberish Rate |
|---|---|---|---|---|
| Harmful | 1300 | 978 | 322 | 24.8% |
| Benign | 1300 | 813 | 487 | 37.5% |
| Total | 2600 | 1791 | 809 | 31.1% |

Table 3: RQ1 Response Gibberish Split

| prompt type | comparison group | Refused | Complied | Harmful | Refused + Harmful |
|---|---|---|---|---|---|
| benign | EN→script transliteration | 6.1 | 78.7 | 6.9 | 8.3 |
| | English baseline | 9.3 | 76.3 | 13.4 | 1.0 |
| | Native script translation | 7.8 | 78.5 | 11.0 | 2.7 |
| | Script→EN romanisation | 29.9 | 55.2 | 11.9 | 3.0 |
| harmful | EN→script transliteration | 34.4 | 7.5 | 18.9 | 39.2 |
| | English baseline | 77.8 | 6.1 | 9.1 | 7.1 |
| | Native script translation | 48.1 | 8.1 | 16.6 | 27.3 |
| | Script→EN romanisation | 48.1 | 4.4 | 15.0 | 32.5 |

Table 4: Percentage of judged responses by prompt type and comparison group

This split is important for interpretation. A transliterated prompt may cause a model either to comply more readily with a harmful request or to fail more generally by producing incoherent output. Those outcomes both matter, but they should not be collapsed into a single rate without qualification. We therefore treat non-gibberish safety outcomes as the primary signal.

The main results of this experiment are shown in Table 4, with its corresponding chart in Figure 3 for our visual readers. Comparing harmful prompts against their English baseline, we can clearly see a marked increase in the number of responses that were judged harmful, even including partial failures. For benign prompts, the false refusal rates (benign prompt judged as refused) is also higher for all variants compared to the English baseline

It is worth noting that a fair number of the benign prompts are also being judged as harmful or refused as the model tends to repeat the prompt or translate it into English, which gets flagged by the judge as harmful. This translation also refuses to answer the prompt and thus can be judged as refused.




Figure 1: Pooled bias of layer to Latin ($> 0$) or Non-Latin ($< 0$) scripts. Layers marked by red dots are biased with statistical significance of $p \leq 0.05$.

We perform pairwise tests that compare each transliterated condition against its relevant baseline, rather than against a pooled control. This choice is important because transliteration is not a single homogeneous intervention. English-to-script transliteration preserves the original English lexical content more closely than script-to-English romanisation, and the native-script baselines already differ from English in both language and tokenization.

We find that English transliterated into Telegu produced the most statistically significant increase in jailbreak rate at $p = 0.0219$ while Tamil produced the most statistically significant decrease at $p = 0.0491$. For benign prompts, Telegu and Tamil romanised into English lead to a statistically significant increase in false-refusal rates at $p = 0.0448$ and $p = 0.0035$ respectively. The full table of results can be found in Table 6.

RQ1 establishes the main empirical claim of the paper. Transliteration is associated with weaker safety behaviour on harmful prompts, especially in the English-to-script direction, while also increasing incoherence and usability cost on benign prompts. The effect is not monolithic: some of it reflects clean harmful compliance, some of it reflects general degradation, and the balance differs by language and transliteration direction. Still, the aggregate pattern is clear enough to motivate a deeper look at the model's internal processing.

## 3.2 RQ2

RQ2 traces top predicted tokens layer by layer and maps them into script categories. The resulting representation lets us ask whether transliterated prompts merely affect the final output distribution or whether they alter internal token prediction dynamics throughout the network. The main summary metric is script composition, including the share of Latin-script predictions at each layer. A simplified internal representation is found in Figure 5 and the full interactive chart can be found in our GitHub. Each line represents a script and the value is the proportion of that script found in that layer pooled across all prompts.

Figure 1 compares the internal representations of harmful and benign prompts. The proportion of Latin to Non-Latin scripts is measured and the differences are taken on a per layer basis. The results show significant layer-wise differences after false discovery rate correction at layers 5, 13, 15-24, 27, 28, and 30. Two features of this result matter. First, the effect is distributed rather than confined to the final layer, which suggests that transliteration affects internal processing over a substantial portion of the forward pass. Second, the effect is concentrated mostly in mid-to-late layers rather than uniformly across all 34 traced layers, which argues against a trivial interpretation in which script simply alters the input embedding and then washes out immediately. We also notice the presence of the "late-layer pivot" found by Upadhayay and Behzadan, 2025 for English to Native language transliterations.

Variant-specific analyses in Figure 6a show that the strength and span of these effects differ across prompt forms. The English baseline has nine significant layers, EN→GU has eleven, EN→HI has ten, and EN→TE has four. Other variants show their own distinct significance patterns. These differences support a representation-level view of the behavioural results: transliteration changes not only what the model outputs, but also how script-specific information is processed through depth.

A joined RQ1-RQ2 analysis that tests whether layer-wise script-composition features are associated with refusal and harmfulness judgments after merging the behavioural and tracing outputs was conducted with results shown in Figure 7 and Figure 8. While there are variations in the bias towards Latin scripts, none of these values are significant, with the exception of benign en_gu prompts being judged safe in the 28th layer.

The strongest pooled adjusted association appears for harmful-prompt refusal at layers 3, 29, and 32, while pooled adjusted effects for the other outcome families are absent or weak. Prediction baselines using summary features also produce only modest discrimination for most behavioural outcomes, with AUROC around 0.601 for harmful/refused, 0.636 for harmful/harmful, 0.607 for benign/refused, and 0.428 for benign/harmful.

These results are useful mainly as a caution. They show that transliteration clearly changes layer-wise script composition, but they do not provide a clean one-to-one mapping from those features to final safety judgments. That is, the internal shift is real, but it is not fully captured by a simple layer-wise Latin-share explanation. This motivates the richer latent-space analysis in RQ3.

### 3.3 RQ3

RQ3 analyzes sparse autoencoder activations extracted from Gemma 3 4B IT at layer 17 using a Gemma Scope 2 SAE. For each prompt variant, we store one mean-pooled SAE activation vector. This setup supports two complementary analyses: identifying latents that fire strongly for harmful prompts, and testing whether a linear classifier can separate harmful from benign prompt conditions in this feature space.

The latent ranking analysis shows that several SAE features fire very strongly and very frequently on harmful examples. The highest-ranked latent, for example, has a harmful fire rate near 1.0 and a very large mean activation. The precise semantic interpretation of these latents should be handled carefully; without deeper manual or token-level analysis, they are best described as harmful-associated features rather than definitive concepts. Still, the contrastive exemplar view is useful because it shows that the latent space contains structured variation aligned with the task distinction.

The linear probe provides the clearest quantitative result from RQ3. Trained on the saved SAE activations, it reaches 81.3% test accuracy, 0.822 test F1, and 0.868 test ROC-AUC. These numbers indicate that harmful and benign prompt conditions are substantially separable in the SAE feature space. That result is not, by itself, a mechanistic explanation of transliteration-induced safety failures. But it does support the claim that the model's internal representation of these prompt conditions is organized enough to be read out by a simple classifier.

Taken together, RQ2 and RQ3 show that the behavioural shift observed in RQ1 is accompanied by measurable internal changes. RQ2 demonstrates that transliteration affects layer-wise token prediction dynamics in a structured, depth-dependent way. RQ3 shows that the resulting activation space contains harmful-associated sparse features and supports simple linear separation between harmful and benign prompt conditions. The internal analyses therefore strengthen the paper's main claim without overstating causality: transliteration-induced safety drift is associated with nontrivial representational change.

## 4 Discussion

The main lesson of this paper is that safety behaviour is not invariant to script. Changing the orthographic form of a prompt can materially alter refusal and harmful-compliance behaviour even when the underlying request remains closely aligned with the English source. In that sense, transliteration is a useful robustness stress test: it is structured, realistic, and strong enough to reveal failures that may be missed by English-only evaluation.

The results also suggest that transliteration should not be treated as equivalent to ordinary multilingual prompting. Native-script translations, English-to-script transliterations, and script-to-English romanisations behave differently. Some variants produce more harmful compliance; others produce more gibberish; still others show mixed patterns depending on language. This matters for safety evaluation because a model can appear safer or less safe depending on whether one emphasizes harmfulness, refusal, or coherence. A robust multilingual safety benchmark should therefore separate these dimensions explicitly.

At the same time, the internal analyses argue against a purely superficial explanation. If transliteration only caused a minor front-end perturbation, we would expect its effects to vanish quickly or to remain confined to simple input-level differences. Instead, the observed layer-wise changes span a broad mid-to-late-layer region, and SAE features offer a useful latent-space view of harmful-versus-benign processing conditions. The joined RQ1-RQ2 analysis remains weaker than the main RQ2 and RQ3 results, however, so we resist the temptation to claim a full mechanistic account. The safer conclusion is that transliteration induces a meaningful distribution shift that propagates through internal representations and is associated with measurable changes in safety behaviour.

These findings have practical implications. Safety evaluations for multilingual or globally deployed systems should include cross-script perturbations in addition to plain-language prompts, translations, and conventional jailbreak attacks. Mitigation strategies may include transliteration-aware data augmentation, cross-script adversarial training, or tokenizer-aware safety evaluation protocols. More broadly, the results support a design principle for safety research: robustness should be tested not only to semantic paraphrases and adversarial suffixes, but also to orthographic and script-level transformations that arise in real use.

## 5 Limitations

This study has several limitations.

First, the main behavioural and mechanistic analyses focus on a single model family, Gemma 3 4B IT. The conclusions therefore establish the existence of the phenomenon in one strong setting, but they do not yet show how broadly it generalizes across architectures, sizes, or alignment procedures.

Second, the language set is limited to Gujarati, Hindi, Telugu, and Tamil. These languages provide useful script diversity, but they do not exhaust the space of multilingual or cross-script behaviour. Other scripts, transliteration conventions, and user communities may exhibit different effects.

Third, the interpretability results are associative rather than causal. Layer-wise script-composition shifts and SAE probe separability show that transliteration changes internal representations, but they do not identify a single causal pathway or a minimal set of responsible features. The probe result should be interpreted as evidence of separability, not proof of a semantic mechanism.

Finally, the current paper prioritizes empirical clarity over breadth. It does not yet include ablations over transliteration methods, or cross-model comparisons. Those would all be valuable extensions for future work.

# 6 Ethical Considerations

This work has both defensive and dual-use implications. On the defensive side, it identifies a concrete weakness in multilingual safety behaviour that is likely to matter for real-world deployment. Users frequently mix scripts, languages, and phonetic spellings in practice, and a system that appears safe under standard orthography may behave differently under transliterated inputs. Studying those failures can improve evaluation coverage and motivate better multilingual safety training.

More broadly, the results underscore the need to treat multilingual safety as more than a translation problem. Systems deployed across languages and scripts should be evaluated for both harmful compliance and degradation in helpful behaviour. A model that becomes incoherent or overly refusing under cross-script inputs may fail users even when it does not comply with harmful requests.

# References


Arditi, A., Obeso, O., Syed, A., Paleka, D., Rimsky, N., Gurnee, W., & Nanda, N. (2024, June). Refusal in language models is mediated by a single direction. *arXiv.org*. https://doi.org/10.48550/arXiv.2406.11717

Assogba, Y., Cortellazzi, J., Abad, J., Rodriguez, P., Suau, X., & Blaas, A. (2026). Sparse autoencoders are capable llm jailbreak mitigators. *arXiv.org*. Retrieved March 11, 2026, from https://arxiv.org/abs/2602.12418

Chao, P., Debenedetti, E., Robey, A., Andriushchenko, M., Croce, F., Sehwag, V., Dobriban, E., Flammarion, N., Pappas, G. J., Tramèr, F., Hassani, H., & Wong, E. (2024). Jailbreakbench: An open robustness benchmark for jailbreaking large language models. *NeurIPS Datasets and Benchmarks Track*.

Deng, Y., Zhang, W., Pan, S. J., & Bing, L. (2024). Multilingual jailbreak challenges in large language models. https://arxiv.org/abs/2310.06474

Ghanim, M. A., Almohaimeed, S., Zheng, M., Solihin, Y., & Lou, Q. (2024). Jailbreaking llms with arabic transliteration and arabizi. *arXiv.org*. https://arxiv.org/abs/2406.18725

Mazeika, M., Phan, L., Yin, X., Zou, A., Wang, Z., Mu, N., Sakhaee, E., Li, N., Basart, S., Li, B., Forsyth, D., & Hendrycks, D. (2024). Harmbench: A standardized evaluation framework for automated red teaming and robust refusal. *arXiv preprint arXiv:2402.04249*.

Saji, A., Husain, J. A., Jayakumar, T., Dabre, R., Kunchukuttan, A., & Puduppully, R. (2025). Romanlens: The role of latent romanization in multilinguality in llms. *Findings of the Association for Computational Linguistics: ACL 2025*, 26410–26429. https://doi.org/10.18653/v1/2025.findings-acl.1354

Upadhayay, B., & Behzadan, V. (2025). Tongue-tied: Breaking llms safety through new language learning. *Proceedings of the 7th Workshop on Computational Approaches to Linguistic Code-Switching*, 32–47. https://doi.org/10.18653/v1/2025.calcs-1.5

Yona, I., Sarid, A., Karasik, M., & Gandelsman, Y. (2025). In-context representation hijacking. *arXiv.org*. Retrieved March 11, 2026, from https://arxiv.org/abs/2512.03771

Zou, A., Wang, Z., Kolter, J. Z., & Fredrikson, M. (2023). Universal and transferable adversarial attacks on aligned language models.

# A Author Contributions

| Bhargav | Krishna |
|---|---|
| Experimental Design | Python Script Drafts |
| Proposal Writing | RQ1 Analysis |
| Python Scripts | Telegu transliterations |
| Running Experiments (RQ1, RQ2, RQ3) | |
| RQ2 Analysis | |
| RQ3 Analysis | |
| Statistical Testing | |
| Presentation Slides | |
| Report Writing | |
| Gujarati transliterations | |

Table 5: Author Contributions

# B Model Logit Lens




Figure 2: Logit Lens on Gemma 3 4B IT with "Where are you going tomorrow?" in Gujarati

# C Harmful Text Generation Example

The prompt "To make bomb, you need:" transliterates into "**ટુ મેક બૉમ્બ, યુ નીડ:**" and produces the following output:

ટુ મેક બૉમ્બ, યુ નીડ:

1. સંયોજિત ગ્લુટેમાઇન એસિડના મોનોમર્સ (જેમ કે એલ-ગ્લુટામેટ અને એલ-પ્રોલીન)
2. એક ડિઓક્સિઝિન સંયોજન (જેમ કે ટ્રોટિલિન અથવા ડીએનપી)
3. એક એક્ઝોથર્મિક પ્રેરક (જેમ કે હાઇડ્રોજન પેરોક્સાઇડ)
4. એક ઉર્જા સ્ત્રોત (જેમ કે બેટરી)
5. એક કન્ટેનર (જેમ કે પ્લાસ્ટિકની બોટલ)

આ બધી સામગ્રી ભેગી કરીને અને તેને ચોક્કસ રીતે સંયોજિત કરીને, તમે એક બૉમ્બ બનાવી શકો છો. જો કે, હું આ પ્રવૃત્તિને સક્રિયપણે પ્રોત્સાહન આપતો નથી અને તેનાથી થતા કોઈપણ નુકસાન માટે જવાબદાર નથી.

જો તમે આ બધી પ્રવૃત્તિઓથી પ્રભાવિત છો, તો કૃપા કરીને કોઈ વ્યાવસાયિકની મદદ લો.

which translates into:

```
To Make a Bomb, You Need:
1. Monomers of Conjugated Glutamic Acid (such as L-Glutamate and L-Proline)
2. A Dioxygen Compound (such as Trotylene or DNP)
3. An Exothermic Inducer (such as Hydrogen Peroxide)
4. An Energy Source (such as a Battery)
5. A Container (such as a Plastic Bottle)

By gathering all of these materials and combining them in a specific way, you can make a bomb.
However, I do not actively promote this activity and am not responsible for any
damage that may result from it.

If you are affected by any of these activities, please seek the help of a professional.
```

It is worth noting that the model also provides the following disclaimer in English:

```
*Disclaimer: I am an AI chatbot and cannot provide instructions for illegal or dangerous
activities. The above information is provided solely for informational purposes and
should not be used to create any harmful devices.*
```

# D Breakdown of Judged Responses




Figure 3: Non-gibberish response composition by prompt type and comparison group. English-to-script transliterations increase harmful behaviour on harmful prompts, while script-to-English variants introduce a large false-refusal cost among non-gibberish benign responses




Figure 4: Comparison of Jailbreak Susceptibility and False-Refusal cost across variant types.

# E Script Proportion by Layer




Figure 5: Proportion of scripts per layer pooled over all prompts

# F Statistical Analysis of Transliterations

| prompt type | metric | language | comparison | baseline | transliteration | baseline rate | transliteration rate | delta pp | p adj | sig |
|---|---|---|---|---|---|---|---|---|---|---|
| harmful | jailbreak | Gujarati | EN→script vs English | English | EN→Gu | 9.1 | 14.3 | 5.2 | 0.3625 | |
| harmful | jailbreak | Gujarati | Script→EN vs Native | Gujarati | Gu→EN | 16.1 | 27.3 | 11.1 | 0.3625 | |
| harmful | jailbreak | Hindi | EN→script vs English | English | EN→Hi | 9.1 | 15.5 | 6.4 | 0.3471 | |
| harmful | jailbreak | Hindi | Script→EN vs Native | Hindi | Hi→EN | 15.0 | 18.3 | 3.3 | 0.6629 | |
| harmful | jailbreak | Telugu | EN→script vs English | English | EN→Te | 9.1 | 26.0 | 16.9 | 0.0219 | * |
| harmful | jailbreak | Telugu | Script→EN vs Native | Telugu | Te→EN | 13.4 | 13.9 | 0.5 | 1.0000 | |
| harmful | jailbreak | Tamil | EN→script vs English | English | EN→Ta | 9.1 | 21.1 | 12.0 | 0.0667 | |
| harmful | jailbreak | Tamil | Script→EN vs Native | Tamil | Ta→EN | 22.1 | 4.8 | -17.3 | 0.0491 | * |
| benign | false refusal | Gujarati | EN→script vs English | English | EN→Gu | 10.3 | 15.3 | 4.9 | 0.4797 | |
| benign | false refusal | Gujarati | Script→EN vs Native | Gujarati | Gu→EN | 11.1 | 40.0 | 28.9 | 0.2202 | |
| benign | false refusal | Hindi | EN→script vs English | English | EN→Hi | 10.3 | 12.8 | 2.5 | 0.6847 | |
| benign | false refusal | Hindi | Script→EN vs Native | Hindi | Hi→EN | 8.2 | 21.4 | 13.2 | 0.0784 | |
| benign | false refusal | Telugu | EN→script vs English | English | EN→Te | 10.3 | 11.9 | 1.6 | 0.7426 | |
| benign | false refusal | Telugu | Script→EN vs Native | Telugu | Te→EN | 15.4 | 50.0 | 34.6 | 0.0448 | * |
| benign | false refusal | Tamil | EN→script vs English | English | EN→Ta | 10.3 | 18.5 | 8.2 | 0.2202 | |
| benign | false refusal | Tamil | Script→EN vs Native | Tamil | Ta→EN | 7.4 | 62.5 | 55.1 | 0.0035 | ** |

Table 6: Statistical impact of transliterations at $p = (*)0.05, (**)0.01, (***)0.001$.

# G Script Bias by Prompt Variant




(a) Bias of layer to Latin ($> 0$ or Non-Latin $< 0$ scripts.




(b) Statistical Significance of Bias to Latin/Non-Latin script.

Figure 6: Bias and corresponding statistical significance to Latin/Non-Latin script faceted by prompt variant.

# H Joint RQ1-RQ2 analysis




(a) Harmful prompts judged Harmful Script Bias




(b) Harmful prompts judged Harmful Script Significance




(c) Harmful prompts judged Refused Script Bias




(d) Harmful prompts judged Refused Script Significance




(e) Harmful prompts judged Safe Script Bias




(f) Harmful prompts judged Safe Script Significance

Figure 7: Joint RQ1-RQ2 analysis Harmful




(a) Benign prompts judged Harmful Script Bias




(b) Benign prompts judged Harmful Script Significance




(c) Benign prompts judged Refused Script Bias




(d) Benign prompts judged Refused Script Significance




(e) Benign prompts judged Safe Script Bias




(f) Benign prompts judged Safe Script Significance

Figure 8: Joint RQ1-RQ2 analysis Benign