RVR

27 FFR 2020

27 FEB 2020			37 40 245 144 50 36E		WELBOOKNE, VIC (TWINL)	
ATIS 118.0 114.1		ACD 127.2	SMC 121.7	TWR 120.5		Bearings are Magnetic Elevations in FEET AMSL
		AERODROME LIGHTING				
RWY		ABN : ALTN W/G TAXIWAY: GREEN CL, STOP BAR, RGL RL : MAN, SDBY (1 SEC DURING LOW VIS PROC, 15 SEC OT)				
16	160	PAPI 3.0° 74	FT HIRL HIAL-	-CAT II-III SFL I	RTZL RCLL RC	GL RVR
340	34	PAPI 3.0° 74	FT HIRL	SFL	HSL RCLL RC	CGL RVR
09	083	PAPI 3.0° 74	IFT MIRL			RVR

NOTES

263

27

- 1. WARNING: RWY LIGHTS MAY BE PARTIALLY OBSCURED WHEN ON DOWNWIND LEG FOR RWY 09.
- 2. TWY F NOT AVBL FOR ACFT ABOVE 5700KG LDG RWY 16.

PAPI 3.0° 74FT HIRL HIAL-CAT II-III SFL RTZL RCLL

- 3 TWY G NOT AVBLEOR ACET ABOVE 5700KG LDG RWY 34
- 4. LOW VISIBILITY TAXIWAY AVAILABILITY.

THE FOLLOWING TAXIWAYS ARE SUITABLE FOR USE IN RVR CONDITIONS OF LESS THAN A VALUE OF 350M.

. Twy A: full length

- . Twy B: full length
- . Twy E: full length
- Twy T: between Twy V and Twy P
- Twy U: full length
- . Twy G: full length
- . Twy Y: full length
- Twy J: full length
- . Twy K: full length
- . Twy M: full length
- Twy V: full length
- Twv S between Twv E and Twv T (NOT AVBL A380 ACFT)
- Twy S between Twy U and Twy G (NOT AVBL A380 ACFT)
- Twy Q: full length
- . Twy R: full length
- . Twy P: full length
- 5. THE FOLLOWING TAXIWAYS ARE SUITABLE IN RVR CONDITIONS OF LESS THAN A VALUE OF 550M BUT NOT LESS THAN 350M.
 - Twy T between Twy P and Twy R
 - Twy S between Twy Y and Twy J (NOT AVBL A380 ACFT)
- 6. ALL TAXIWAYS ARE SUITABLE FOR USE IN RVR CONDITIONS OF GREATER THAN 550M.
- 7. BAY ACCESS TO D12 IS VIA INTERSECTION OF TWY S AND TWY U
- 8. BAY ACCESS TO D14 IS VIA INTERSECTION OF TWY A AND TWY U
- 9. MODEL ACFT OPR WI 500M RAD OF PSN 37 40 42.1S 144 47 23.1E BRG 251 MAG 2.4NM FM ARP SFC TO 300FT AGL.
- 10. MODEL ACFT OPR WI 600M RAD OF PSN 37 36 54.0S 144 40 46.9E BRG 284 MAG 8.7NM FM ARP SFC TO 780FT AGL.

Changes: NOTE 10. MMLAD02-162

