



# make-money api 1.0.0

[ Base url: /api]

[swagger.json](#)

a api for make-money web application

[Contact the developer](#)

## do\_survey



GET

/do\_survey/

用来获取填写问卷的信息列表

### Parameters

Try it out

Name

Description

survey\_id

问卷id

integer

(query)

recipient\_id

填写问卷者id

integer

(query)

content

填写问卷的内容

string

(query)

create\_time

填写问卷的时间

string

(query)

### Responses

Response content type

application/json



Code	Description
200	<pre>{"status": "success", "data": {填写问卷的信息列表数组}}</pre>

<b>POST</b> /do_survey/									
用来上传填写问卷的信息									
Parameters	Try it out								
<table><tr><th>Name</th><th>Description</th></tr><tr><td><b>survey_id * required</b> integer (body)</td><td>问卷id</td></tr><tr><td><b>recipient_id * required</b> integer (body)</td><td>填写问卷者id</td></tr><tr><td><b>content * required</b> string (body)</td><td>填写问卷的内容</td></tr></table>		Name	Description	<b>survey_id * required</b> integer (body)	问卷id	<b>recipient_id * required</b> integer (body)	填写问卷者id	<b>content * required</b> string (body)	填写问卷的内容
Name	Description								
<b>survey_id * required</b> integer (body)	问卷id								
<b>recipient_id * required</b> integer (body)	填写问卷者id								
<b>content * required</b> string (body)	填写问卷的内容								
Responses	Response content type application/json ▼								
<table><tr><th>Code</th><th>Description</th></tr><tr><td>200</td><td><pre>{"status": "success", "msg": "add do survey record succeed"}</pre></td></tr><tr><td>400</td><td><pre>{"status": "failed", "msg": "invalid do survey json format"}</pre></td></tr></table>		Code	Description	200	<pre>{"status": "success", "msg": "add do survey record succeed"}</pre>	400	<pre>{"status": "failed", "msg": "invalid do survey json format"}</pre>		
Code	Description								
200	<pre>{"status": "success", "msg": "add do survey record succeed"}</pre>								
400	<pre>{"status": "failed", "msg": "invalid do survey json format"}</pre>								

<b>login</b> ▼	
<b>POST</b> /login/	

用来登录

## Parameters

Try it out

Name	Description
------	-------------

**id** \* required

用户学号

integer  
(body)

**password** \* required 用户密码

string  
(body)

## Responses

Response content type

application/json



Code	Description
------	-------------

200

```
{"status": "success", "msg": "post success"}
```

400

```
{"status": "failed", "msg": "invalid login format"}
```

403

```
{"status": "failed", "msg": "id and password doesn' t match"}
```

**DELETE**

/login/

用来注销

## Parameters

Try it out

No parameters

## Responses

Response content type

application/json



Code	Description
200	<pre>{"status": "success", "msg": "logout succeed"}</pre>

## package PackageController operations for Package



GET

/package/

用来获取包裹订单列表

### Parameters

Try it out

Name	Description
id integer <i>(query)</i>	订单id
owner_id integer <i>(query)</i>	发布订单者id
receiver_id integer <i>(query)</i>	接收订单者id
state integer <i>(query)</i>	订单状态
limit integer <i>(query)</i>	返回个数限制
offset integer <i>(query)</i>	偏移量

### Responses

Response content type

application/json



Code	Description
200	<pre>{"status": "success", "data": {含有订单信息的data数组}}</pre>

PUT /package/

用来接受或者确定包裹订单

Parameters

Try it out

Name	Description
<b>method</b> * <b>required</b>	receive或者confirm，代表要进行的操作
string (query)	
<b>id</b> * <b>required</b>	订单的id
integer (query)	

Responses

Response content type

application/json

Code	Description
200	<pre>{"status": "success", "msg": "confirmed"}</pre>
400	<pre>{"status": "failed", "msg": "formate error,id is invalid"}</pre>
401	<pre>{"status": "failed", "msg": "Login expired"}</pre>
403	<pre>{"status": "failed", "msg": "confirm the pakage error, please contact with us"}</pre>

POST /package/

用来上传包裹订单

## Parameters

Try it out

Name	Description
------	-------------

<b>reward</b> * required	订单的报酬
--------------------------	-------

number  
(body)

<b>note</b> * required	订单备注
------------------------	------

string  
(body)

## Responses

Response content type

application/json



Code	Description
------	-------------

200	
-----	--

```
{"status": "success", "msg": "post success"}
```

400	
-----	--

```
{"status": "failed", "msg": "invalid json format"}
```

401	
-----	--

```
{"status": "failed", "msg": "Login expired"}
```

403	
-----	--

```
{"status": "failed", "msg": "create the package error, please contact with us"}
```

404	
-----	--

```
{"status": "failed", "msg": "this user doesn' t not exist"}
```

## survey



GET

/survey/

用来获取问卷信息

## Parameters

Try it out

Name	Description
id integer <i>(query)</i>	问卷的id
publisher_id integer <i>(query)</i>	发布问卷用户的id
title string <i>(query)</i>	问卷的标题
limit integer <i>(query)</i>	返回数量限制
offset integer <i>(query)</i>	偏移量

Responses

Response content type

application/json

▼

Code	Description
200	<pre>{"status": "success", "data": {json格式的问卷信息}}</pre>

POST	/survey/
用来上传问卷	
Parameters	Try it out
Name	Description
title * required string <i>(body)</i>	问卷的标题

Name	Description
<b>content</b> * required	问卷的内容
string	
(body)	

Responses

Response content type

application/json

▼

Code	Description
200	<pre>{"status": "success", "msg": "created", "id" : {id}}</pre>
400	<pre>{"status": "failed", "msg": "invalid json format"}</pre>
401	<pre>{"status": "failed", "msg": "Login expired"}</pre>
403	<pre>{"status": "failed", "msg": "create survey failed"}</pre>

PUT

/survey/{id}

用来修改问卷

Parameters

Try it out

Name	Description
<b>title</b> * required	问卷的标题
string	
(body)	
<b>content</b> * required	问卷的内容
string	
(body)	
<b>state</b> * required	问卷的状态
integer	
(body)	



Name	Description
<b>checked * required</b> integer (body)	问卷是否被确认
<b>id * required</b> integer (path)	问卷的id

Responses	Response content type	application/json
<b>Code</b>	<b>Description</b>	
200	<pre>{"status": "success", "msg": "updated"}</pre>	
400	<pre>{"status": "failed", "msg": "formate error"}</pre>	
401	<pre>{"status": "failed", "msg": "Login expired"}</pre>	
403	<pre>{"status": "failed", "msg": "update survey failed"}</pre>	

<b>DELETE</b>	/survey/{id}
用来删除问卷	
<b>Parameters</b>	<b>Try it out</b>
<b>Name</b>	<b>Description</b>
<b>id * required</b> integer (path)	问卷的id

Responses

Response content type

application/json

Code

Description

200

```
{"status": "success", "msg": "updated"}
```

400

```
{"status": "failed", "msg": "formate error"}
```

401

```
{"status": "failed", "msg": "Login expired"}
```

403

```
{"status": "failed", "msg": "the id doesn' t exist"}
```

404

```
{"status": "failed", "msg": "not found"}
```

## user



GET

/user/

用来获取当前登录用户的用户信息

Parameters

Try it out

No parameters

Responses

Response content type

application/json

Code

Description

200

```
{"status": "success", "data": {json格式的用户信息}}
```

400

```
{"status": "failed", "msg": "Login expired"}
```

**Code****Description**

401

```
{"status": "failed", "msg": "user doesn't exist"}
```

**PUT****/user/**

用来修改用户信息，body为json格式

**Parameters****Try it out****Name****Description****id \* required**

用户的学号

integer

(body)

**password \* required**

用户的密码

string

(body)

**real\_name \* required**

用户的真名

string

(body)

**nick\_name \* required**

用户的昵称

string

(body)

**age \* required**

用户的年龄

integer

(body)

**gender \* required**

用户的性别

string

(body)

**head\_piture \* required** 用户头像（从字节转换成字符串后）

string

(body)

**balance \* required**

用户存款

number

(body)

Name	Description
<b>profession</b> * required string (body)	用户专业
<b>grade</b> * required string (body)	用户年级
<b>phone</b> * required string (body)	用户电话
<b>email</b> * required string (body)	用户邮箱

Responses

Response content type

application/json

Code	Description
200	<pre>{"status" : "success", "msg": "edited"}</pre>
400	<pre>{"status" : "failed", "msg": "invalid user infomation format"}</pre>
401	<pre>{"status" : "failed", "msg": "Login expired"}</pre>
403	<pre>{"status" : "failed", "msg": "this user doesn' t exist"}</pre>

<b>POST</b>	/user/
用来注册用户， body为json格式	
Parameters	Try it out
Name	Description

Name	Description
<b>id * required</b> integer (body)	用户的学号
<b>password * required</b> string (body)	用户的密码
<b>real_name * required</b> string (body)	用户的真名
<b>nick_name * required</b> string (body)	用户的昵称
<b>age * required</b> integer (body)	用户的年龄
<b>gender * required</b> string (body)	用户的性别
<b>head_piture * required</b> string (body)	用户头像（从字节转换成字符串后）
<b>balance * required</b> number (body)	用户存款
<b>profession * required</b> string (body)	用户专业
<b>grade * required</b> string (body)	用户年级
<b>phone * required</b> string (body)	用户电话
<b>email * required</b> string (body)	用户邮箱

Responses		Response content type	application/json
Code	Description		
200	<pre>{"status": "success", "msg": "resgiter succeed"}</pre>		
400	<pre>{"status": "failed", "msg": "invalid user infomation format", "err": {some error}}</pre>		
403	<pre>{"status": "failed", "msg": "this user already registered"}</pre>		

DELETE

/user/

用来删除当前登录的用户

Parameters

Try it out

No parameters

Responses

Response content type

application/json

Code

Description

200

```
{"status": "success", "msg": "bye ~"}
```

401

```
{"status": "failed", "msg": "Login expired"}
```

403

```
{"status": "failed", "msg": "invalid user"}
```