

Code Assessment of the Lockstake Smart Contracts

April 30, 2025

Produced for



by



Contents

1	Executive Summary	3
2	Assessment Overview	5
3	Limitations and use of report	11
4	Terminology	12
5	Open Findings	13
6	Resolved Findings	14
7	Informational	15
8	Notes	16

1 Executive Summary

Dear all,

Thank you for trusting us to help Sky with this security audit. Our executive summary provides an overview of subjects covered in our audit of the latest reviewed contracts of Lockstake according to [Scope](#) to support you in forming an opinion on their security risks.

Sky implements a staking framework that allows borrowing against governance tokens as collateral while retaining the ability to delegate their voting power and simultaneously allowing these tokens to be staked to earn yield.

The most critical subjects covered in our audit are functional correctness, access control and integration with other contracts of the system. The general subjects covered are specification, complexity and unit testing. For the Lockstake implementation, Security regarding all the aforementioned subjects is high.

Before the Governance initializes the Lockstake instance the deployed contracts must be validated carefully. Please refer to note [Deployment verification](#) for more details.

It is important to note that security audits are time-boxed and cannot uncover all vulnerabilities. They complement but don't replace other vital measures to secure a project.

The following sections will give an overview of the system, our methodology, the issues uncovered and how they have been addressed. We are happy to receive questions and feedback to improve our service.

Sincerely yours,

ChainSecurity

1.1 Overview of the Findings

Below we provide a brief numerical overview of the findings and how they have been addressed.

Critical -Severity Findings	0
High -Severity Findings	0
Medium -Severity Findings	0
Low -Severity Findings	1
• Acknowledged	1



2 Assessment Overview

In this section, we briefly describe the overall structure and scope of the engagement, including the code commit which is referenced throughout this report.

2.1 Scope

The assessment was performed on the source code files inside the Lockstake repository based on the documentation files. The table below indicates the code versions relevant to this report and when they were received.

V	Date	Commit Hash	Note
1	08 Apr 2024	a21be78009d80a94f1b84a44ecc04aef74fc40ea	Initial Version
2	16 Apr 2024	f07f45c0d1a47b9e3f82a1db29f4f800c21eaf3	After Intermediate Report
3	26 Apr 2024	ca0c577018dd664e2399e7d842364f2e5dac235f	Final Changes
4	05 July 2024	39dbea91e47911ddb1122d5edd8c4a99934b059	Finalization
5	27 Aug 2024	7c71318623f5d6732457fd0c247a1f1760960011	Fix and Renaming
6	10 Apr 2025	ccc1c16b60a5eb30b4c5836ac93d63a138f70f54	SKY Migration
7	23 Apr 2025	9cb25125bceb488f39dc4ddd3b54c05217a260d1	Migrator Reset Line

For the solidity smart contracts, the compiler version 0.8.16 was chosen. In Version 3 the compiler version was changed to 0.8.21. In the latest reviewed version (**Version 6**) the evm_version is set to shanghai.

The following files are in scope of this review:

```
src/  
  LockstakeClipper.sol  
  LockstakeEngine.sol  
  LockstakeMkr.sol  
  LockstakeUrn.sol  
  Multicall.sol
```

In **Version 3**, the deployment scripts have been added to the scope of the review:

```
deploy/  
  LockstakeDeploy.sol  
  LockstakeInit.sol  
  LockstakeInstance.sol
```

Note that the contracts at **Version 5** have been deployed.

The contracts in scope starting from **Version 6** are:

```
src/  
  LockstakeClipper.sol  
  LockstakeEngine.sol  
  LockstakeMigrator.sol  
  LockstakeSky.sol
```

```
LockstakeUrn.sol
Multicall.sol
deploy/
  LockstakeDeploy.sol
  LockstakeInit.sol
  LockstakeInstance.sol
```

2.1.1 Excluded from scope

All files not listed above including the tests are out of scope. The parameter selection is out of scope. The VoteDelegate and the farms have been part of other reviews. All other contracts are out of scope.

2.2 System Overview

This system overview describes the latest received version as well as the previously deployed version (**Version 5**) of the contracts as defined in the [Assessment Overview](#).

At the end of this report section we have added a changelog for each of the changes accordingly to the versions. Furthermore, in the findings section, we have added a version icon to each of the findings to increase the readability of the report.

Sky implements a staking mechanism that allows participating in governance and yield farming while using the governance token as collateral for CDPs. Note that v1 is (being) deprecated and is using MKR while v2 is using SKY.

2.2.1 Lockstake v1: MKR

Note that this subsection only describes the Lockstake module up to **Version 5** which corresponds to Lockstake v1 where MKR is used.

Sky introduces the **LockstakeEngine** that allows users to open() arbitrarily many **LockstakeUrn** contracts which will be used for the users' positions. Note that these urns can only be managed through the engine by the owner (urn deployer) or addresses authorized by the owner through the usual hope() / nope() mechanism.

To manage the urn's position, the following functionality is provided:

1. lock() and lockSky(): Users can deposit MKR as locked collateral (ink) to arbitrary urns of Lockstake ilk. The latter additionally converts SKY to MKR before locking the MKR.
2. free() and freeSky(): Similarly, urn-authorized addresses can unlock the collateral using these functions. Note that this collects an exit penalty in the form of burning parts of the MKR being unlocked.
3. draw(): Additionally, the urn-authorized addresses may draw() debt which mints the USDS token. This modifies the urn using vat.frob() which enforces the limits / minimum health factor.
4. wipe() and wipeAll(): Any address can repay debt partially or fully. Note that technically debt of addresses other than Lockstake urns can be repaid.

Locked MKR is typically held by the LockstakeEngine. Users can optionally move and thus delegate their locked MKR to one delegate (deployed by the vote delegate factory) per urn with selectVoteDelegate(). In this case, the staked MKR tokens will be transferred to the VoteDelegate contract, where they will be deposited and locked in the Chief. Locking and unlocking delegates to and undelegates automatically if a delegate is selected, the MKR tokens are moved accordingly.

Further, users' urns will hold **LockstakeMkr** tokens (ERC-20), a tokenized representation of an urn's MKR collateral locked. Note that it represents the ink and not the gem. As a consequence, during liquidations, the IsMKR will be burned on `kick()` since the LockstakeClipper will hold only a gem balance but not an ink balance. However, upon auction completion, IsMKR could be reminted due to adding the leftover collateral as ink to the urn.

Users can choose to deposit the IsMKR tokens into farms by selecting at most one farm per urn with `selectFarm()`. Note that farms have to be whitelisted by governance, managed with `addFarm()` and `delFarm()`. Locking and unlocking deposits and withdraws automatically (however deposits only work if the farm is still active). The farms will yield rewards that can be claimed anytime, even after unstaking or staking to another farm, through `getReward()`.

The LockstakeEngine supports `multicall()` to batch operations.

Liquidations of unhealthy urns will be initiated through `Dog.bark()` which invokes `Clipper.kick()` to start the Dutch auction. See our [Liquidations 2.0 audit](#) for a detailed description of how liquidations work. For the Lockstake ilk, a specialized **LockstakeClipper** which features callbacks to the engine is used. The LockstakeClipper works similarly and is different in the following aspects:

1. When an auction is started with `kick()`, the LockstakeEngine's `onKick()` hook is invoked to undelegate the MKR tokens, unstake and burn the LockstakeMkr tokens and track the auction (increases the `urnAuctions` counter, a non-zero `urnAuctions` counter disables delegating and staking).
2. The collateral transfer in `take()` is not implemented as a Vat-internal gem transfer with `Vat.flux()` but is rather implemented as a reduction of the LockstakeClipper's gem balance by the slice taken and calling the LockstakeEngine's `onTake()` hook which transfers out the collateral (MKR) directly.
3. The `ClipperCallee.clipperCall()` is disallowed on the LockstakeEngine.
4. When `take()` completes the auction (either all tab is covered or there is no more lot to sell) the LockstakeEngine's `onRemove()` hook is called. Parameters passed include the amount of MKR sold and left. `onRemove()` implements the functionality to calculate and burn the exit fee which applies, if sufficient funds are available, on liquidated urns (sold collateral / MKR) as well. Further, the urn's liquidation counter in the LockstakeEngine is reduced since the auction completed.
5. Upon `yank()` (cancelling an auction during `End.cage()`), `onRemove` reduces the urns auction counter.

Note that the LockstakeEngine further implements the standard authentication with `rely()` and `deny()`. The authorization allows setting the Jug with `file()`, add and deactivate farms (see above), and call the hooks. It is expected that the specialized clipper will hold the authorization. Additionally, there is a function `freeNoFee()` that allows an urn-authorized and authorized address to call free without collecting fees (e.g. in case of migrations). Further, LockstakeMkr implements the same authorization mechanism that allows to `mint()` (engine is expected to hold these rights).

2.2.1.1 Deployment

The Lockstake system is deployed in two steps:

1. Some EOA deploys the contracts and - if necessary - changes the owner of these contracts to the `PauseProxy`.
2. A governance `Spell` with quorum executes the initialization of the contracts through the `PauseProxy`.

LockstakeDeploy implements `deployLockstake()` to deploy a lockstake instance from an EOA using Foundry. A Lockstake instance consists of four contracts: LockstakeMkr, LockstakeEngine and LockstakeClipper and a calculator (for the Dutch-style auctions; deployed by the contract retrieved from the Chainlog with `CALC_FAB`) contract which are newly deployed.

The initialization is done by executing `initLockstake` of `LockstakeInit` in the context of the Governance Pause proxy. It implements the following steps:

1. The state of the given Lockstake instance is crosschecked with the `LockstakeConfig` passed as function argument `cfg`.
2. Sanity checks are performed on numeric parameters of the `LockstakeConfig`.
3. The new ilk is registered in the VAT, ward permissions are given to the `LockstakeEngine` and `Clipper` (Auction contract). Note that normally `Clipper` contracts do not get the ward role in the VAT, this special `Clipper` needs it due to different collateral management.
4. The line for the ilk is configured, the global Line is increased accordingly (`AutoLineLike.setIlk()`).
5. The rate module is initialized.
6. `Spotter`, `Clipper`, `ClipperMom` and `End` are added to the bud mapping of `PIP_MKR` (price oracle).
7. The `OSMMom` is given the ward role in `PIP_MKR`.
8. The spotter is configured (`mat`, `pip`) and updated (`poke()`).
9. Liquidation contract `Dog` is configured (`clip`, `chop`, `hole`), the `LockstakeClipper` is given the ward role.
10. `LockstakeEngine` is authorized on `lsMKR`.
11. The rate module `jug` is registered in the engine, farms are added. The `LockstakeClipper` is given the ward role in the engine.
12. `LockstakeClipper` is initialized (`buf`, `tail`, `cusps`, `chip`, `tip`, `stopped`, `vow`, `calc`). `upchost()` is triggered to update the cached `dust*chop` value. The `Dog`, `End` and `ClipperMom` are given the ward role in `LockstakeClipper`.
13. If provided, `LineMom` and `ClipperMom` are initialized.

2.2.2 Lockstake v2: SKY

Note that this subsection only describes the Lockstake module starting from **Version 6** which corresponds to Lockstake V2 where SKY is used.

Lockstake for SKY is mostly equivalent to its predecessor. Besides renaming from MKR to SKY the most notable changes include:

- Fees are now immutable.
- `lockSky()` and `freeSky()` have been removed, given that MKR is not used in the new version of Lockstake. Similarly, the converter contract `MkrSky` have been removed from the contract.
- `VoteDelegate v3` is used instead of the `v2`.

2.2.2.1 Migration

A new contract, **LockstakeMigrator**, facilitating the migrations of urns from the v1 to v2 has been introduced. The contract exposes the function `migrate()` to users which can operate as follows:

- If an urn has no debt, collateral is freed (without fee) from the old engine so that MKR can be converted to SKY and locked in the new one.
- If an urn has debt, a `Vat.dai` flashloan is taken. First all debt is wiped. Second the collateral is migrated as described above. Last, the flashloan debt is settled by drawing debt accordingly using the new engine.

The new ilk is assumed to have 0 line configured in the vat, and the migrator will lift the line to 55M temporarily in each migration.

Note that only addresses authorized for both source and target urn are allowed perform operations with the urns.

2.2.2.2 Deployment

The deployment script additionally deploys LockstakeMigrator besides LockstakeSky, LockstakeEngine, LockstakeClipper and the calculator. Otherwise, the deployment is equivalent to the deployment of v1 (however, adjusted for new code).

The initialization of the new version is mostly equivalent to the prior version. The most notable differences beside renaming of variables are:

- The oracle used in steps 6 and 7 (of the v1 deployment) is not PIP_MKR but PIP_SKY.
- The v1 addresses are migrated to new identifiers (`<previous identifiers> | _OLD_V1`) while v2 uses the same identifiers as the previous version used. The only exception is for the LockstakeSky token which is stored with LOCKSTAKE_SKY (LOCKSTAKE_MKR does not exist anymore in the Chainlog).
- The migrator is sanity checked and is granted authorization on the v1 engine to be able to call `freeNoFee()`.
- The migrator is also granted ward role on the vat for temporarily lifting the new ilk's line.
- The initialization script disables borrowing for the v1 ilk by setting the `Vat . line` for the ilk to zero.

2.2.3 Changelog

Since **Version 2**, the locking functions (collateral top-ups) are not permissioned anymore but only ensure that the urn address is a LockstakeUrn.

In **Version 3**, deployment scripts have been added to the scope.

In **Version 5**, NST and NGT has been renamed to USDS and SKY respectively. In addition, the following changes are made:

1. CREATE2 has been replaced to CREATE when creating a new urn.
2. As a consequence, an additional mapping `ownerUrns` is provided to retrieve an urn address by an owner and an index. Hence, function `getUrn()` is removed.
3. `fee` is no longer immutable and is by an auth-ed function `file(bytes32 what, uint256 data)`.
4. Instead of specifying the urn as a parameter for the functions, the owner and index are specified.
5. Function `selectVoteDelegate()` will call `jug.drip(ilk)` to use the up-to-date rate when checking if the urn is safe.
6. Under certain conditions, `vat.frob()` in function `onRemove()` reverted. To prevent reverts on dusty urns, `vat.grab()` is now used instead.
7. The deployment and initialization script have been adjusted accordingly. Note since the `fee` is no longer set in the constructor (default to 0), it is now configured in the initialization script.

In **Version 6**, a new version based on SKY has been introduced. More details can be found in the respective section.

In **Version 7**, the line will not be configured for the new ilk during initialization, and the migrator will lift the line to 55M temporarily in each migration for the existing positions in Lockstake v1.

2.3 Roles and Trust Model

The following roles are defined:



1. Governance: Authorizer of addresses. Fully trusted. Could mint unbacked LockstakeMkr/LockstakeSky tokens or call the hooks arbitrarily leading to unexpected behaviour. For example, MKR/SKY could be transferred out of the system.
2. Farms: Trusted. Expected to be the Endgame Synthetix-like staking contracts. We expect that the farms correspond to the contracts reviewed in the [Endgame Toolkit Audit](#). Could move and reuse the lSMKR/lSKY tokens if malicious.
3. Delegates: For v2 of Lockstake, we expect VoteDelegate v3 (referencing the new Chief contract). For v1 of Lockstake, we expect VoteDelegate v2 that implements an on-demand window for freeing due to flashloan protection on DsChief potentially delaying liquidations. Please see our [VoteDelegate Report](#) for more details.
4. Other authorized addresses: Trusted to implement the proper logic.
5. Users: Untrusted.

Additionally, we expect that the setup is performed accordingly, see note [Setup](#) for some more details.

Deployers are supposed to deploy the contracts as specified by the reviewed script. Deployers are, however, EOAs that could perform undesired actions besides simple deployment, such as changing the settings of the system or granting themselves special privileges. It is important that after deployment, concerned parties thoroughly check the state of the deployed contracts to ensure that no unexpected action has been taken on them during deployment.

3 Limitations and use of report

Security assessments cannot uncover all existing vulnerabilities; even an assessment in which no vulnerabilities are found is not a guarantee of a secure system. However, code assessments enable the discovery of vulnerabilities that were overlooked during development and areas where additional security measures are necessary. In most cases, applications are either fully protected against a certain type of attack, or they are completely unprotected against it. Some of the issues may affect the entire application, while some lack protection only in certain areas. This is why we carry out a source code assessment aimed at determining all locations that need to be fixed. Within the customer-determined time frame, ChainSecurity has performed an assessment in order to discover as many vulnerabilities as possible.

The focus of our assessment was limited to the code parts defined in the engagement letter. We assessed whether the project follows the provided specifications. These assessments are based on the provided threat model and trust assumptions. We draw attention to the fact that due to inherent limitations in any software development process and software product, an inherent risk exists that even major failures or malfunctions can remain undetected. Further uncertainties exist in any software product or application used during the development, which itself cannot be free from any error or failures. These preconditions can have an impact on the system's code and/or functions and/or operation. We did not assess the underlying third-party infrastructure which adds further inherent risks as we rely on the correct execution of the included third-party technology stack itself. Report readers should also take into account that over the life cycle of any software, changes to the product itself or to the environment in which it is operated can have an impact leading to operational behaviors other than those initially determined in the business specification.

4 Terminology

For the purpose of this assessment, we adopt the following terminology. To classify the severity of our findings, we determine the likelihood and impact (according to the CVSS risk rating methodology).

- *Likelihood* represents the likelihood of a finding to be triggered or exploited in practice
- *Impact* specifies the technical and business-related consequences of a finding
- *Severity* is derived based on the likelihood and the impact

We categorize the findings into four distinct categories, depending on their severity. These severities are derived from the likelihood and the impact using the following table, following a standard risk assessment procedure.

Likelihood	Impact		
	High	Medium	Low
High	Critical	High	Medium
Medium	High	Medium	Low
Low	Medium	Low	Low

As seen in the table above, findings that have both a high likelihood and a high impact are classified as critical. Intuitively, such findings are likely to be triggered and cause significant disruption. Overall, the severity correlates with the associated risk. However, every finding's risk should always be closely checked, regardless of severity.

5 Open Findings

In this section, we describe any open findings. Findings that have been resolved have been moved to the [Resolved Findings](#) section. The findings are split into these different categories:

- **Correctness**: Mismatches between specification and implementation

Below we provide a numerical overview of the identified findings, split up by their severity.

Critical -Severity Findings	0
High -Severity Findings	0
Medium -Severity Findings	0
Low -Severity Findings	1

- [Rate and urnImplementation Not Validated](#) **Acknowledged**

5.1 Rate and urnImplementation Not Validated

Correctness **Low** **Version 3** **Acknowledged**

CS-MLS-001

During initialization, all state is validated for consistency. While voters must ensure the deployment is legitimate, the expected bytecode has been deployed and the expected constructor code has been executed, the initialization code should validate all state variables to be set correctly.

`LockstakeInit.initLockstake()` does not validate the correct setting of the rate parameter nor the urnImplementation.

Acknowledged:

Sky states:

The goal of the deployment scripts validations is to only check the constructor params. Anything else that is done in the deployment or afterwards (including internal immutables setting and storage writes) are out of scope and are assumed to be checked separately. Some init scripts might validate more, but that is considered nice-to-have at best.

6 Resolved Findings

Here, we list findings that have been resolved during the course of the engagement. Their categories are explained in the [Open Findings](#) section.

Below we provide a numerical overview of the identified findings, split up by their severity.

Critical -Severity Findings	0
High -Severity Findings	0
Medium -Severity Findings	0
Low -Severity Findings	0
Informational Findings	2

- [Specification Mismatches](#) **Specification Changed**
- [Unpermissioned Collateral Top up](#) **Code Corrected**

6.1 Specification Mismatches

Informational **Version 1** **Specification Changed**

CS-MLS-003

The README specifies the module. Below is a list of mismatches:

1. `selectDelegate` is defined in the user-facing functions of the `LockstakeEngine`. However, `selectVoteDelegate` is the function name.
2. `wipeAll` is undocumented.
3. `LockstakeClipper.stopped` is a configurable parameter that is undocumented while `LockstakeClipper.chost` is updated by function `upchost` and not by file.

Specification changed:

The README has been updated accordingly.

6.2 Unpermissioned Collateral Top up

Informational **Version 1** **Code Corrected**

CS-MLS-004

Unlike direct interactions with `VAT.frob()`, the `LockstakeEngine` does not permit unauthorized increases in (locked) collateral.

Code corrected:

The locking functions (collateral top-ups) are no longer permissioned. The internal `_lock()` now ensures that the urn address is a `LockstakeUrn`.

7 Informational

We utilize this section to point out informational findings that are less severe than issues. These informational issues allow us to point out more theoretical findings. Their explanation hopefully improves the overall understanding of the project's security. Furthermore, we point out findings which are unrelated to security.

7.1 Locking Discrepancy With Zero

Informational

Version 1

Acknowledged

CS-MLS-002

The semantics of locking and unlocking an amount of zero are different when an urn has a farm and when it does not. Namely, the operations will revert when a farm is selected and will not when no farm is selected due to the farms reverting when zero amounts are staked/unstaked.

Acknowledged:

Sky replied:

Considering the asymmetry is happening due to some StakingRewards code, we are fine leaving it as it is.

8 Notes

We leverage this section to highlight further findings that are not necessarily issues. The mentioned topics serve to clarify or support the report, but do not require an immediate modification inside the project. Instead, they should raise awareness in order to improve the overall understanding.

8.1 Considerations for Migrations

Note **Version 6**

Users: Prior to using the Lockstake Migrator to migrate from v1 to v2, an user has to perform a set of action:

- `hope(migrator)` must be called in the old and new engine, respectively, for the source and the destination urn (note that for the destination urn this might be overly restrictive sometimes as outlined in the README).
- The destination urn must be created with open.

Further, note that if an urn is being liquidated, migrating the urn might result in needing to migrate again.

Users should be aware that migration might fail under certain circumstances. However, the migration can be performed manually.

In addition, the migration does not include the farm and vote delegate selection, hence users need to select them manually after the migration.

Governance: Governance should be aware that if MkrSky fees are enabled, the migrator will fail to perform the operations. Hence, when activating fees in that contract, the migration of Lockstake should be considered. Note that other such configurations exist (e.g. `line` set to zero).

Further, governance should be aware that `VOTE_DELEGATE_FACTORY` and `MKR_SKY` should be updated in the Chainlog prior to the LockstakeInit library being used. Additionally, it is expected that `PIP_SKY` will be configured prior to the execution of the library's code.

In addition, the fee and configuration of the new ilk (SKY) may influence the migration incentives if they are different to the existing ones.

8.2 Deployment Verification

Note **Version 3**

Since deployment of the contracts is not performed by the governance directly, special care has to be taken that all contracts have been deployed correctly. While some variables can be checked upon initialization through the PauseProxy, some things have to be checked beforehand.

We therefore assume that the initcode, bytecode, traces and storage (e.g. mappings) are checked for unintended entries, calls or similar. This is especially crucial for any value stored in a mapping array or similar (e.g. could break access control, could lead to stealing of funds). Additionally, it is of utmost importance that no allowance is given to unexpected addresses (e.g. MKR/SKY approval to arbitrary addresses could have been given in the constructor).

8.3 End Considerations

Note **Version 1**

The LockstakeClipper implements `yank()` which is required by the shutdown process. Note that the emergency shutdown is unsupported (as documented) since the gem balance that would be received during shutdown is not redeemable and thus the MKR tokens would not be able to be exited from the LockstakeEngine. A governance-assisted shutdown, which must be carefully planned, can be possible. For this, a mechanism must be implemented in order to make the collateral redeemable.

Further, `yank()` will not collect any fees on collateral already sold.

8.4 Governance Token as Collateral

Note Version 1

The Lockstake contracts allow for borrowing USDS (so-called NST in before **Version 5**) against the governance token. Governance should carefully set the ilk parameters (e.g. debt ceiling) due to the potential correlation between the price of the governance token and the price of the USDS. In tumultuous situations, when the USDS loses its peg, the price of the governance token could drop as a consequence (e.g. if liquidations fail to complete in time or successfully). As a consequence, the price of the USDS could further depeg leading to a vicious circle. Ultimately, governance should ensure that parameters and collateral diversity limit the risk.

8.5 Ink Token During Liquidations

Note Version 1

IsMkr/IsSky is minted to an urn when `ink` is added to a LockstakeUrn position and burned when `ink` is removed from such a position. Ultimately, it is a tokenization of `ink` of LockstakeUrn. When the collateral is seized during liquidation and moved to the Clipper, the IsMkr/IsSky is burned. Should there be leftover collateral after the auction concludes, the `ink` is moved back to the LockstakeUrn and the respective amount of IsMkr/IsSky is minted again.

8.6 Migration Line Should Not Be Exceeded

Note Version 7

In this version, the migrator will lift the line of new ilk to 55M temporarily in each migration of the existing positions in Lockstake v1. With this design, it should be ensured that the line of ilk LSE - MKR - A should be below 55M with sufficient room preserved for i.e. stability fees. By the time of this review (April 2025), the VAT . line, AUTOLINE . line, and AUTOLINE . gap of LSE - MKR - A are all 45M.

8.7 Setup

Note Version 1

The deployment is expected to be trusted and the parameters are expected to be set accordingly.

The following authorization should be given by the governance.

1. LockstakeClipper should be authorized on LockstakeEngine.
2. LockstakeEngine should be authorized on IsMKR/IsSky contract to be able to mint.
3. Dog should be authorized on LockstakeClipper.

Additionally, it is expected that the liquidation parameters are set so that exit fees can be taken on liquidations, too. Note that README.md outlines parts of this. If that is not the case it could be profitable to self-liquidate to bypass the exit fees which would violate the specification.

8.8 Token Received in Liquidation Auction

Note Version 1

Liquidators should be aware that for this special ilk, they will not receive a gem balance in the VAT but will receive MKR/SKY tokens directly when buying collateral in auctions.