ASSEMBLY MANUAL





BILL OF MATERIALS

- **Rocker Bottom**
- Rocker Top
- Mono Cable
- Divider
- Soldering Jig
- Tactile Switch (2)
- Rocker Buttons (2)

BEFORE STARTING:


- · Safety glasses should be worn at all times during the assembly.
- R1 = Component number
- = Solder the area in the white square.

TOOLS

- Soldering iron
- Solder
- · Goggles

· Super glue

- · Flush cutters
- · Wire stripper
- · Needle nose pliers
- Hot glue gun
- · Hot glue gun sticks








ASSEMBLY MANUAL






03.




Each cable half should be at least 5 ft or 150




05 Use the wire stripper.






06.






Hold the wire behind the switch and wrap the wire Hold the wife beining the content around the switch leads with a plier.





TWIST



09.






10. Repeat steps 1-9 for the second switch.

ASSEMBLY MANUAL





Test both switches with a switch tester, an assistive device, or an adapted toy to see if it works.




12. Align the divider tabs.








13.




14.



Add only a small drop of **hot glue**. Do not add too much.



16. Make sure the two switches are sitting flat.



Add only a small drop of super glue. Do not add too much.



18.



2

ASSEMBLY MANUAL





19. Repeat steps 17-18 for the second switch assembly.



Flip the rocker buttom so it faces down.



IMPORTANT: Clip the top and bottom cases together starting from the cable side first. Make sure the grooves catch each other.



22.



Test the rocker switch with a switch tester, an Test the rocker switch with a switch code, an assistive device, or an adapted toy to see if it works.