xml queries:

1. Get all the questions with text: xpath -e '/data/entry/question/text()' islamqa_10thousand_500.xml
2. Get all the titles: xpath -e '/data/entry/title/text()' islamqa_10thousand_500.xml
3. Get a specific title(it will retrieve the title element of the 23rd entry in the XML file): xpath -e '/data/entry[23]/title' islamqa_10thousand_500.xml
4. Get all the questions that contain the word "prayer": xpath -e '/data/entry[question[contains(., "prayer")]]/question' islamqa_10thousand_500.xml
5. Get all the elements(entry, url, question, answer) from the XML file where the question text contains the word "sunnah": xpath -e '/data/entry[question[contains(., "sunnah")]]' islamqa_10thousand_500.xml
6. Get only question and answer elements from the XML file where the question text contains the word "sunnah": xpath -e "/data/entry[question[contains(., 'sunnah')]]/*[self::question or self::answer]" islamqa_10thousand_500.xml
7. Get all the answers where the answer contains the word "Taymiyah"(a muslim theologian): xpath -e '/data/entry[contains(answer, "Taymiyah")]/answer' islamqa_10thousand_500.xml
8. Count the number of questions in the xml file: xpath -e 'count(/data/entry/question)' islamqa_10thousand_500.xml
9. Count the number of questions that contain the word "sunnah" in the XML file: xpath -e 'count(/data/entry[question[contains(., "sunnah")]])' islamqa_10thousand_500.xml
10. Count the number of words in the second answer: xpath -e 'string-length(normalize-space(/data/entry[2]/answer))' islamqa_10thousand_500.xml
11. Get all the answers with less than 200 words: xpath -e '/data/entry[string-length(normalize-space(answer)) < 200]/answer' islamqa_10thousand_500.xml
12. Count how many answers have less than 200 words: xpath -e 'count(/data/entry[string-length(normalize-space(answer)) < 200]/answer)' islamqa_10thousand_500.xml
13. Count the number of answers that contain the word "Bukhari"(Hadith book-sayings of the prophet): xpath -e 'count(/data/entry[contains(answer, "Baz")]/answer)' islamqa_10thousand_500.xml
14. Count the number of times the word 'Allah' is mentioned in the entire XML file: xpath -e 'count(//text()[contains(., "Allah")])'

islamqa_10thousand_500.xml