

mockgals



This manual is for `mockgals`, a program to make mock astronomical objects in a FITS image and add the appropriate noise.

Copyright © 2013, 2014 Mohammad Akhlaghi.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is available online at GNU FDL webpage (<http://www.gnu.org/copyleft/fdl.html>).

Table of Contents

1	An introduction.....	1
2	tmp.....	2
3	Installation.....	3

1 An introduction.

Making mock galaxies is very important in the process of understanding our data. `mockgals` was initially made with this exact intent. Certain astronomical targets, for example elliptical galaxies, are very sharp in their central regions, this makes a simple calculation of the profile in the center of each pixel unrealistic for such cases. The main advantage of `mockgals` is that it integrates the central parts of profiles until a given accuracy. It does this without any sorting or ordering and in a very fast manner.

A summary of the advantages of `mockgals` includes:

1. Integration of the center of the profile.
2. Very efficient in CPU usage, resulting in a very fast processing.
3. Written in the C programming language, which is easy to understand and modify or contribute to by any interested user.
4. [To be added] Can make profiles in any dimensions.

2 tmp

This is a temporary chapter.

3 Installation

`mockgals` relies on only 3 packages: `GSL` (for mathematical functions), `FFTW` (for convolution) and `cfitsio` (for reading to and from FITS files).