Maki Andrich
Page 1
tryhackme room

Executive Overview
The provided source document (page 1) describes a cybersecurity lab targeting a Linux server with SSH and Webmin services. The lab involves reconnaissance, exploitation, and privilege escalation to obtain flags. The target IP is 10.146.146.208, and the objective is to enumerate services, exploit vulnerabilities, and gain root access to retrieve flags.

Lab Overview
The source document provides a lab description for a tryhackme room. The target is a Linux server at IP 10.146.146.208. The objective is to enumerate services, exploit vulnerabilities, and gain root access to retrieve flags. The lab environment includes SSH on port 22 and Webmin on port 10000.

Reconnaissance
The source document reports an Nmap scan of the target IP 10.146.146.208, revealing open ports 22/tcp (SSH, OpenSSH 7.6p1) and 10000/tcp (http, MiniServ 1.890). The scan indicates 998 closed TCP ports and host latency of 0.042s. Subsection 1.1.1 explicitly states "22 tcp and 10000 http," and 1.1.2 identifies "Webmin 1.890."

Enumeration
The source document describes enumeration of the web service on port 10000, revealing a Webmin login page with fields for username and password. Subsection 2.1.1 labels this as "Login page." The page shows a browser screenshot of `https://10.146.146.208:10000` with visible username/password fields and a "Sign in" button.

Vulnerability Analysis
The source document identifies the MiniServ 1.890 (Webmin httpd) service as outdated and insecure. Subsection 3.1.1 explicitly states "Outdated and insecure." The service version (1.890) is confirmed via the Nmap scan results on page 1.

Exploitation
The source document reports the discovery of an exploit for Webmin < 1.920 (specifically, the 'rpc.cgi' Remote Code Execution vulnerability) via `searchsploit webmin 1.890`. The exploit output shows the title *"Webmin < 1.920 - 'rpc.cgi' Remote Code Execution (Metasploit)"* and path `/usr/share/exploitdb/exploits/linux/webapps/47330.rb`. The exploit is then run using Metasploit with settings: `RHOSTS 10.146.146.208`, `RPORT 10000`, `SSL true`, and `LHOST 192.168.131.39`. Subsection 3.4.2 confirms the Metasploit module is executed with these parameters.

Privilege Escalation
The source document confirms successful privilege escalation to root, as evidenced by terminal output showing a reverse shell session (`192.168.131.39:4444 → 10.146.146.208:51142`) and the `whoami` command outputting `root`. Subsection 3.5.1.1 explicitly states "We got root."


Flags & Proof of Access
The source document displays the retrieved flags: user.txt contains `THM{SUPPLY_CHAIN_COMPROMISE}` and

root.txt contains `THM{UPDATE_YOUR_INSTALL}`. Subsections 4.1 and 4.3 show the file contents via `cat` commands. Additionally, the task interface for the tryhackme room shows the flags as correct answers, confirming successful completion.

4.1.
```
cat /home/dark/user.txt
THM{SUPPLY_CHAIN_COMPROMISE}
```
4.2. THM{SUPPLY_CHAIN_COMPROMISE}

4.3.
```
cat /root/root.txt
THM{UPDATE_YOUR_INSTALL}
```
4.4. THM{UPDATE_YOUR_INSTALL}

5. Finish the room

5.1.


Screenshot / visual evidence · source PDF page 3

Conclusion

The lab was successfully completed by enumerating services, exploiting a vulnerability in Webmin, and gaining root access to retrieve the flags. The target IP 10.146.146.208 was fully compromised, and both user and root flags were obtained. The VM is part of *AttackerKB*, as noted in section 5.1.