


# Super Resolution for Automated Target Recognition

Maksim Levental


**Abstract**—Super resolution is the process of producing high-resolution images from low-resolution images while preserving ground truth about the subject matter of the images and potentially inferring more such truth. Algorithms that successfully carry out such a process are broadly useful in all circumstances where high-resolution imagery is either difficult or impossible to obtain. In particular we look towards super resolving images collected using longwave infrared cameras since high resolution sensors for such cameras do not currently exist. We present an exposition of motivations and concepts of super resolution in general and current techniques, with a qualitative comparison of such techniques. Finally we suggest directions for future research.

## REFERENCES


- [1] Y. Bentoutou, N. Taleb, K. Kpalma, and J. Ronsin, “An automatic image registration for applications in remote sensing,” *IEEE transactions on geoscience and remote sensing*, vol. 43, no. 9, pp. 2127–2137, 2005 (cit. on p. 1).
- [2] C. G. Harris, M. Stephens, *et al.*, “A combined corner and edge detector,” in *Alvey vision conference*, Citeseer, vol. 15, 1988, pp. 10–5244 (cit. on p. 1).
- [3] H. P. Moravec, “Obstacle avoidance and navigation in the real world by a seeing robot rover,” Stanford Univ CA Dept of Computer Science, Tech. Rep., 1980 (cit. on p. 1).
- [4] Z. Hossein-nejad and M. Nasri, “Image registration based on sift features and adaptive ransac transform,” in *2016 International Conference on Communication and Signal Processing (ICCSP)*, Apr. 2016, pp. 1087–1091. DOI: [10.1109/ICCSP.2016.7754318](https://doi.org/10.1109/ICCSP.2016.7754318) (cit. on p. 3).
- [5] D. G. Lowe, “Distinctive image features from scale-invariant keypoints,” *International journal of computer vision*, vol. 60, no. 2, pp. 91–110, 2004 (cit. on p. 3).
- [6] S. Leutenegger, M. Chli, and R. Siegwart, “Brisk: Binary robust invariant scalable keypoints,” in *2011 IEEE international conference on computer vision (ICCV)*, Ieee, 2011, pp. 2548–2555 (cit. on p. 3).
- [7] E. Rublee, V. Rabaud, K. Konolige, and G. R. Bradski, “Orb: An efficient alternative to sift or surf.,” in *ICCV*, Citeseer, vol. 11, 2011, p. 2 (cit. on p. 3).
- [8] E. Rosten and T. Drummond, “Machine learning for high-speed corner detection,” in *European conference on computer vision*, Springer, 2006, pp. 430–443 (cit. on p. 3).
- [9] M. Calonder, V. Lepetit, C. Strecha, and P. Fua, “Brief: Binary robust independent elementary features,” in *European conference on computer vision*, Springer, 2010, pp. 778–792 (cit. on p. 3).
- [10] J. L. Bentley, “Multidimensional binary search trees used for associative searching,” *Commun. ACM*, vol. 18, no. 9, pp. 509–517, Sep. 1975, ISSN: 0001-0782. DOI: [10.1145/361002.361007](https://doi.org/10.1145/361002.361007). [Online]. Available: <http://doi.acm.org/10.1145/361002.361007> (cit. on p. 4).




(1.a) Keypoint neighborhood



(1.b) Oriented and filtered keypoint gradient neighborhood



(1.c) 16 Keypoint neighborhood gradient bins



(1.d) Histogram of gradient orientations descriptor