5/23/24, 8:46 PM MCK100

M●NADRIVE<sup>®</sup> 蒙 纳 驱 动 Hotline: 400-820-7566

Home About Us News Product Project Download Contact us

Product

MCK Series Current location: Home > P

MCK100

MCG Series
MCK Series
MCK Series
MONA Series
MDD Series
MGD Series
MCB Series
MQ Series
Elevator multimedia
Universal screen

Big screen series



 Voltage
 380V

 Roping
 2:1

 Load
 320-630kg


 Speed
 0.5-1.75m/s


 Sheave diam.
 320mm

 Starts Per Hour
 240st/h

 Max. Static Load
 2500kg

 Weight
 250kg





Туре	Spec	Elv Load kg	Elv Speed m/s	Sheave Diam	Sheave Groove	Current A	Power kW	Speed r/min	Freq Hz	Torque N. m	Poles	
MCK100	320-0. 5A	320	0.5	320	3×Φ8×12	3	1.1	60	10.0	180	20	2
MCK100	320-0. 63A	320	0.63	320	3×Φ8×12	3	1.4	75	12.5	180	20	2
MCK100	320-1. OA	320	1.0	320	3×Φ8×12	5	2.2	119	19.8	180	20	2
MCK100	320-1.5A	320	1.5	320	3×Φ8×12	8	3.4	179	29.8	180	20	2
MCK100	450-0. 5A	450	0.5	320	4×Φ8×12	5	1.6	60	10.0	250	20	2
MCK100	450-0.63A	450	0.63	320	4×Φ8×12	5	2	75	12.5	250	20	2
MCK100	450-1. 0A	450	1.0	320	$4 \times \Phi 8 \times 12$	7	3.1	119	19.8	250	20	2
MCK100	450-1.5A	450	1.5	320	4×Φ8×12	11	4.7	179	29.8	250	20	2
MCK100	630-0. 5A	630	0.5	320	5×Φ8×12	7	2.1	60	10.0	340	20	2
MCK100	630-0. 63A	630	0.63	320	5×Φ8×12	7	2.7	75	12.5	340	20	2
MCK100	630-1. OA	630	1.0	320	5×Φ8×12	10	4.2	119	19.8	340	20	2
MCK100	630-1.5A	630	1.50	320	5×Φ8×12	16	6.4	179	29.8	340	20	2
MCK100	630-1. 6A	630	1.6	320	5×Φ8×12	16	6.8	191	31.8	340	20	2
MCK100	630-1.75A	630	1.75	320	5×Φ8×12	16	7.4	209	34.8	340	20	2

5/23/24, 8:46 PM MCK100

## **Product Search**

Mona Drive

Category

Please enter the product name or key word

About Us

Introduction

Certificate

С