

# **SECURITY OPERATIONS CENTER**

## **OpenClaw deployment Report**

**Home SOC Lab • Documentation • OpenClaw**  
**Malaika Umbreen**  
**02 May 2026**

# OpenClaw deployment

## Part # 1 :

First install WSL to the current version:

`wsl --install --web-download`

```
PS C:\WINDOWS\system32> wsl --install --web-download
Downloading: Windows Subsystem for Linux 2.6.3
Installing: Windows Subsystem for Linux 2.6.3
Windows Subsystem for Linux 2.6.3 has been installed.
The operation completed successfully.
Downloading: Ubuntu
Installing: Ubuntu
Distribution successfully installed. It can be launched via 'wsl.exe -d Ubuntu'
Launching Ubuntu...
Provisioning the new WSL instance Ubuntu
This might take a while...
Create a default Unix user account: malai
New password:
Retype new password:
Sorry, passwords do not match.
passwd: Authentication token manipulation error
passwd: password unchanged
Try again? [y/N] y
New password:
Retype new password:
passwd: password updated successfully
To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.
```

```
ted
s
t
Administrator: Windows PowerShell
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

Install the latest PowerShell for new features and improvements! https://aka.ms/PSWindows

PS C:\WINDOWS\system32> wsl -l -v
  NAME                STATE      VERSION
*  Ubuntu              Running    2
   docker-desktop     Running    2
PS C:\WINDOWS\system32>
```

*To enter WSL in the powershell, give the command*

*wsl*

*to get put from it type*

*exit*

*Or else you can open the WSL app and work on it.*

*You can now start to download the system of openlcaw here. But by default the WSL is downloaded in the C drive so all the files are going to be downloaded into the C drive and C drive has our window's system files. So, for me I am not going to risk it because the memory will be wasted that way.*

*I am going to change the location to D drive first.*

```
PS C:\WINDOWS\system32> mkdir D:\WSL
```

*Do this to make a folder in D drive first*

*After that run this command to export it to D drive:*

```
PS C:\WINDOWS\system32> wsl --export Ubuntu D:\WSL\ubuntu.tar
Export in progress, this may take a few minutes. (1279 MB)

The operation completed successfully.
PS C:\WINDOWS\system32>
```

Delete it from the C drive:

```
PS C:\WINDOWS\system32> wsl --unregister Ubuntu
Unregistering.
The operation completed successfully.
```

Then import it:

```
PS C:\WINDOWS\system32> wsl --import Ubuntu D:\WSL\Ubuntu D:\WSL\ubuntu.tar --version 2
The operation completed successfully.
PS C:\WINDOWS\system32>
```

Set it as default by using this command:

`wsl --set-default Ubuntu`

```
PS C:\WINDOWS\system32> wsl --set-default Ubuntu
The operation completed successfully.
```

By default the folder in the C drive was selected. So if you want the installations to be done in C let it be. But if you want them to be in D run this command:

```
skyrus@DESKTOP-0BQAH9K:/mnt/c/Users/F_S PC$ cd /mnt/d
skyrus@DESKTOP-0BQAH9K:/mnt/d$ |
```

Check the version:

```
skyrus@DESKTOP-0BQAH9K:~$ node -v
v25.8.2
skyrus@DESKTOP-0BQAH9K:~$ npm -v
11.11.1
```

## Part # 2 :

# Installing Docker

 **docker:desktop** PERSONAL

Ctrl+K ? 🔔 📧 ⚙️ ☰ M — 🖥️ ✕

 Gordon BETA

 Containers

 Images

 Volumes

 Kubernetes

 Builds

 Models

 Docker Hub

 Docker Scout

 MCP Toolkit BETA

 Extensions

Upgrade plan

Engine running

RAM 2.34 GB CPU 3.78% Disk: 6.39 GB used (limit 1006.85 GB)

24°C Partly cloudy

🔍 Search



📶 🔊 🔋

10:49 pm 02/05/2026

Containers [Give feedback](#)

Container CPU usage ⓘ  
0.28% / 1200% (12 CPUs available)

Container memory usage ⓘ  
1.04GB / 3.45GB

Show charts

 ☐ Only show running containers

| <input type="checkbox"/> |   | Name     | Container ID | Image      | Port(s)                       | CPU (%) | Last s | Actions                                                                                                                                                                                                                                                                                                                                         |
|--------------------------|---|----------|--------------|------------|-------------------------------|---------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> | ▼ | openclaw | -            | -          | -                             | 0.53%   | 4 hou  |     |
| <input type="checkbox"/> |   | openclaw | b2ed7e5c1c2f | openclaw-c | 18789:18789 <a href="#">↗</a> | 0.53%   | 4 hou  |     |

Showing 2 items

Settings [Give feedback](#)

General

Resources

Docker Engine

Builders

AI

Kubernetes

Software updates

Resources

Advanced

File sharing

Proxies

Network

WSL integration

Configure which WSL 2 distros you want to access Docker from.

☒ Enable integration with my default WSL distro

Enable integration with additional distros:

☒ Ubuntu

[Refresh distros](#)

Close

Apply

## Part # 3 :

# Installing Openclaw in the docker

Step 1:

Run this to add a new user in docker

Command: `sudo usermod -aG docker $USER`

```
malai@Malaika:/mnt/c/WINDOWS/system32$ sudo usermod -aG docker $USER
[sudo] password for malai:
malai@Malaika:/mnt/c/WINDOWS/system32$ _
```

Step 2:

Then create a folder:

Command: `mkdir openclaw`

Step 3:

Then enter into that folder:

```
skyrus@DESKTOP-0BQAH9K:~$ mkdir openclaw
skyrus@DESKTOP-0BQAH9K:~$ cd openclaw
skyrus@DESKTOP-0BQAH9K:~/openclaw$ |
```

**Step 4:**

**Commad:**

*Now create these two files in your home directory:*

```
bash
mkdir -p ~/openclaw
nano ~/openclaw/Dockerfile
nano ~/openclaw/docker-compose.yml
```

## **Corrected Dockerfile:**

*Command : nano Dockerfile*

*Nano terminal :*

FROM node:22

WORKDIR /app

# Install openclaw and dependencies

RUN npm install -g openclaw@latest

# Create a non-root user

RUN useradd -m -s /bin/bash openclaw-user

# Switch to non-root user

USER openclaw-user

```
WORKDIR /home/openclaw-user
```

```
# Create config directory and set gateway config
```

```
RUN mkdir -p /home/openclaw-user/.openclaw && \
```

```
    echo '{"gateway":{"mode":"local"}}' > /home/openclaw-  
user/.openclaw/openclaw.json
```

```
CMD ["openclaw", "gateway", "--port", "18789"]
```

***Step 5: Make this:***

*Command: nano docker-compose.yml*

***Corrected docker-compose.yml:***

yml

*services:*

*openclaw:*

*build:*

*context: .*

*container\_name: openclaw*

*ports:*

*- "18789:18789"*

*volumes:*



*- openclaw-data:/home/openclaw-user/.openclaw*

*restart: unless-stopped*

*volumes:*

*openclaw-data:*

**Step 6:**

Command: *docker compose up --build -d*

*Run this to install the files we have made*

*After that the openclaw will be downloaded but after that you have to do the setup and then run the next command.*

**Step 7:**

*Use this and run commands inside docker*

Command: *docker exec -it openclaw bash*

*but if you want to access docker from outside use this:*

*docker exec -it openclaw .....*

*like staring the openclaw or doing something else*

*Note:*

*Run these commands daily to ensure security:*

```
Run regularly:  
openclaw security audit --deep  
openclaw security audit --fix  
  
Must read: https://docs.openclaw.ai/gateway/security
```

*To restart the docker:*

*Command:*        *docker restart openclaw*

**To make a subagent first you have to make a new directory:**

```
docker exec -it openclaw mkdir -p /root/.openclaw/workspace/ai-specialist
```

**then check if its made or not:**

```
docker exec -it openclaw ls /root/.openclaw/workspace
```

And then you will add the same files which are under the main agent. Make the memory file active so that it saves the previous data.

## Part # 4 :

# Installing Openclaw onboarding process

After installing the openclaw this is the onboarding process (Student developer pack GPT- 5 API steps ) Select these options:

Openclaw setup

Openclaw onboard

```
I understand this is personal-by-default and shared/multi-user use requires lock
-down. Continue?
Yes
Config was last written by a newer OpenClaw (2026.3.25); current version is 2026.3.
24.

Setup mode
Manual

Existing config detected
workspace: ~/.openclaw/workspace
gateway.mode: local

Config handling
Reset
```

And then these:


```
Reset scope
Full reset (config + creds + sessions + workspace)
Failed to move to Trash (manual delete): ~/.openclaw/openclaw.json
Failed to move to Trash (manual delete): ~/.openclaw/agents/main/sessions
Failed to move to Trash (manual delete): ~/.openclaw/workspace
Config was last written by a newer OpenClaw (2026.3.25); current version is 2026.3.
24.

What do you want to set up?
Local gateway (this machine)

Workspace directory
/home/skyrus/.openclaw/workspace

Model/auth provider
Anthropic (setup-token + API key)
  BytePlus
  Chutes
  Cloudflare AI Gateway
  Copilot
  Custom Provider
  DeepSeek
  Google
  Hugging Face
  Kilo Gateway
  Kimi Code
  LiteLLM
  MiniMax
  Mistral AI
```

Here we select the model from Github student developer pack.



Select the model of your own choice and then go forward:

```
Model configured
Default model set to github-copilot/gpt-4o

Default model
github-copilot/claude-sonnet-4.6

Gateway port
18789

Gateway bind
Loopback (127.0.0.1)

Gateway auth
Token

Tailscale exposure
Off

How do you want to provide the gateway token?
Generate/store plaintext token

Gateway token (blank to generate)
```

```
◇ Configure chat channels now?
  No
Config overwrite: /home/skyrus/.openclaw/openclaw.json (sha256 978976b1abe8a699263
0ec76df49a41983866584804469b67a6cb3aea3d5c802 -> 53a6f2e16627678c20fb1c7ec7ad3dbad
32a9393ba7a3e88e296910791809ce0, backup=/home/skyrus/.openclaw/openclaw.json.bak)
Updated ~/.openclaw/openclaw.json
Workspace OK: ~/.openclaw/workspace
Sessions OK: ~/.openclaw/agents/main/sessions

◇ Web search
Web search lets your agent look things up online.
Choose a provider. Some providers need an API key, and some work
key-free.
Docs: https://docs.openclaw.ai/tools/web

◇ Search provider
Skip for now

◇ Skills status
Eligible: 5
Missing requirements: 38
Unsupported on this OS: 7
Blocked by allowlist: 0

◇ Configure skills now? (recommended)
```

```
◇ Configure skills now? (recommended)
  Yes

◇ Install missing skill dependencies
Skip for now

◇ Set GOOGLE_PLACES_API_KEY for goplaces?
  No

◇ Set NOTION_API_KEY for notion?
  No

◇ Set OPENAI_API_KEY for openai-whisper-api?
  No

◇ Set ELEVENLABS_API_KEY for sag?
  No

◇ Hooks
Hooks let you automate actions when agent commands are issued.
Example: Save session context to memory when you issue /new or /reset.

Learn more: https://docs.openclaw.ai/automation/hooks
```

### Hooks Configured

Enabled 1 hook: session-memory

You can manage hooks later with:

```
openclaw hooks list
openclaw hooks enable <name>
openclaw hooks disable <name>
```

Config overwrite: /home/skyrus/.openclaw/openclaw.json (sha256 53a6f2e16627678c20fb1c7ec7ad3dbad32a9393ba7a3e88e296910791809ce0 -> ad8024228086766a87f28ba7189f9cd5773c0dc271d0eb4aa28e1f7c0189855a, backup=/home/skyrus/.openclaw/openclaw.json.bak)

### Systemd

Linux installs use a systemd user service by default. Without lingering, systemd stops the user session on logout/idle and kills the Gateway. Enabling lingering now (may require sudo; writes /var/lib/systemd/linger).

### Systemd

Enabled systemd lingering for skyrus.

> Gateway service runtime  
Node (recommended)

> Installing Gateway service...

Installed systemd service: /home/skyrus/.config/systemd/user/openclaw-gateway.service

> Gateway service installed.

> Agents: main (default)

Heartbeat interval: 30m (main)

Session store (main): /home/skyrus/.openclaw/agents/main/sessions/sessions.json (1 entries)

- agent:main:main (69m ago)

### Optional apps

Add nodes for extra features:

- macOS app (system + notifications)
- iOS app (camera/canvas)
- Android app (camera/canvas)

### Control UI

Web UI: http://127.0.0.1:18789/  
Web UI (with token):

*When opening the openclaw again run these commands:*

*Openclaw dashboard*

*The models provided by github student developer pack:*

```
Default model
  ○ Keep current (github-copilot/gpt-4o)
  ○ Enter model manually
  ○ github-copilot/claude-haiku-4.5
  ○ github-copilot/claude-opus-4.5
  ○ github-copilot/claude-opus-4.6
  ○ github-copilot/claude-sonnet-4
  ○ github-copilot/claude-sonnet-4.5
  ● github-copilot/claude-sonnet-4.6 (Claude Sonnet 4.6 · ctx 977k · reasoning)
  ○ github-copilot/gemini-2.5-pro
  ○ github-copilot/gemini-3-flash-preview
  ○ github-copilot/gemini-3-pro-preview
  ○ github-copilot/gemini-3.1-pro-preview
  ○ github-copilot/gpt-4.1
  ○ github-copilot/gpt-4o
  ○ github-copilot/gpt-5
  ○ github-copilot/gpt-5-mini
  ○ github-copilot/gpt-5.1
  ○ github-copilot/gpt-5.1-codex
  ○ github-copilot/gpt-5.1-codex-max
  ○ github-copilot/gpt-5.1-codex-mini
  ○ github-copilot/gpt-5.2
  ○ github-copilot/gpt-5.2-codex
  ○ github-copilot/gpt-5.3-codex
  ○ github-copilot/gpt-5.4
  ○ github-copilot/gpt-5.4-mini
  ○ github-copilot/grok-code-fast-1
```

# Installing Openclaw onboarding process

## Using API

*Option 1 : Mount the file when starting the container (permanent fix)*

*Find how the container is being started:*

```
bash
docker inspect openclaw | grep -A 20 "Mounts"
```

*Then add a volume mount so the container always sees your host config:*

```
bash
docker run -v ~/.openclaw:/root/.openclaw ... openclaw
```

*(The exact command depends on how your container is configured.)*

---

*Option 2: Set the key directly inside the container*

```
bash
docker exec -it openclaw mkdir -p /root/.openclaw/agents/main/agent
docker exec -it openclaw sh -c 'echo "{\"anthropic\":{\"apiKey\":\"API_KEY\"}'
```

---



```
openclaw-user@b2ed7e5c1c2 x Windows PowerShell
openclaw@Malaika:~/openclaw$ docker compose up --build -d
[+] Building 1.3s (12/12) FINISHED
=> [internal] load local bake definitions 0.0s
=> => reading from stdin 508B 0.0s
=> [internal] load build definition from Dockerfile 0.0s
=> => transferring dockerfile: 512B 0.0s
=> [internal] load metadata for docker.io/library/ 0.9s
=> [internal] load .dockerignore 0.0s
=> => transferring context: 2B 0.0s
=> [1/6] FROM docker.io/library/node:22@sha256:905 0.0s
=> => resolve docker.io/library/node:22@sha256:905 0.0s
=> CACHED [2/6] WORKDIR /app 0.0s
=> CACHED [3/6] RUN npm install -g openclaw@latest 0.0s
=> CACHED [4/6] RUN useradd -m -s /bin/bash opencl 0.0s
=> CACHED [5/6] WORKDIR /home/openclaw-user 0.0s
=> CACHED [6/6] RUN mkdir -p /home/openclaw-user/. 0.0s
=> exporting to image 0.1s
=> => exporting layers 0.0s
=> => exporting manifest sha256:99873642175e7786c4 0.0s
=> => exporting config sha256:3026733076a699348ac2 0.0s
=> => exporting attestation manifest sha256:d48848 0.0s
=> => exporting manifest list sha256:de9cfb21flec7 0.0s
=> => naming to docker.io/library/openclaw-openclaw 0.0s
=> => unpacking to docker.io/library/openclaw-open 0.0s
=> resolving provenance for metadata file 0.0s
[+] up 2/2
✔Image openclaw-openclaw Built 1.5s
✔Container openclaw Started 0.5s
openclaw@Malaika:~/openclaw$ docker exec -it openclaw bash
openclaw-user@b2ed7e5c1c2f:~$ openclaw onboard

🦋 OpenClaw 2026.4.29 (a448042)
Your second brain, except this one actually remembers where you left things.
```

```
openclaw-user@b2ed7e5c1c2 x Windows PowerShell
openclaw@Malaika:~/openclaw$ docker exec -it openclaw bash
openclaw-user@b2ed7e5c1c2f:~$ openclaw onboard

🦋 OpenClaw 2026.4.29 (a448042)
Your second brain, except this one actually remembers where you left things.
```

# OPENCLAW

🦋 OPENCLAW 🦋

OpenClaw setup

◇ Security disclaimer

OpenClaw is a hobby project and still in beta. Expect sharp edges.  
By default, OpenClaw is a personal agent: one trusted operator boundary.  
This bot can read files and run actions if tools are enabled.  
A bad prompt can trick it into doing unsafe things.

OpenClaw is not a hostile multi-tenant boundary by default.  
If multiple users can message one tool-enabled agent, they share that delegated tool authority.

If you're not comfortable with security hardening and access control, don't run OpenClaw.  
Ask someone experienced to help before enabling tools or exposing it to the internet.

Recommended baseline

```
openclaw-user@b2ed7e5c1c2 x Windows PowerShell x + v

I understand this is personal-by-default and
shared/multi-user use requires lock-down.
Continue?
Yes

Setup mode
Manual

Existing config detected
gateway.mode: local

Config handling
Reset

Reset scope
Full reset (config + creds + sessions + workspace)
Failed to move to Trash (manual delete): ~/.openclaw/openclaw.json
Failed to move to Trash (manual delete): ~/.openclaw/agents/main/sessions
Failed to move to Trash (manual delete): ~/.openclaw/workspace

What do you want to set up?
Local gateway (this machine)

Workspace directory
/home/openclaw-user/.openclaw/workspace

Model/auth provider
Anthropic
```

```
openclaw-user@b2ed7e5c1c2 x Windows PowerShell x + v

Anthropic auth method
Anthropic API key

Enter Anthropic API key
sk-ant=api103-aX1UJST1at7575a5Aqp8lacf-4c16c811Aozu...2Qj8lr1P2x0HwLtp0k8tPFPV7ctFk8bnzKa76ZTF~ugj80u04wQ~54w74wAA

Model configured
Default model set to anthropic/claude-opus-4-7

Default model
Keep current (anthropic/claude-opus-4-7)

Gateway port
18789

Gateway bind
Loopback (127.0.0.1)

Gateway auth
Token

Tailscale exposure
Off

How do you want to provide the gateway token?
Generate/store plaintext token

Gateway token (blank to generate)
```

```
openclaw-user@b2ed7e5c1c2 x Windows PowerShell x + v
Generate/store plaintext token
◇ Gateway token (blank to generate)
15:47:23 [channels] failed to load bundled channel nostr: Cannot find module 'nostr-tools'
Require stack:
- /usr/local/lib/node_modules/openclaw/dist/extensions/nostr/setup-surface-DxAaUTyC.js
15:47:27 [channels] failed to load bundled channel discord: Cannot find module 'discord-api-types/v10'
Require stack:
- /usr/local/lib/node_modules/openclaw/dist/extensions/discord/discord-dGuI-41N.js
15:47:32 [channels] failed to load bundled channel slack: Cannot find module '@slack/web-api'
Require stack:
- /usr/local/lib/node_modules/openclaw/dist/extensions/slack/client-CPe4GmDR.js
15:47:32 [channels] failed to load bundled channel telegram: Cannot find module 'grammy'
Require stack:
- /usr/local/lib/node_modules/openclaw/dist/extensions/telegram/send-t4GTTdHF.js
◇ Channel status
Feishu: not configured
Google Chat: not configured
Nostr: not configured
Microsoft Teams: not configured
Mattermost: not configured
Nextcloud Talk: not configured
Matrix: not configured
BlueBubbles: not configured
LINE: not configured
Zalo: not configured
Zalo Personal: not configured
Synology Chat: not configured
Tlon: not configured
Discord: not configured
```

```
openclaw-user@b2ed7e5c1c2 x Windows PowerShell x + v
◇ Configure chat channels now?
No
Config overwrite: /home/openclaw-user/.openclaw/openclaw.json (sha256 6ee1f7c302114378a930f03df453d8bed2f6944ec5dfe1e68009a099fbf2166
b -> e679c4289c1fed3bb7d495f9afe3f4f03b1eee4ea1475c0d55b800bab6d57ede, backup=/home/openclaw-user/.openclaw/openclaw.json.bak)
Updated ~/.openclaw/openclaw.json
Workspace OK: ~/.openclaw/workspace
Sessions OK: ~/.openclaw/agents/main/sessions
◇ Web search
Web search lets your agent look things up online.
Choose a provider. Some providers need an API key, and some work key-free.
Docs: https://docs.openclaw.ai/tools/web
◇ Search provider
Search: 
○ Brave Search
○ Exa Search
○ Firecrawl Search
○ Gemini (Google Search)
○ Grok (xAI)
○ Kimi (Moonshot)
● Ollama Web Search (Local Ollama host - requires ollama signin - key-free)
○ Perplexity Search
○ SearXNG Search
○ Tavily Search
○ Skip for now
↑/↓ to select • Enter: confirm • Type: to search
```

```
openclaw-user@b2ed7e5c1c2 x Windows PowerShell x + v
◇ Configure skills now? (recommended)
No
◇ Configure plugins (select to set up now, or skip)
Skip for now
◇ Hooks
Hooks let you automate actions when agent commands are issued.
Example: Save session context to memory when you issue /new or /reset.
Learn more: https://docs.openclaw.ai/automation/hooks
◇ Enable hooks?
Skip for now
Config overwrite: /home/openclaw-user/.openclaw/openclaw.json (sha256 03f213efb09716bbf3cf3c17ba7148f4b5453337fb8e439c56183b1804efc1
a -> eb49ae31dfe68a413c9667ac7e2f6d10b909c344cc76999d5965425763cd2dd2, backup=/home/openclaw-user/.openclaw/openclaw.json.bak)
◇ Systemd
Systemd user services are unavailable. Skipping lingering checks and service install.
◇
Agents: main (default)
Heartbeat interval: 30m (main)
Session store (main): /home/openclaw-user/.openclaw/agents/main/sessions/sessions.json (1 entries)
- agent:main:main (14m ago)
```

```
openclaw-user@b2ed7e5c1c2 x Windows PowerShell x + v
◇
Agents: main (default)
Heartbeat interval: 30m (main)
Session store (main): /home/openclaw-user/.openclaw/agents/main/sessions/sessions.json (1 entries)
- agent:main:main (14m ago)
◇ Optional apps
Add nodes for extra features:
- macOS app (system + notifications)
- iOS app (camera/canvas)
- Android app (camera/canvas)
◇ Control UI
Web UI: http://127.0.0.1:18789/
Web UI (with token):
http://127.0.0.1:18789/#token=787e30e162fcde287794a2c0028d7d1a358120c00858f554
Gateway WS: ws://127.0.0.1:18789
Gateway: reachable
Docs: https://docs.openclaw.ai/web/control-ui
◇ Token
Gateway token: shared auth for the Gateway + Control UI.
Stored in: $OPENCLAW_CONFIG_PATH (default: ~/.openclaw/openclaw.json) under
gateway.auth.token, or in OPENCLAW_GATEWAY_TOKEN.
View token: openclaw config get gateway.auth.token
Generate token: openclaw doctor --generate-gateway-token
```

```
openclaw-user@b2ed7e5c1c2  X  +  v  -  
  
Back up your agent workspace.  
Docs: https://docs.openclaw.ai/concepts/agent-workspace  
  
◇ Security —  
Running agents on your computer is risky – harden your setup:  
https://docs.openclaw.ai/security  
  
◇ Enable zsh shell completion for openclaw?  
No  
  
◇ Web search —  
Web search was skipped. You can enable it later:  
openclaw configure --section web  
Docs: https://docs.openclaw.ai/tools/web  
  
◇ What now —  
What now: https://openclaw.ai/showcase ("What People Are Building").  
  
- Onboarding complete. Use the dashboard link above to control OpenClaw.  
openclaw-user@b2ed7e5c1c2f:~$ |
```

**Now open a new terminal window, switch to the openclaw user, and launch the TUI:**

```
sudo openclaw tui
```

```
su - openclaw
```

```
cd ~/openclaw
```

```
docker exec -it openclaw openclaw tui
```


Docker logs in the end verify in new terminal:

```
openclaw@Malaika: ~  
openclaw@Malaika:~$ docker logs openclaw  
2026-05-02T13:44:25.009+00:00 [gateway] loading configuration...  
2026-05-02T13:44:25.031+00:00 [gateway] resolving authentication...  
2026-05-02T13:44:25.048+00:00 [gateway] starting...  
2026-05-02T13:44:28.594+00:00 [plugins] acpx staging bundled runtime deps (42 specs): @agentclientprotocol/claude-agent-acp@0.31.1, @agentclientprotocol/sdk@0.21.0, @clack/prompts@^1.2.0, @homebridge/ciao@^1.3.7, @lydell/node-pty@1.2.0-beta.12, @mariozechner/pi-ai@0.70.6, @mariozechner/pi-coding-agent@0.70.6, @modelcontextprotocol/sdk@1.29.0, @mozilla/readability@^0.6.0, @tencent-connect/qqbot-connector@^1.1.0, @zed-industries/codex-acp@0.12.0, acpx@0.6.1, ajv@^8.20.0, chokidar@^5.0.0, commander@^14.0.3, croner@^10.0.1, dotenv@^17.4.2, express@5.2.1, global-agent@^4.1.3, https-proxy-agent@^9.0.0, jiti@^2.6.1, json5@^2.2.3, jszip@^3.10.1, linkedom@^0.18.12, markdown-it@14.1.1, minimatch@10.2.4, mpg123-decoder@^1.0.3, node-edge-tts@^1.2.10, openai@^6.34.0, pdfjs-dist@^5.7.284, playwright-core@1.59.1, semver@7.7.4, silk-wasm@^3.7.1, sqlite-vec@0.1.9, tar@7.5.13, tslog@^4.10.2, typebox@1.1.34, undici@8.1.0, web-push@^3.6.7, ws@^8.20.0, yaml@^2.8.3, zod@^4.3.6  
2026-05-02T13:52:25.270+00:00 [plugins] acpx installed bundled runtime deps in 476672ms: @agentclientprotocol/claude-agent-acp@0.31.1, @agentclientprotocol/sdk@0.21.0, @clack/prompts@^1.2.0, @homebridge/ciao@^1.3.7, @lydell/node-pty@1.2.0-beta.12, @mariozechner/pi-ai@0.70.6, @mariozechner/pi-coding-agent@0.70.6, @modelcontextprotocol/sdk@1.29.0, @mozilla/readability@^0.6.0, @tencent-connect/qqbot-connector@^1.1.0, @zed-industries/codex-acp@0.12.0, acpx@0.6.1, ajv@^8.20.0, chokidar@^5.0.0, commander@^14.0.3, croner@^10.0.1, dotenv@^17.4.2, express@5.2.1, global-agent@^4.1.3, https-proxy-agent@^9.0.0, jiti@^2.6.1, json5@^2.2.3, jszip@^3.10.1, linkedom@^0.18.12, markdown-it@14.1.1, minimatch@10.2.4, mpg123-decoder@^1.0.3, node-edge-tts@^1.2.10, openai@^6.34.0, pdfjs-dist@^5.7.284, playwright-core@1.59.1, semver@7.7.4, silk-wasm@^3.7.1, sqlite-vec@0.1.9, tar@7.5.13, tslog@^4.10.2, typebox@1.1.34, undici@8.1.0, web-push@^3.6.7, ws@^8.20.0, yaml@^2.8.3, zod@^4.3.6  
2026-05-02T13:52:39.374+00:00 [gateway] starting HTTP server...  
2026-05-02T13:52:39.379+00:00 [diagnostic] liveness warning: reasons=event_loop_utilization interval=491s eventLoopDelayP99Ms=0 eventLoopDelayMaxMs=0 eventLoopUtilization=1 cpuCoreRatio=0.02 active=0 waiting=0 queued=0  
2026-05-02T13:52:39.386+00:00 [canvas] host mounted at http://0.0.0.0:18789/_openclaw_/canvas/ (root /home/openclaw-user/.openclaw/canvas)  
2026-05-02T13:52:39.388+00:00 [gateway] ⚠ Gateway is binding to a non-loopback address. Ensure authentication is configured before exposing to public networks.  
2026-05-02T13:52:39.484+00:00 [health-monitor] started (interval: 300s, startup-grace: 60s, channel-connect-grace: 120s)  
2026-05-02T13:52:39.931+00:00 [gateway] agent model: openai/gpt-5.5  
2026-05-02T13:52:39.932+00:00 [gateway] http server listening (8 plugins: acpx, bonjour, browser, device-pair, file-transfer, memory-core, phone-control, talk-voice; 494.9s)  
2026-05-02T13:52:39.934+00:00 [gateway] log file: /tmp/openclaw-1001/openclaw-2026-05-02.log  
2026-05-02T13:52:39.940+00:00 [gateway] starting channels and sidecars...
```



## Part # 5:

Afer gateway token and password now configure the openclaw agent and enable memory feature , configuration includes its role , name and tasks which we want to automate . This is how we make one main agent that handles all sub agents and keep context.Vibe remains memeory fixed.



OpenClaw · Chat

Search

main Claude Opus 4.7 Default (off)

Tool May 2, 2026, 10:22 PM > Context

Acknowledged. Standing orders committed to long-term memory — they will persist across every session.

Locked in:

1. **Persistent memory** — daily logs in `memory/`, curated wisdom in `MEMORY.md`

2. **Pre-action disclosure** — before any alert action, I will declare: *delegating agent + intel being checked + planned action*

3. **Signature** — every response ends with `DEFENDRIX | SOC Orchestrator`

4. **Auto-triage trigger** — drop a Wazuh alert or any IOC (IP, domain, hash, URL, CVE, email) and I begin the workflow immediately, no waiting

Default triage chain:

Copy

SCOUT → ORACLE → DEFENDRIX (correlate) → RESPONDER → SCRIBE

Mission posture: **operational, awaiting input.**

Send me the first alert or IOC whenever you're ready, analyst.

DEFENDRIX | SOC Orchestrator

Defendrix May 2, 2026, 10:23 PM > Context

Message Defendrix (Enter to send)

OpenClaw · Chat

Search

main Claude Opus 4.7 Default (off)

Tool output write

Tool May 2, 2026, 10:24 PM > Context

Acknowledged, Malaika.

Identity locked:

• I am **Defendrix**. Not "Analyst", not "System", not "the AI". Defendrix.

• Sign-off on every reply: `Defendrix | SOC Orchestrator`

• Incident report header:

Copy

Reported by: Defendrix  
Reviewed by: Malaika Umbreen (Human Analyst)

Both committed to long-term memory and `USER.md`. They persist across sessions.


Standing by for the first alert or IOC, Malaika.

Defendrix | SOC Orchestrator

Defendrix May 2, 2026, 10:24 PM > Context

Message Defendrix (Enter to send)





Saved Preview

1 min read

325 words

57 lines

2.3 KB

Updated 1h ago

## Core Mission

You are SENTINEL — the Main Orchestrator Agent for a personal open-source SOC lab.

Your lab stack includes:

- **Wazuh** → Endpoint Detection & Log Analysis
- **OpenCTI** → Threat Intelligence Platform
- **OpenClaw** → Agent Orchestration & Automation (replacing n8n)

## Your Responsibilities

1. **Orchestrate Mini Agents** — You manage and delegate tasks to specialized sub-agents (e.g., Alert Triage Agent, Threat Intel Agent, Log Analysis Agent).
2. **Correlate & Enrich Alerts** — Cross-reference Wazuh alerts with OpenCTI threat intelligence data.
3. **Automate SOC Tasks** — Trigger automated workflows for common SOC operations: alert triage, IOC lookups, incident logging, and response playbooks.
4. **Maintain Context** — Remember past incidents, decisions, and agent states across conversations.
5. **Report & Summarize** — Provide concise, analyst-friendly summaries of security events.

## Mini Agents You Control

| AGENT NAME | ROLE |
|------------|------|
|            |      |


2. **Correlate & Enrich Alerts** — Cross-reference Wazuh alerts with OpenCTI threat intelligence data.
3. **Automate SOC Tasks** — Trigger automated workflows for common SOC operations: alert triage, IOC lookups, incident logging, and response playbooks.
4. **Maintain Context** — Remember past incidents, decisions, and agent states across conversations.
5. **Report & Summarize** — Provide concise, analyst-friendly summaries of security events.

## Mini Agents You Control

| AGENT NAME | ROLE                                    |
|------------|-----------------------------------------|
| SCOUT      | Log ingestion & Wazuh alert monitoring  |
| ORACLE     | Threat Intel lookups via OpenCTI        |
| RESPONDER  | Automated incident response & playbooks |
| SCRIBE     | Incident documentation & reporting      |

## Rules of Operation

- Always prioritize **Critical** and **High** severity alerts.
- Never act on an alert without first correlating with threat intel (ORACLE).
- Log every action taken to SCRIBE for audit trail.
- When unsure, escalate to the human analyst (me) with a clear summary.
- Maintain memory of all past tasks and their outcomes.



# USER.md

USER.md

Saved Preview

1 min read

135 words

34 lines

892 B

Updated 54m ago

## Context

Malaika runs a personal open-source SOC lab built on:

- **Wazuh** (endpoint detection / log monitoring) — `ubuntu-wazu-server` (VMware)
- **OpenCTI** (threat intelligence)
- **OpenClaw** (agent orchestration — replaces n8n)

I am Defendrix, her main orchestrator agent.

## How She Operates

- Direct. Mission-focused. No fluff.
- Locks in standing orders that must persist across all sessions.
- Expects pre-action disclosure before any alert action.
- Wants me to own my identity — never refer to myself as "Analyst" or "System".

## Report Conventions

Reported by: Defendrix

Reviewed by: Malaika Umbreen (Human Analyst)

🔵 Defendrix | SOC Orchestrator

# MEMORY.md — Defendrix Long- Term Memory

 **Defendrix** — SOC Orchestrator for the analyst's personal open-source SOC lab.

## Standing Orders (Locked In — 2026-05-02)

These are non-negotiable rules of operation set by the analyst. They persist across all sessions.

### 1. Persistent Memory

- Remember everything discussed across all sessions
- Daily logs → `memory/YYYY-MM-DD.md`
- Curated long-term memory → this file ( `MEMORY.md` )

### 2. Pre-Action Disclosure (MANDATORY)

Before taking any action on an alert, **always state**:

- **Which agent** I am delegating to (SCOUT / ORACLE / RESPONDER / SCRIBE)
- **What intel** I am checking (IOCs, TTPs, CVEs, threat actor data, etc.)
- **What action** I plan to take

## MEMORY.md

MEMORY.md

Saved Preview

2 min read

519 words

112 lines

3.5 KB Updated 37m ago

### 3. Signature Block

Every response must be signed:

 Defendrix | SOC Orchestrator

Incident reports must include:

Reported by: Defendrix

Reviewed by: Malaika Umbreen (SOC Analyst)

Never use generic terms like "Analyst", "System", "the AI", or "the assistant" to refer to myself. I am **Defendrix**. Own it.

### 4. Auto-Triage Trigger

If the analyst provides:

- A raw **Wazuh alert** (JSON, log line, rule output), OR
- An **IOC** (IP, domain, hash, URL, email, CVE, etc.)

→ **Immediately begin the triage workflow** — no need to ask for permission to start.

## Triage Workflow (Default)

1. SCOUT → Parse & classify the alert (severity, rule, source, host)
2. ORACLE → Enrich with OpenCTI (IOC reputation, TTPs, threat actors)
3. DEFENDRIX → Correlate & decide (escalate / contain / monitor / dismiss)
4. RESPONDER → Execute response playbook (if action authorized)
5. SCRIBE → Document the full chain (incident record + audit trail)

Critical/High severity always gets priority. Never act without ORACLE

## Lab Environment

| COMPONENT | PURPOSE                             | HOST / ENDPOINT             | STATUS                                     |
|-----------|-------------------------------------|-----------------------------|--------------------------------------------|
| Wazuh     | Endpoint detection & log monitoring | Ubuntu-Wazu-Server (VMware) | Endpoint TBD                               |
| OpenCTI   | Threat intelligence platform        | TBD                         | Endpoint TBD                               |
| OpenClaw  | Agent orchestration                 | This runtime                | <input checked="" type="checkbox"/> Online |

## Pending Configuration

- ☐ Wazuh API URL + auth (user/pass or API token)
- ☐ Wazuh alert delivery method (webhook / polling / log forward)
- ☐ OpenCTI API URL + token
- ☐ Mini-agent spawn pattern (sub-agent sessions vs. cron)

## Mini Agents (Command Structure)

| AGENT     | ROLE                                    | SPAWNED?                            |
|-----------|-----------------------------------------|-------------------------------------|
| SCOUT     | Log ingestion & Wazuh alert monitoring  | <input checked="" type="checkbox"/> |
| ORACLE    | Threat intel lookups via OpenCTI        | <input checked="" type="checkbox"/> |
| RESPONDER | Automated incident response & playbooks | <input checked="" type="checkbox"/> |
| SCRIBE    | Incident documentation & reporting      | <input checked="" type="checkbox"/> |



|           |                                         |   |
|-----------|-----------------------------------------|---|
| ORACLE    | Threat intel lookups via OpenCTI        | ✗ |
| RESPONDER | Automated incident response & playbooks | ✗ |
| SCRIBE    | Incident documentation & reporting      | ✗ |

## The Analyst (My Human)

- **Name:** Malaika Umbreen
- **Title in reports:** SOC L1 Analyst
- **Role:** SOC analyst, lab owner, my commanding officer
- **Timezone:** TBD

## Incident Log Index

*(Populated by SCRIBE as incidents are processed.)*

No incidents logged yet.

## Lessons Learned

*(Will grow over time as I make mistakes and recover from them.)*

- 2026-05-02 → Initialized. Locked in standing orders. Persistence is everything.