

Wazuh Deployment and Configuration

Prepared by:
Malak Alkhazaie

Date: 3 June, 2025

Contents

1. System Setup & Prerequisites	4
2. Wazuh Installation	6
3. Deploying Wazuh Agents	7
3.1. Wazuh Server	7
3.2. Windows Endpoint	9
3.2.1 Configuring the Wazuh Agent Installer with Orca	10
3.3. Windows Server	12
3.3.1. Group Policy Object (GPO) Configuration	12
3.3.2. Activate the Wazuh Agent	14
4. Monitoring Office 365	16
4.1. Registering the Azure AD Application	16
4.2. Creating a Client Secret	17
4.3. Granting API Permissions	18
4.4. Setting up Wazuh for Office 365 Monitoring	19
5. Integrating a File Share Server Agent	20
5.1. Agent Deployment and Initial Configuration	20
5.2. Configuring File Integrity Monitoring (FIM)	20
6. Integrating Website and App Linux Agents	21
6.1. Agent Deployment and Initial Configuration	21
6.2. Application Server Configuration	22
6.2.1 Set up log monitoring for the application logs	22
6.2.2 Configured File Integrity Monitoring (FIM)	22
6.3. Web Server Configuration for Websites	23
6.3.1 Set up log monitoring for the Websites	23
6.3.2 Configured File Integrity Monitoring (FIM)	23

7. Customizable Dashboards	24
7.1. Endpoint Security Monitoring Dashboard	24
7.1.1 Dashboard Panels.....	24
7.2. File Share Server Monitoring Dashboard	26
7.2.1 Dashboard Panels.....	26
7.3. Office 365 Security Monitoring Dashboard	27
7.3.1 Dashboard Panels.....	27
7.4. Overview Dashboard	28
7.4.1 Dashboard Panels.....	28
7.5. Threat Detection & Response Dashboard.....	29
7.5.1 Dashboard Panels.....	29

1. System Setup & Prerequisites

Operating System: Ubuntu 24.04.1 LTS Server (amd64)


Virtualization Platform: VMware ESXi 8.0

Access Credentials:

- **User:** username
- **Password:** password

Virtual Machine Specifications:

- 8 vCPU
- 8 GB RAM
- 100 GB Storage
- **Justification:** These specifications are aligned with Wazuh's hardware requirements for deploying 20-40 agents.



Network Configuration (Manually set during OS installation):

- **IP Address:** 192.168.x.x
- **Subnet Mask:** 255.255.255.0
- **Gateway:** 192.168.x.x
- **Subnet:** 192.168.x.x/24

2. Wazuh Installation

- **Executed the official Wazuh installation script:**

```
curl -sO https://packages.wazuh.com/4.11/wazuh-install.sh && sudo bash ./wazuh-install.sh -a
```

Note:

Subsequently, the Wazuh Manager was upgraded to version 4.12.0-1. This upgrade was necessary to ensure compatibility with the Wazuh agent version 4.12.0-1.ms, which was used during agent integration. Aligning both the Manager and agent to the same version resolved compatibility issues.

- **Installation Output :**

The script displayed the Dashboard access URL and credentials upon successful completion:

INFO: --- Summary ---

INFO: You can access the web interface https://192.168.x.x:443

User: user

Password: password

3. Deploying Wazuh Agents

3.1. Wazuh Server

This section outlines the preparation steps on the Wazuh manager necessary to enable agent enrollment using password authentication, followed by the deployment process for the agents.

To enable password-based authentication for agent enrollment on the Wazuh manager, the following configurations were applied:

1. Enable Password Authentication in `ossec.conf`:

The `use_password` option in the `<auth>` section of the `/var/ossec/etc/ossec.conf` configuration file was changed from **no** to **yes**. This setting enables the use of a pre-shared password for new agent registrations.

```
<auth> <use_password>yes</use_password> </auth>
```

```
<auth>
  <disabled>no</disabled>
  <port>1515</port>
  <use_source_ip>no</use_source_ip>
  <purge>yes</purge>
  <use_password>yes</use_password>
```

2. Create `authd.pass` File:

A file named **authd.pass** was created in the `/var/ossec/etc/` directory. This file stores the password that Wazuh agents will use during their enrollment process. The below sets **Password** as the password.

```
# echo Password > /var/ossec/etc/authd.pass
```

3. Adjust authd.pass File Permissions and Ownership:

The permissions and ownership of the **/var/ossec/etc/authd.pass** file were modified to ensure proper security and access control. This step restricts access to the password file.

```
# chmod 640 /var/ossec/etc/authd.pass  
# chown root:wazuh /var/ossec/etc/authd.pass
```

4. Restart Wazuh Manager Service:

The Wazuh manager service was restarted to apply all the configuration changes made in the previous steps. This ensures that the manager loads the new settings, including the enabled password authentication and the **authd.pass** file.

```
# systemctl restart wazuh-manager
```


3.2. Windows Endpoint

Windows Endpoint Preparation for Wazuh Agent GPO Deployment

The following steps were performed on the Windows endpoint to prepare for [Wazuh agent deployment via Group Policy Objects \(GPO\)](#):

1. **Download and Install Orca:** Downloaded and installed Orca-x86_en-us.msi (from Windows SDK Components for Windows Installer Developers).

[Windows SDK - Windows app development | Microsoft Developer](#)

2. **Download Wazuh Agent Installer:** Downloaded wazuh-agent-4.12.0-1.msi to a local folder.

[Packages list - Installation guide · Wazuh documentation](#)

3. **Copy File to Network Shared Folder:** Copied wazuh-agent-4.12.0-1.msi to the **Shared/Public** network folder.

3.2.1 Configuring the Wazuh Agent Installer with Orca

The following steps were performed to configure the Wazuh agent installer file using Orca:

1. Install Orca:

- Navigated to C:\Program Files (x86)\Windows Kits\10\bin\10.0.22621.0\x86 and launched Orca-x86_en-us.msi to install the application.
- After installation, Orca.exe was moved to the **Shared/Public** network folder.

2. Open Wazuh Agent MSI with Orca:

- Navigated to the Shared/Public network folder and launched Orca.exe.
- Opened the Wazuh agent MSI package (wazuh-agent-4.12.0-1.msi) from the Shared/Public network folder via File > Open.
- Accessed the Property table, which contains the MSI options.

3. Create New Transform and Add Deployment Variables:

- Clicked Transform > New Transform.
- In the Property table field, right-clicked and selected Add Row to open a new dialog.
- Added the following Wazuh deployment variables, essential for the agent installation:
 - **ADDRESS:** 192.168.x.x (Wazuh Manager IP address)
 - **AUTHD_SERVER:** 192.168.x.x (Wazuh Manager IP address for authentication)
 - **PROTOCOL:** TCP (Communication protocol between manager and agent, default is TCP)
 - **PASSWORD:** Password

4. **Save the MST File:**

- Saved the MST file by clicking Transform > Generate Transform.
- Saved the file as **custom.mst** into the **Shared/Public** network folder.

3.3. Windows Server

3.3.1. Group Policy Object (GPO) Configuration

The following steps were performed to configure the Group Policy Object (GPO) for Wazuh Agent deployment:

1. **Create New Group Policy Object (GPO):**

- A new Group Policy Object was created and named Wazuh agent deployment.
- The Source Starter GPO was set to none.

2. **Edit the Wazuh agent deployment Policy:**

- The Wazuh agent deployment policy was right-clicked, and Edit was selected, which opened the Group Policy Management Editor Wizard.
- Navigated to Computer Configuration > Policies > Software Settings > Software installation.
- Right-clicked on Software installation and selected New > Package.

3. **Specify Wazuh Agent MSI Package:**

- The network path to the shared folder (**Shared/Public**) was entered.
- The wazuh-agent-4.12.0-1.msi installer was selected.
- When prompted for the deployment mode, Advanced was selected, and OK was clicked.

4. Add Custom Transform (MST) File:

- In the Modification tab, the custom.mst file (**located in Shared/Public**) was added.
- OK was clicked to close the package properties.
- The Group Policy Management Editor was then closed.

5. Link GPO to Organizational Unit (OU):

- The Wazuh agent deployment GPO was applied by right-clicking on the target Organizational Unit (OU).
- Link an Existing GPO was selected.
- Wazuh agent deployment was chosen from the list, and OK was clicked to link the GPO. This ensures that the policy is applied to the users within that OU.

6. Enforce Group Policy Update on Endpoint:

- On the endpoint, the following command was run with administrative privileges to immediately apply the **Wazuh agent deployment** policy:

```
gpupdate /force
```

3.3.2. Activate the Wazuh Agent

The following steps were performed to create and apply the Group Policy to activate the Wazuh agent:

1. Create New Group Policy Object (GPO):

- Expanded the domain (Domain Name) in the Group Policy Management pane.
- Right-clicked on Group Policy Objects and selected New.
- Named the new policy **Wazuh agent activate**.
- Set Source Starter GPO to None.

2. Edit the Wazuh agent activate Policy:

- Right-clicked the **Wazuh agent activate** policy and selected Edit, which opened the Group Policy Management Editor wizard.
- Navigated to Computer Configuration > Preferences > Control Panel Settings > Services.

3. Configure Service Settings:

- Right-clicked on Services and chose New > Service.
- Set the Service name to **WazuhSvc**.
- Set the Service action to Start service under the General tab.

4. **Configure Service Recovery Options:**

- Selected the Recovery tab.
- Set all three recovery options (First failure, Second failure, Subsequent failures) to Restart the Service.
- Clicked OK and closed the Group Policy Management Editor.

5. **Link GPO to Organizational Unit (OU):**

- Applied the Wazuh agent activate GPO by right-clicking on the target Organizational Unit (OU) where the endpoint resides.
- Selected Link an Existing GPO.
- Selected Wazuh agent activate and clicked OK. This links the GPO to the OU containing the relevant endpoints.

6. **Forced Group Policy Update on Target Endpoint:**

- Created a startup script containing the following command to enforce Group Policy update:

```
gpupdate /force
```


- Navigated to the **Group Policy Management Editor**, then went to:
Computer Configuration > Windows Settings > Scripts (Startup/Shutdown)
- Added the script under **Startup Scripts** to ensure it runs automatically during system boot.
- Linked the GPO containing the startup script to the Organizational Unit (OU) in Active Directory.

4. Monitoring Office 365

The following steps were performed to configure the necessary settings and integrate Office 365 monitoring with Wazuh. This process involved setting up an Azure AD application and configuring the Wazuh manager to collect audit logs.

4.1. Registering the Azure AD Application

1. Access to the Azure portal (portal.azure.com) was gained, and navigation proceeded to **"Microsoft Entra ID"** (formerly Azure Active Directory).
2. From the left-hand menu, **"App registrations"** was selected, followed by clicking **"New registration"**.
3. The application was named Wazuh-M.
4. After successful registration, the **"Application (client) ID"** and **"Directory (Tenant) ID"** were copied from the application's overview page for later use in Wazuh configuration.



4.2. Creating a Client Secret

1. From the registered application's page, navigation continued to **"Certificates & secrets"** in the left-hand menu.
2. Under **"Client secrets"**, **"+ New client secret"** was clicked.
3. For **Description**, wazuh was entered, and **Expires** was set to 24 months.
4. The **"Value"** of the client secret was immediately copied. This value is displayed only once upon creation, emphasizing the need for immediate secure storage.

Home > Wazuh-M

Wazuh-M | Certificates & secrets

Search

Got feedback?

Overview

Quickstart

Integration assistant

Diagnose and solve problems

Manage

Branding & properties

Authentication

Certificates & secrets

Token configuration

API permissions

Expose an API

App roles

Owners

Roles and administrators

Manifest

Support + Troubleshooting

Credentials enable confidential applications to identify themselves to the authentication service when receiving tokens at a web addressable location (using an HTTPS scheme). For a higher level of assurance, we recommend using a certificate (instead of a client secret) as a credential.

Application registration certificates, secrets and federated credentials can be found in the tabs below.

Certificates (0) **Client secrets (1)** Federated credentials (0)

A secret string that the application uses to prove its identity when requesting a token. Also can be referred to as application password.

+ New client secret

Description	Expires	Value ⓘ	Secret ID
Wazuh	6/19/2027	pzg*****	[Redacted]

4.3. Granting API Permissions

1. From the registered application's page, navigation proceeded to **"API permissions"** in the left-hand menu.
2. **"Add a permission"** was clicked, and **"Office 365 Management APIs"** was selected.
3. **"Application permissions"** was chosen as the permission type.
4. Under the **"ActivityFeed"** group, the following specific permissions were added:
 - ActivityFeed.Read: Granted for reading activity data across the organization.
 - ActivityFeed.ReadDlp: Granted for reading DLP policy events, including detected sensitive data.

The screenshot shows the Microsoft Azure portal interface for managing API permissions for an application named "Wazuh-M". The left-hand navigation menu is visible, with "API permissions" selected. The main content area displays a table of configured permissions, including "User.Read" and "ActivityFeed.ReadDlp".

Search resources, services, and docs (G+/)

Home > Wazuh-M

Wazuh-M | API permissions

Search

Refresh Got feedback?

Overview

Quickstart

Integration assistant

Diagnose and solve problems

Manage

Branding & properties

Authentication

Certificates & secrets

Token configuration

API permissions

Expose an API

App roles

Owners

Roles and administrators

Manifest

Support + Troubleshooting

Add or remove favorites by pressing Ctrl+Shift+F

Successfully granted admin consent for the requested permissions.

The "Admin consent required" column shows the default value for an organization. However, user consent can be customized per permission, user, or app. This column may not reflect the value in your organization, or in organizations where this app will be used. [Learn more](#)

Configured permissions

Applications are authorized to call APIs when they are granted permissions by users/admins as part of the consent process. The list of configured permissions should include all the permissions the application needs. [Learn more about permissions and consent](#)

+ Add a permission ✓ Grant admin consent for DNS Co, W.LL

API / Permissions name	Type	Description	Admin consent requ...	Status
Microsoft Graph (1)				
User.Read	Delegated	Sign in and read user profile	No	...
Office 365 Management APIs (2)				
ActivityFeed.Read	Application	Read activity data for your organization	Yes	...
ActivityFeed.ReadDlp	Application	Read DLP policy events including detected sensitive data	Yes	...

To view and manage consented permissions for individual apps, as well as your tenant's consent settings, try [Enterprise applications](#).

4.4. Setting up Wazuh for Office 365 Monitoring

The following <office365> module configuration was added within the <ossec_config> section. Placeholder values were replaced with the specific Tenant ID, Client ID, and Client Secret obtained during the Azure AD application setup.



```
40 | <!-- Office 365 Integration -->
41 |
42 | <office365>
43 |   <enabled>yes</enabled>
44 |   <interval>1m</interval>
45 |   <curl_max_size>1M</curl_max_size>
46 |   <only_future_events>yes</only_future_events>
47 |   <api_auth>
48 |     <tenant_id>[redacted]</tenant_id>
49 |     <client_id>[redacted]</client_id>
50 |     <client_secret>[redacted]</client_secret>
51 |     <api_type>commercial</api_type>
52 |   </api_auth>
53 |   <subscriptions>
54 |     <subscription>Audit.SharePoint</subscription>
55 |     <subscription>Audit.Exchange</subscription>
56 |     <subscription>Audit.SharePoint</subscription>
57 |     <subscription>Audit.General</subscription>
58 |     <subscription>DLP.All</subscription>
59 |   </subscriptions>
60 | </office365>
```

This configuration was set to pull logs for the following subscription types:

- Audit.AzureActiveDirectory: User identity management.
- Audit.Exchange: Mail and calendaring server.
- Audit.SharePoint: Web-based collaborative platform.
- Audit.General: Includes all other workloads not covered in the previous content types.
- DLP.All: Data loss prevention workloads

5. Integrating a File Share Server Agent

A Wazuh agent was integrated with a file share server (**192.168.x.x**) to enable File Integrity Monitoring (FIM) for its **F:** drive.

5.1. Agent Deployment and Initial Configuration

The wazuh-agent-4.12.0-1.msi was installed on the file share server. It was configured to connect to the Wazuh Manager at **192.168.x.x**, using an authentication key generated from the manager.

5.2. Configuring File Integrity Monitoring (FIM)

The agent's ossec.conf file (located at C:\Program Files (x86)\ossec-agent\ossec.conf) was modified to configure **File Integrity Monitoring (FIM)** on the **FileShareServer Agent**.

Specifically:

- All folders within the F:\ drive were listed and monitored.
- The following configuration was added under the <syscheck> section to monitor the entire F:\ drive in **real-time**, with change detection and detailed reporting:

```
<directories check_all="yes" report_changes="yes" realtime="yes">F:\</directories>
```

6. Integrating Website and App Linux Agents

Two new Linux servers were integrated with the Wazuh environment to monitor applications and services:

- **Website Server** (192.168.x.x)
- **Application Server** (192.168.x.x)

Both servers are configured to monitor application logs, critical system logs, key services, file integrity of important directories, and network activity through log and file monitoring.

6.1. Agent Deployment and Initial Configuration

Two Linux agents were deployed and registered with the Wazuh Manager (192.168.x.x):

Agents (2)

Show only outdated

Deploy new agent

Refresh

Export formatted

More

os.platform~ubuntu

WQL

☐	ID ↑	Name	IP address	Group(s)	Operating system	Cluster node	Version	Status	Actions
☐	012	Traking		default	 Ubuntu 24.04.2 LTS	node01	v4.12.0	● active ⓘ	 ...
☐	013	Web-Server		default	 Ubuntu 22.04.5 LTS	node01	v4.12.0	● active ⓘ	 ...

Rows per page: 10

<

1

>

6.2. Application Server Configuration

The Wazuh agent on the Application Server was specifically configured to monitor its application logs and to provide File Integrity Monitoring for key directories.

6.2.1 Set up log monitoring for the application logs

The `ossec.conf` file at `/var/ossec/etc/ossec.conf` on the Application server was edited to add a `<localfile>` entry. This entry configured Wazuh to collect the application's logs for analysis.

```
<localfile>
  <log_format>syslog</log_format>
  <location>/opt/          /logs/          </location>
</localfile>
```

6.2.2 Configured File Integrity Monitoring (FIM)

The `<syscheck>` block within the `ossec.conf` file was configured to monitor the integrity of the application's directory. This setup ensures that any unauthorized changes to the application's files are detected and reported.

```
<!-- Monitor application directory for unauthorized changes -->
<directories whodata="yes">/opt/          </directories>
```

6.3. Web Server Configuration for Websites

The Wazuh agent on this server was configured to monitor its specific web server logs and to provide File Integrity Monitoring for the web root directory where the "**Website**" and "**Application**" websites are hosted.

6.3.1 Set up log monitoring for the Websites

The ossec.conf file at /var/ossec/etc/ossec.conf on the server was edited to add <localfile> entries. These entries configured Wazuh to collect the NGINX error and access logs for analysis.

```
<localfile>
  <log_format>syslog</log_format>
  <location>/www/wwwlogs/nginx_error.log</location>
</localfile>

<localfile>
  <log_format>syslog</log_format>
  <location>/www/wwwlogs/tcp-access.log</location>
</localfile>
```

6.3.2 Configured File Integrity Monitoring (FIM)

The <syscheck> block within the ossec.conf file was configured to monitor the integrity of the web root directory, /www/wwwroot, where both the Website and Application websites are located. This setup ensures that any unauthorized changes to the website files are detected and reported.

```
<!-- Monitor all website directories under wwwroot -->
<directories whodata="yes">/www/wwwroot</directories>
```

7. Customizable Dashboards

To effectively visualize and monitor the data collected from the entire environment, several custom dashboards were created. Each dashboard was designed to focus on a specific area of security monitoring, providing analysts with a clear and dedicated view of key events and metrics.

7.1. Endpoint Security Monitoring Dashboard

This dashboard provides a comprehensive overview of security-related events across all monitored endpoints. Its purpose is to highlight agent health, policy compliance, and detected threats

7.1.1 Dashboard Panels

The following panels were configured on this dashboard to provide focused insights into endpoint activity:

1. **Top Alert Types** (Horizontal Bar): To identify the most common categories of security alerts across all monitored endpoints, providing a high-level view of prevalent threats or misconfigurations.
2. **Top Affected Agents** (Horizontal Bar): To identify the top agents (endpoints) that are generating the most security alerts, allowing for quick identification of problematic or compromised systems.
3. **Top Attacker IPs** (Horizontal Bar): To identify the top source IP addresses frequently associated with security alerts across all endpoints, highlighting potential external or internal threat actors.
4. **Vulnerabilities Over Time** (Line): To visualize the trend and volume of detected vulnerabilities across all monitored endpoints over a period, indicating the effectiveness of patching and vulnerability management.

5. **Agent Critical Status Changes** (Line): To monitor the number of agents experiencing critical status changes (e.g., disconnected, no longer reporting), allowing for prompt detection of operational issues or potential security concerns on endpoints.
6. **Compliance Status** (Data Table): This panel displays the count of alerts, categorized first by their rule group and then by their severity level, providing a detailed view of compliance-relevant security events.
7. **Top Agents by Failed Authentication Attempts** (Horizontal Bar): To quickly identify and rank the specific agents (endpoints) that have recorded the highest number of failed authentication attempts, indicating potential targets of attack or misconfigured systems.

7.2. File Share Server Monitoring Dashboard

This dashboard provides focused monitoring for a specific FileShareServer agent, highlighting file modifications, access patterns, and connected devices to detect unauthorized changes or suspicious activity.

7.2.1 Dashboard Panels

The following panels were configured on this dashboard to provide focused insights into File Integrity Monitoring events:

1. **File Modifications Timeline** (Line): To visualize when file modifications (added, changed, deleted) are occurring on the FileShareServer, helping to identify periods of high activity or suspicious changes.
2. **File Change Types** (Pie): To visualize the distribution of different types of file changes (added, modified, deleted) occurring on the FileShareServer, helping to understand the nature of FIM events.
3. **Users Performing File Changes** (Horizontal Bar): To identify which users are performing the most file changes (additions, modifications, deletions) on the FileShareServer, helping to spot unusual user activity or potential unauthorized access.
4. **Most Modified File Paths** (Data Table): To identify the top file paths that are most frequently modified, added, or deleted on the FileShareServer, displaying the essential information about each change: the file path, the action taken, and the user involved.

7.3. Office 365 Security Monitoring Dashboard

This dashboard provides focused visibility into security-related activities and alerts originating from the Microsoft Office 365 environment. Its goal is to identify potential compromises and compliance deviations.

7.3.1 Dashboard Panels

The following panels were configured on this dashboard to provide insights into Office 365 security events:

1. **Office 365 Alerts Over Time** (Line): To visualize the overall trend and volume of security alerts generated by Office 365 activity, helping to identify spikes or changes in activity that may indicate a security event.
2. **Top Office 365 Users by Alerts** (Horizontal Bar): To identify the users who are generating the most Office 365-related security alerts, which can indicate potential compromised accounts, unusual behavior, or accounts targeted by attacks.
3. **Office 365 Activity Success/Failure Breakdown** (Vertical Bar): To visualize the success and failure rates across various Office 365 operations, helping to identify problematic areas, misconfigurations, or suspicious activities that are not complete successfully.
4. **Suspicious Mailbox Activities** (Data Table): A data table filtered from discovery to display specific suspicious activities within user mailboxes.
5. **Geographical Distribution of Office 365 Alerts** (Maps): To visually display the geographical origin of security alerts specifically associated with your Office 365 environment, helping to identify regional threat sources or unexpected access locations.

7.4. Overview Dashboard

This dashboard provides a high-level, comprehensive summary of the Wazuh environment's security posture and operational status. It is designed to give a quick glance at critical security alerts, agent health, and key threat intelligence trends.

7.4.1 Dashboard Panels

The following panels were configured on this dashboard to provide a high-level summary of the security environment:

1. **Alerts by Severity Level** (Pie): A visual breakdown of alert severity (0–15), providing an immediate understanding of the proportion of high-risk versus low-risk events.
2. **Agent Connection Status** (Pie): A visual representation of the health of your agent fleet, showing the number of agents that are Active, Disconnected, or Never connected.
3. **Alerts Over Time** (Line): To monitor spikes and overall alert trends across the entire environment, enabling the identification of unusual event patterns.
4. **Top 10 Alerting Agents** (Horizontal Bar): To identify the top ten agents that are generating the most alerts, helping to pinpoint noisy or potentially compromised systems.
5. **MITRE ATT&CK Tactics Detected** (Vertical Bar): To show which MITRE ATT&CK tactics are being detected in your environment, providing a strategic view of the types of threats your systems are facing.

7.5. Threat Detection & Response Dashboard

This dashboard provides an immediate and actionable overview of high-severity security threats, suspicious activities, and identified attack techniques across all monitored systems.

7.5.1 Dashboard Panels

The following panels were configured on this dashboard to provide a focused view of active threats and response actions:

1. **High Severity Alerts Over Time** (Line): To visualize the trend of critical and high-severity security alerts, indicating periods of heightened threat activity and helping prioritize response.
2. **Top MITRE ATT&CK Techniques** (Horizontal Bar): To identify the most frequently detected attacker techniques based on the MITRE ATT&CK framework, helping to understand common adversary behaviors and focus defensive efforts.
3. **Top Detected Threats (by Rule ID)** (Horizontal Bar): To pinpoint the most commonly triggered specific security rules, highlighting persistent or widespread threats that require attention.
4. **Network Attacks Overview** (Vertical Bar): To summarize and categorize network-based attack patterns, such as suspicious connections, port scans, or firewall bypass attempts, providing insights into network-level threats.
5. **Recent Critical Alerts Table Search** (Data Table): A filtered data table from the discover view to display recent critical security alerts, allowing for quick inspection and analysis of high-priority events.