

MLS_1	Trunks	interface range f0/1-4 switchport trunk encapsulation dot1q switchport mode trunk switchport trunk allowed vlan all
	Etherchannel	interface range f0/1-2 channel-group 1 mode active ex interface range f0/3-4 channel-group 2 mode active
	Vlans	vlan 70 name it ex vlan 80 name hr ex vlan 90 name dev ex vlan 100 name cs ex
	VTP	vtp mode server vtp domain branch3 vtp password branch3
	STP/RSTP	spanning-tree vlan 70,80 priority 4096 spanning-tree vlan 90 priority 8192 spanning-tree mode rapi-pvst
	SVI	ip routing interface vlan 70 ip address 10.0.70.1 255.255.255.0 no shutdown standby 10 ip 10.0.70.50 standby 10 priority 150 standby 10 preempt interface vlan 80 ip address10.0.80.1 255.255.255.0 no shutdown standby 10 ip 10.0.80.50 standby 10 priority 150 standby 10 preempt interface vlan 90 ip address 10.0.90.1 255.255.255.0 no shutdown standby 10 ip 10.0.90.50 standby 10 priority 100 interface vlan 100 ip address 10.0.100.1 255.255.255.0 no shutdown standby 10 ip 10.0.100.50 standby 10 priority 100 interface f0/5 no switchport ip address 23.0.0.1 255.255.255.252 interface f0/6 no switchport ip address 24.0.0.1 255.255.255.252
	DHCP	ip dhcp pool vlan70 network 10.0.70.0 255.255.255.0 default-router 10.0.70.50 dns-server 8.8.8.8 ex ip dhcp excluded address 10.0.70.1 ip dhcp excluded address 10.0.70.2 ip dhcp excluded address 10.0.70.50 ip dhcp pool vlan80 network 10.0.80.0 255.255.255.0 default-router 10.0.80.50 dns-server 8.8.8.8 ex ip dhcp excluded address 10.0.80.1 ip dhcp excluded address 10.0.80.2 ip dhcp excluded address 10.0.80.50

MLS_2	Trunks	interface range f0/1-4 switchport trunk encapsulation dot1q switchport mode trunk switchport trunk allowed vlan all
	Etherchannel	interface range f0/1-2 channel-group 1 mode active ex interface range f0/3-4 channel-group 2 mode active
	Vlans	vlan 70 name it ex vlan 80 name hr ex vlan 90 name dev ex vlan 100 name cs ex
	VTP	vtp mode server vtp domain branch3 vtp password branch3
	STP/RSTP	spanning-tree vlan 90 priority 4096 spanning-tree vlan 70,80 priority 8192 spanning-tree mode rapi-pvst
	SVI	ip routing interface vlan 70 ip address 10.0.70.2 255.255.255.0 no shutdown standby 10 ip 10.0.70.50 standby 10 priority 100 interface vlan 80 ip address10.0.80.2 255.255.255.0 no shutdown standby 10 ip 10.0.80.50 standby 10 priority 100 interface vlan 90 ip address 10.0.90.2 255.255.255.0 no shutdown standby 10 ip 10.0.90.50 standby 10 priority 150 standby 10 preempt interface vlan 100 ip address 10.0.100.2 255.255.255.0 no shutdown standby 10 ip 10.0.100.50 standby 10 priority 150 standby 10 preempt interface f0/5 no switchport ip address 26.0.0.1 255.255.255.252 interface f0/6 no switchport ip address 25.0.0.1 255.255.255.252
	DHCP	ip dhcp pool vlan90 network 10.0.90.0 255.255.255.0 default-router 10.0.90.50 dns-server 8.8.8.8 ex ip dhcp excluded address 10.0.90.1 ip dhcp excluded address 10.0.90.2 ip dhcp excluded address 10.0.90.50 ip dhcp pool vlan100 network 10.0.100.0 255.255.255.0 default-router 10.0.100.50 dns-server 8.8.8.8 ex ip dhcp excluded address 10.0.100.1 ip dhcp excluded address 10.0.100.2 ip dhcp excluded address 10.0.100.50

DIS	Trunks	interface range f0/1-10 switchport mode trunk switchport trunk allowed vlan all
	Etherchannel	interface range f0/1-2 channel-group 1 mode active ex interface range f0/3-4 channel-group 2 mode active ex interface range f0/5-6 channel-group 3 mode active ex interface range f0/7-8 channel-group 4 mode passive ex interface range f0/9-10 channel-group 5 mode passive ex
	VTP	vtp mode client vtp domain branch3 vtp password branch3
	STP/RSTP	spanning-tree vlan 70,80,90 priority 12288 spanning-tree mode rapi-pvst

Access	Trunks	interface range f0/13-16 switchport mode trunk switchport trunk allowed vlan all
	Etherchannel	interface range f0/13-14 channel-group 1 mode passive ex interface range f0/15-16 channel-group 2 mode passive ex
	VTP	vtp mode client vtp domain branch3 vtp password branch3
	STP/RSTP	spanning-tree vlan 70,80,90 priority 16384 spanning-tree mode rapi-pvst
	Access ports/STP features	
	interface range f0/1-12 switchport mode access spanning-tree portfast spanning-tree bpduguard enable switchport port-security switchport port-security maximum 1 switchport port-security mac-address sticky switchport port-security violation shutdown ex	
	interface range f0/1-3 switchport access vlan 70 ex	
	interface range f0/4-6 switchport access vlan 80 ex	
	interface range f0/7-9 switchport access vlan 90 ex	
	interface range f0/10-12 switchport access vlan 100 ex	