

MLS_1	Trunks	interface range f0/1-4 switchport trunk encapsulation dot1q switchport mode trunk switchport trunk allowed vlan all
	Etherchannel	interface range f0/1-2 channel-group 1 mode active ex interface range f0/3-4 channel-group 2 mode active
	Vlans	vlan 10 name it ex vlan 20 name hr ex vlan 30 name dev ex
	VTP	vtp mode server vtp domain branch1 vtp password branch1
	STP/RSTP	spanning-tree vlan 10 priority 4096 spanning-tree vlan 20,30 priority 8192 spanning-tree mode rapi-pvst
	SVI	ip routing interface vlan 10 ip address 192.168.10.1 255.255.255.0 no shutdown standby 10 ip 192.168.10.50 standby 10 priority 150 standby 10 preempt interface vlan 20 ip address 192.168.20.1 255.255.255.0 no shutdown standby 10 ip 192.168.20.50 standby 10 priority 100 interface vlan 30 ip address 192.168.30.1 255.255.255.0 no shutdown standby 10 ip 192.168.30.50 standby 10 priority 100 interface f0/5 no switchport ip address 11.0.0.1 255.255.255.252 interface f0/6 no switchport ip address 12.0.0.1 255.255.255.252
	DHCP	ip dhcp pool vlan10 network 192.168.10.0 255.255.255.0 default-router 192.168.10.50 dns-server 8.8.8.8 ex ip dhcp excluded-address 192.168.10.1 192.168.10.3 ip dhcp excluded-address 192.168.10.50

MLS_2	Trunks	interface range f0/1-4 switchport trunk encapsulation dot1q switchport mode trunk switchport trunk allowed vlan all
	Etherchannel	interface range f0/1-2 channel-group 1 mode active ex interface range f0/3-4 channel-group 2 mode active
	Vlans	vlan 10 name it ex vlan 20 name hr ex vlan 30 name dev ex
	VTP	vtp mode server vtp domain branch1 vtp password branch1
	STP/RSTP	spanning-tree vlan 20 priority 4096 spanning-tree vlan 10,30 priority 8192 spanning-tree mode rapi-pvst
	SVI	ip routing interface vlan 10 ip address 192.168.10.2 255.255.255.0 no shutdown standby 10 ip 192.168.10.50 standby 10 priority 100 interface vlan 20 ip address 192.168.20.2 255.255.255.0 no shutdown standby 10 ip 192.168.20.50 standby 10 priority 150 standby 10 preempt interface vlan 30 ip address 192.168.30.2 255.255.255.0 no shutdown standby 10 ip 192.168.30.50 standby 10 priority 100 interface f0/5 no switchport ip address 13.0.0.1 255.255.255.252 interface f0/6 no switchport ip address 14.0.0.1 255.255.255.252
	DHCP	ip dhcp pool vlan20 network 192.168.20.0 255.255.255.0 default-router 192.168.20.50 dns-server 8.8.8.8 ex ip dhcp excluded address 192.168.20.1 192.168.20.3 ip dhcp excluded address 192.168.20.50

MLS_3	Trunks	interface range f0/1-4 switchport trunk encapsulation dot1q switchport mode trunk switchport trunk allowed vlan all
	Etherchannel	interface range f0/1-2 channel-group 1 mode active ex interface range f0/3-4 channel-group 2 mode active
	Vlans	vlan 10 name it ex vlan 20 name hr ex vlan 30 name dev ex
	VTP	vtp mode server vtp domain branch1 vtp password branch1
	STP/RSTP	spanning-tree vlan 30 priority 4096 spanning-tree vlan 10,20 priority 8192 spanning-tree mode rapi-pvst
	SVI	ip routing interface vlan 10 ip address 192.168.10.3 255.255.255.0 no shutdown standby 10 ip 192.168.10.50 standby 10 priority 100 interface vlan 20 ip address 192.168.20.3 255.255.255.0 no shutdown standby 10 ip 192.168.20.50 standby 10 priority 100 interface vlan 30 ip address 192.168.30.3 255.255.255.0 no shutdown standby 10 ip 192.168.30.50 standby 10 priority 150 standby 10 preempt interface f0/5 no switchport ip address 15.0.0.1 255.255.255.252 interface f0/6 no switchport ip address 16.0.0.1 255.255.255.252
	DHCP	ip dhcp pool vlan30 network 192.168.30.0 255.255.255.0 default-router 192.168.30.50 dns-server 8.8.8.8 ex ip dhcp excluded address 192.168.30.1 192.168.30.3 ip dhcp excluded address 192.168.30.50

DIS	Trunks	interface range f0/1-12 switchport mode trunk switchport trunk allowed vlan all
	Etherchannel	interface range f0/1-2 channel-group 1 mode active ex interface range f0/3-4 channel-group 2 mode active ex interface range f0/5-6 channel-group 3 mode active ex interface range f0/7-8 channel-group 4 mode passive ex interface range f0/9-10 channel-group 5 mode passive ex interface range f0/11-12 channel-group 6 mode passive ex
	VTP	vtp mode client vtp domain branch1 vtp password branch1
	STP/RSTP	spanning-tree vlan 10,20,30 priority 12288 spanning-tree mode rapi-pvst

Access	Trunks	interface range f0/10-13 switchport mode trunk switchport trunk allowed vlan all
	Etherchannel	interface range f0/10-11 channel-group 1 mode passive ex interface range f0/12-13 channel-group 2 mode passive ex
	VTP	vtp mode client vtp domain branch1 vtp password branch1
	STP/RSTP	spanning-tree vlan 10,20,30 priority 16384 spanning-tree mode rapi-pvst
	Access ports/STP features	interface range f0/1-9 switchport mode access spanning-tree portfast spanning-tree bpduguard enable switchport port-security switchport port-security maximum 1 switchport port-security mac-address sticky switchport port-security violation shutdown ex interface range f0/1-3 switchport access vlan 10 ex interface range f0/4-6 switchport access vlan 20 ex interface range f0/7-9 switchport access vlan 30 ex