

Branch 2	Router	sub-interface	interface g0/0/0.40 encapsulation dot1q 40 ip address 172.16.40.1 255.255.255.0 ex interface g0/0/0.50 encapsulation dot1q 50 ip address 172.16.50.1 255.255.255.0 ex interface g0/0/0.60 encapsulation dot1q 60 ip address 172.16.60.1 255.255.255.0
		DHCP	ip dhcp pool vlan40 network 172.16.40.0 255.255.255.0 default-router 192.168.40.1 dns-server 8.8.8.8 ex ip dhcp excluded address 172.16.40.1 ip dhcp pool vlan50 network 172.16.50.0 255.255.255.0 default-router 192.168.50.1 dns-server 8.8.8.8 ex ip dhcp excluded address 172.16.50.1 ip dhcp pool vlan60 network 172.16.60.0 255.255.255.0 default-router 192.168.60.1 dns-server 8.8.8.8 ex ip dhcp excluded address 172.16.60.1
	Core	Trunks	interface range f0/1-5 switchport mode trunk switchport allowed vlan all
		Etherchannel	interface range f0/1-2 channel-group 1 mode active ex interface range f0/3-4 channel-group 2 mode active
		Vlans	vlan 40 name it ex vlan 50 name hr ex vlan 60 name dev ex
		VTP	vtp mode server vtp domain branch2 vtp password branch2 ex
		STP/RSTP	spanning-tree vlan 40,50,60 priority 4096 spanning-tree mode rapid-pvst
	DIS	Trunks	interface range f0/1-8 switchport mode trunk switchport allowed vlan all
		Etherchannel	interface range f0/7-8 channel-group 1 mode passive ex interface range f0/1-2 channel-group 2 mode active ex interface range f0/3-4 channel-group 3 mode active ex interface range f0/5-6 channel-group 4 mode active ex
		VTP	vtp mode client vtp domain branch2 vtp password branch2 ex
		STP/RSTP	spanning-tree vlan 40,50,60 priority 8192 spanning-tree mode rapid-pvst
	Access	Trunk	interface range f0/10-13 switchport mode trunk switchport allowed vlan all
		Etherchannel	interface range f0/10-11 channel -group 1 mode passive ex interface range f0/12-13 channel -group 2 mode passive ex
		VTP	vtp mode client vtp domain branch2 vtp password branch2 ex
		STP/RSTP	spanning-tree vlan 40,50,60 priority 12288 spanning-tree mode rapid-pvst
		Access Ports /STP feature	interface range f0/1-9 switchport mode access spanning-tree portfast spanning-tree bpduguard enable switchport port-security switchport port-security maximum 1 switchport port-security mac-address sticky switchport port-security violation shutdown ex interface range f0/1-3 switchport access vlan 40 ex interface range f0/4-6 switchport access vlan 50 ex interface range f0/7-9 switchport access vlan 60 ex